

Date Prepared/Revised: 4/4/2014 Version no.: 02 Supersedes: (11/30/2010)

### 1.) Identification of the Mixture and of the Company

Product identifier: Aervoe Marking Chalk - Aerosol

Product name: Marking Chalk

2	14 Blue	215 White	216 Red 217 Orange	218 Yellow	219 Green

Relevant identified uses of the substance: Marking Chalk is designed to temporarily mark most paved surfaces, soil, and grass. Use for utility marking, construction sites, surveying, landscaping, and athletic field marking.

Uses advised against: This aerosol product is designed to spray upside down or at an angle not greater than 30° from vertical. Use caution if surface is wet, or if rain is imminent within 4 hours of application. Do not apply additional product until the previous coat is dry.

CAS No.: Not Applicable (mixture)

Manufacturer/Supplier: Aervoe Industries Incorporated

Street address/P.O. Box: 1100 Mark Circle

Country ID/Postcode/Place Gardnerville, Nevada 89410
Telephone number: 001 (0) 1-775-782-0100

Telephone number: 001 (0) 1-775-782-0100 mailbox@aervoe.com

National contact: Aervoe industries Incorporated

For Product Information: 001 (0) 1-800-227-0196

Emergency telephone number: **001 (0) 1-800-424-9300 (CHEMTREC – 24 hrs)** 

**English Language Service** 

### 2. Hazards identification

This product does not meet the criteria for classification according to Directive 1999/45/EC

Potential health effects: See Section 11

Primary routes of entry: Inhalation, Skin, Eyes, Ingestion

## 3. Composition / Information on Ingredients

Material	CAS Number	EINECS	Weight	Risk and Safety Phrases	Notes
		Number	Percent		
Dimethyl Ether	115-10-6	204-065-8	10-30%	R12, S2, S9, S16, S33	
Isopropanol	67-63-0	200-661-7	5-10%	R11, R36, R67, S2, S7,	
				S16, S24/25, S26	

For full text of R&S- phrases: see section 16.

R Code Summation: R11, R12, R36, R67

S Code Summation: S2, S7, S9, S16, S24, S25, S26, S33

### 4.) First Aid Measures



Date Prepared/Revised: 4/4/2014 Version no.: 02 Supersedes: (11/30/2010)

**General Advice:** If symptoms persist, always call a doctor.

**Inhalation First Aid:** Remove victim to fresh air and provide oxygen if breathing is

difficult. If not breathing, give artificial respiration, preferably

mouth to mouth. Get medical attention immediately.

**Skin Contact First Aid:** Wash with soap and water. Remove contaminated clothing and

shoes. Get medical attention immediately. Wash clothing before

reuse.

**Eye Contact First Aid:** If contact with eyes, immediately flush eyes with plenty of water

for at least 15 minutes, while holding eyelids open. Get medical

attention immediately.

**Ingestion First Aid:** If swallowed, wash out mouth with water provided the person is

conscious. Do not induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention immediately.

## 5. Fire Fighting Measures

Flammable Properties: Aerosol

Flash Point: <0° F (-18° C) Auto Ignition Temperature: Not Available

Flammable Limits in Air:

% by Volume: LEL: 2% UEL: 18%

Suitable extinguishing media: Carbon dioxide, dry chemical, water spray.

Unsuitable extinguishing media: None known

Special hazards arising from the

substance or mixture: None known

Hazardous combustion products: Carbon dioxide, Carbon monoxide

Fire & Explosion Hazards: Closed Containers may rupture due to the buildup of pressure

from extreme temperatures.

Advice for fire-fighters: Use water spray to cool containers exposed to heat or fire to prevent pressure

build up. In the event of a fire, wear full protective clothing and NIOSH-

approved self-contained breathing apparatus with full face piece operated in the

pressure demand or other positive pressure mode.

### **6. Accidental Release Measures**

### PERSONAL PRECAUTIONARY MEASURES:

- 1) Follow personal protective equipment recommendations found in section 8.
- 2) Maintain adequate ventilation.

### **SPILL CLEAN-UP PROCEDURES:**

- 1.) Evacuate unprotected personnel from the area.
- 2.) Remove sources of ignition if safe to do so.
- 3.) Pickup spilled materials using non-sparking tools and place in an appropriate container for disposal.
- 4.) Contain spill to prevent material from entering sewage or ground water systems.



Date Prepared/Revised: 4/4/2014 Version no.: 02 Supersedes: (11/30/2010)

5.) Always dispose of waste materials in accordance with all EU, National and Local Regulations.

### 7. Handling and Storage

Flammable Aerosol, use in a well ventilated area.

Do not use near sources of ignition.

Store out of direct sunlight.

Storage Temperature:  $40^{\circ}$  to  $120^{\circ}F$  ( $4^{\circ}$  to  $49^{\circ}C$ )

Do not to eat, drink and smoke while working with this material.

Wash hands after use.

## 8. Exposure Controls / Personal Protection

### **Appropriate engineering controls:**

Ensure adequate ventilation. A system of local and/or general exhaust is recommended to keep employee exposures below the Airborne Exposure Limits.

Keep away from sources of ignition.

Take precautionary measures against static discharge.

#### **Personal Protection:**

Eye & face protection devices such as safety glasses, safety goggles or face shield are recommended.

### **Skin protection**

Wear the appropriate protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

## **Respiratory protection:**

Use only in an adequately ventilated area. For unknown vapor concentrations use a positive-pressure, pressure-demand, self-contained breathing apparatus (SCBA).

Hazardous Ingredient	CAS Number	TWA	STEL
Dimethyl Ether	115-10-6	N/AV	N/AV
Isopropanol	67-63-0	400	500

## 9. Information on Basic Physical and Chemical Properties

Appearance: Opaque Liquid	Odor: Alcohol odor	
Odor Threshold: N/AV	pH: Not Applicale (solvent Base)	
Melting Point: N/AV	Freezing Point: N/AV	
Initial Boiling Point: N/AV	Boiling Point Range: N/AV	
Flash Point: <0° F (-18° C)	Evaporation Rate: Faster than n-Butyl	
	Acetate	
Flammability Solid/Gas: Flammable gas	Upper LEL: 2% Lower LEL: 18%	
Vapor Pressure: N/AV	Vapor Density: Heavier Than Air	



Date Prepared/Revised: 4/4/2014 Version no.: 02 Supersedes: (11/30/2010)

Relative Density: N/AV	Solubility: Negligible
Partition Coefficient:	Auto-ignition Temperature: N/AV
n-octanol/ water: N/AV	
Decomposition Temperature: N/AV	Viscosity: N/AV
Explosive Properties: N/AV	Oxidizing Properties: N/AV

## 10. Stability & Reactivity

Possibility of hazardous reactions: Hazardous polymerization will not occur under normal conditions

Conditions to avoid: Heat and ignition sources Incompatible materials: Strong Oxidizing Agents Hazardous decomposition products: Will not occur

## 11. Toxicological Information

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart and blood

## 12. Ecological Information

Toxicity: No Data Available

Persistence and degradability: **No Data Available** Bioaccumulative potential: **No Data Available** 

Mobility in soil: No Data Available

Results of PBT and vPvB assessment: No Data Available

Other adverse effects: No Data Available

### 13. Disposal Considerations

**Waste Disposal:** Dispose of material in accordance with EU, national and local requirements. For proper disposal of used material, an assessment must be completed to determine the proper and permissible waste management options permitted under applicable rules, regulations and/or laws governing your location.

**Product / Packaging disposal:** Dispose of packaging in accordance with federal, state and local requirements, regulations and/or laws governing your location.

### 14. Transportation Information

### **US DOT**

UN	Proper Shipping Name	Hazard	Packing	Marine	Special
Number		Class	Group	Pollutant	Provisions
UN1950	Aerosols	2.1	Not	Not	Not
			Applicable	Applicable	Applicable

### **IMDG**

UN Proper Shipping Name	Hazard	Packing	Marine	Special	
-------------------------	--------	---------	--------	---------	--



Date Prepared/Revised: 4/4/2014 Version no.: 02 Supersedes: (11/30/2010)

Number		Class	Group	Pollutant	Provisions
UN1950	Aerosols	2.1	Not	Not	Not
			Applicable	Applicable	Applicable

#### **IATA:**

UN	Proper Shipping Name	Hazard	Packing	Marine	Special
Number		Class	Group	Pollutant	Provisions
UN1950	Aerosols	2.1	Not	Not	Not
			Applicable	Applicable	Applicable

### 15. Regulatory Information

## **Workplace classification:**

This product is considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200). The Occupational Safety and Health Administration's interpretation of the product's hazard to workers.

#### **SARA Title 3:**

Section 311/312 Categorizations (40 CFR 372): This product is a hazardous chemical under 29 CFR 1910.1200, and is categorized as an immediate and delayed health, and flammability physical hazard. Superfund Amendment and Reauthorization Act (SARA) category. SARA requires reporting any spill of any hazardous substance.

**TSCA status:** All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

**PROP 65 (CA):** Warning: This product may contain chemicals know to the state of California to cause cancer, birth defects or other reproductive harm.

### 16. Other Information

List of relevant Risk and Safety phrases:

#### R Phrases:

R11: Highly flammable R12: Extremely flammable

R36: Irritating to eyes R45: May cause cancer

R67: Vapours may cause drowsiness and dizziness

**S Phrases:** S2: Keep out of the reach of children

S7: Keep container tightly closed

S9: Keep container in a well-ventilated place

S16: Keep away from sources of ignition - No smoking

S24: Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer)

S25: Avoid contact with eyes

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

Date Prepared/Revised: 4/4/2014 Version no.: 02 Supersedes: (11/30/2010)

S33: Take precautionary measures against static discharges

### **National Fire Protection Association (NFPA) ratings**

Health = 2 Flammability = 4 Reactivity = 1

This SDS has been completed in accordance with Regulation (EC) No. 1907/2006

Date of Preparation/Revision: 4/4/2014

Supersedes: (11/30/2010)

To the best of our knowledge, the information contained herein is believed to be accurate. However, the above data does not imply any guarantee or warranty of any kind, expressed or implied. The final determination of the suitability of any material is the sole responsibility of the user. All materials made present un-known hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee these are the only hazards existing.