Toward Short-Term Glucose Prediction Solely Based on CGM Time Series

Ming Cheng*, Xingjian Diao*, Ziyi Zhou*[†], Yanjun Cui, Wenjun Liu, Shitong Cheng

¹Department of Computer Science, Dartmouth College, Hanover, NH 03755, USA

Email: ziyi.zhou.gr@dartmouth.edu

Abstract—The global diabetes epidemic highlights the importance of maintaining good glycemic control. Glucose prediction is a fundamental aspect of diabetes management, facilitating real-time decision-making. Recent research has introduced models focusing on long-term glucose trend prediction, which are unsuitable for real-time decision-making and result in delayed responses. Conversely, models designed to respond to immediate glucose level changes cannot analyze glucose variability comprehensively. Moreover, contemporary research generally integrates various physiological parameters (e.g. insulin doses, food intake, etc.), which inevitably raises data privacy concerns. To bridge such a research gap, we propose TimeGlu - an endto-end pipeline for short-term glucose prediction solely based on CGM time series data. We implement four baseline methods to conduct a comprehensive comparative analysis of the model's performance. Through extensive experiments on two contrasting datasets (CGM Glucose and Colás dataset), TimeGlu achieves state-of-the-art performance without the need for additional personal data from patients, providing effective guidance for realworld diabetic glucose management.

I. INTRODUCTION

Approximately 537 million people globally are currently living with diabetes [1], and this number is expected to continue increasing [2]. This escalating trend highlights the complexities of managing the condition, particularly the challenge of maintaining good glycemic control [3] amid diverse factors [4]. Consequently, there is an increased demand for accurate blood glucose prediction, a key aspect of diabetes management [5].

Blood glucose prediction, with the goal of forecasting future blood glucose levels to enable real-time decision-making in diabetes management, has gained substantial importance amid the growing diabetes epidemic [1], [2] and evolving digital health technologies [6], [7] for effective glycemic control. This pursuit has notably advanced in prominence and relevance within the healthcare and medical research communities, influencing applications including anomaly detection [8] and monitoring [9], [10], preventive healthcare [11], wearable health technology [12], [13], [14], and artificial pancreas development [15].

Recent blood glucose prediction models in diabetes management typically fall into *two* types. The *first* emphasizes the prediction of long-term blood glucose trends. These models [16], [17] provide an extensive view of glycemic

*Equal contribution. [†]Corresponding author.

control over time, crucial for strategic treatment and lifestyle adjustments [18]. They are valuable in identifying long-term patterns [19] and potential complications [20] arising from sustained hyperglycemia or hypoglycemia. However, these models are less effective for real-time decision-making as they focus on long-term data analysis rather than current fluctuations. In addition, the emphasis on long-term trends can lead to delayed responses to acute changes in glucose levels, potentially missing immediate risks [21], [22]. The *second* path particularly focuses on responding to immediate glucose level changes. Although these models [23], [24] are effective for immediate adjustments, they tend to be reactive, concentrating on current glucose values and often lacking the capability to predict future trends or analyze patterns in glucose variability.

Moreover, many current models in glucose level prediction often integrate various physiological parameters [3], such as insulin doses, food intake, and physical activity, alongside CGM data. They come with a significant drawback while showing efficacy: The reliance on multiple data sources can complicate their use in real-world settings due to data availability [25] and patient compliance issues [26]. Additionally, such models cannot fully exploit temporal patterns in CGM data.

A notable gap in current research is the utilization of historical CGM data for forecasting short-term glucose trends. Predicting these trends solely based on CGM data is important for decision-making and proactive diabetes management [27], [28].

Addressing these challenges is crucial not only for individual healthcare management [29] but also for broader medical research [30], [31], which aims to develop more efficient monitoring and intervention methods. Consequently, one crucial question has arisen: Is it feasible to accurately forecast high-frequency blood glucose level trends over short periods using only CGM data?

To overcome the challenges above, we propose **TimeGlu** – a one-stage end-to-end pipeline for short-term glucose prediction solely based on CGM time series.

In summary, our contribution is threefold:

 One-stage end-to-end pipeline. We propose TimeGlu – an effective one-stage end-to-end pipeline that forecasts the high-frequency blood glucose level trend over a short time series manner.

- 2) Effective high-frequency glucose level prediction. TimeGlu enables forecasting the high-frequency blood glucose level trend over a short time series manner.
- 3) State-of-the-art performance. We conduct extensive experiments on the CGM Glucose dataset¹ and the Colás dataset [32] with various methods to do time seriesbased glucose prediction. To the best of our knowledge, ours is the first study to do glucose prediction solely based on time series on the Colás dataset. Our model can consistently accurately predict high-frequency blood glucose level trends across different conditions.

II. METHODS

To obtain accurate glucose prediction results, we employ four different methods for time series-based glucose prediction. Afterward, we analyze and compare the results of these methods to determine the optimal glucose prediction model.

A. Exponential Smoothing

The Exponential Smoothing method [33] is widely used in accurate prediction for short-term time series, making it suitable for glucose prediction. It assigns greater importance to recent observations, with exponentially diminishing weights for observations that are farther in the past. Considering that short-term glucose changes are trending over time, we adopt the Double Exponential Smoothing (DFS) model [34] for glucose prediction. Formally, given $X = \{x_1, x_2, ..., x_n\}$ as the observed time series, for time t > 0, its smoothed value (s_t) and the best estimate of the trend (b_t) are expressed as follows:

$$s_t = \alpha x_t + (1 - \alpha)(s_{t-1} + b_{t-1}) \tag{1}$$

$$b_t = \beta(s_t - s_{t-1}) + (1 - \beta)b_{t-1} \tag{2}$$

where α and β are time/trend smoothing factor, and initially $s_0 = x_0, b_0 = x_1 - x_0$.

Therefore, the prediction value (\tilde{x}_{t+k}) at time (t+k) is expressed as:

$$\tilde{x}_{t+k} = s_t + kb_t \tag{3}$$

B. Auto ARIMA

As a commonly employed method for time series data forecasting, ARIMA is characterized by three order parameters: p, d, q. Generally, for an *ARIMA*(p, d, q) model, p indicates the order of the autoregressive part, d stands for the degree of first differencing involved, and q refers to the order of the moving average part [35]. Formally, given $X = \{x_1, x_2, ..., x_n\}$ as the observed time series, the predicted value $(\tilde{x_t})$ at time t by the model *ARIMA*(p, q) can be expressed as [36]:

$$\tilde{x_t} = \delta + \sum_{i=1}^p \phi_i x_{t-i} + \sum_{j=1}^q \theta_i \epsilon_{t-j} + \epsilon_t$$
(4)

where ϵ_t is the error term, and ϕ_i, θ_i, δ are parameters.

Instead of choosing the parameters in Equation 4 manually, modern research mainly utilizes Auto ARIMA [35], [37],

[38] to find the best parameter combinations automatically by comparing the AIC/BIC criterion [39] of different models, which significantly reduces the required human resources for selecting the parameters of the ARIMA model.

C. BATS and TBATS

Based on the previously mentioned Exponential Smoothing method and the ARMA model, the BATS model [40] considering the Box-Cox Transformation [41] for time series forecasting is proposed. Specifically, befitting from the ability to deal with non-linear data and de-correlate the time series data, BATS showcases the improvement in time series prediction performance [42] over the methods mentioned above.

Considering the limitations of BATS when the data seasonality is complex and high frequency (e.g. seasonalities of time in a day), BATS with Trigonometric Seasonality (TBATS) [40] is constructed. Experimental results (Section III) on the CGM dataset demonstrate the advantages of the TBATS over BATS in dealing with time series data.

D. Neural Networks - TimeGlu

Considering the powerful deep feature extraction capability of neural network models and inspired by the mainstream encoder-decoder designs [44], [45], [46], we design a novel encoder-decoder-based pipeline for glucose prediction solely based on CGM time series data, as shown in Figure 1.

Assume x as the observed time series glucose data, the noise with normal distribution $n \sim (0, \delta^2)$ is applied for data augmentation, considering the variability of glucose changes across the temporal domain. The augmented data is then input into TimeGlu to obtain the predicted data \tilde{x} , as expressed below:

$$\tilde{x} = D(E(x+n)), \quad n \sim \mathcal{N}(0, \delta^2)$$
 (5)

where E and D indicate the encoder and decoder of TimeGlu, respectively.

To train the pipeline, the Mean Square Error (MSE) [47] is constructed between the predicted glucose value and the ground truth:

$$L_{MSE} = \left| \left| \tilde{x} - y \right| \right|^2 \tag{6}$$

where y indicates the ground truth.

1) Encoder Architecture: The encoder module is designed with sequential Bidirectional LSTM (Bi-LSTM) [48] blocks followed by an Additive Attention [43] layer.

Specifically, Bi-LSTM processes sequences bidirectionally to learn past and future contexts simultaneously, with each direction containing an LSTM network. Let $X = \{x_1, x_2, ..., x_t\}$ denote the input sequence to the Bi-LSTM, where each x_t is the data point at time step t. This sequence can consist of various forms of time-sensitive data including physiological measurements in healthcare applications. Formally, the hidden states of the forward LSTM (h_t^f) and backward LSTM (h_t^b) at timestamp t are expressed as follows:

$$h_t^f = LSTM(x_t, h_{t-1}^f), \quad h_t^b = LSTM(x_t, h_{t+1}^b)$$
(7)

¹https://github.com/DigitalBiomarkerDiscoveryPipeline/Case_Studies



Fig. 1. **Overview of the proposed TimeGlu pipeline.** Noise with standard normal distribution is applied to the input data for data augmentation, which is then input into the encoder-decoder-based architecture. To precisely and comprehensively extract the time series features, a sequential Bi-LSTM structure with an Additive Attention [43] module is designed. The high-dimensional features will be input into a lightweight decoder to generate the predicted glucose value. An MSE loss is constructed for pipeline training.

TABLE I SUMMARY OF CGM GLUCOSE DATASET AND COLÁS DATASET

Dataset	Attribute	Mean ± STD	Range
CGM Glucose	Number of Data Points Time Range (day) Glucose Value (mg/dL)	$ \begin{array}{c c} 2147 \\ 9 \\ 111.9 \pm 28.8 \end{array} $	49.0 - 261.0
Colás	Subjects / Data Points Time Range (year) Gender Ratio (F/M) Age (yrs) BMI Follow-up Range	$\begin{array}{c} 208 \ / \ 114,912 \\ - \\ 105 \ / \ 103 \\ 59.6 \ \pm \ 10.1 \\ 30.0 \ \pm \ 4.7 \\ 979.8 \ \pm \ 371.9 \end{array}$	2012-2015 - 29 - 88 18.1 - 48.7 176.0 - 2211.0

The output of Bi-LSTM at timestamp t is then combined through the concatenation operation:

$$h_t = h_t^f \oplus h_t^b \tag{8}$$

Inspired by existing attention-based structures [28], [49], [50], an Additive Attention module [43] is applied to instruct the model to selectively focus on the relevant parts of the input sequence, following the Bi-LSTM output. Since the attention mechanism is employed within h_t (as shown in Figure 1), this module dynamically lets the model capture key components of the features. Afterward, inspired by the fusion operation introduced in [51], the output of the attention is then concatenated together with the Bi-LSTM output to assign adaptive weights to different parts of the learned features. Therefore, the output of the encoder (x'_t) at timestamp t can be expressed as:

$$x'_t = Con(h_t, attn(h_t, h_t)) \tag{9}$$

where Con represents the concatenation operation.

2) Decoder Architecture: A lightweight decoder containing Bi-LSTM and a Dense layer is constructed to generate the predicted value. Benefiting from the deep and dense blocks of the encoder, TimeGlu can accurately predict glucose values with only a lightweight decoder. In contrast to some complex decoder modules, this design allows TimeGlu to infer in real time, enabling its generalization to practical applications.

III. EXPERIMENTS

A. Dataset Description

We conduct extensive experiments on two publicly available datasets: the CGM Glucose dataset and the Colás dataset. The CGM Glucose dataset is collected from a single person's week-long CGM data which has been de-identified and timeshifted for privacy protection, while the Colás dataset includes 208 patients from the outpatient clinic of hypertension and vascular risk of the University Hospital of Móstoles in Madrid from January 2012 to May 2015 [32].

B. Dataset Analysis

1) CGM Glucose Dataset: The dataset is summarized in Table I. This week-long dataset contains 2147 data points of a single person, ranging from October 24th to November 1st in 2016. The glucose value of the selected person is relatively diverse, ranging from 49.0 to 261.0 including normal/abnormal states. The left part of Figure 2 illustrates glucose changes more intuitively throughout the day, where the glucose value is beyond the normal range in the daytime (from 4:00 AM to 6:00 PM) and reaches the highest at around 5:00 AM and 3:00 PM. The glucose changes throughout the entire week are shown in the right part of Figure 2, where a markedly abnormal range in glucose can be observed on October 27th and 31st.

2) Colás Dataset: The Colás dataset, as a relatively largescale one exhibiting diversity, involves 114,912 datapoints from 208 subjects in total, as summarized in Table I. Moreover, it is collected from 103 male and 105 female patients aged from 29 to 88, making it a challenging dataset for glucose prediction. Figure 3 demonstrates an example of glucose range from 30 randomly selected patients, where the variety of data points is evidently to be proved. This gender-balanced dataset saturated with data diversity makes it an ideal dataset for evaluating the model.

C. Evaluation Metrics

To evaluate the performance of each method, we employ two objective evaluation metrics: Mean Absolute Error (MAE) [52] and Mean Absolute Percentage Error (MAPE) [53], to assess the accuracy of model predictions. Suppose y and \tilde{y}



Fig. 2. Visualization of the CGM Glucose dataset. Left: Three different ranges are demonstrated across days within one week. Right: TIR/TAR/TBR visualization of the dataset. Multiple levels (median, min, max, etc.) of glucose values are illustrated.



Fig. 3. Visualization of the Colás dataset. Left: 30 subjects with the most abnormal blood glucose situations are shown as an example. Right: 30 randomly selected subjects are illustrated through the box plot to showcase the variety and data diversity of the dataset.

are actual and predicted data points, respectively, the MAE and MAPE criterion can be expressed as below:

$$MAE = \frac{\sum |y - \tilde{y}|}{n}, \quad MAPE = \frac{\sum \frac{|y - \tilde{y}|}{y}}{n}$$
(10)

where n indicates the total number of data points. MAE treats overestimation and underestimation equally and provides a balanced view of how well a model is performing in terms of both positive and negative errors. In addition, MAPE quantifies the average magnitude of errors produced by the model, working as the most common metric of model prediction accuracy.

D. Quantitative Results

The quantitative results on the CGM Glucose dataset and Colás dataset are shown in Table II.

As indicated in the table, TimeGlu showcases a significant advancement in predicting glucose levels compared to the existing models (DFS, BATS, TBATS, and Auto ARIMA) across two datasets. In the comparative analysis, it is evident that TimeGlu not only outperforms these models but also sets a new standard in glucose level prediction.

1) Accuracy: In terms of accuracy, as measured by the MAE, TimeGlu exhibits remarkable performance. On the CGM Glucose dataset, TimeGlu achieves an MAE of 2.99, showing an improvement of over 99.28% compared to DFS

TABLE II Comparison of Glucose Value Predictions By Multiple Methods on Different Datasets

Mathada	CGM Glucose		Colás	
Wiethous	MAE ↓	$\mathbf{MAPE} \downarrow$	MAE \downarrow	MAPE ↓
DFS [34]	413.12	3.699	388.84	2.868
BATS [40]	32.58	0.288	50.60	0.384
TBATS [40]	29.22	0.247	21.36	0.156
Auto ARIMA [35]	25.62	0.199	20.99	0.154
TimeGlu (Ours)	2.99	0.027	13.49	0.118

(the least MAE of 413.12), 90.83% compared to BATS (32.58), 89.77% compared to TBATS (29.22), and 88.33% compared to Auto ARIMA (25.62). Similarly, for the Colás dataset, TimeGlu's MAE of 13.49 represents improvements ranging from 35.75% to 96.53% compared to other models.

These results indicate that TimeGlu is remarkably more accurate in its predictions. The significant reduction in MAE suggests that TimeGlu is capable of closely tracking the intricate patterns of glucose levels, which is crucial for reliable diabetes management and treatment planning. The exceptional performance of our model can be largely attributed to the Bi-LSTM structure it employs. Bi-LSTM processes data in both forward and backward directions, allowing the model to learn from complex temporal dynamics of both past and future.



Fig. 4. Visualization of glucose value prediction of TimeGlu on the CGM Glucose dataset. TimeGlu is capable of accurately predicting glucose trends and specific values over time on the CGM Glucose dataset.



Fig. 5. Visualization of glucose value prediction of TimeGlu on the Colás dataset. For more clear demonstration, 114 data points are illustrated in the figure. For large-scale datasets, TimeGlu provides robust generalization capabilities to accurately predict blood glucose trends as well as glucose values.

2) Adaptability: Regarding adaptability, assessed through MAPE, TimeGlu achieves 0.027/0.118 on the CGM Glucose and the Colás dataset, reflecting improvements from 86.43% to 99.27% and 23.38% to 95.89% over other models, respectively. As a relative error metric, MAPE can reflect the model's ability to adapt to different scales and conditions of blood glucose levels. This adaptability is essential for personalized treatment based on individual blood glucose patterns.

E. Qualitative Results

The qualitative results of our prediction are shown in Figure 4 and 5, where it is evidently to prove the model generalization and robustness across datasets. Specifically, for a relatively small dataset where week-long data points are collected, TimeGlu generates accurate predictions since the golden line and blue line consistently overlap over time. Particularly, TimeGlu offers precise predictions for both normal values (e.g. $\sim 100 \text{ mg/dL}$) and outliers (e.g. $\sim 250 \text{ mg/dL}$), showing the robustness of our model in various situations.

For a large-scale (Colás) dataset consisting of 208 subjects with diverse genders, ages, and BMIs, TimeGlu produces remarkable prediction results on trends and values, where the pink line and blue line are closely aligned. Although when blood glucose values are outside of the normal range

 TABLE III

 Ablation Studies on The Structure of TimeGlu Pipeline

Methods	MAE ↓	MAPE ↓
$LSTM_{Encoder}$	4.51	0.041
$LSTM_{Decoder}$	3.52	0.032
w/o Attention	3.40	0.030
TimeGlu (Ours)	2.99	0.027

($\sim 60 \text{ mg/dL}$), TimeGlu remains highly predictive at precise time stamps. This demonstrates the potential of our model to perform glucose prediction for timely intervention in real-life applications and provide guidance for the physical health of human beings.

F. Ablation Studies

The ablation studies on pipeline design are shown in Table III and Figure 6, where the effectiveness of the model structure is proved from multiple perspectives. In Table III, $LSTM_{Encoder}$ and $LSTM_{Decoder}$ indicate that we replace Bi-LSTM with LSTM in encoder/decoder, where a significant decrease of accuracy can be observed (e.g. MAE error increases from 2.99 to 4.51 with LSTM in the encoder). Since MAE and MAPE criteria measure accuracy and interpretability,



Fig. 6. Ablation studies on different encoder backbones. The training losses as epoch changes with different encoder backbones are shown.

utilizing features from both directions (forward and backward) contributes to learning comprehensive representations from the time series data, which showcases the effectiveness in sequence modeling tasks (glucose value prediction).

Moreover, the Additive Attention module specializes in assigning adaptive weights to extract key components from highdimensional features, an increase in prediction accuracy is reflected with the attention block (MAE/MAPE error drops by 12.1%/10.0%). This quantitative result objectively showcases the effectiveness of our model architecture design.

As qualitatively shown in Figure 6, stacked LSTM blocks in the encoder will enhance representation learning in multi-scale compared with a single-block module, representing significantly lower loss values (e.g. orange/red lines). In comparison with LSTM, Bi-LSTM in the encoder captures features from both directions to learn more intricate temporal information about glucose levels (e.g. orange/blue lines).

IV. CONCLUSION

This paper proposes a novel end-to-end glucose prediction model, TimeGlu, that utilizes only time series features to achieve state-of-the-art short-term glucose prediction. Four different baseline methods (DFS, Auto ARIMA, BATS, and TBATS) are also implemented in this paper for a thorough performance comparison. Through extensive experiments on the CGM Glucose and Colás dataset, TimeGlu achieves optimal glucose prediction accuracy without requiring additional personal data, demonstrating the potential of TimeGlu for future application in real-life diabetes management.

REFERENCES

- P. Belsare, B. Lu, A. Bartolome, and T. Prioleau, "Investigating temporal patterns of glycemic control around holidays," in 2022 44th Annual International Conference of the IEEE Engineering in Medicine & Biology Society (EMBC), 2022, pp. 1074–1077.
- [2] P. Saeedi, I. Petersohn, P. Salpea, B. Malanda, S. Karuranga, N. Unwin, S. Colagiuri, L. Guariguata, A. A. Motala, K. Ogurtsova *et al.*, "Global and regional diabetes prevalence estimates for 2019 and projections for 2030 and 2045: Results from the international diabetes federation diabetes atlas," *Diabetes research and clinical practice*, vol. 157, p. 107843, 2019.

- [3] A. Bartolome and T. Prioleau, "A computational framework for discovering digital biomarkers of glycemic control," *NPJ Digital Medicine*, vol. 5, no. 1, p. 111, 2022.
- [4] N. S. Ahmad, F. Islahudin, and T. Paraidathathu, "Factors associated with good glycemic control among patients with type 2 diabetes mellitus," *Journal of diabetes investigation*, vol. 5, no. 5, pp. 563–569, 2014.
- [5] M. Vettoretti, G. Cappon, A. Facchinetti, and G. Sparacino, "Advanced diabetes management using artificial intelligence and continuous glucose monitoring sensors," *Sensors*, vol. 20, no. 14, p. 3870, 2020.
- [6] D. H. Solomon and R. S. Rudin, "Digital health technologies: opportunities and challenges in rheumatology," *Nature Reviews Rheumatology*, vol. 16, no. 9, pp. 525–535, 2020.
- [7] A. Bartolome, S. Shah, and T. Prioleau, "Glucomine: A case for improving the use of wearable device data in diabetes management," *Proceedings of the ACM on Interactive, Mobile, Wearable and Ubiquitous Technologies*, vol. 5, no. 3, pp. 1–24, 2021.
- [8] Z. Wang, N. Luo, and P. Zhou, "Guardhealth: Blockchain empowered secure data management and graph convolutional network enabled anomaly detection in smart healthcare," *Journal of Parallel and Distributed Computing*, vol. 142, pp. 1–12, 2020.
- [9] X. Li, X. Huang, J. Mo, H. Wang, Q. Huang, C. Yang, T. Zhang, H.-J. Chen, T. Hang, F. Liu *et al.*, "A fully integrated closed-loop system based on mesoporous microneedles-iontophoresis for diabetes treatment," *Advanced Science*, vol. 8, no. 16, p. 2100827, 2021.
- [10] Z. Wang, Z. Yang, I. Azimi, and A. M. Rahmani, "Differential private federated transfer learning for mental health monitoring in everyday settings: A case study on stress detection," *arXiv preprint arXiv:2402.10862*, 2024.
- [11] A. Ng, B. Wei, J. Jain, E. A. Ward, S. D. Tandon, J. T. Moskowitz, S. Krogh-Jespersen, L. S. Wakschlag, and N. Alshurafa, "Predicting the next-day perceived and physiological stress of pregnant women by using machine learning and explainability: algorithm development and validation," *JMIR mHealth and uHealth*, vol. 10, no. 8, p. e33850, 2022.
- [12] B. Wei, S. Zhang, X. Diao, Q. Xu, Y. Gao, and N. Alshurafa, "An endto-end energy-efficient approach for intake detection with low inference time using wrist-worn sensor," *IEEE Journal of Biomedical and Health Informatics*, vol. 27, no. 8, pp. 3878–3888, 2023.
- [13] X. Li, C. Zhan, Q. Huang, M. He, C. Yang, C. Yang, X. Huang, M. Chen, X. Xie, and H.-J. Chen, "Smart diaper based on integrated multiplex carbon nanotube-coated electrode array sensors for in situ urine monitoring," ACS Applied Nano Materials, vol. 5, no. 4, pp. 4767– 4778, 2022.
- [14] H. A. Koshkak, Z. Wang, A. Kanduri, P. Liljeberg, A. M. Rahmani, and N. Dutt, "SEAL: Sensing Efficient Active Learning on Wearables through Context-awareness," in *Proceedings of the IEEE/ACM Design*, *Automation and Test in Europe Conference*, Spain, Mar 2024, dATE'24.
- [15] M. Nwokolo and R. Hovorka, "The artificial pancreas and type 1 diabetes," *The Journal of Clinical Endocrinology & Metabolism*, vol. 108, no. 7, pp. 1614–1623, 2023.
- [16] C. Liu, J. Vehí, P. Avari, M. Reddy, N. Oliver, P. Georgiou, and P. Herrero, "Long-term glucose forecasting using a physiological model and deconvolution of the continuous glucose monitoring signal," *Sensors*, vol. 19, no. 19, p. 4338, 2019.
- [17] M. Jaloli and M. Cescon, "Long-term prediction of blood glucose levels in type 1 diabetes using a cnn-lstm-based deep neural network," *Journal* of *Diabetes Science and Technology*, vol. 17, no. 6, pp. 1590–1601, 2023.
- [18] H. J. Choe, E.-J. Rhee, J. C. Won, K. S. Park, W.-Y. Lee, and Y. M. Cho, "Effects of patient-driven lifestyle modification using intermittently scanned continuous glucose monitoring in patients with type 2 diabetes: results from the randomized open-label pdf study," *Diabetes Care*, vol. 45, no. 10, pp. 2224–2230, 2022.
- [19] N. Keum, K. H. Ha, Y. Bao, M. J. Chung, H. C. Kim, and E. L. Giovannucci, "Long-term patterns of fasting blood glucose levels and pancreatic cancer incidence," *Cancer Causes & Control*, vol. 29, pp. 135–142, 2018.
- [20] S. A. Mezil and B. A. Abed, "Complication of diabetes mellitus," Annals of the Romanian Society for Cell Biology, pp. 1546–1556, 2021.
- [21] N. Jafar, H. Edriss, and K. Nugent, "The effect of short-term hyperglycemia on the innate immune system," *The American journal of the medical sciences*, vol. 351, no. 2, pp. 201–211, 2016.
- [22] A. Mantovani, G. Grani, L. Chioma, G. Vancieri, I. Giordani, R. Rendina, M. E. Rinaldi, A. Andreadi, C. Coccaro, C. Boccardo *et al.*, "Severe hypoglycemia in patients with known diabetes requiring emergency

department care: A report from an italian multicenter study," *Journal of Clinical & Translational Endocrinology*, vol. 5, pp. 46–52, 2016.

- [23] E. Dassau, F. Cameron, H. Lee, B. W. Bequette, H. Zisser, L. Jovanovič, H. P. Chase, D. M. Wilson, B. A. Buckingham, and F. J. Doyle III, "Real-time hypoglycemia prediction suite using continuous glucose monitoring: a safety net for the artificial pancreas," *Diabetes care*, vol. 33, no. 6, pp. 1249–1254, 2010.
- [24] N. Ben Brahim, J. Place, E. Renard, and M. D. Breton, "Identification of main factors explaining glucose dynamics during and immediately after moderate exercise in patients with type 1 diabetes," *Journal of diabetes science and technology*, vol. 9, no. 6, pp. 1185–1191, 2015.
- [25] R. Avram, J. E. Olgin, P. Kuhar, J. W. Hughes, G. M. Marcus, M. J. Pletcher, K. Aschbacher, and G. H. Tison, "A digital biomarker of diabetes from smartphone-based vascular signals," *Nature medicine*, vol. 26, no. 10, pp. 1576–1582, 2020.
- [26] M. Cheng, X. Diao, S. Cheng, and W. Liu, "Saic: Integration of speech anonymization and identity classification," *arXiv preprint* arXiv:2312.15190, 2023.
- [27] M. George, A. Chacko, and S. K. Kurien, "Proactive diabetes management: research directions," in *Proceedings of the 20th International conference on distributed computing and networking*, 2019, pp. 486– 491.
- [28] Z. Zhou, M. Cheng, Y. Cui, X. Diao, and Z. Ma, "Crossgp: Cross-day glucose prediction excluding physiological information," 2024.
- [29] F. J. Pasquel, M. C. Lansang, K. Dhatariya, and G. E. Umpierrez, "Management of diabetes and hyperglycaemia in the hospital," *The lancet Diabetes & endocrinology*, vol. 9, no. 3, pp. 174–188, 2021.
- [30] Z. Zhou, B. Guo, and C. Zhang, "Doseguide: A graph-based dynamic time-aware prediction system for postoperative pain," in 2021 IEEE 27th International Conference on Parallel and Distributed Systems (ICPADS). IEEE, 2021, pp. 474–481.
- [31] C. Zhang, X. Zhao, Z. Zhou, X. Liang, and S. Wang, "Doseformer: Dynamic graph transformer for postoperative pain prediction," *Electronics*, vol. 12, no. 16, p. 3507, 2023.
- [32] A. Colás, L. Vigil, B. Vargas, D. Cuesta-Frau, and M. Varela, "Detrended fluctuation analysis in the prediction of type 2 diabetes mellitus in patients at risk: Model optimization and comparison with other metrics," *PloS one*, vol. 14, no. 12, p. e0225817, 2019.
- [33] E. S. Gardner Jr, "Exponential smoothing: The state of the art," *Journal of forecasting*, vol. 4, no. 1, pp. 1–28, 1985.
- [34] N. A. Heckert, J. J. Filliben, C. M. Croarkin, B. Hembree, W. F. Guthrie, P. Tobias, and J. Prinz, "Handbook 151: Nist/sematech e-handbook of statistical methods," 2002.
- [35] T. M. Awan and F. Aslam, "Prediction of daily covid-19 cases in european countries using automatic arima model," *Journal of public health research*, vol. 9, no. 3, pp. jphr–2020, 2020.
- [36] R. J. Hyndman and G. Athanasopoulos, *Forecasting: principles and practice*. OTexts, 2018.
- [37] G. Melard and J.-M. Pasteels, "Automatic arima modeling including interventions, using time series expert software," *International Journal* of Forecasting, vol. 16, no. 4, pp. 497–508, 2000.
- [38] N. Tran and D. A. Reed, "Automatic arima time series modeling for adaptive i/o prefetching," *IEEE Transactions on parallel and distributed* systems, vol. 15, no. 4, pp. 362–377, 2004.
- [39] S. I. Vrieze, "Model selection and psychological theory: a discussion of the differences between the akaike information criterion (aic) and the bayesian information criterion (bic)." *Psychological methods*, vol. 17, no. 2, p. 228, 2012.
- [40] A. M. De Livera, R. J. Hyndman, and R. D. Snyder, "Forecasting time series with complex seasonal patterns using exponential smoothing," *Journal of the American statistical association*, vol. 106, no. 496, pp. 1513–1527, 2011.
- [41] R. M. Sakia, "The box-cox transformation technique: a review," *Journal of the Royal Statistical Society Series D: The Statistician*, vol. 41, no. 2, pp. 169–178, 1992.
- [42] A. M. De Livera *et al.*, "Automatic forecasting with a modified exponential smoothing state space framework," *Monash Econometrics and Business Statistics Working Papers*, vol. 10, no. 10, p. 6, 2010.
- [43] D. Bahdanau, K. Cho, and Y. Bengio, "Neural machine translation by jointly learning to align and translate," *arXiv preprint arXiv:1409.0473*, 2014.
- [44] P. Lyu, N. Chen, S. Mao, and M. Li, "Lstm based encoder-decoder for short-term predictions of gas concentration using multi-sensor fusion,"

Process Safety and Environmental Protection, vol. 137, pp. 93–105, 2020.

- [45] H. Hu, Z. Qiao, M. Cheng, Z. Liu, and H. Wang, "Dasgil: Domain adaptation for semantic and geometric-aware image-based localization," *IEEE Transactions on Image Processing*, vol. 30, pp. 1342–1353, 2020.
- [46] B. Zhang, G. Zou, D. Qin, Y. Lu, Y. Jin, and H. Wang, "A novel encoderdecoder model based on read-first lstm for air pollutant prediction," *Science of the Total Environment*, vol. 765, p. 144507, 2021.
- [47] D. M. Allen, "Mean square error of prediction as a criterion for selecting variables," *Technometrics*, vol. 13, no. 3, pp. 469–475, 1971.
- [48] S. Siami-Namini, N. Tavakoli, and A. S. Namin, "The performance of lstm and bilstm in forecasting time series," in 2019 IEEE International conference on big data (Big Data). IEEE, 2019, pp. 3285–3292.
- [49] C. Wu, F. Wu, T. Qi, Y. Huang, and X. Xie, "Fastformer: Additive attention can be all you need," arXiv preprint arXiv:2108.09084, 2021.
- [50] X. Diao, M. Cheng, and S. Cheng, "Av-maskenhancer: Enhancing video representations through audio-visual masked autoencoder," in 2023 IEEE 35th International Conference on Tools with Artificial Intelligence (ICTAI). IEEE, 2023, pp. 354–360.
- [51] X. Diao, M. Cheng, W. Barrios, and S. Jin, "Ft2tf: First-person statement text-to-talking face generation," arXiv preprint arXiv:2312.05430, 2023.
- [52] R. J. Hyndman and A. B. Koehler, "Another look at measures of forecast accuracy," *International journal of forecasting*, vol. 22, no. 4, pp. 679– 688, 2006.
- [53] U. Khair, H. Fahmi, S. Al Hakim, and R. Rahim, "Forecasting error calculation with mean absolute deviation and mean absolute percentage error," in *journal of physics: conference series*, vol. 930, no. 1. IOP Publishing, 2017, p. 012002.