



API Reference

AWS Data Exchange



AWS Data Exchange: API Reference

Copyright © 2024 Amazon Web Services, Inc. and/or its affiliates. All rights reserved.

Amazon's trademarks and trade dress may not be used in connection with any product or service that is not Amazon's, in any manner that is likely to cause confusion among customers, or in any manner that disparages or discredits Amazon. All other trademarks not owned by Amazon are the property of their respective owners, who may or may not be affiliated with, connected to, or sponsored by Amazon.

Table of Contents

Welcome	1
Data sets and products	2
API access control	2
Endpoints and AWS Regions	2
Service quotas	3
Actions	4
AcceptDataGrant	6
Request Syntax	6
URI Request Parameters	6
Request Body	6
Response Syntax	6
Response Elements	7
Errors	9
See Also	10
CancelJob	11
Request Syntax	11
URI Request Parameters	11
Request Body	11
Response Syntax	11
Response Elements	11
Errors	11
See Also	12
CreateDataGrant	13
Request Syntax	13
URI Request Parameters	13
Request Body	13
Response Syntax	15
Response Elements	15
Errors	17
See Also	18
CreateDataSet	20
Request Syntax	20
URI Request Parameters	20
Request Body	20

Response Syntax	21
Response Elements	22
Errors	23
See Also	24
CreateEventAction	25
Request Syntax	25
URI Request Parameters	25
Request Body	25
Response Syntax	26
Response Elements	26
Errors	27
See Also	28
CreateJob	29
Request Syntax	29
URI Request Parameters	31
Request Body	31
Response Syntax	32
Response Elements	36
Errors	37
See Also	38
CreateRevision	39
Request Syntax	39
URI Request Parameters	39
Request Body	39
Response Syntax	40
Response Elements	40
Errors	42
See Also	43
DeleteAsset	44
Request Syntax	44
URI Request Parameters	44
Request Body	44
Response Syntax	44
Response Elements	44
Errors	45
See Also	45

DeleteDataGrant	47
Request Syntax	47
URI Request Parameters	47
Request Body	47
Response Syntax	47
Response Elements	47
Errors	47
See Also	48
DeleteDataSet	49
Request Syntax	49
URI Request Parameters	49
Request Body	49
Response Syntax	49
Response Elements	49
Errors	49
See Also	50
DeleteEventAction	52
Request Syntax	52
URI Request Parameters	52
Request Body	52
Response Syntax	52
Response Elements	52
Errors	52
See Also	53
DeleteRevision	54
Request Syntax	54
URI Request Parameters	54
Request Body	54
Response Syntax	54
Response Elements	54
Errors	54
See Also	55
GetAsset	57
Request Syntax	57
URI Request Parameters	57
Request Body	57

Response Syntax	57
Response Elements	59
Errors	61
See Also	61
GetDataGrant	63
Request Syntax	63
URI Request Parameters	63
Request Body	63
Response Syntax	63
Response Elements	64
Errors	66
See Also	67
GetDataSet	68
Request Syntax	68
URI Request Parameters	68
Request Body	68
Response Syntax	68
Response Elements	69
Errors	70
See Also	71
GetEventAction	72
Request Syntax	72
URI Request Parameters	72
Request Body	72
Response Syntax	72
Response Elements	73
Errors	74
See Also	74
GetJob	76
Request Syntax	76
URI Request Parameters	76
Request Body	76
Response Syntax	76
Response Elements	80
Errors	81
See Also	82

GetReceivedDataGrant	83
Request Syntax	83
URI Request Parameters	83
Request Body	83
Response Syntax	83
Response Elements	84
Errors	86
See Also	86
GetRevision	88
Request Syntax	88
URI Request Parameters	88
Request Body	88
Response Syntax	88
Response Elements	89
Errors	91
See Also	91
ListDataGrants	93
Request Syntax	93
URI Request Parameters	93
Request Body	93
Response Syntax	93
Response Elements	94
Errors	94
See Also	95
ListDataSetRevisions	96
Request Syntax	96
URI Request Parameters	96
Request Body	96
Response Syntax	96
Response Elements	97
Errors	97
See Also	98
ListDataSets	99
Request Syntax	99
URI Request Parameters	99
Request Body	99

Response Syntax	99
Response Elements	100
Errors	100
See Also	101
ListEventActions	102
Request Syntax	102
URI Request Parameters	102
Request Body	102
Response Syntax	102
Response Elements	103
Errors	103
See Also	104
ListJobs	105
Request Syntax	105
URI Request Parameters	105
Request Body	105
Response Syntax	105
Response Elements	109
Errors	109
See Also	110
ListReceivedDataGrants	111
Request Syntax	111
URI Request Parameters	111
Request Body	111
Response Syntax	111
Response Elements	112
Errors	112
See Also	113
ListRevisionAssets	114
Request Syntax	114
URI Request Parameters	114
Request Body	114
Response Syntax	114
Response Elements	116
Errors	117
See Also	117

ListTagsForResource	119
Request Syntax	119
URI Request Parameters	119
Request Body	119
Response Syntax	119
Response Elements	119
Errors	120
See Also	120
RevokeRevision	121
Request Syntax	121
URI Request Parameters	121
Request Body	121
Response Syntax	122
Response Elements	122
Errors	124
See Also	125
SendApiAsset	126
Request Syntax	126
URI Request Parameters	126
Request Body	127
Response Syntax	127
Response Elements	127
Errors	127
See Also	128
SendDataSetNotification	130
Request Syntax	130
URI Request Parameters	131
Request Body	131
Response Syntax	132
Response Elements	132
Errors	132
See Also	133
StartJob	135
Request Syntax	135
URI Request Parameters	135
Request Body	135

Response Syntax	135
Response Elements	135
Errors	135
See Also	136
TagResource	138
Request Syntax	138
URI Request Parameters	138
Request Body	138
Response Syntax	138
Response Elements	139
Errors	139
See Also	139
UntagResource	140
Request Syntax	140
URI Request Parameters	140
Request Body	140
Response Syntax	140
Response Elements	140
Errors	140
See Also	141
UpdateAsset	142
Request Syntax	142
URI Request Parameters	142
Request Body	142
Response Syntax	143
Response Elements	145
Errors	146
See Also	147
UpdateDataSet	148
Request Syntax	148
URI Request Parameters	148
Request Body	148
Response Syntax	149
Response Elements	149
Errors	151
See Also	151

UpdateEventAction	153
Request Syntax	153
URI Request Parameters	153
Request Body	153
Response Syntax	154
Response Elements	154
Errors	155
See Also	156
UpdateRevision	157
Request Syntax	157
URI Request Parameters	157
Request Body	157
Response Syntax	158
Response Elements	158
Errors	160
See Also	161
Data Types	162
Action	165
Contents	165
See Also	165
ApiGatewayApiAsset	166
Contents	166
See Also	167
AssetDestinationEntry	168
Contents	168
See Also	168
AssetDetails	169
Contents	169
See Also	170
AssetEntry	171
Contents	171
See Also	173
AssetSourceEntry	174
Contents	174
See Also	174
AutoExportRevisionDestinationEntry	175

Contents	175
See Also	175
AutoExportRevisionToS3RequestDetails	176
Contents	176
See Also	176
CreateS3DataAccessFromS3BucketRequestDetails	177
Contents	177
See Also	177
CreateS3DataAccessFromS3BucketResponseDetails	178
Contents	178
See Also	178
DatabaseLFTagPolicy	179
Contents	179
See Also	179
DatabaseLFTagPolicyAndPermissions	180
Contents	180
See Also	180
DataGrantSummaryEntry	181
Contents	181
See Also	183
DataSetEntry	184
Contents	184
See Also	186
DataUpdateRequestDetails	187
Contents	187
See Also	187
DeprecationRequestDetails	188
Contents	188
See Also	188
Details	189
Contents	189
See Also	189
Event	190
Contents	190
See Also	190
EventActionEntry	191

Contents	191
See Also	192
ExportAssetsToS3RequestDetails	193
Contents	193
See Also	193
ExportAssetsToS3ResponseDetails	195
Contents	195
See Also	195
ExportAssetToSignedUrlRequestDetails	197
Contents	197
See Also	197
ExportAssetToSignedUrlResponseDetails	198
Contents	198
See Also	199
ExportRevisionsToS3RequestDetails	200
Contents	200
See Also	200
ExportRevisionsToS3ResponseDetails	201
Contents	201
See Also	201
ExportServerSideEncryption	203
Contents	203
See Also	203
ImportAssetFromApiGatewayApiRequestDetails	204
Contents	204
See Also	205
ImportAssetFromApiGatewayApiResponseDetails	207
Contents	207
See Also	209
ImportAssetFromSignedUrlJobErrorDetails	210
Contents	210
See Also	210
ImportAssetFromSignedUrlRequestDetails	211
Contents	211
See Also	212
ImportAssetFromSignedUrlResponseDetails	213

Contents	213
See Also	214
ImportAssetsFromLakeFormationTagPolicyRequestDetails	215
Contents	215
See Also	216
ImportAssetsFromLakeFormationTagPolicyResponseDetails	217
Contents	217
See Also	218
ImportAssetsFromRedshiftDataSharesRequestDetails	219
Contents	219
See Also	219
ImportAssetsFromRedshiftDataSharesResponseDetails	220
Contents	220
See Also	220
ImportAssetsFromS3RequestDetails	221
Contents	221
See Also	221
ImportAssetsFromS3ResponseDetails	222
Contents	222
See Also	222
JobEntry	223
Contents	223
See Also	224
JobError	226
Contents	226
See Also	227
KmsKeyToGrant	228
Contents	228
See Also	228
LakeFormationDataPermissionAsset	229
Contents	229
See Also	230
LakeFormationDataPermissionDetails	231
Contents	231
See Also	231
LakeFormationTagPolicyDetails	232

Contents	232
See Also	232
LFResourceDetails	233
Contents	233
See Also	233
LFTag	234
Contents	234
See Also	234
LFTagPolicyDetails	235
Contents	235
See Also	235
NotificationDetails	237
Contents	237
See Also	237
OriginDetails	238
Contents	238
See Also	238
ReceivedDataGrantSummariesEntry	239
Contents	239
See Also	241
RedshiftDataShareAsset	242
Contents	242
See Also	242
RedshiftDataShareAssetSourceEntry	243
Contents	243
See Also	243
RedshiftDataShareDetails	244
Contents	244
See Also	245
RequestDetails	246
Contents	246
See Also	247
ResponseDetails	248
Contents	248
See Also	249
RevisionDestinationEntry	250

Contents	250
See Also	250
RevisionEntry	251
Contents	251
See Also	253
RevisionPublished	254
Contents	254
See Also	254
S3DataAccessAsset	255
Contents	255
See Also	256
S3DataAccessAssetSourceEntry	257
Contents	257
See Also	257
S3DataAccessDetails	259
Contents	259
See Also	259
S3SnapshotAsset	260
Contents	260
See Also	260
SchemaChangeDetails	261
Contents	261
See Also	261
SchemaChangeRequestDetails	263
Contents	263
See Also	263
ScopeDetails	264
Contents	264
See Also	264
TableLFTagPolicy	265
Contents	265
See Also	265
TableLFTagPolicyAndPermissions	266
Contents	266
See Also	266
Common Parameters	267

Common Errors	270
Document history	272

Welcome

Welcome to the *AWS Data Exchange API Reference*. AWS Data Exchange is a service that helps AWS customers to exchange data in the AWS Cloud. You can use the AWS Data Exchange API operations in the AWS Cloud.

As a subscriber, you can view and access the data sets that you have an entitlement to through a subscription. You can use the API operations to download (export) or copy your entitled data sets to Amazon Simple Storage Service (Amazon S3) for use across a variety of AWS analytics and machine learning services.

As a provider, you can create and manage your data sets that you want to publish to a product. You can download (export) or copy your assets or revisions to Amazon S3 or a signed URL. In addition, providers can import assets from an Amazon API Gateway API or import assets from an Amazon Redshift datashare.

A *data set* in AWS Data Exchange is a collection of data that can be changed or updated over time. Data sets can be updated using revisions, which represent a new version or incremental change to a data set. A revision contains one or more assets.

An *asset* in AWS Data Exchange is a piece of data. The asset can be one of the following:

- A structured data file, an image file, or some other data file that is stored as an Amazon S3 object.
- An Amazon Redshift datashare. Datashares are created in Amazon Redshift based on an existing database within a cluster that contain schemas, tables, views, or user-defined functions.
- A REST API that you created in Amazon API Gateway.
- An Amazon S3 access point that allows read-only access to an Amazon S3 bucket or subset of a bucket.
- An AWS Lake Formation data permission (Preview).

As a subscriber, you can view and access the data sets that you have an entitlement to through a subscription. You can use the API operations to export or copy your entitled data sets for use across a variety of AWS analytics and machine learning services, or download them locally.

As a provider, you can create and manage your data sets that you want to publish to a product. Providers can import assets locally, from an Amazon Simple Storage Service (S3) bucket, an

Amazon API Gateway API, from an Amazon Redshift datashare, or from an AWS Lake Formation data permission (Preview).

Jobs are asynchronous import or export operations used to create or copy assets.

To learn more about these and other AWS Data Exchange concepts, procedures, best practices, and AWS Marketplace integration, see the [AWS Marketplace Catalog API Reference](#) and the [AWS Data Exchange User Guide](#).

Note

Currently, the `SendApiAsset` operation is not supported for AWS SDKs for Java or Swift.

Data sets and products

You can manage and interact with data sets by using the AWS Data Exchange API operations. You can perform product publishing and product subscription tasks through the AWS Marketplace Catalog API or the AWS Data Exchange console. For more information, see the [AWS Data Exchange User Guide](#).

API access control

You use [AWS Identity and Access Management](#) (IAM) to create IAM roles and assign policies that grant limited permissions to end users. The policies define the actions that the role can take on your data sets, revisions, assets, and associated jobs in the AWS Data Exchange API. For example, you can define roles such as engineering, marketing, and pricing. A user in your organization who has been added to the engineering role might be granted permissions to import an asset from Amazon S3 but can't finalize a revision for your data set.

For more information about AWS Data Exchange permissions, including managed policies, and a permissions reference for AWS Data Exchange actions and resources, see [Identity and Access Management in AWS Data Exchange](#) in the *AWS Data Exchange User Guide*.

Endpoints and AWS Regions

For information about AWS Regions and endpoints that are supported for AWS Data Exchange, see [AWS Data Exchange endpoints and quotas](#) in the *AWS General Reference*.

Service quotas

For information about the quotas for using AWS Data Exchange, see [AWS Data Exchange endpoints and quotas](#) in the *AWS General Reference*.

Actions

The following actions are supported:

- [AcceptDataGrant](#)
- [CancelJob](#)
- [CreateDataGrant](#)
- [CreateDataSet](#)
- [CreateEventAction](#)
- [CreateJob](#)
- [CreateRevision](#)
- [DeleteAsset](#)
- [DeleteDataGrant](#)
- [DeleteDataSet](#)
- [DeleteEventAction](#)
- [DeleteRevision](#)
- [GetAsset](#)
- [GetDataGrant](#)
- [GetDataSet](#)
- [GetEventAction](#)
- [GetJob](#)
- [GetReceivedDataGrant](#)
- [GetRevision](#)
- [ListDataGrants](#)
- [ListDataSetRevisions](#)
- [ListDataSets](#)
- [ListEventActions](#)
- [ListJobs](#)
- [ListReceivedDataGrants](#)
- [ListRevisionAssets](#)
- [ListTagsForResource](#)

- [RevokeRevision](#)
- [SendApiAsset](#)
- [SendDataSetNotification](#)
- [StartJob](#)
- [TagResource](#)
- [UntagResource](#)
- [UpdateAsset](#)
- [UpdateDataSet](#)
- [UpdateEventAction](#)
- [UpdateRevision](#)

AcceptDataGrant

This operation accepts a data grant.

Request Syntax

```
POST /v1/data-grants/DataGrantArn/accept HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

DataGrantArn

The Amazon Resource Name (ARN) of the data grant to accept.

Pattern: `arn:aws:dataexchange:[\ -a-z0-9]*:(\d{12}):data-grants\[a-zA-Z0-9]{30,40}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "AcceptanceState": "string",
  "AcceptedAt": "string",
  "Arn": "string",
  "CreatedAt": "string",
  "DataSetId": "string",
  "Description": "string",
  "EndsAt": "string",
  "GrantDistributionScope": "string",
  "Id": "string",
```

```
"Name": "string",  
"ReceiverPrincipal": "string",  
"SenderPrincipal": "string",  
"UpdatedAt": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AcceptanceState

The acceptance state of the data grant.

Type: String

Valid Values: PENDING_RECEIVER_ACCEPTANCE | ACCEPTED

AcceptedAt

The timestamp of when the data grant was accepted.

Type: Timestamp

Arn

The Amazon Resource Name (ARN) of the accepted data grant.

Type: String

CreatedAt

The timestamp of when the data grant was created.

Type: Timestamp

DataSetId

The ID of the data set associated to the data grant.

Type: String

Description

The description of the accepted data grant.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 16384.

EndsAt

The timestamp of when access to the associated data set ends.

Type: Timestamp

GrantDistributionScope

The distribution scope for the data grant.

Type: String

Valid Values: AWS_ORGANIZATION | NONE

Id

The ID of the data grant.

Type: String

Name

The name of the accepted data grant.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

ReceiverPrincipal

The AWS account ID of the data grant receiver.

Type: String

Pattern: \d{12}

SenderPrincipal

The AWS account ID of the data grant sender.

Type: String

Pattern: \d{12}

UpdatedAt

The timestamp of when the data grant was last updated.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to the resource is denied.

HTTP Status Code: 403

ConflictException

The request couldn't be completed because it conflicted with the current state of the resource.

HTTP Status Code: 409

InternalServerErrorException

An exception occurred with the service.

HTTP Status Code: 500

ResourceNotFoundException

The resource couldn't be found.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CancelJob

This operation cancels a job. Jobs can be cancelled only when they are in the WAITING state.

Request Syntax

```
DELETE /v1/jobs/JobId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

JobId

The unique identifier for a job.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

ConflictException

The request couldn't be completed because it conflicted with the current state of the resource.

HTTP Status Code: 409

InternalServerErrorException

An exception occurred with the service.

HTTP Status Code: 500

ResourceNotFoundException

The resource couldn't be found.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateDataGrant

This operation creates a data grant.

Request Syntax

```
POST /v1/data-grants HTTP/1.1
Content-type: application/json

{
  "Description": "string",
  "EndsAt": "string",
  "GrantDistributionScope": "string",
  "Name": "string",
  "ReceiverPrincipal": "string",
  "SourceDataSetId": "string",
  "Tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Description

The description of the data grant.

Type: String

Required: No

EndsAt

The timestamp of when access to the associated data set ends.

Type: Timestamp

Required: No

GrantDistributionScope

The distribution scope of the data grant.

Type: String

Valid Values: AWS_ORGANIZATION | NONE

Required: Yes

Name

The name of the data grant.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

ReceiverPrincipal

The AWS account ID of the data grant receiver.

Type: String

Pattern: \d{12}

Required: Yes

SourceDataSetId

The ID of the data set used to create the data grant.

Type: String

Required: Yes

Tags

The tags to add to the data grant. A tag is a key-value pair.

Type: String to string map

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "AcceptanceState": "string",
  "AcceptedAt": "string",
  "Arn": "string",
  "CreatedAt": "string",
  "DataSetId": "string",
  "Description": "string",
  "EndsAt": "string",
  "GrantDistributionScope": "string",
  "Id": "string",
  "Name": "string",
  "ReceiverPrincipal": "string",
  "SenderPrincipal": "string",
  "SourceDataSetId": "string",
  "Tags": {
    "string" : "string"
  },
  "UpdatedAt": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

AcceptanceState

The acceptance state of the data grant.

Type: String

Valid Values: PENDING_RECEIVER_ACCEPTANCE | ACCEPTED

AcceptedAt

The timestamp of when the data grant was accepted.

Type: Timestamp

Arn

The Amazon Resource Name (ARN) of the data grant.

Type: String

CreatedAt

The timestamp of when the data grant was created.

Type: Timestamp

DataSetId

The ID of the data set associated to the data grant.

Type: String

Description

The description of the data grant.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 16384.

EndsAt

The timestamp of when access to the associated data set ends.

Type: Timestamp

GrantDistributionScope

The distribution scope for the data grant.

Type: String

Valid Values: AWS_ORGANIZATION | NONE

Id

The ID of the data grant.

Type: String

Name

The name of the data grant.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

ReceiverPrincipal

The AWS account ID of the data grant receiver.

Type: String

Pattern: `\d{12}`

SenderPrincipal

The AWS account ID of the data grant sender.

Type: String

Pattern: `\d{12}`

SourceDataSetId

The ID of the data set used to create the data grant.

Type: String

Tags

The tags associated to the data grant. A tag is a key-value pair.

Type: String to string map

UpdatedAt

The timestamp of when the data grant was last updated.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to the resource is denied.

HTTP Status Code: 403

InternalServerErrorException

An exception occurred with the service.

HTTP Status Code: 500

ResourceNotFoundException

The resource couldn't be found.

HTTP Status Code: 404

ServiceLimitExceededException

The request has exceeded the quotas imposed by the service.

HTTP Status Code: 402

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)

- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateDataSet

This operation creates a data set.

Request Syntax

```
POST /v1/data-sets HTTP/1.1
Content-type: application/json

{
  "AssetType": "string",
  "Description": "string",
  "Name": "string",
  "Tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

AssetType

The type of asset that is added to a data set.

Type: String

Valid Values: S3_SNAPSHOT | REDSHIFT_DATA_SHARE | API_GATEWAY_API | S3_DATA_ACCESS | LAKE_FORMATION_DATA_PERMISSION

Required: Yes

Description

A description for the data set. This value can be up to 16,348 characters long.

Type: String

Required: Yes

Name

The name of the data set.

Type: String

Required: Yes

Tags

A data set tag is an optional label that you can assign to a data set when you create it. Each tag consists of a key and an optional value, both of which you define. When you use tagging, you can also use tag-based access control in IAM policies to control access to these data sets and revisions.

Type: String to string map

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "Arn": "string",
  "AssetType": "string",
  "CreatedAt": "string",
  "Description": "string",
  "Id": "string",
  "Name": "string",
  "Origin": "string",
  "OriginDetails": {
    "DataGrantId": "string",
    "ProductId": "string"
  },
  "SourceId": "string",
  "Tags": {
    "string" : "string"
  },
  "UpdatedAt": "string"
}
```

```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

Arn

The ARN for the data set.

Type: String

AssetType

The type of asset that is added to a data set.

Type: String

Valid Values: S3_SNAPSHOT | REDSHIFT_DATA_SHARE | API_GATEWAY_API | S3_DATA_ACCESS | LAKE_FORMATION_DATA_PERMISSION

CreatedAt

The date and time that the data set was created, in ISO 8601 format.

Type: Timestamp

Description

The description for the data set.

Type: String

Id

The unique identifier for the data set.

Type: String

Name

The name of the data set.

Type: String

Origin

A property that defines the data set as OWNED by the account (for providers) or ENTITLED to the account (for subscribers).

Type: String

Valid Values: OWNED | ENTITLED

OriginDetails

If the origin of this data set is ENTITLED, includes the details for the product on AWS Marketplace.

Type: [OriginDetails](#) object

SourceId

The data set ID of the owned data set corresponding to the entitled data set being viewed. This parameter is returned when a data set owner is viewing the entitled copy of its owned data set.

Type: String

Tags

The tags for the data set.

Type: String to string map

UpdatedAt

The date and time that the data set was last updated, in ISO 8601 format.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to the resource is denied.

HTTP Status Code: 403

InternalServerErrorException

An exception occurred with the service.

HTTP Status Code: 500

ServiceLimitExceededException

The request has exceeded the quotas imposed by the service.

HTTP Status Code: 402

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateEventAction

This operation creates an event action.

Request Syntax

```
POST /v1/event-actions HTTP/1.1
Content-type: application/json

{
  "Action": {
    "ExportRevisionToS3": {
      "Encryption": {
        "KmsKeyArn": "string",
        "Type": "string"
      },
      "RevisionDestination": {
        "Bucket": "string",
        "KeyPattern": "string"
      }
    }
  },
  "Event": {
    "RevisionPublished": {
      "DataSetId": "string"
    }
  }
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Action

What occurs after a certain event.

Type: [Action](#) object

Required: Yes

Event

What occurs to start an action.

Type: [Event](#) object

Required: Yes

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "Action": {
    "ExportRevisionToS3": {
      "Encryption": {
        "KmsKeyArn": "string",
        "Type": "string"
      },
      "RevisionDestination": {
        "Bucket": "string",
        "KeyPattern": "string"
      }
    }
  },
  "Arn": "string",
  "CreatedAt": "string",
  "Event": {
    "RevisionPublished": {
      "DataSetId": "string"
    }
  },
  "Id": "string",
  "UpdatedAt": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

Action

What occurs after a certain event.

Type: [Action](#) object

Arn

The ARN for the event action.

Type: String

CreatedAt

The date and time that the event action was created, in ISO 8601 format.

Type: Timestamp

Event

What occurs to start an action.

Type: [Event](#) object

Id

The unique identifier for the event action.

Type: String

UpdatedAt

The date and time that the event action was last updated, in ISO 8601 format.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to the resource is denied.

HTTP Status Code: 403

InternalServerErrorException

An exception occurred with the service.

HTTP Status Code: 500

ServiceLimitExceededException

The request has exceeded the quotas imposed by the service.

HTTP Status Code: 402

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateJob

This operation creates a job.

Request Syntax

```
POST /v1/jobs HTTP/1.1
```

```
Content-type: application/json
```

```
{
  "Details": {
    "CreateS3DataAccessFromS3Bucket": {
      "AssetSource": {
        "Bucket": "string",
        "KeyPrefixes": [ "string" ],
        "Keys": [ "string" ],
        "KmsKeysToGrant": [
          {
            "KmsKeyArn": "string"
          }
        ]
      },
      "DataSetId": "string",
      "RevisionId": "string"
    },
    "ExportAssetsToS3": {
      "AssetDestinations": [
        {
          "AssetId": "string",
          "Bucket": "string",
          "Key": "string"
        }
      ],
      "DataSetId": "string",
      "Encryption": {
        "KmsKeyArn": "string",
        "Type": "string"
      },
      "RevisionId": "string"
    },
    "ExportAssetToSignedUrl": {
      "AssetId": "string",
      "DataSetId": "string",

```

```

    "RevisionId": "string"
  },
  "ExportRevisionsToS3": {
    "DataSetId": "string",
    "Encryption": {
      "KmsKeyArn": "string",
      "Type": "string"
    },
  },
  "RevisionDestinations": [
    {
      "Bucket": "string",
      "KeyPattern": "string",
      "RevisionId": "string"
    }
  ]
},
"ImportAssetFromApiGatewayApi": {
  "ApiDescription": "string",
  "ApiId": "string",
  "ApiKey": "string",
  "ApiName": "string",
  "ApiSpecificationMd5Hash": "string",
  "DataSetId": "string",
  "ProtocolType": "string",
  "RevisionId": "string",
  "Stage": "string"
},
"ImportAssetFromSignedUrl": {
  "AssetName": "string",
  "DataSetId": "string",
  "Md5Hash": "string",
  "RevisionId": "string"
},
"ImportAssetsFromLakeFormationTagPolicy": {
  "CatalogId": "string",
  "Database": {
    "Expression": [
      {
        "TagKey": "string",
        "TagValues": [ "string" ]
      }
    ],
  },
  "Permissions": [ "string" ]
},

```

```
"DataSetId": "string",
"RevisionId": "string",
"RoleArn": "string",
"Table": {
  "Expression": [
    {
      "TagKey": "string",
      "TagValues": [ "string" ]
    }
  ],
  "Permissions": [ "string" ]
},
"ImportAssetsFromRedshiftDataShares": {
  "AssetSources": [
    {
      "DataShareArn": "string"
    }
  ],
  "DataSetId": "string",
  "RevisionId": "string"
},
"ImportAssetsFromS3": {
  "AssetSources": [
    {
      "Bucket": "string",
      "Key": "string"
    }
  ],
  "DataSetId": "string",
  "RevisionId": "string"
}
},
"Type": "string"
}
```

URI Request Parameters

The request does not use any URI parameters.

Request Body

The request accepts the following data in JSON format.

Details

The details for the CreateJob request.

Type: [RequestDetails](#) object

Required: Yes

Type

The type of job to be created.

Type: String

Valid Values: IMPORT_ASSETS_FROM_S3 | IMPORT_ASSET_FROM_SIGNED_URL
| EXPORT_ASSETS_TO_S3 | EXPORT_ASSET_TO_SIGNED_URL |
EXPORT_REVISIONS_TO_S3 | IMPORT_ASSETS_FROM_REDSHIFT_DATA_SHARES |
IMPORT_ASSET_FROM_API_GATEWAY_API | CREATE_S3_DATA_ACCESS_FROM_S3_BUCKET
| IMPORT_ASSETS_FROM_LAKE_FORMATION_TAG_POLICY

Required: Yes

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "Arn": "string",
  "CreatedAt": "string",
  "Details": {
    "CreateS3DataAccessFromS3Bucket": {
      "AssetSource": {
        "Bucket": "string",
        "KeyPrefixes": [ "string" ],
        "Keys": [ "string" ],
        "KmsKeysToGrant": [
          {
            "KmsKeyArn": "string"
          }
        ]
      }
    },
    "DataSetId": "string",
```

```
    "RevisionId": "string"
  },
  "ExportAssetsToS3": {
    "AssetDestinations": [
      {
        "AssetId": "string",
        "Bucket": "string",
        "Key": "string"
      }
    ],
    "DataSetId": "string",
    "Encryption": {
      "KmsKeyArn": "string",
      "Type": "string"
    },
    "RevisionId": "string"
  },
  "ExportAssetToSignedUrl": {
    "AssetId": "string",
    "DataSetId": "string",
    "RevisionId": "string",
    "SignedUrl": "string",
    "SignedUrlExpiresAt": "string"
  },
  "ExportRevisionsToS3": {
    "DataSetId": "string",
    "Encryption": {
      "KmsKeyArn": "string",
      "Type": "string"
    },
    "EventActionArn": "string",
    "RevisionDestinations": [
      {
        "Bucket": "string",
        "KeyPattern": "string",
        "RevisionId": "string"
      }
    ]
  },
  "ImportAssetFromApiGatewayApi": {
    "ApiDescription": "string",
    "ApiId": "string",
    "ApiKey": "string",
    "ApiName": "string",
```

```

    "ApiSpecificationMd5Hash": "string",
    "ApiSpecificationUploadUrl": "string",
    "ApiSpecificationUploadUrlExpiresAt": "string",
    "DataSetId": "string",
    "ProtocolType": "string",
    "RevisionId": "string",
    "Stage": "string"
  },
  "ImportAssetFromSignedUrl": {
    "AssetName": "string",
    "DataSetId": "string",
    "Md5Hash": "string",
    "RevisionId": "string",
    "SignedUrl": "string",
    "SignedUrlExpiresAt": "string"
  },
  "ImportAssetsFromLakeFormationTagPolicy": {
    "CatalogId": "string",
    "Database": {
      "Expression": [
        {
          "TagKey": "string",
          "TagValues": [ "string" ]
        }
      ],
      "Permissions": [ "string" ]
    },
    "DataSetId": "string",
    "RevisionId": "string",
    "RoleArn": "string",
    "Table": {
      "Expression": [
        {
          "TagKey": "string",
          "TagValues": [ "string" ]
        }
      ],
      "Permissions": [ "string" ]
    }
  },
  "ImportAssetsFromRedshiftDataShares": {
    "AssetSources": [
      {
        "DataShareArn": "string"
      }
    ]
  }
}

```

```

    }
  ],
  "DataSetId": "string",
  "RevisionId": "string"
},
"ImportAssetsFromS3": {
  "AssetSources": [
    {
      "Bucket": "string",
      "Key": "string"
    }
  ],
  "DataSetId": "string",
  "RevisionId": "string"
}
},
"Errors": [
  {
    "Code": "string",
    "Details": {
      "ImportAssetFromSignedUrlJobErrorDetails": {
        "AssetName": "string"
      },
      "ImportAssetsFromS3JobErrorDetails": [
        {
          "Bucket": "string",
          "Key": "string"
        }
      ]
    }
  },
  "LimitName": "string",
  "LimitValue": number,
  "Message": "string",
  "ResourceId": "string",
  "ResourceType": "string"
}
],
"Id": "string",
"State": "string",
"Type": "string",
"UpdatedAt": "string"
}

```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

Arn

The ARN for the job.

Type: String

CreatedAt

The date and time that the job was created, in ISO 8601 format.

Type: Timestamp

Details

Details about the job.

Type: [ResponseDetails](#) object

Errors

The errors associated with jobs.

Type: Array of [JobError](#) objects

Id

The unique identifier for the job.

Type: String

State

The state of the job.

Type: String

Valid Values: WAITING | IN_PROGRESS | ERROR | COMPLETED | CANCELLED | TIMED_OUT

Type

The job type.

Type: String

Valid Values: IMPORT_ASSETS_FROM_S3 | IMPORT_ASSET_FROM_SIGNED_URL
| EXPORT_ASSETS_TO_S3 | EXPORT_ASSET_TO_SIGNED_URL |
EXPORT_REVISIONS_TO_S3 | IMPORT_ASSETS_FROM_REDSHIFT_DATA_SHARES |
IMPORT_ASSET_FROM_API_GATEWAY_API | CREATE_S3_DATA_ACCESS_FROM_S3_BUCKET
| IMPORT_ASSETS_FROM_LAKE_FORMATION_TAG_POLICY

UpdatedAt

The date and time that the job was last updated, in ISO 8601 format.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to the resource is denied.

HTTP Status Code: 403

ConflictException

The request couldn't be completed because it conflicted with the current state of the resource.

HTTP Status Code: 409

InternalServerErrorException

An exception occurred with the service.

HTTP Status Code: 500

ResourceNotFoundException

The resource couldn't be found.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

CreateRevision

This operation creates a revision for a data set.

Request Syntax

```
POST /v1/data-sets/DataSetId/revisions HTTP/1.1
Content-type: application/json
```

```
{
  "Comment": "string",
  "Tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

DataSetId

The unique identifier for a data set.

Required: Yes

Request Body

The request accepts the following data in JSON format.

Comment

An optional comment about the revision.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

Tags

A revision tag is an optional label that you can assign to a revision when you create it. Each tag consists of a key and an optional value, both of which you define. When you use tagging, you can also use tag-based access control in IAM policies to control access to these data sets and revisions.

Type: String to string map

Required: No

Response Syntax

```
HTTP/1.1 201
Content-type: application/json

{
  "Arn": "string",
  "Comment": "string",
  "CreatedAt": "string",
  "DataSetId": "string",
  "Finalized": boolean,
  "Id": "string",
  "RevocationComment": "string",
  "Revoked": boolean,
  "RevokedAt": "string",
  "SourceId": "string",
  "Tags": {
    "string" : "string"
  },
  "UpdatedAt": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 201 response.

The following data is returned in JSON format by the service.

[Arn](#)

The ARN for the revision.

Type: String

Comment

An optional comment about the revision.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

CreatedAt

The date and time that the revision was created, in ISO 8601 format.

Type: Timestamp

DataSetId

The unique identifier for the data set associated with the data set revision.

Type: String

Finalized

To publish a revision to a data set in a product, the revision must first be finalized. Finalizing a revision tells AWS Data Exchange that your changes to the assets in the revision are complete. After it's in this read-only state, you can publish the revision to your products. Finalized revisions can be published through the AWS Data Exchange console or the AWS Marketplace Catalog API, using the StartChangeSet AWS Marketplace Catalog API action. When using the API, revisions are uniquely identified by their ARN.

Type: Boolean

Id

The unique identifier for the revision.

Type: String

RevocationComment

A required comment to inform subscribers of the reason their access to the revision was revoked.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 512.

Revoked

A status indicating that subscribers' access to the revision was revoked.

Type: Boolean

RevokedAt

The date and time that the revision was revoked, in ISO 8601 format.

Type: Timestamp

SourceId

The revision ID of the owned revision corresponding to the entitled revision being viewed. This parameter is returned when a revision owner is viewing the entitled copy of its owned revision.

Type: String

Tags

The tags for the revision.

Type: String to string map

UpdatedAt

The date and time that the revision was last updated, in ISO 8601 format.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to the resource is denied.

HTTP Status Code: 403

InternalServerError

An exception occurred with the service.

HTTP Status Code: 500

ResourceNotFoundException

The resource couldn't be found.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteAsset

This operation deletes an asset.

Request Syntax

```
DELETE /v1/data-sets/DataSetId/revisions/RevisionId/assets/AssetId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

AssetId

The unique identifier for an asset.

Required: Yes

DataSetId

The unique identifier for a data set.

Required: Yes

RevisionId

The unique identifier for a revision.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to the resource is denied.

HTTP Status Code: 403

ConflictException

The request couldn't be completed because it conflicted with the current state of the resource.

HTTP Status Code: 409

InternalServerErrorException

An exception occurred with the service.

HTTP Status Code: 500

ResourceNotFoundException

The resource couldn't be found.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)

- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteDataGrant

This operation deletes a data grant.

Request Syntax

```
DELETE /v1/data-grants/DataGrantId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

DataGrantId

The ID of the data grant to delete.

Pattern: `[a-zA-Z0-9]{30,40}$|^arn:aws:dataexchange:[\a-z0-9]*:(\d{12}):data-grants\[a-zA-Z0-9]{30,40}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to the resource is denied.

HTTP Status Code: 403

InternalServerErrorException

An exception occurred with the service.

HTTP Status Code: 500

ResourceNotFoundException

The resource couldn't be found.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteDataSet

This operation deletes a data set.

Request Syntax

```
DELETE /v1/data-sets/DataSetId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

DataSetId

The unique identifier for a data set.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to the resource is denied.

HTTP Status Code: 403

ConflictException

The request couldn't be completed because it conflicted with the current state of the resource.

HTTP Status Code: 409

InternalServerError

An exception occurred with the service.

HTTP Status Code: 500

ResourceNotFoundException

The resource couldn't be found.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteEventAction

This operation deletes the event action.

Request Syntax

```
DELETE /v1/event-actions/EventActionId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

EventActionId

The unique identifier for the event action.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

An exception occurred with the service.

HTTP Status Code: 500

ResourceNotFoundException

The resource couldn't be found.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

DeleteRevision

This operation deletes a revision.

Request Syntax

```
DELETE /v1/data-sets/DataSetId/revisions/RevisionId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

DataSetId

The unique identifier for a data set.

Required: Yes

RevisionId

The unique identifier for a revision.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to the resource is denied.

HTTP Status Code: 403

ConflictException

The request couldn't be completed because it conflicted with the current state of the resource.

HTTP Status Code: 409

InternalServerErrorException

An exception occurred with the service.

HTTP Status Code: 500

ResourceNotFoundException

The resource couldn't be found.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetAsset

This operation returns information about an asset.

Request Syntax

```
GET /v1/data-sets/DataSetId/revisions/RevisionId/assets/AssetId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

AssetId

The unique identifier for an asset.

Required: Yes

DataSetId

The unique identifier for a data set.

Required: Yes

RevisionId

The unique identifier for a revision.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string",
  "AssetDetails": {
    "ApiGatewayApiAsset": {
```

```

    "ApiDescription": "string",
    "ApiEndpoint": "string",
    "ApiId": "string",
    "ApiKey": "string",
    "ApiName": "string",
    "ApiSpecificationDownloadUrl": "string",
    "ApiSpecificationDownloadUrlExpiresAt": "string",
    "ProtocolType": "string",
    "Stage": "string"
  },
  "LakeFormationDataPermissionAsset": {
    "LakeFormationDataPermissionDetails": {
      "LFTagPolicy": {
        "CatalogId": "string",
        "ResourceDetails": {
          "Database": {
            "Expression": [
              {
                "TagKey": "string",
                "TagValues": [ "string" ]
              }
            ]
          },
          "Table": {
            "Expression": [
              {
                "TagKey": "string",
                "TagValues": [ "string" ]
              }
            ]
          }
        }
      },
      "ResourceType": "string"
    }
  },
  "LakeFormationDataPermissionType": "string",
  "Permissions": [ "string" ],
  "RoleArn": "string"
},
"RedshiftDataShareAsset": {
  "Arn": "string"
},
"S3DataAccessAsset": {
  "Bucket": "string",

```

```
    "KeyPrefixes": [ "string" ],
    "Keys": [ "string" ],
    "KmsKeysToGrant": [
      {
        "KmsKeyArn": "string"
      }
    ],
    "S3AccessPointAlias": "string",
    "S3AccessPointArn": "string"
  },
  "S3SnapshotAsset": {
    "Size": number
  }
},
"AssetType": "string",
"CreatedAt": "string",
"DataSetId": "string",
"Id": "string",
"Name": "string",
"RevisionId": "string",
"SourceId": "string",
"UpdatedAt": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Arn](#)

The ARN for the asset.

Type: String

[AssetDetails](#)

Details about the asset.

Type: [AssetDetails](#) object

[AssetType](#)

The type of asset that is added to a data set.

Type: String

Valid Values: S3_SNAPSHOT | REDSHIFT_DATA_SHARE | API_GATEWAY_API | S3_DATA_ACCESS | LAKE_FORMATION_DATA_PERMISSION

CreatedAt

The date and time that the asset was created, in ISO 8601 format.

Type: Timestamp

DataSetId

The unique identifier for the data set associated with this asset.

Type: String

Id

The unique identifier for the asset.

Type: String

Name

The name of the asset. When importing from Amazon S3, the Amazon S3 object key is used as the asset name. When exporting to Amazon S3, the asset name is used as default target Amazon S3 object key. When importing from Amazon API Gateway API, the API name is used as the asset name. When importing from Amazon Redshift, the datashare name is used as the asset name. When importing from AWS Lake Formation, the static values of "Database(s) included in the LF-tag policy" or "Table(s) included in the LF-tag policy" are used as the asset name.

Type: String

RevisionId

The unique identifier for the revision associated with this asset.

Type: String

SourceId

The asset ID of the owned asset corresponding to the entitled asset being viewed. This parameter is returned when an asset owner is viewing the entitled copy of its owned asset.

Type: String

UpdatedAt

The date and time that the asset was last updated, in ISO 8601 format.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An exception occurred with the service.

HTTP Status Code: 500

ResourceNotFoundException

The resource couldn't be found.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)

- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetDataGrant

This operation returns information about a data grant.

Request Syntax

```
GET /v1/data-grants/DataGrantId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

DataGrantId

The ID of the data grant.

Pattern: `[a-zA-Z0-9]{30,40}$|^arn:aws:dataexchange:[\a-z0-9]*:(\d{12}):data-grants\[a-zA-Z0-9]{30,40}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "AcceptanceState": "string",
  "AcceptedAt": "string",
  "Arn": "string",
  "CreatedAt": "string",
  "DataSetId": "string",
  "Description": "string",
  "EndsAt": "string",
  "GrantDistributionScope": "string",
  "Id": "string",
```



```
"Name": "string",
"ReceiverPrincipal": "string",
"SenderPrincipal": "string",
"SourceDataSetId": "string",
"Tags": {
  "string" : "string"
},
"UpdatedAt": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AcceptanceState

The acceptance state of the data grant.

Type: String

Valid Values: PENDING_RECEIVER_ACCEPTANCE | ACCEPTED

AcceptedAt

The timestamp of when the data grant was accepted.

Type: Timestamp

Arn

The Amazon Resource Name (ARN) of the data grant.

Type: String

CreatedAt

The timestamp of when the data grant was created.

Type: Timestamp

DataSetId

The ID of the data set associated to the data grant.

Type: String

Description

The description of the data grant.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 16384.

EndsAt

The timestamp of when access to the associated data set ends.

Type: Timestamp

GrantDistributionScope

The distribution scope for the data grant.

Type: String

Valid Values: AWS_ORGANIZATION | NONE

Id

The ID of the data grant.

Type: String

Name

The name of the data grant.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

ReceiverPrincipal

The AWS account ID of the data grant receiver.

Type: String

Pattern: `\d{12}`

SenderPrincipal

The AWS account ID of the data grant sender.

Type: String

Pattern: \d{12}

SourceDataSetId

The ID of the data set used to create the data grant.

Type: String

Tags

The tags associated to the data grant. A tag is a key-value pair.

Type: String to string map

UpdatedAt

The timestamp of when the data grant was last updated.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to the resource is denied.

HTTP Status Code: 403

InternalServerErrorException

An exception occurred with the service.

HTTP Status Code: 500

ResourceNotFoundException

The resource couldn't be found.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetDataSet

This operation returns information about a data set.

Request Syntax

```
GET /v1/data-sets/DataSetId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

DataSetId

The unique identifier for a data set.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string",
  "AssetType": "string",
  "CreatedAt": "string",
  "Description": "string",
  "Id": "string",
  "Name": "string",
  "Origin": "string",
  "OriginDetails": {
    "DataGrantId": "string",
    "ProductId": "string"
  },
  "SourceId": "string",
```

```
"Tags": {  
  "string" : "string"  
},  
"UpdatedAt": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The ARN for the data set.

Type: String

AssetType

The type of asset that is added to a data set.

Type: String

Valid Values: S3_SNAPSHOT | REDSHIFT_DATA_SHARE | API_GATEWAY_API | S3_DATA_ACCESS | LAKE_FORMATION_DATA_PERMISSION

CreatedAt

The date and time that the data set was created, in ISO 8601 format.

Type: Timestamp

Description

The description for the data set.

Type: String

Id

The unique identifier for the data set.

Type: String

Name

The name of the data set.

Type: String

Origin

A property that defines the data set as OWNED by the account (for providers) or ENTITLED to the account (for subscribers).

Type: String

Valid Values: OWNED | ENTITLED

OriginDetails

If the origin of this data set is ENTITLED, includes the details for the product on AWS Marketplace.

Type: [OriginDetails](#) object

SourceId

The data set ID of the owned data set corresponding to the entitled data set being viewed. This parameter is returned when a data set owner is viewing the entitled copy of its owned data set.

Type: String

Tags

The tags for the data set.

Type: String to string map

UpdatedAt

The date and time that the data set was last updated, in ISO 8601 format.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An exception occurred with the service.

HTTP Status Code: 500

ResourceNotFoundException

The resource couldn't be found.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetEventAction

This operation retrieves information about an event action.

Request Syntax

```
GET /v1/event-actions/EventActionId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

EventActionId

The unique identifier for the event action.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Action": {
    "ExportRevisionToS3": {
      "Encryption": {
        "KmsKeyArn": "string",
        "Type": "string"
      },
      "RevisionDestination": {
        "Bucket": "string",
        "KeyPattern": "string"
      }
    }
  }
},
```

```
"Arn": "string",
"CreatedAt": "string",
"Event": {
  "RevisionPublished": {
    "DataSetId": "string"
  }
},
"Id": "string",
"UpdatedAt": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Action

What occurs after a certain event.

Type: [Action](#) object

Arn

The ARN for the event action.

Type: String

CreatedAt

The date and time that the event action was created, in ISO 8601 format.

Type: Timestamp

Event

What occurs to start an action.

Type: [Event](#) object

Id

The unique identifier for the event action.

Type: String

UpdatedAt

The date and time that the event action was last updated, in ISO 8601 format.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An exception occurred with the service.

HTTP Status Code: 500

ResourceNotFoundException

The resource couldn't be found.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetJob

This operation returns information about a job.

Request Syntax

```
GET /v1/jobs/JobId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

JobId

The unique identifier for a job.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string",
  "CreatedAt": "string",
  "Details": {
    "CreateS3DataAccessFromS3Bucket": {
      "AssetSource": {
        "Bucket": "string",
        "KeyPrefixes": [ "string ],
        "Keys": [ "string ],
        "KmsKeysToGrant": [
          {
            "KmsKeyArn": "string"
          }
        ]
      }
    }
  }
}
```

```
    },
    "DataSetId": "string",
    "RevisionId": "string"
  },
  "ExportAssetsToS3": {
    "AssetDestinations": [
      {
        "AssetId": "string",
        "Bucket": "string",
        "Key": "string"
      }
    ],
    "DataSetId": "string",
    "Encryption": {
      "KmsKeyArn": "string",
      "Type": "string"
    },
    "RevisionId": "string"
  },
  "ExportAssetToSignedUrl": {
    "AssetId": "string",
    "DataSetId": "string",
    "RevisionId": "string",
    "SignedUrl": "string",
    "SignedUrlExpiresAt": "string"
  },
  "ExportRevisionsToS3": {
    "DataSetId": "string",
    "Encryption": {
      "KmsKeyArn": "string",
      "Type": "string"
    },
    "EventActionArn": "string",
    "RevisionDestinations": [
      {
        "Bucket": "string",
        "KeyPattern": "string",
        "RevisionId": "string"
      }
    ]
  },
  "ImportAssetFromApiGatewayApi": {
    "ApiDescription": "string",
    "ApiId": "string",
```

```

    "ApiKey": "string",
    "ApiName": "string",
    "ApiSpecificationMd5Hash": "string",
    "ApiSpecificationUploadUrl": "string",
    "ApiSpecificationUploadUrlExpiresAt": "string",
    "DataSetId": "string",
    "ProtocolType": "string",
    "RevisionId": "string",
    "Stage": "string"
  },
  "ImportAssetFromSignedUrl": {
    "AssetName": "string",
    "DataSetId": "string",
    "Md5Hash": "string",
    "RevisionId": "string",
    "SignedUrl": "string",
    "SignedUrlExpiresAt": "string"
  },
  "ImportAssetsFromLakeFormationTagPolicy": {
    "CatalogId": "string",
    "Database": {
      "Expression": [
        {
          "TagKey": "string",
          "TagValues": [ "string" ]
        }
      ],
      "Permissions": [ "string" ]
    },
    "DataSetId": "string",
    "RevisionId": "string",
    "RoleArn": "string",
    "Table": {
      "Expression": [
        {
          "TagKey": "string",
          "TagValues": [ "string" ]
        }
      ],
      "Permissions": [ "string" ]
    }
  },
  "ImportAssetsFromRedshiftDataShares": {
    "AssetSources": [

```

```

    {
      "DataShareArn": "string"
    }
  ],
  "DataSetId": "string",
  "RevisionId": "string"
},
"ImportAssetsFromS3": {
  "AssetSources": [
    {
      "Bucket": "string",
      "Key": "string"
    }
  ],
  "DataSetId": "string",
  "RevisionId": "string"
}
},
"Errors": [
  {
    "Code": "string",
    "Details": {
      "ImportAssetFromSignedUrlJobErrorDetails": {
        "AssetName": "string"
      },
      "ImportAssetsFromS3JobErrorDetails": [
        {
          "Bucket": "string",
          "Key": "string"
        }
      ]
    },
    "LimitName": "string",
    "LimitValue": number,
    "Message": "string",
    "ResourceId": "string",
    "ResourceType": "string"
  }
],
"Id": "string",
"State": "string",
"Type": "string",
"UpdatedAt": "string"

```



```
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The ARN for the job.

Type: String

CreatedAt

The date and time that the job was created, in ISO 8601 format.

Type: Timestamp

Details

Details about the job.

Type: [ResponseDetails](#) object

Errors

The errors associated with jobs.

Type: Array of [JobError](#) objects

Id

The unique identifier for the job.

Type: String

State

The state of the job.

Type: String

Valid Values: WAITING | IN_PROGRESS | ERROR | COMPLETED | CANCELLED | TIMED_OUT

Type

The job type.

Type: String

Valid Values: IMPORT_ASSETS_FROM_S3 | IMPORT_ASSET_FROM_SIGNED_URL
| EXPORT_ASSETS_TO_S3 | EXPORT_ASSET_TO_SIGNED_URL |
EXPORT_REVISIONS_TO_S3 | IMPORT_ASSETS_FROM_REDSHIFT_DATA_SHARES |
IMPORT_ASSET_FROM_API_GATEWAY_API | CREATE_S3_DATA_ACCESS_FROM_S3_BUCKET
| IMPORT_ASSETS_FROM_LAKE_FORMATION_TAG_POLICY

UpdatedAt

The date and time that the job was last updated, in ISO 8601 format.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An exception occurred with the service.

HTTP Status Code: 500

ResourceNotFoundException

The resource couldn't be found.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetReceivedDataGrant

This operation returns information about a received data grant.

Request Syntax

```
GET /v1/received-data-grants/DataGrantArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

DataGrantArn

The Amazon Resource Name (ARN) of the data grant.

Pattern: `arn:aws:dataexchange:[\ -a-z0-9]*:(\d{12}):data-grants\[a-zA-Z0-9\]{30,40}`

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "AcceptanceState": "string",
  "AcceptedAt": "string",
  "Arn": "string",
  "CreatedAt": "string",
  "DataSetId": "string",
  "Description": "string",
  "EndsAt": "string",
  "GrantDistributionScope": "string",
  "Id": "string",
```

```
"Name": "string",  
"ReceiverPrincipal": "string",  
"SenderPrincipal": "string",  
"UpdatedAt": "string"  
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

AcceptanceState

The acceptance state of the data grant.

Type: String

Valid Values: PENDING_RECEIVER_ACCEPTANCE | ACCEPTED

AcceptedAt

The timestamp of when the data grant was accepted.

Type: Timestamp

Arn

The Amazon Resource Name (ARN) of the data grant.

Type: String

CreatedAt

The timestamp of when the data grant was created.

Type: Timestamp

DataSetId

The ID of the data set associated to the data grant.

Type: String

Description

The description of the data grant.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 16384.

EndsAt

The timestamp of when access to the associated data set ends.

Type: Timestamp

GrantDistributionScope

The distribution scope for the data grant.

Type: String

Valid Values: AWS_ORGANIZATION | NONE

Id

The ID of the data grant.

Type: String

Name

The name of the data grant.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

ReceiverPrincipal

The AWS account ID of the data grant receiver.

Type: String

Pattern: \d{12}

SenderPrincipal

The AWS account ID of the data grant sender.

Type: String

Pattern: \d{12}

UpdatedAt

The timestamp of when the data grant was last updated.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to the resource is denied.

HTTP Status Code: 403

InternalServerErrorException

An exception occurred with the service.

HTTP Status Code: 500

ResourceNotFoundException

The resource couldn't be found.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

GetRevision

This operation returns information about a revision.

Request Syntax

```
GET /v1/data-sets/DataSetId/revisions/RevisionId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

DataSetId

The unique identifier for a data set.

Required: Yes

RevisionId

The unique identifier for a revision.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string",
  "Comment": "string",
  "CreatedAt": "string",
  "DataSetId": "string",
  "Finalized": boolean,
  "Id": "string",
  "RevocationComment": "string",
```

```
"Revoked": boolean,
"RevokedAt": "string",
"SourceId": "string",
"Tags": {
  "string" : "string"
},
"UpdatedAt": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The ARN for the revision.

Type: String

Comment

An optional comment about the revision.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

CreatedAt

The date and time that the revision was created, in ISO 8601 format.

Type: Timestamp

DataSetId

The unique identifier for the data set associated with the data set revision.

Type: String

Finalized

To publish a revision to a data set in a product, the revision must first be finalized. Finalizing a revision tells AWS Data Exchange that your changes to the assets in the revision are complete.

After it's in this read-only state, you can publish the revision to your products. Finalized revisions can be published through the AWS Data Exchange console or the AWS Marketplace Catalog API, using the StartChangeSet AWS Marketplace Catalog API action. When using the API, revisions are uniquely identified by their ARN.

Type: Boolean

Id

The unique identifier for the revision.

Type: String

RevocationComment

A required comment to inform subscribers of the reason their access to the revision was revoked.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 512.

Revoked

A status indicating that subscribers' access to the revision was revoked.

Type: Boolean

RevokedAt

The date and time that the revision was revoked, in ISO 8601 format.

Type: Timestamp

SourceId

The revision ID of the owned revision corresponding to the entitled revision being viewed. This parameter is returned when a revision owner is viewing the entitled copy of its owned revision.

Type: String

Tags

The tags for the revision.

Type: String to string map

UpdatedAt

The date and time that the revision was last updated, in ISO 8601 format.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An exception occurred with the service.

HTTP Status Code: 500

ResourceNotFoundException

The resource couldn't be found.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListDataGrants

This operation returns information about all data grants.

Request Syntax

```
GET /v1/data-grants?maxResults=MaxResults&nextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[MaxResults](#)

The maximum number of results to be included in the next page.

Valid Range: Minimum value of 1. Maximum value of 200.

[NextToken](#)

The pagination token used to retrieve the next page of results for this operation.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "DataGrantSummaries": [
    {
      "AcceptanceState": "string",
      "AcceptedAt": "string",
      "Arn": "string",
      "CreatedAt": "string",
      "DataSetId": "string",
      "EndsAt": "string",
      "Id": "string",
```

```
    "Name": "string",
    "ReceiverPrincipal": "string",
    "SenderPrincipal": "string",
    "SourceDataSetId": "string",
    "UpdatedAt": "string"
  }
],
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DataGrantSummaries

An object that contains a list of data grant information.

Type: Array of [DataGrantSummaryEntry](#) objects

NextToken

The pagination token used to retrieve the next page of results for this operation.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to the resource is denied.

HTTP Status Code: 403

InternalServerErrorException

An exception occurred with the service.

HTTP Status Code: 500

ResourceNotFoundException

The resource couldn't be found.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListDataSetRevisions

This operation lists a data set's revisions sorted by CreatedAt in descending order.

Request Syntax

```
GET /v1/data-sets/DataSetId/revisions?maxResults=MaxResults&nextToken=NextToken  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[DataSetId](#)

The unique identifier for a data set.

Required: Yes

[MaxResults](#)

The maximum number of results returned by a single call.

Valid Range: Minimum value of 1. Maximum value of 200.

[NextToken](#)

The token value retrieved from a previous call to access the next page of results.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json  
  
{  
  "NextToken": "string",  
  "Revisions": [  
    ...  
  ]  
}
```

```
{
  "Arn": "string",
  "Comment": "string",
  "CreatedAt": "string",
  "DataSetId": "string",
  "Finalized": boolean,
  "Id": "string",
  "RevocationComment": "string",
  "Revoked": boolean,
  "RevokedAt": "string",
  "SourceId": "string",
  "UpdatedAt": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

NextToken

The token value retrieved from a previous call to access the next page of results.

Type: String

Revisions

The asset objects listed by the request.

Type: Array of [RevisionEntry](#) objects

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

An exception occurred with the service.

HTTP Status Code: 500

ResourceNotFoundException

The resource couldn't be found.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListDataSets

This operation lists your data sets. When listing by origin OWNED, results are sorted by CreatedAt in descending order. When listing by origin ENTITLED, there is no order.

Request Syntax

```
GET /v1/data-sets?maxResults=MaxResults&nextToken=NextToken&origin=Origin HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

MaxResults

The maximum number of results returned by a single call.

Valid Range: Minimum value of 1. Maximum value of 200.

NextToken

The token value retrieved from a previous call to access the next page of results.

Origin

A property that defines the data set as OWNED by the account (for providers) or ENTITLED to the account (for subscribers).

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "DataSets": [
    {
```

```
    "Arn": "string",
    "AssetType": "string",
    "CreatedAt": "string",
    "Description": "string",
    "Id": "string",
    "Name": "string",
    "Origin": "string",
    "OriginDetails": {
      "DataGrantId": "string",
      "ProductId": "string"
    },
    "SourceId": "string",
    "UpdatedAt": "string"
  }
],
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DataSets

The data set objects listed by the request.

Type: Array of [DataSetEntry](#) objects

NextToken

The token value retrieved from a previous call to access the next page of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An exception occurred with the service.

HTTP Status Code: 500

ResourceNotFoundException

The resource couldn't be found.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListEventActions

This operation lists your event actions.

Request Syntax

```
GET /v1/event-actions?  
eventSourceId=EventSourceId&maxResults=MaxResults&nextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

EventSourceId

The unique identifier for the event source.

MaxResults

The maximum number of results returned by a single call.

Valid Range: Minimum value of 1. Maximum value of 200.

NextToken

The token value retrieved from a previous call to access the next page of results.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json  
  
{  
  "EventActions": [  
    {  
      "Action": {  
        "ExportRevisionToS3": {  
          "Encryption": {  
            "KmsKeyArn": "string",
```

```

        "Type": "string"
      },
      "RevisionDestination": {
        "Bucket": "string",
        "KeyPattern": "string"
      }
    }
  },
  "Arn": "string",
  "CreatedAt": "string",
  "Event": {
    "RevisionPublished": {
      "DataSetId": "string"
    }
  },
  "Id": "string",
  "UpdatedAt": "string"
}
],
"NextToken": "string"
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

EventActions

The event action objects listed by the request.

Type: Array of [EventActionEntry](#) objects

NextToken

The token value retrieved from a previous call to access the next page of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An exception occurred with the service.

HTTP Status Code: 500

ResourceNotFoundException

The resource couldn't be found.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListJobs

This operation lists your jobs sorted by CreatedAt in descending order.

Request Syntax

```
GET /v1/jobs?  
dataSetId=DataSetId&maxResults=MaxResults&nextToken=NextToken&revisionId=RevisionId  
HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

[DataSetId](#)

The unique identifier for a data set.

[MaxResults](#)

The maximum number of results returned by a single call.

Valid Range: Minimum value of 1. Maximum value of 200.

[NextToken](#)

The token value retrieved from a previous call to access the next page of results.

[RevisionId](#)

The unique identifier for a revision.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json  
  
{  
  "Jobs": [  
    {  
      "CreatedAt": "2017-08-01T12:00:00.000Z"  
    }  
  ]  
}
```

```

{
  "Arn": "string",
  "CreatedAt": "string",
  "Details": {
    "CreateS3DataAccessFromS3Bucket": {
      "AssetSource": {
        "Bucket": "string",
        "KeyPrefixes": [ "string" ],
        "Keys": [ "string" ],
        "KmsKeysToGrant": [
          {
            "KmsKeyArn": "string"
          }
        ]
      },
      "DataSetId": "string",
      "RevisionId": "string"
    },
    "ExportAssetsToS3": {
      "AssetDestinations": [
        {
          "AssetId": "string",
          "Bucket": "string",
          "Key": "string"
        }
      ],
      "DataSetId": "string",
      "Encryption": {
        "KmsKeyArn": "string",
        "Type": "string"
      },
      "RevisionId": "string"
    },
    "ExportAssetToSignedUrl": {
      "AssetId": "string",
      "DataSetId": "string",
      "RevisionId": "string",
      "SignedUrl": "string",
      "SignedUrlExpiresAt": "string"
    },
    "ExportRevisionsToS3": {
      "DataSetId": "string",
      "Encryption": {
        "KmsKeyArn": "string",

```

```

    "Type": "string"
  },
  "EventActionArn": "string",
  "RevisionDestinations": [
    {
      "Bucket": "string",
      "KeyPattern": "string",
      "RevisionId": "string"
    }
  ]
},
"ImportAssetFromApiGatewayApi": {
  "ApiDescription": "string",
  "ApiId": "string",
  "ApiKey": "string",
  "ApiName": "string",
  "ApiSpecificationMd5Hash": "string",
  "ApiSpecificationUploadUrl": "string",
  "ApiSpecificationUploadUrlExpiresAt": "string",
  "DataSetId": "string",
  "ProtocolType": "string",
  "RevisionId": "string",
  "Stage": "string"
},
"ImportAssetFromSignedUrl": {
  "AssetName": "string",
  "DataSetId": "string",
  "Md5Hash": "string",
  "RevisionId": "string",
  "SignedUrl": "string",
  "SignedUrlExpiresAt": "string"
},
"ImportAssetsFromLakeFormationTagPolicy": {
  "CatalogId": "string",
  "Database": {
    "Expression": [
      {
        "TagKey": "string",
        "TagValues": [ "string" ]
      }
    ],
    "Permissions": [ "string" ]
  },
  "DataSetId": "string",

```

```

    "RevisionId": "string",
    "RoleArn": "string",
    "Table": {
      "Expression": [
        {
          "TagKey": "string",
          "TagValues": [ "string" ]
        }
      ],
      "Permissions": [ "string" ]
    }
  },
  "ImportAssetsFromRedshiftDataShares": {
    "AssetSources": [
      {
        "DataShareArn": "string"
      }
    ],
    "DataSetId": "string",
    "RevisionId": "string"
  },
  "ImportAssetsFromS3": {
    "AssetSources": [
      {
        "Bucket": "string",
        "Key": "string"
      }
    ],
    "DataSetId": "string",
    "RevisionId": "string"
  }
},
"Errors": [
  {
    "Code": "string",
    "Details": {
      "ImportAssetFromSignedUrlJobErrorDetails": {
        "AssetName": "string"
      },
      "ImportAssetsFromS3JobErrorDetails": [
        {
          "Bucket": "string",
          "Key": "string"
        }
      ]
    }
  }
]

```

```
    ]
    },
    "LimitName": "string",
    "LimitValue": number,
    "Message": "string",
    "ResourceId": "string",
    "ResourceType": "string"
  }
],
"Id": "string",
"State": "string",
"Type": "string",
"UpdatedAt": "string"
}
],
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Jobs

The jobs listed by the request.

Type: Array of [JobEntry](#) objects

NextToken

The token value retrieved from a previous call to access the next page of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerError

An exception occurred with the service.

HTTP Status Code: 500

ResourceNotFoundException

The resource couldn't be found.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListReceivedDataGrants

This operation returns information about all received data grants.

Request Syntax

```
GET /v1/received-data-grants?  
acceptanceState=AcceptanceState&maxResults=MaxResults&nextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

AcceptanceState

The acceptance state of the data grants to list.

Valid Values: PENDING_RECEIVER_ACCEPTANCE | ACCEPTED

MaxResults

The maximum number of results to be included in the next page.

Valid Range: Minimum value of 1. Maximum value of 200.

NextToken

The pagination token used to retrieve the next page of results for this operation.

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json  
  
{  
  "DataGrantSummaries": [  
    {
```



```
    "AcceptanceState": "string",
    "AcceptedAt": "string",
    "Arn": "string",
    "CreatedAt": "string",
    "DataSetId": "string",
    "EndsAt": "string",
    "Id": "string",
    "Name": "string",
    "ReceiverPrincipal": "string",
    "SenderPrincipal": "string",
    "UpdatedAt": "string"
  }
],
"NextToken": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

DataGrantSummaries

An object that contains a list of received data grant information.

Type: Array of [ReceivedDataGrantSummariesEntry](#) objects

NextToken

The pagination token used to retrieve the next page of results for this operation.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to the resource is denied.

HTTP Status Code: 403

InternalServerErrorException

An exception occurred with the service.

HTTP Status Code: 500

ResourceNotFoundException

The resource couldn't be found.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListRevisionAssets

This operation lists a revision's assets sorted alphabetically in descending order.

Request Syntax

```
GET /v1/data-sets/DataSetId/revisions/RevisionId/assets?  
maxResults=MaxResults&nextToken=NextToken HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

DataSetId

The unique identifier for a data set.

Required: Yes

MaxResults

The maximum number of results returned by a single call.

Valid Range: Minimum value of 1. Maximum value of 200.

NextToken

The token value retrieved from a previous call to access the next page of results.

RevisionId

The unique identifier for a revision.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200  
Content-type: application/json
```

```

{
  "Assets": [
    {
      "Arn": "string",
      "AssetDetails": {
        "ApiGatewayApiAsset": {
          "ApiDescription": "string",
          "ApiEndpoint": "string",
          "ApiId": "string",
          "ApiKey": "string",
          "ApiName": "string",
          "ApiSpecificationDownloadUrl": "string",
          "ApiSpecificationDownloadUrlExpiresAt": "string",
          "ProtocolType": "string",
          "Stage": "string"
        },
        "LakeFormationDataPermissionAsset": {
          "LakeFormationDataPermissionDetails": {
            "LFTagPolicy": {
              "CatalogId": "string",
              "ResourceDetails": {
                "Database": {
                  "Expression": [
                    {
                      "TagKey": "string",
                      "TagValues": [ "string" ]
                    }
                  ]
                },
              "Table": {
                "Expression": [
                  {
                    "TagKey": "string",
                    "TagValues": [ "string" ]
                  }
                ]
              }
            },
            "ResourceType": "string"
          }
        },
        "LakeFormationDataPermissionType": "string",
        "Permissions": [ "string" ],
        "RoleArn": "string"
      }
    }
  ]
}

```

```

    },
    "RedshiftDataShareAsset": {
      "Arn": "string"
    },
    "S3DataAccessAsset": {
      "Bucket": "string",
      "KeyPrefixes": [ "string" ],
      "Keys": [ "string" ],
      "KmsKeysToGrant": [
        {
          "KmsKeyArn": "string"
        }
      ],
      "S3AccessPointAlias": "string",
      "S3AccessPointArn": "string"
    },
    "S3SnapshotAsset": {
      "Size": number
    }
  },
  "AssetType": "string",
  "CreatedAt": "string",
  "DataSetId": "string",
  "Id": "string",
  "Name": "string",
  "RevisionId": "string",
  "SourceId": "string",
  "UpdatedAt": "string"
}
],
"NextToken": "string"
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Assets

The asset objects listed by the request.

Type: Array of [AssetEntry](#) objects

NextToken

The token value retrieved from a previous call to access the next page of results.

Type: String

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

InternalServerErrorException

An exception occurred with the service.

HTTP Status Code: 500

ResourceNotFoundException

The resource couldn't be found.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

ListTagsForResource

This operation lists the tags on the resource.

Request Syntax

```
GET /tags/ResourceArn HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ResourceArn

An Amazon Resource Name (ARN) that uniquely identifies an AWS resource.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "tags": {
    "string" : "string"
  }
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

tags

A label that consists of a customer-defined key and an optional value.

Type: String to string map

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

RevokeRevision

This operation revokes subscribers' access to a revision.

Request Syntax

```
POST /v1/data-sets/DataSetId/revisions/RevisionId/revoke HTTP/1.1
Content-type: application/json

{
  "RevocationComment": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

DataSetId

The unique identifier for a data set.

Required: Yes

RevisionId

The unique identifier for a revision.

Required: Yes

Request Body

The request accepts the following data in JSON format.

RevocationComment

A required comment to inform subscribers of the reason their access to the revision was revoked.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 512.

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string",
  "Comment": "string",
  "CreatedAt": "string",
  "DataSetId": "string",
  "Finalized": boolean,
  "Id": "string",
  "RevocationComment": "string",
  "Revoked": boolean,
  "RevokedAt": "string",
  "SourceId": "string",
  "UpdatedAt": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The ARN for the revision.

Type: String

Comment

An optional comment about the revision.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

CreatedAt

The date and time that the revision was created, in ISO 8601 format.

Type: Timestamp

DataSetId

The unique identifier for the data set associated with the data set revision.

Type: String

Finalized

To publish a revision to a data set in a product, the revision must first be finalized. Finalizing a revision tells AWS Data Exchange that changes to the assets in the revision are complete. After it's in this read-only state, you can publish the revision to your products. Finalized revisions can be published through the AWS Data Exchange console or the AWS Marketplace Catalog API, using the StartChangeSet AWS Marketplace Catalog API action. When using the API, revisions are uniquely identified by their ARN.

Type: Boolean

Id

The unique identifier for the revision.

Type: String

RevocationComment

A required comment to inform subscribers of the reason their access to the revision was revoked.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 512.

Revoked

A status indicating that subscribers' access to the revision was revoked.

Type: Boolean

RevokedAt

The date and time that the revision was revoked, in ISO 8601 format.

Type: Timestamp

SourceId

The revision ID of the owned revision corresponding to the entitled revision being viewed. This parameter is returned when a revision owner is viewing the entitled copy of its owned revision.

Type: String

UpdatedAt

The date and time that the revision was last updated, in ISO 8601 format.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to the resource is denied.

HTTP Status Code: 403

ConflictException

The request couldn't be completed because it conflicted with the current state of the resource.

HTTP Status Code: 409

InternalServerError

An exception occurred with the service.

HTTP Status Code: 500

ResourceNotFoundException

The resource couldn't be found.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

SendApiAsset

This operation invokes an API Gateway API asset. The request is proxied to the provider's API Gateway API.

Request Syntax

```
POST /v1?QueryStringParameters HTTP/1.1
x-amzn-dataexchange-asset-id: AssetId
x-amzn-dataexchange-data-set-id: DataSetId
x-amzn-dataexchange-http-method: Method
x-amzn-dataexchange-path: Path
x-amzn-dataexchange-revision-id: RevisionId
```

Body

URI Request Parameters

The request uses the following URI parameters.

[AssetId](#)

Asset ID value for the API request.

Required: Yes

[DataSetId](#)

Data set ID value for the API request.

Required: Yes

[Method](#)

HTTP method value for the API request. Alternatively, you can use the appropriate verb in your request.

[Path](#)

URI path value for the API request. Alternatively, you can set the URI path directly by invoking /v1/{pathValue}.

QueryStringParameters

Attach query string parameters to the end of the URI (for example, /v1/examplePath?exampleParam=exampleValue).

RevisionId

Revision ID value for the API request.

Required: Yes

Request Body

The request accepts the following string data.

Body

The request body.

Response Syntax

```
HTTP/1.1 200
```

Body

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The response returns the following as the HTTP body.

Body

The response body from the underlying API tracked by the API asset.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to the resource is denied.

HTTP Status Code: 403

InternalServerError

An exception occurred with the service.

HTTP Status Code: 500

ResourceNotFoundException

The resource couldn't be found.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

SendDataSetNotification

The type of event associated with the data set.

Request Syntax

```
POST /v1/data-sets/DataSetId/notification HTTP/1.1
```

```
Content-type: application/json
```

```
{
  "ClientToken": "string",
  "Comment": "string",
  "Details": {
    "DataUpdate": {
      "DataUpdatedAt": "string"
    },
    "Deprecation": {
      "DeprecationAt": "string"
    },
    "SchemaChange": {
      "Changes": [
        {
          "Description": "string",
          "Name": "string",
          "Type": "string"
        }
      ],
      "SchemaChangeAt": "string"
    }
  },
  "Scope": {
    "LakeFormationTagPolicies": [
      {
        "Database": "string",
        "Table": "string"
      }
    ],
    "RedshiftDataShares": [
      {
        "Arn": "string",
        "Database": "string",
        "Function": "string",
        "Schema": "string",

```

```
    "Table": "string",
    "View": "string"
  }
],
"S3DataAccesses": [
  {
    "KeyPrefixes": [ "string" ],
    "Keys": [ "string" ]
  }
]
},
"Type": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

DataSetId

Affected data set of the notification.

Required: Yes

Request Body

The request accepts the following data in JSON format.

ClientToken

Idempotency key for the notification, this key allows us to deduplicate notifications that are sent in quick succession erroneously.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 64.

Pattern: `[\x21-\x7E]{1,64}`

Required: No

Comment

Free-form text field for providers to add information about their notifications.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 4096.

Required: No

Details

Extra details specific to this notification type.

Type: [NotificationDetails](#) object

Required: No

Scope

Affected scope of this notification such as the underlying resources affected by the notification event.

Type: [ScopeDetails](#) object

Required: No

Type

The type of the notification. Describing the kind of event the notification is alerting you to.

Type: String

Valid Values: DATA_DELAY | DATA_UPDATE | DEPRECATION | SCHEMA_CHANGE

Required: Yes

Response Syntax

```
HTTP/1.1 202
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to the resource is denied.

HTTP Status Code: 403

ConflictException

The request couldn't be completed because it conflicted with the current state of the resource.

HTTP Status Code: 409

InternalServerErrorException

An exception occurred with the service.

HTTP Status Code: 500

ResourceNotFoundException

The resource couldn't be found.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)

- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

StartJob

This operation starts a job.

Request Syntax

```
PATCH /v1/jobs/JobId HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

JobId

The unique identifier for a job.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 202
```

Response Elements

If the action is successful, the service sends back an HTTP 202 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to the resource is denied.

HTTP Status Code: 403

ConflictException

The request couldn't be completed because it conflicted with the current state of the resource.

HTTP Status Code: 409

InternalServerErrorException

An exception occurred with the service.

HTTP Status Code: 500

ResourceNotFoundException

The resource couldn't be found.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)

- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

TagResource

This operation tags a resource.

Request Syntax

```
POST /tags/ResourceArn HTTP/1.1
Content-type: application/json
```

```
{
  "tags": {
    "string" : "string"
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

ResourceArn

An Amazon Resource Name (ARN) that uniquely identifies an AWS resource.

Required: Yes

Request Body

The request accepts the following data in JSON format.

tags

A label that consists of a customer-defined key and an optional value.

Type: String to string map

Required: Yes

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UntagResource

This operation removes one or more tags from a resource.

Request Syntax

```
DELETE /tags/ResourceArn?tagKeys=TagKeys HTTP/1.1
```

URI Request Parameters

The request uses the following URI parameters.

ResourceArn

An Amazon Resource Name (ARN) that uniquely identifies an AWS resource.

Required: Yes

TagKeys

The key tags.

Required: Yes

Request Body

The request does not have a request body.

Response Syntax

```
HTTP/1.1 204
```

Response Elements

If the action is successful, the service sends back an HTTP 204 response with an empty HTTP body.

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateAsset

This operation updates an asset.

Request Syntax

```
PATCH /v1/data-sets/DataSetId/revisions/RevisionId/assets/AssetId HTTP/1.1  
Content-type: application/json
```

```
{  
  "Name": "string"  
}
```

URI Request Parameters

The request uses the following URI parameters.

AssetId

The unique identifier for an asset.

Required: Yes

DataSetId

The unique identifier for a data set.

Required: Yes

RevisionId

The unique identifier for a revision.

Required: Yes

Request Body

The request accepts the following data in JSON format.

Name

The name of the asset. When importing from Amazon S3, the Amazon S3 object key is used as the asset name. When exporting to Amazon S3, the asset name is used as default target

Amazon S3 object key. When importing from Amazon API Gateway API, the API name is used as the asset name. When importing from Amazon Redshift, the datashare name is used as the asset name. When importing from AWS Lake Formation, the static values of "Database(s) included in the LF-tag policy" or "Table(s) included in LF-tag policy" are used as the name.

Type: String

Required: Yes

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string",
  "AssetDetails": {
    "ApiGatewayApiAsset": {
      "ApiDescription": "string",
      "ApiEndpoint": "string",
      "ApiId": "string",
      "ApiKey": "string",
      "ApiName": "string",
      "ApiSpecificationDownloadUrl": "string",
      "ApiSpecificationDownloadUrlExpiresAt": "string",
      "ProtocolType": "string",
      "Stage": "string"
    },
    "LakeFormationDataPermissionAsset": {
      "LakeFormationDataPermissionDetails": {
        "LFTagPolicy": {
          "CatalogId": "string",
          "ResourceDetails": {
            "Database": {
              "Expression": [
                {
                  "TagKey": "string",
                  "TagValues": [ "string" ]
                }
              ]
            }
          }
        },
        "Table": {
```



```

        "Expression": [
            {
                "TagKey": "string",
                "TagValues": [ "string" ]
            }
        ]
    },
    "ResourceType": "string"
}
},
"LakeFormationDataPermissionType": "string",
"Permissions": [ "string" ],
"RoleArn": "string"
},
"RedshiftDataShareAsset": {
    "Arn": "string"
},
"S3DataAccessAsset": {
    "Bucket": "string",
    "KeyPrefixes": [ "string" ],
    "Keys": [ "string" ],
    "KmsKeysToGrant": [
        {
            "KmsKeyArn": "string"
        }
    ],
    "S3AccessPointAlias": "string",
    "S3AccessPointArn": "string"
},
"S3SnapshotAsset": {
    "Size": number
}
},
"AssetType": "string",
"CreatedAt": "string",
"DataSetId": "string",
"Id": "string",
"Name": "string",
"RevisionId": "string",
"SourceId": "string",
"UpdatedAt": "string"
}

```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The ARN for the asset.

Type: String

AssetDetails

Details about the asset.

Type: [AssetDetails](#) object

AssetType

The type of asset that is added to a data set.

Type: String

Valid Values: S3_SNAPSHOT | REDSHIFT_DATA_SHARE | API_GATEWAY_API | S3_DATA_ACCESS | LAKE_FORMATION_DATA_PERMISSION

CreatedAt

The date and time that the asset was created, in ISO 8601 format.

Type: Timestamp

DataSetId

The unique identifier for the data set associated with this asset.

Type: String

Id

The unique identifier for the asset.

Type: String

Name

The name of the asset. When importing from Amazon S3, the Amazon S3 object key is used as the asset name. When exporting to Amazon S3, the asset name is used as default target Amazon S3 object key. When importing from Amazon API Gateway API, the API name is used as the asset name. When importing from Amazon Redshift, the datashare name is used as the asset name. When importing from AWS Lake Formation, the static values of "Database(s) included in the LF-tag policy"- or "Table(s) included in LF-tag policy" are used as the asset name.

Type: String

RevisionId

The unique identifier for the revision associated with this asset.

Type: String

SourceId

The asset ID of the owned asset corresponding to the entitled asset being viewed. This parameter is returned when an asset owner is viewing the entitled copy of its owned asset.

Type: String

UpdatedAt

The date and time that the asset was last updated, in ISO 8601 format.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to the resource is denied.

HTTP Status Code: 403

ConflictException

The request couldn't be completed because it conflicted with the current state of the resource.

HTTP Status Code: 409

InternalServerErrorException

An exception occurred with the service.

HTTP Status Code: 500

ResourceNotFoundException

The resource couldn't be found.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateDataSet

This operation updates a data set.

Request Syntax

```
PATCH /v1/data-sets/DataSetId HTTP/1.1
Content-type: application/json

{
  "Description": "string",
  "Name": "string"
}
```

URI Request Parameters

The request uses the following URI parameters.

DataSetId

The unique identifier for a data set.

Required: Yes

Request Body

The request accepts the following data in JSON format.

Description

The description for the data set.

Type: String

Required: No

Name

The name of the data set.

Type: String

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string",
  "AssetType": "string",
  "CreatedAt": "string",
  "Description": "string",
  "Id": "string",
  "Name": "string",
  "Origin": "string",
  "OriginDetails": {
    "DataGrantId": "string",
    "ProductId": "string"
  },
  "SourceId": "string",
  "UpdatedAt": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The ARN for the data set.

Type: String

AssetType

The type of asset that is added to a data set.

Type: String

Valid Values: S3_SNAPSHOT | REDSHIFT_DATA_SHARE | API_GATEWAY_API | S3_DATA_ACCESS | LAKE_FORMATION_DATA_PERMISSION

CreatedAt

The date and time that the data set was created, in ISO 8601 format.

Type: Timestamp

Description

The description for the data set.

Type: String

Id

The unique identifier for the data set.

Type: String

Name

The name of the data set.

Type: String

Origin

A property that defines the data set as OWNED by the account (for providers) or ENTITLED to the account (for subscribers).

Type: String

Valid Values: OWNED | ENTITLED

OriginDetails

If the origin of this data set is ENTITLED, includes the details for the product on AWS Marketplace.

Type: [OriginDetails](#) object

SourceId

The data set ID of the owned data set corresponding to the entitled data set being viewed. This parameter is returned when a data set owner is viewing the entitled copy of its owned data set.

Type: String

UpdatedAt

The date and time that the data set was last updated, in ISO 8601 format.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to the resource is denied.

HTTP Status Code: 403

InternalServerErrorException

An exception occurred with the service.

HTTP Status Code: 500

ResourceNotFoundException

The resource couldn't be found.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateEventAction

This operation updates the event action.

Request Syntax

```
PATCH /v1/event-actions/EventActionId HTTP/1.1
Content-type: application/json
```

```
{
  "Action": {
    "ExportRevisionToS3": {
      "Encryption": {
        "KmsKeyArn": "string",
        "Type": "string"
      },
      "RevisionDestination": {
        "Bucket": "string",
        "KeyPattern": "string"
      }
    }
  }
}
```

URI Request Parameters

The request uses the following URI parameters.

EventActionId

The unique identifier for the event action.

Required: Yes

Request Body

The request accepts the following data in JSON format.

Action

What occurs after a certain event.

Type: [Action](#) object

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Action": {
    "ExportRevisionToS3": {
      "Encryption": {
        "KmsKeyArn": "string",
        "Type": "string"
      },
      "RevisionDestination": {
        "Bucket": "string",
        "KeyPattern": "string"
      }
    }
  },
  "Arn": "string",
  "CreatedAt": "string",
  "Event": {
    "RevisionPublished": {
      "DataSetId": "string"
    }
  },
  "Id": "string",
  "UpdatedAt": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

[Action](#)

What occurs after a certain event.

Type: [Action](#) object

[Arn](#)

The ARN for the event action.

Type: String

[CreatedAt](#)

The date and time that the event action was created, in ISO 8601 format.

Type: Timestamp

[Event](#)

What occurs to start an action.

Type: [Event](#) object

[Id](#)

The unique identifier for the event action.

Type: String

[UpdatedAt](#)

The date and time that the event action was last updated, in ISO 8601 format.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to the resource is denied.

HTTP Status Code: 403

InternalServerError

An exception occurred with the service.

HTTP Status Code: 500

ResourceNotFoundException

The resource couldn't be found.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

UpdateRevision

This operation updates a revision.

Request Syntax

```
PATCH /v1/data-sets/DataSetId/revisions/RevisionId HTTP/1.1
Content-type: application/json

{
  "Comment": "string",
  "Finalized": boolean
}
```

URI Request Parameters

The request uses the following URI parameters.

DataSetId

The unique identifier for a data set.

Required: Yes

RevisionId

The unique identifier for a revision.

Required: Yes

Request Body

The request accepts the following data in JSON format.

Comment

An optional comment about the revision.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

Finalized

Finalizing a revision tells AWS Data Exchange that your changes to the assets in the revision are complete. After it's in this read-only state, you can publish the revision to your products.

Type: Boolean

Required: No

Response Syntax

```
HTTP/1.1 200
Content-type: application/json

{
  "Arn": "string",
  "Comment": "string",
  "CreatedAt": "string",
  "DataSetId": "string",
  "Finalized": boolean,
  "Id": "string",
  "RevocationComment": "string",
  "Revoked": boolean,
  "RevokedAt": "string",
  "SourceId": "string",
  "UpdatedAt": "string"
}
```

Response Elements

If the action is successful, the service sends back an HTTP 200 response.

The following data is returned in JSON format by the service.

Arn

The ARN for the revision.

Type: String

Comment

An optional comment about the revision.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

CreatedAt

The date and time that the revision was created, in ISO 8601 format.

Type: Timestamp

DataSetId

The unique identifier for the data set associated with the data set revision.

Type: String

Finalized

To publish a revision to a data set in a product, the revision must first be finalized. Finalizing a revision tells AWS Data Exchange that changes to the assets in the revision are complete. After it's in this read-only state, you can publish the revision to your products. Finalized revisions can be published through the AWS Data Exchange console or the AWS Marketplace Catalog API, using the StartChangeSet AWS Marketplace Catalog API action. When using the API, revisions are uniquely identified by their ARN.

Type: Boolean

Id

The unique identifier for the revision.

Type: String

RevocationComment

A required comment to inform subscribers of the reason their access to the revision was revoked.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 512.

Revoked

A status indicating that subscribers' access to the revision was revoked.

Type: Boolean

RevokedAt

The date and time that the revision was revoked, in ISO 8601 format.

Type: Timestamp

SourceId

The revision ID of the owned revision corresponding to the entitled revision being viewed. This parameter is returned when a revision owner is viewing the entitled copy of its owned revision.

Type: String

UpdatedAt

The date and time that the revision was last updated, in ISO 8601 format.

Type: Timestamp

Errors

For information about the errors that are common to all actions, see [Common Errors](#).

AccessDeniedException

Access to the resource is denied.

HTTP Status Code: 403

ConflictException

The request couldn't be completed because it conflicted with the current state of the resource.

HTTP Status Code: 409

InternalServerErrorException

An exception occurred with the service.

HTTP Status Code: 500

ResourceNotFoundException

The resource couldn't be found.

HTTP Status Code: 404

ThrottlingException

The limit on the number of requests per second was exceeded.

HTTP Status Code: 429

ValidationException

The request was invalid.

HTTP Status Code: 400

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS Command Line Interface](#)
- [AWS SDK for .NET](#)
- [AWS SDK for C++](#)
- [AWS SDK for Go v2](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for JavaScript V3](#)
- [AWS SDK for PHP V3](#)
- [AWS SDK for Python](#)
- [AWS SDK for Ruby V3](#)

Data Types

The AWS Data Exchange API contains several data types that various actions use. This section describes each data type in detail.

Note

The order of each element in a data type structure is not guaranteed. Applications should not assume a particular order.

The following data types are supported:

- [Action](#)
- [ApiGatewayApiAsset](#)
- [AssetDestinationEntry](#)
- [AssetDetails](#)
- [AssetEntry](#)
- [AssetSourceEntry](#)
- [AutoExportRevisionDestinationEntry](#)
- [AutoExportRevisionToS3RequestDetails](#)
- [CreateS3DataAccessFromS3BucketRequestDetails](#)
- [CreateS3DataAccessFromS3BucketResponseDetails](#)
- [DatabaseLFTagPolicy](#)
- [DatabaseLFTagPolicyAndPermissions](#)
- [DataGrantSummaryEntry](#)
- [DataSetEntry](#)
- [DataUpdateRequestDetails](#)
- [DeprecationRequestDetails](#)
- [Details](#)
- [Event](#)
- [EventActionEntry](#)
- [ExportAssetsToS3RequestDetails](#)

- [ExportAssetsToS3ResponseDetails](#)
- [ExportAssetToSignedUrlRequestDetails](#)
- [ExportAssetToSignedUrlResponseDetails](#)
- [ExportRevisionsToS3RequestDetails](#)
- [ExportRevisionsToS3ResponseDetails](#)
- [ExportServerSideEncryption](#)
- [ImportAssetFromApiGatewayApiRequestDetails](#)
- [ImportAssetFromApiGatewayApiResponseDetails](#)
- [ImportAssetFromSignedUrlJobErrorDetails](#)
- [ImportAssetFromSignedUrlRequestDetails](#)
- [ImportAssetFromSignedUrlResponseDetails](#)
- [ImportAssetsFromLakeFormationTagPolicyRequestDetails](#)
- [ImportAssetsFromLakeFormationTagPolicyResponseDetails](#)
- [ImportAssetsFromRedshiftDataSharesRequestDetails](#)
- [ImportAssetsFromRedshiftDataSharesResponseDetails](#)
- [ImportAssetsFromS3RequestDetails](#)
- [ImportAssetsFromS3ResponseDetails](#)
- [JobEntry](#)
- [JobError](#)
- [KmsKeyToGrant](#)
- [LakeFormationDataPermissionAsset](#)
- [LakeFormationDataPermissionDetails](#)
- [LakeFormationTagPolicyDetails](#)
- [LFResourceDetails](#)
- [LFTag](#)
- [LFTagPolicyDetails](#)
- [NotificationDetails](#)
- [OriginDetails](#)
- [ReceivedDataGrantSummariesEntry](#)
- [RedshiftDataShareAsset](#)

- [RedshiftDataShareAssetSourceEntry](#)
- [RedshiftDataShareDetails](#)
- [RequestDetails](#)
- [ResponseDetails](#)
- [RevisionDestinationEntry](#)
- [RevisionEntry](#)
- [RevisionPublished](#)
- [S3DataAccessAsset](#)
- [S3DataAccessAssetSourceEntry](#)
- [S3DataAccessDetails](#)
- [S3SnapshotAsset](#)
- [SchemaChangeDetails](#)
- [SchemaChangeRequestDetails](#)
- [ScopeDetails](#)
- [TableLFTagPolicy](#)
- [TableLFTagPolicyAndPermissions](#)

Action

What occurs after a certain event.

Contents

ExportRevisionToS3

Details for the export revision to Amazon S3 action.

Type: [AutoExportRevisionToS3RequestDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ApiGatewayApiAsset

The API Gateway API that is the asset.

Contents

ApiDescription

The API description of the API asset.

Type: String

Required: No

ApiEndpoint

The API endpoint of the API asset.

Type: String

Required: No

ApiId

The unique identifier of the API asset.

Type: String

Required: No

ApiKey

The API key of the API asset.

Type: String

Required: No

ApiName

The API name of the API asset.

Type: String

Required: No

ApiSpecificationDownloadUrl

The download URL of the API specification of the API asset.

Type: String

Required: No

ApiSpecificationDownloadUrlExpiresAt

The date and time that the upload URL expires, in ISO 8601 format.

Type: Timestamp

Required: No

ProtocolType

The protocol type of the API asset.

Type: String

Valid Values: REST

Required: No

Stage

The stage of the API asset.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssetDestinationEntry

The destination for the asset.

Contents

AssetId

The unique identifier for the asset.

Type: String

Required: Yes

Bucket

The Amazon S3 bucket that is the destination for the asset.

Type: String

Required: Yes

Key

The name of the object in Amazon S3 for the asset.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssetDetails

Details about the asset.

Contents

ApiGatewayApiAsset

Information about the API Gateway API asset.

Type: [ApiGatewayApiAsset](#) object

Required: No

LakeFormationDataPermissionAsset

The AWS Lake Formation data permission that is the asset.

Type: [LakeFormationDataPermissionAsset](#) object

Required: No

RedshiftDataShareAsset

The Amazon Redshift datashare that is the asset.

Type: [RedshiftDataShareAsset](#) object

Required: No

S3DataAccessAsset

The Amazon S3 data access that is the asset.

Type: [S3DataAccessAsset](#) object

Required: No

S3SnapshotAsset

The Amazon S3 object that is the asset.

Type: [S3SnapshotAsset](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssetEntry

An asset in AWS Data Exchange is a piece of data (Amazon S3 object) or a means of fulfilling data (Amazon Redshift datashare or Amazon API Gateway API, AWS Lake Formation data permission, or Amazon S3 data access). The asset can be a structured data file, an image file, or some other data file that can be stored as an Amazon S3 object, an Amazon API Gateway API, or an Amazon Redshift datashare, an AWS Lake Formation data permission, or an Amazon S3 data access. When you create an import job for your files, API Gateway APIs, Amazon Redshift datashares, AWS Lake Formation data permission, or Amazon S3 data access, you create an asset in AWS Data Exchange.

Contents

Arn

The ARN for the asset.

Type: String

Required: Yes

AssetDetails

Details about the asset.

Type: [AssetDetails](#) object

Required: Yes

AssetType

The type of asset that is added to a data set.

Type: String

Valid Values: S3_SNAPSHOT | REDSHIFT_DATA_SHARE | API_GATEWAY_API | S3_DATA_ACCESS | LAKE_FORMATION_DATA_PERMISSION

Required: Yes

CreatedAt

The date and time that the asset was created, in ISO 8601 format.

Type: Timestamp

Required: Yes

DataSetId

The unique identifier for the data set associated with this asset.

Type: String

Required: Yes

Id

The unique identifier for the asset.

Type: String

Required: Yes

Name

The name of the asset. When importing from Amazon S3, the Amazon S3 object key is used as the asset name. When exporting to Amazon S3, the asset name is used as default target Amazon S3 object key. When importing from Amazon API Gateway API, the API name is used as the asset name. When importing from Amazon Redshift, the datashare name is used as the asset name. When importing from AWS Lake Formation, the static values of "Database(s) included in LF-tag policy" or "Table(s) included in LF-tag policy" are used as the asset name.

Type: String

Required: Yes

RevisionId

The unique identifier for the revision associated with this asset.

Type: String

Required: Yes

UpdatedAt

The date and time that the asset was last updated, in ISO 8601 format.

Type: Timestamp

Required: Yes

SourceId

The asset ID of the owned asset corresponding to the entitled asset being viewed. This parameter is returned when an asset owner is viewing the entitled copy of its owned asset.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AssetSourceEntry

The source of the assets.

Contents

Bucket

The Amazon S3 bucket that's part of the source of the asset.

Type: String

Required: Yes

Key

The name of the object in Amazon S3 for the asset.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AutoExportRevisionDestinationEntry

A revision destination is the Amazon S3 bucket folder destination to where the export will be sent.

Contents

Bucket

The Amazon S3 bucket that is the destination for the event action.

Type: String

Required: Yes

KeyPattern

A string representing the pattern for generated names of the individual assets in the revision. For more information about key patterns, see [Key patterns when exporting revisions](#).

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

AutoExportRevisionToS3RequestDetails

Details of the operation to be performed by the job.

Contents

RevisionDestination

A revision destination is the Amazon S3 bucket folder destination to where the export will be sent.

Type: [AutoExportRevisionDestinationEntry](#) object

Required: Yes

Encryption

Encryption configuration for the auto export job.

Type: [ExportServerSideEncryption](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CreateS3DataAccessFromS3BucketRequestDetails

Details of the operation to create an Amazon S3 data access from an S3 bucket.

Contents

AssetSource

Details about the S3 data access source asset.

Type: [S3DataAccessAssetSourceEntry](#) object

Required: Yes

DataSetId

The unique identifier for the data set associated with the creation of this Amazon S3 data access.

Type: String

Required: Yes

RevisionId

The unique identifier for a revision.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

CreateS3DataAccessFromS3BucketResponseDetails

Details about the response of the operation to create an S3 data access from an S3 bucket.

Contents

AssetSource

Details about the asset source from an Amazon S3 bucket.

Type: [S3DataAccessAssetSourceEntry](#) object

Required: Yes

DataSetId

The unique identifier for this data set.

Type: String

Required: Yes

RevisionId

The unique identifier for the revision.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DatabaseLFTagPolicy

The LF-tag policy for database resources.

Contents

Expression

A list of LF-tag conditions that apply to database resources.

Type: Array of [LFTag](#) objects

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DatabaseLFTagPolicyAndPermissions

The LF-tag policy and permissions for database resources.

Contents

Expression

A list of LF-tag conditions that apply to database resources.

Type: Array of [LFTag](#) objects

Required: Yes

Permissions

The permissions granted to subscribers on database resources.

Type: Array of strings

Valid Values: DESCRIBE

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DataGrantSummaryEntry

Information about a data grant.

Contents

AcceptanceState

The acceptance state of the data grant.

Type: String

Valid Values: PENDING_RECEIVER_ACCEPTANCE | ACCEPTED

Required: Yes

Arn

The Amazon Resource Name (ARN) of the data grant.

Type: String

Required: Yes

CreatedAt

The timestamp of when the data grant was created.

Type: Timestamp

Required: Yes

DataSetId

The ID of the data set associated to the data grant.

Type: String

Required: Yes

Id

The ID of the data grant.

Type: String

Required: Yes

Name

The name of the data grant.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

ReceiverPrincipal

The AWS account ID of the data grant receiver.

Type: String

Pattern: `\d{12}`

Required: Yes

SenderPrincipal

The AWS account ID of the data grant sender.

Type: String

Pattern: `\d{12}`

Required: Yes

SourceDataSetId

The ID of the data set used to create the data grant.

Type: String

Required: Yes

UpdatedAt

The timestamp of when the data grant was last updated.

Type: Timestamp

Required: Yes

AcceptedAt

The timestamp of when the data grant was accepted.

Type: Timestamp

Required: No

EndsAt

The timestamp of when access to the associated data set ends.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DataSetEntry

A data set is an AWS resource with one or more revisions.

Contents

Arn

The ARN for the data set.

Type: String

Required: Yes

AssetType

The type of asset that is added to a data set.

Type: String

Valid Values: S3_SNAPSHOT | REDSHIFT_DATA_SHARE | API_GATEWAY_API | S3_DATA_ACCESS | LAKE_FORMATION_DATA_PERMISSION

Required: Yes

CreatedAt

The date and time that the data set was created, in ISO 8601 format.

Type: Timestamp

Required: Yes

Description

The description for the data set.

Type: String

Required: Yes

Id

The unique identifier for the data set.

Type: String

Required: Yes

Name

The name of the data set.

Type: String

Required: Yes

Origin

A property that defines the data set as OWNED by the account (for providers) or ENTITLED to the account (for subscribers).

Type: String

Valid Values: OWNED | ENTITLED

Required: Yes

UpdatedAt

The date and time that the data set was last updated, in ISO 8601 format.

Type: Timestamp

Required: Yes

OriginDetails

If the origin of this data set is ENTITLED, includes the details for the product on AWS Marketplace.

Type: [OriginDetails](#) object

Required: No

SourceId

The data set ID of the owned data set corresponding to the entitled data set being viewed. This parameter is returned when a data set owner is viewing the entitled copy of its owned data set.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DataUpdateRequestDetails

Extra details specific to a data update type notification.

Contents

DataUpdatedAt

A datetime in the past when the data was updated. This typically means that the underlying resource supporting the data set was updated.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

DeprecationRequestDetails

Extra details specific to a deprecation type notification.

Contents

DeprecationAt

A datetime in the future when the data set will be deprecated.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Details

Information about the job error.

Contents

ImportAssetFromSignedUrlJobErrorDetails

Information about the job error.

Type: [ImportAssetFromSignedUrlJobErrorDetails](#) object

Required: No

ImportAssetsFromS3JobErrorDetails

Details about the job error.

Type: Array of [AssetSourceEntry](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Event

What occurs to start an action.

Contents

RevisionPublished

What occurs to start the revision publish action.

Type: [RevisionPublished](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

EventActionEntry

An event action is an object that defines the relationship between a specific event and an automated action that will be taken on behalf of the customer.

Contents

Action

What occurs after a certain event.

Type: [Action](#) object

Required: Yes

Arn

The Amazon Resource Name (ARN) for the event action.

Type: String

Required: Yes

CreatedAt

The date and time that the event action was created, in ISO 8601 format.

Type: Timestamp

Required: Yes

Event

What occurs to start an action.

Type: [Event](#) object

Required: Yes

Id

The unique identifier for the event action.

Type: String

Required: Yes

UpdatedAt

The date and time that the event action was last updated, in ISO 8601 format.

Type: Timestamp

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ExportAssetsToS3RequestDetails

Details of the operation to be performed by the job.

Contents

AssetDestinations

The destination for the asset.

Type: Array of [AssetDestinationEntry](#) objects

Required: Yes

DataSetId

The unique identifier for the data set associated with this export job.

Type: String

Required: Yes

RevisionId

The unique identifier for the revision associated with this export request.

Type: String

Required: Yes

Encryption

Encryption configuration for the export job.

Type: [ExportServerSideEncryption](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ExportAssetsToS3ResponseDetails

Details about the export to Amazon S3 response.

Contents

AssetDestinations

The destination in Amazon S3 where the asset is exported.

Type: Array of [AssetDestinationEntry](#) objects

Required: Yes

DataSetId

The unique identifier for the data set associated with this export job.

Type: String

Required: Yes

RevisionId

The unique identifier for the revision associated with this export response.

Type: String

Required: Yes

Encryption

Encryption configuration of the export job.

Type: [ExportServerSideEncryption](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ExportAssetToSignedUrlRequestDetails

Details of the operation to be performed by the job.

Contents

AssetId

The unique identifier for the asset that is exported to a signed URL.

Type: String

Required: Yes

DataSetId

The unique identifier for the data set associated with this export job.

Type: String

Required: Yes

RevisionId

The unique identifier for the revision associated with this export request.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ExportAssetToSignedUrlResponseDetails

The details of the export to signed URL response.

Contents

AssetId

The unique identifier for the asset associated with this export job.

Type: String

Required: Yes

DataSetId

The unique identifier for the data set associated with this export job.

Type: String

Required: Yes

RevisionId

The unique identifier for the revision associated with this export response.

Type: String

Required: Yes

SignedUrl

The signed URL for the export request.

Type: String

Required: No

SignedUrlExpiresAt

The date and time that the signed URL expires, in ISO 8601 format.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ExportRevisionsToS3RequestDetails

Details of the operation to be performed by the job.

Contents

DataSetId

The unique identifier for the data set associated with this export job.

Type: String

Required: Yes

RevisionDestinations

The destination for the revision.

Type: Array of [RevisionDestinationEntry](#) objects

Required: Yes

Encryption

Encryption configuration for the export job.

Type: [ExportServerSideEncryption](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ExportRevisionsToS3ResponseDetails

Details about the export revisions to Amazon S3 response.

Contents

DataSetId

The unique identifier for the data set associated with this export job.

Type: String

Required: Yes

RevisionDestinations

The destination in Amazon S3 where the revision is exported.

Type: Array of [RevisionDestinationEntry](#) objects

Required: Yes

Encryption

Encryption configuration of the export job.

Type: [ExportServerSideEncryption](#) object

Required: No

EventActionArn

The Amazon Resource Name (ARN) of the event action.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ExportServerSideEncryption

Encryption configuration of the export job. Includes the encryption type in addition to the AWS KMS key. The KMS key is only necessary if you chose the KMS encryption type.

Contents

Type

The type of server side encryption used for encrypting the objects in Amazon S3.

Type: String

Valid Values: `aws:kms` | `AES256`

Required: Yes

KmsKeyArn

The Amazon Resource Name (ARN) of the AWS KMS key you want to use to encrypt the Amazon S3 objects. This parameter is required if you choose `aws:kms` as an encryption type.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImportAssetFromApiGatewayApiRequestDetails

The request details.

Contents

ApiId

The API Gateway API ID.

Type: String

Required: Yes

ApiName

The API name.

Type: String

Required: Yes

ApiSpecificationMd5Hash

The Base64-encoded MD5 hash of the OpenAPI 3.0 JSON API specification file. It is used to ensure the integrity of the file.

Type: String

Length Constraints: Fixed length of 24.

Pattern: (?:[A-Za-z0-9+/\]{4})*(?:[A-Za-z0-9+/\]{2}==|[A-Za-z0-9+/\]{3}=)?

Required: Yes

DataSetId

The data set ID.

Type: String

Required: Yes

ProtocolType

The protocol type.

Type: String

Valid Values: REST

Required: Yes

RevisionId

The revision ID.

Type: String

Required: Yes

Stage

The API stage.

Type: String

Required: Yes

ApiDescription

The API description. Markdown supported.

Type: String

Required: No

ApiKey

The API Gateway API key.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

ImportAssetFromApiGatewayApiResponseDetails

The response details.

Contents

ApiId

The API ID.

Type: String

Required: Yes

ApiName

The API name.

Type: String

Required: Yes

ApiSpecificationMd5Hash

The Base64-encoded Md5 hash for the API asset, used to ensure the integrity of the API at that location.

Type: String

Length Constraints: Fixed length of 24.

Pattern: (? : [A-Za-z0-9+ /] {4}) * (? : [A-Za-z0-9+ /] {2} = = | [A-Za-z0-9+ /] {3} =) ?

Required: Yes

ApiSpecificationUploadUrl

The upload URL of the API specification.

Type: String

Required: Yes

ApiSpecificationUploadUrlExpiresAt

The date and time that the upload URL expires, in ISO 8601 format.

Type: Timestamp

Required: Yes

DataSetId

The data set ID.

Type: String

Required: Yes

ProtocolType

The protocol type.

Type: String

Valid Values: REST

Required: Yes

RevisionId

The revision ID.

Type: String

Required: Yes

Stage

The API stage.

Type: String

Required: Yes

ApiDescription

The API description.

Type: String

Required: No

ApiKey

The API key.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImportAssetFromSignedUrlJobErrorDetails

Details about the job error.

Contents

AssetName

Details about the job error.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImportAssetFromSignedUrlRequestDetails

Details of the operation to be performed by the job.

Contents

AssetName

The name of the asset. When importing from Amazon S3, the Amazon S3 object key is used as the asset name.

Type: String

Required: Yes

DataSetId

The unique identifier for the data set associated with this import job.

Type: String

Required: Yes

Md5Hash

The Base64-encoded Md5 hash for the asset, used to ensure the integrity of the file at that location.

Type: String

Length Constraints: Fixed length of 24.

Pattern: `(?:[A-Za-z0-9+/]{4})*(?:[A-Za-z0-9+/]{2}=|[A-Za-z0-9+/]{3}=)?`

Required: Yes

RevisionId

The unique identifier for the revision associated with this import request.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImportAssetFromSignedUrlResponseDetails

The details in the response for an import request, including the signed URL and other information.

Contents

AssetName

The name for the asset associated with this import job.

Type: String

Required: Yes

DataSetId

The unique identifier for the data set associated with this import job.

Type: String

Required: Yes

RevisionId

The unique identifier for the revision associated with this import response.

Type: String

Required: Yes

Md5Hash

The Base64-encoded Md5 hash for the asset, used to ensure the integrity of the file at that location.

Type: String

Length Constraints: Fixed length of 24.

Pattern: (? : [A-Za-z0-9+ /] {4}) * (? : [A-Za-z0-9+ /] {2} = = | [A-Za-z0-9+ /] {3} =) ?

Required: No

SignedUrl

The signed URL.

Type: String

Required: No

SignedUrlExpiresAt

The time and date at which the signed URL expires, in ISO 8601 format.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImportAssetsFromLakeFormationTagPolicyRequestDetails

Details about the assets imported from an AWS Lake Formation tag policy request.

Contents

CatalogId

The identifier for the AWS Glue Data Catalog.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `.*\/^[\\d]{12}$\/.*`

Required: Yes

DataSetId

The unique identifier for the data set associated with this import job.

Type: String

Required: Yes

RevisionId

The unique identifier for the revision associated with this import job.

Type: String

Required: Yes

RoleArn

The IAM role's ARN that allows AWS Data Exchange to assume the role and grant and revoke permissions of subscribers to AWS Lake Formation data permissions.

Type: String

Pattern: `arn:aws:iam::(\\d{12}):role\\/.+`

Required: Yes

Database

A structure for the database object.

Type: [DatabaseLFTagPolicyAndPermissions](#) object

Required: No

Table

A structure for the table object.

Type: [TableLFTagPolicyAndPermissions](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImportAssetsFromLakeFormationTagPolicyResponseDetails

Details from an import AWS Lake Formation tag policy job response.

Contents

CatalogId

The identifier for the AWS Glue Data Catalog.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `.*\/^[\\d]{12}$\/.*`

Required: Yes

DataSetId

The unique identifier for the data set associated with this import job.

Type: String

Required: Yes

RevisionId

The unique identifier for the revision associated with this import job.

Type: String

Required: Yes

RoleArn

The IAM role's ARN that allows AWS Data Exchange to assume the role and grant and revoke permissions to AWS Lake Formation data permissions.

Type: String

Pattern: `arn:aws:iam::(\\d{12}):role\\/.+`

Required: Yes

Database

A structure for the database object.

Type: [DatabaseLFTagPolicyAndPermissions](#) object

Required: No

Table

A structure for the table object.

Type: [TableLFTagPolicyAndPermissions](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImportAssetsFromRedshiftDataSharesRequestDetails

Details from an import from Amazon Redshift datashare request.

Contents

AssetSources

A list of Amazon Redshift datashare assets.

Type: Array of [RedshiftDataShareAssetSourceEntry](#) objects

Required: Yes

DataSetId

The unique identifier for the data set associated with this import job.

Type: String

Required: Yes

RevisionId

The unique identifier for the revision associated with this import job.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImportAssetsFromRedshiftDataSharesResponseDetails

Details from an import from Amazon Redshift datashare response.

Contents

AssetSources

A list of Amazon Redshift datashare asset sources.

Type: Array of [RedshiftDataShareAssetSourceEntry](#) objects

Required: Yes

DataSetId

The unique identifier for the data set associated with this import job.

Type: String

Required: Yes

RevisionId

The unique identifier for the revision associated with this import job.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImportAssetsFromS3RequestDetails

Details of the operation to be performed by the job.

Contents

AssetSources

Is a list of Amazon S3 bucket and object key pairs.

Type: Array of [AssetSourceEntry](#) objects

Required: Yes

DataSetId

The unique identifier for the data set associated with this import job.

Type: String

Required: Yes

RevisionId

The unique identifier for the revision associated with this import request.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ImportAssetsFromS3ResponseDetails

Details from an import from Amazon S3 response.

Contents

AssetSources

Is a list of Amazon S3 bucket and object key pairs.

Type: Array of [AssetSourceEntry](#) objects

Required: Yes

DataSetId

The unique identifier for the data set associated with this import job.

Type: String

Required: Yes

RevisionId

The unique identifier for the revision associated with this import response.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

JobEntry

AWS Data Exchange Jobs are asynchronous import or export operations used to create or copy assets. A data set owner can both import and export as they see fit. Someone with an entitlement to a data set can only export. Jobs are deleted 90 days after they are created.

Contents

Arn

The ARN for the job.

Type: String

Required: Yes

CreatedAt

The date and time that the job was created, in ISO 8601 format.

Type: Timestamp

Required: Yes

Details

Details of the operation to be performed by the job, such as export destination details or import source details.

Type: [ResponseDetails](#) object

Required: Yes

Id

The unique identifier for the job.

Type: String

Required: Yes

State

The state of the job.

Type: String

Valid Values: WAITING | IN_PROGRESS | ERROR | COMPLETED | CANCELLED | TIMED_OUT

Required: Yes

Type

The job type.

Type: String

Valid Values: IMPORT_ASSETS_FROM_S3 | IMPORT_ASSET_FROM_SIGNED_URL | EXPORT_ASSETS_TO_S3 | EXPORT_ASSET_TO_SIGNED_URL | EXPORT_REVISIONS_TO_S3 | IMPORT_ASSETS_FROM_REDSHIFT_DATA_SHARES | IMPORT_ASSET_FROM_API_GATEWAY_API | CREATE_S3_DATA_ACCESS_FROM_S3_BUCKET | IMPORT_ASSETS_FROM_LAKE_FORMATION_TAG_POLICY

Required: Yes

UpdatedAt

The date and time that the job was last updated, in ISO 8601 format.

Type: Timestamp

Required: Yes

Errors

Errors for jobs.

Type: Array of [JobError](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)

- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

JobError

An error that occurred with the job request.

Contents

Code

The code for the job error.

Type: String

Valid Values: ACCESS_DENIED_EXCEPTION | INTERNAL_SERVER_EXCEPTION
| MALWARE_DETECTED | RESOURCE_NOT_FOUND_EXCEPTION |
SERVICE_QUOTA_EXCEEDED_EXCEPTION | VALIDATION_EXCEPTION |
MALWARE_SCAN_ENCRYPTED_FILE

Required: Yes

Message

The message related to the job error.

Type: String

Required: Yes

Details

The details about the job error.

Type: [Details](#) object

Required: No

LimitName

The name of the limit that was reached.

Type: String

Valid Values: Assets per revision | Asset size in GB | Amazon Redshift
datashare assets per revision | AWS Lake Formation data permission
assets per revision | Amazon S3 data access assets per revision

Required: No

LimitValue

The value of the exceeded limit.

Type: Double

Required: No

ResourceId

The unique identifier for the resource related to the error.

Type: String

Required: No

ResourceType

The type of resource related to the error.

Type: String

Valid Values: REVISION | ASSET | DATA_SET

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

KmsKeyToGrant

The Amazon Resource Name (ARN) of the AWS KMS key used to encrypt the shared S3 objects.

Contents

KmsKeyArn

The AWS KMS CMK (Key Management System Customer Managed Key) used to encrypt S3 objects in the shared S3 Bucket. AWS Data exchange will create a KMS grant for each subscriber to allow them to access and decrypt their entitled data that is encrypted using this KMS key specified.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 2048.

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LakeFormationDataPermissionAsset

The AWS Lake Formation data permission asset.

Contents

LakeFormationDataPermissionDetails

Details about the AWS Lake Formation data permission.

Type: [LakeFormationDataPermissionDetails](#) object

Required: Yes

LakeFormationDataPermissionType

The data permission type.

Type: String

Valid Values: LFTagPolicy

Required: Yes

Permissions

The permissions granted to the subscribers on the resource.

Type: Array of strings

Valid Values: DESCRIBE | SELECT

Required: Yes

RoleArn

The IAM role's ARN that allows AWS Data Exchange to assume the role and grant and revoke permissions to AWS Lake Formation data permissions.

Type: String

Pattern: `arn:aws:iam::(\d{12}):role\./.+`

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LakeFormationDataPermissionDetails

Details about the AWS Lake Formation data permission.

Contents

LFTagPolicy

Details about the LF-tag policy.

Type: [LFTagPolicyDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LakeFormationTagPolicyDetails

Extra details specific to the affected scope in this LF data set.

Contents

Database

The underlying Glue database that the notification is referring to.

Type: String

Required: No

Table

The underlying Glue table that the notification is referring to.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LFResourceDetails

Details about the AWS Lake Formation resource (Table or Database) included in the AWS Lake Formation data permission.

Contents

Database

Details about the database resource included in the AWS Lake Formation data permission.

Type: [DatabaseLFTagPolicy](#) object

Required: No

Table

Details about the table resource included in the AWS Lake Formation data permission.

Type: [TableLFTagPolicy](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LFTag

A structure that allows an LF-admin to grant permissions on certain conditions.

Contents

TagKey

The key name for the LF-tag.

Type: String

Required: Yes

TagValues

A list of LF-tag values.

Type: Array of strings

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

LFTagPolicyDetails

Details about the LF-tag policy.

Contents

CatalogId

The identifier for the AWS Glue Data Catalog.

Type: String

Length Constraints: Fixed length of 12.

Pattern: `.*\/^[\\d]{12}$\/.*`

Required: Yes

ResourceDetails

Details for the Lake Formation Resources included in the LF-tag policy.

Type: [LFResourceDetails](#) object

Required: Yes

ResourceType

The resource type for which the LF-tag policy applies.

Type: String

Valid Values: TABLE | DATABASE

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)

- [AWS SDK for Ruby V3](#)

NotificationDetails

Extra details specific to this notification.

Contents

DataUpdate

Extra details specific to a data update type notification.

Type: [DataUpdateRequestDetails](#) object

Required: No

Deprecation

Extra details specific to a deprecation type notification.

Type: [DeprecationRequestDetails](#) object

Required: No

SchemaChange

Extra details specific to a schema change type notification.

Type: [SchemaChangeRequestDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

OriginDetails

Details about the origin of the data set.

Contents

DataGrantId

The ID of the data grant.

Type: String

Required: No

ProductId

The product ID of the origin of the data set.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ReceivedDataGrantSummariesEntry

Information about a received data grant.

Contents

AcceptanceState

The acceptance state of the data grant.

Type: String

Valid Values: PENDING_RECEIVER_ACCEPTANCE | ACCEPTED

Required: Yes

Arn

The Amazon Resource Name (ARN) of the data grant.

Type: String

Required: Yes

CreatedAt

The timestamp of when the data grant was created.

Type: Timestamp

Required: Yes

DataSetId

The ID of the data set associated to the data grant.

Type: String

Required: Yes

Id

The ID of the data grant.

Type: String

Required: Yes

Name

The name of the data grant.

Type: String

Length Constraints: Minimum length of 1. Maximum length of 256.

Required: Yes

ReceiverPrincipal

The AWS account ID of the data grant receiver.

Type: String

Pattern: `\d{12}`

Required: Yes

SenderPrincipal

The AWS account ID of the data grant sender.

Type: String

Pattern: `\d{12}`

Required: Yes

UpdatedAt

The timestamp of when the data grant was last updated.

Type: Timestamp

Required: Yes

AcceptedAt

The timestamp of when the data grant was accepted.

Type: Timestamp

Required: No

EndsAt

The timestamp of when access to the associated data set ends.

Type: Timestamp

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RedshiftDataShareAsset

The Amazon Redshift datashare asset.

Contents

Arn

The Amazon Resource Name (ARN) of the datashare asset.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RedshiftDataShareAssetSourceEntry

The source of the Amazon Redshift datashare asset.

Contents

DataShareArn

The Amazon Resource Name (ARN) of the datashare asset.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RedshiftDataShareDetails

Extra details specific to the affected scope in this Redshift data set.

Contents

Arn

The ARN of the underlying Redshift data share that is being affected by this notification.

Type: String

Required: Yes

Database

The database name in the Redshift data share that is being affected by this notification.

Type: String

Required: Yes

Function

A function name in the Redshift database that is being affected by this notification.

Type: String

Required: No

Schema

A schema name in the Redshift database that is being affected by this notification.

Type: String

Required: No

Table

A table name in the Redshift database that is being affected by this notification.

Type: String

Required: No

View

A view name in the Redshift database that is being affected by this notification.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RequestDetails

The details for the request.

Contents

CreateS3DataAccessFromS3Bucket

Details of the request to create S3 data access from the Amazon S3 bucket.

Type: [CreateS3DataAccessFromS3BucketRequestDetails](#) object

Required: No

ExportAssetsToS3

Details about the export to Amazon S3 request.

Type: [ExportAssetsToS3RequestDetails](#) object

Required: No

ExportAssetToSignedUrl

Details about the export to signed URL request.

Type: [ExportAssetToSignedUrlRequestDetails](#) object

Required: No

ExportRevisionsToS3

Details about the export to Amazon S3 request.

Type: [ExportRevisionsToS3RequestDetails](#) object

Required: No

ImportAssetFromApiGatewayApi

Details about the import from signed URL request.

Type: [ImportAssetFromApiGatewayApiRequestDetails](#) object

Required: No

ImportAssetFromSignedUrl

Details about the import from Amazon S3 request.

Type: [ImportAssetFromSignedUrlRequestDetails](#) object

Required: No

ImportAssetsFromLakeFormationTagPolicy

Request details for the ImportAssetsFromLakeFormationTagPolicy job.

Type: [ImportAssetsFromLakeFormationTagPolicyRequestDetails](#) object

Required: No

ImportAssetsFromRedshiftDataShares

Details from an import from Amazon Redshift datashare request.

Type: [ImportAssetsFromRedshiftDataSharesRequestDetails](#) object

Required: No

ImportAssetsFromS3

Details about the import asset from API Gateway API request.

Type: [ImportAssetsFromS3RequestDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ResponseDetails

Details for the response.

Contents

CreateS3DataAccessFromS3Bucket

Response details from the CreateS3DataAccessFromS3Bucket job.

Type: [CreateS3DataAccessFromS3BucketResponseDetails](#) object

Required: No

ExportAssetsToS3

Details for the export to Amazon S3 response.

Type: [ExportAssetsToS3ResponseDetails](#) object

Required: No

ExportAssetToSignedUrl

Details for the export to signed URL response.

Type: [ExportAssetToSignedUrlResponseDetails](#) object

Required: No

ExportRevisionsToS3

Details for the export revisions to Amazon S3 response.

Type: [ExportRevisionsToS3ResponseDetails](#) object

Required: No

ImportAssetFromApiGatewayApi

The response details.

Type: [ImportAssetFromApiGatewayApiResponseDetails](#) object

Required: No

ImportAssetFromSignedUrl

Details for the import from signed URL response.

Type: [ImportAssetFromSignedUrlResponseDetails](#) object

Required: No

ImportAssetsFromLakeFormationTagPolicy

Response details from the ImportAssetsFromLakeFormationTagPolicy job.

Type: [ImportAssetsFromLakeFormationTagPolicyResponseDetails](#) object

Required: No

ImportAssetsFromRedshiftDataShares

Details from an import from Amazon Redshift datashare response.

Type: [ImportAssetsFromRedshiftDataSharesResponseDetails](#) object

Required: No

ImportAssetsFromS3

Details for the import from Amazon S3 response.

Type: [ImportAssetsFromS3ResponseDetails](#) object

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RevisionDestinationEntry

The destination where the assets in the revision will be exported.

Contents

Bucket

The Amazon S3 bucket that is the destination for the assets in the revision.

Type: String

Required: Yes

RevisionId

The unique identifier for the revision.

Type: String

Required: Yes

KeyPattern

A string representing the pattern for generated names of the individual assets in the revision. For more information about key patterns, see [Key patterns when exporting revisions](#).

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RevisionEntry

A revision is a container for one or more assets.

Contents

Arn

The ARN for the revision.

Type: String

Required: Yes

CreatedAt

The date and time that the revision was created, in ISO 8601 format.

Type: Timestamp

Required: Yes

DataSetId

The unique identifier for the data set associated with the data set revision.

Type: String

Required: Yes

Id

The unique identifier for the revision.

Type: String

Required: Yes

UpdatedAt

The date and time that the revision was last updated, in ISO 8601 format.

Type: Timestamp

Required: Yes

Comment

An optional comment about the revision.

Type: String

Length Constraints: Minimum length of 0. Maximum length of 16384.

Required: No

Finalized

To publish a revision to a data set in a product, the revision must first be finalized. Finalizing a revision tells AWS Data Exchange that your changes to the assets in the revision are complete. After it's in this read-only state, you can publish the revision to your products. Finalized revisions can be published through the AWS Data Exchange console or the AWS Marketplace Catalog API, using the StartChangeSet AWS Marketplace Catalog API action. When using the API, revisions are uniquely identified by their ARN.

Type: Boolean

Required: No

RevocationComment

A required comment to inform subscribers of the reason their access to the revision was revoked.

Type: String

Length Constraints: Minimum length of 10. Maximum length of 512.

Required: No

Revoked

A status indicating that subscribers' access to the revision was revoked.

Type: Boolean

Required: No

RevokedAt

The date and time that the revision was revoked, in ISO 8601 format.

Type: Timestamp

Required: No

SourceId

The revision ID of the owned revision corresponding to the entitled revision being viewed. This parameter is returned when a revision owner is viewing the entitled copy of its owned revision.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

RevisionPublished

Information about the published revision.

Contents

DataSetId

The data set ID of the published revision.

Type: String

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

S3DataAccessAsset

The Amazon S3 data access that is the asset.

Contents

Bucket

The Amazon S3 bucket hosting data to be shared in the S3 data access.

Type: String

Required: Yes

KeyPrefixes

The Amazon S3 bucket used for hosting shared data in the Amazon S3 data access.

Type: Array of strings

Required: No

Keys

S3 keys made available using this asset.

Type: Array of strings

Required: No

KmsKeysToGrant

List of AWS KMS CMKs (Key Management System Customer Managed Keys) and ARNs used to encrypt S3 objects being shared in this S3 Data Access asset. Providers must include all AWS KMS keys used to encrypt these shared S3 objects.

Type: Array of [KmsKeyToGrant](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: No

S3AccessPointAlias

The automatically-generated bucket-style alias for your Amazon S3 Access Point. Customers can access their entitled data using the S3 Access Point alias.

Type: String

Required: No

S3AccessPointArn

The ARN for your Amazon S3 Access Point. Customers can also access their entitled data using the S3 Access Point ARN.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

S3DataAccessAssetSourceEntry

Source details for an Amazon S3 data access asset.

Contents

Bucket

The Amazon S3 bucket used for hosting shared data in the Amazon S3 data access.

Type: String

Required: Yes

KeyPrefixes

Organizes Amazon S3 asset key prefixes stored in an Amazon S3 bucket.

Type: Array of strings

Required: No

Keys

The keys used to create the Amazon S3 data access.

Type: Array of strings

Required: No

KmsKeysToGrant

List of AWS KMS CMKs (Key Management System Customer Managed Keys) and ARNs used to encrypt S3 objects being shared in this S3 Data Access asset.

Type: Array of [KmsKeyToGrant](#) objects

Array Members: Minimum number of 1 item. Maximum number of 10 items.

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

S3DataAccessDetails

Extra details specific to the affected scope in this S3 Data Access data set.

Contents

KeyPrefixes

A list of the key prefixes affected by this notification. This can have up to 50 entries.

Type: Array of strings

Required: No

Keys

A list of the keys affected by this notification. This can have up to 50 entries.

Type: Array of strings

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

S3SnapshotAsset

The Amazon S3 object that is the asset.

Contents

Size

The size of the Amazon S3 object that is the object.

Type: Double

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SchemaChangeDetails

Object encompassing information about a schema change to a single, particular field, a notification can have up to 100 of these.

Contents

Name

Name of the changing field. This value can be up to 255 characters long.

Type: String

Required: Yes

Type

Is the field being added, removed, or modified?

Type: String

Valid Values: ADD | REMOVE | MODIFY

Required: Yes

Description

Description of what's changing about this field. This value can be up to 512 characters long.

Type: String

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

SchemaChangeRequestDetails

Extra details specific to this schema change type notification.

Contents

SchemaChangeAt

A date in the future when the schema change is taking effect.

Type: Timestamp

Required: Yes

Changes

List of schema changes happening in the scope of this notification. This can have up to 100 entries.

Type: Array of [SchemaChangeDetails](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

ScopeDetails

Details about the scope of the notifications such as the affected resources.

Contents

LakeFormationTagPolicies

Underlying LF resources that will be affected by this notification.

Type: Array of [LakeFormationTagPolicyDetails](#) objects

Required: No

RedshiftDataShares

Underlying Redshift resources that will be affected by this notification.

Type: Array of [RedshiftDataShareDetails](#) objects

Required: No

S3DataAccesses

Underlying S3 resources that will be affected by this notification.

Type: Array of [S3DataAccessDetails](#) objects

Required: No

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TableLFTagPolicy

The LF-tag policy for a table resource.

Contents

Expression

A list of LF-tag conditions that apply to table resources.

Type: Array of [LFTag](#) objects

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

TableLFTagPolicyAndPermissions

The LF-tag policy and permissions that apply to table resources.

Contents

Expression

A list of LF-tag conditions that apply to table resources.

Type: Array of [LFTag](#) objects

Required: Yes

Permissions

The permissions granted to subscribers on table resources.

Type: Array of strings

Valid Values: DESCRIBE | SELECT

Required: Yes

See Also

For more information about using this API in one of the language-specific AWS SDKs, see the following:

- [AWS SDK for C++](#)
- [AWS SDK for Java V2](#)
- [AWS SDK for Ruby V3](#)

Common Parameters

The following list contains the parameters that all actions use for signing Signature Version 4 requests with a query string. Any action-specific parameters are listed in the topic for that action. For more information about Signature Version 4, see [Signing AWS API requests](#) in the *IAM User Guide*.

Action

The action to be performed.

Type: string

Required: Yes

Version

The API version that the request is written for, expressed in the format YYYY-MM-DD.

Type: string

Required: Yes

X-Amz-Algorithm

The hash algorithm that you used to create the request signature.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Valid Values: AWS4-HMAC-SHA256

Required: Conditional

X-Amz-Credential

The credential scope value, which is a string that includes your access key, the date, the region you are targeting, the service you are requesting, and a termination string ("aws4_request"). The value is expressed in the following format: *access_key/YYYYMMDD/region/service/aws4_request*.

For more information, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-Date

The date that is used to create the signature. The format must be ISO 8601 basic format (YYYYMMDD'T'HHMMSS'Z'). For example, the following date time is a valid X-Amz-Date value: 20120325T120000Z.

Condition: X-Amz-Date is optional for all requests; it can be used to override the date used for signing requests. If the Date header is specified in the ISO 8601 basic format, X-Amz-Date is not required. When X-Amz-Date is used, it always overrides the value of the Date header. For more information, see [Elements of an AWS API request signature](#) in the *IAM User Guide*.

Type: string

Required: Conditional

X-Amz-Security-Token

The temporary security token that was obtained through a call to AWS Security Token Service (AWS STS). For a list of services that support temporary security credentials from AWS STS, see [AWS services that work with IAM](#) in the *IAM User Guide*.

Condition: If you're using temporary security credentials from AWS STS, you must include the security token.

Type: string

Required: Conditional

X-Amz-Signature

Specifies the hex-encoded signature that was calculated from the string to sign and the derived signing key.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

X-Amz-SignedHeaders

Specifies all the HTTP headers that were included as part of the canonical request. For more information about specifying signed headers, see [Create a signed AWS API request](#) in the *IAM User Guide*.

Condition: Specify this parameter when you include authentication information in a query string instead of in the HTTP authorization header.

Type: string

Required: Conditional

Common Errors

This section lists the errors common to the API actions of all AWS services. For errors specific to an API action for this service, see the topic for that API action.

AccessDeniedException

You do not have sufficient access to perform this action.

HTTP Status Code: 400

IncompleteSignature

The request signature does not conform to AWS standards.

HTTP Status Code: 400

InternalFailure

The request processing has failed because of an unknown error, exception or failure.

HTTP Status Code: 500

InvalidAction

The action or operation requested is invalid. Verify that the action is typed correctly.

HTTP Status Code: 400

InvalidClientTokenId

The X.509 certificate or AWS access key ID provided does not exist in our records.

HTTP Status Code: 403

NotAuthorized

You do not have permission to perform this action.

HTTP Status Code: 400

OptInRequired

The AWS access key ID needs a subscription for the service.

HTTP Status Code: 403

RequestExpired

The request reached the service more than 15 minutes after the date stamp on the request or more than 15 minutes after the request expiration date (such as for pre-signed URLs), or the date stamp on the request is more than 15 minutes in the future.

HTTP Status Code: 400

ServiceUnavailable

The request has failed due to a temporary failure of the server.

HTTP Status Code: 503

ThrottlingException

The request was denied due to request throttling.

HTTP Status Code: 400

ValidationError

The input fails to satisfy the constraints specified by an AWS service.

HTTP Status Code: 400

Document history

The following table describes the documentation for this release of the *AWS Data Exchange API Reference*.

For notification about updates to this documentation, you can subscribe to the RSS feed. To subscribe to the RSS feed, you must have an RSS plug-in enabled for the browser you are using.

Change	Description	Date
Documentation organization enhancements	Documentation-only update to enhance the organization of the AWS Data Exchange API Reference Guide.	September 7, 2022
Revoke Revision API operation	Providers can now use the RevokeRevision API operation to revoke subscriber access to a revision.	March 15, 2022
Send API Asset API operation and updates to Asset, DataSet, and Job API operations	Providers can now use the CreateDataSet API operation to include a new AssetType : IMPORT_ASSET_FROM_API_GATEWAY_API , which adds API assets from Amazon API Gateway. This new job type, which affects the Job shape, comes with its own Details block that looks very similar to other Job types. Subscribers can now use the SendApiAsset API operation to invoke a provider's Amazon API	November 29, 2021

Gateway API that they are entitled to.

[\(Preview\) Updates to Asset, Data Set, and Job API operations](#)

(Preview) Providers can now use the `CreateDataSet` API operation to include a new `AssetType : REDSHIFT_DATA_SHARE`, which affects the Data Set shape. Assets can now be Type `REDSHIFT_DATA_SHARE`, which only affects the Asset shape. There is a new `AssetDetails` object for this type, which points at the Amazon Redshift datashare ARN. Providers can now use the `CreateJob` API operation to run a new job type: `IMPORT_ASSETS_FROM_REDSHIFT_DATA_SHARES`, which adds assets from Amazon Redshift datashares. This new job type, which affects the Job shape, comes with its own `Details` block that looks very similar to other Job types.

October 19, 2021

[Event Action API operation and Event Actions API operation](#)

Subscribers can now use the Event Action API operation and Event Actions API operation to configure jobs to automatically export revisions to an Amazon S3 bucket.

September 30, 2021

[AWS Data Exchange is now generally available](#)

AWS Data Exchange is a service that makes it easy for AWS customers to create, update, maintain, and securely exchange file-based data sets in the AWS Cloud.

November 13, 2019