




(86) Date de dépôt PCT/PCT Filing Date: 2009/10/27
 (87) Date publication PCT/PCT Publication Date: 2010/05/06
 (45) Date de délivrance/Issue Date: 2018/05/08
 (85) Entrée phase nationale/National Entry: 2011/04/27
 (86) N° demande PCT/PCT Application No.: US 2009/062247
 (87) N° publication PCT/PCT Publication No.: 2010/051287
 (30) Priorités/Priorities: 2008/10/27 (US61/108,770);
 2009/05/22 (US61/180,600)

(51) Cl.Int./Int.Cl. *G08B 23/00* (2006.01),
G08B 25/00 (2006.01)
 (72) Inventeurs/Inventors:
 HYLAND, GREGORY E., US;
 KEEFE, ROBERT PAUL, US;
 ZAKAS, MARIETTA EDMUNDS, US;
 BARKER, C. ROBERT, US
 (73) Propriétaire/Owner:
 MUELLER INTERNATIONAL, LLC, US
 (74) Agent: RIDOUT & MAYBEE LLP

(54) Titre : SYSTEME ET PROCEDE DE SURVEILLANCE D'INFRASTRUCTURE
 (54) Title: INFRASTRUCTURE MONITORING SYSTEM AND METHOD



(57) **Abrégé/Abstract:**

An infrastructure monitoring system and method that comprises multiple monitoring devices and/or multiple output devices. Each monitoring device includes at least one sensor for collecting data, a data storage device for storing the data, a processor for analyzing the data, and a communications device for transmitting and receiving data. The system may also include an operations center for controlling and receiving data from the plurality of devices.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
6 May 2010 (06.05.2010)(10) International Publication Number
WO 2010/051287 A1(51) International Patent Classification:
G08B 21/00 (2006.01)(21) International Application Number:
PCT/US2009/062247(22) International Filing Date:
27 October 2009 (27.10.2009)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61/108,770 27 October 2008 (27.10.2008) US
61/180,600 22 May 2009 (22.05.2009) US(71) Applicant (for all designated States except US):
MUELLER INTERNATIONAL, INC. [US/US]; 1200
Abernathy Road, N.E., Suite 1200, Atlanta, GA 30328
(US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **HYLAND, Gregory, E.** [US/US]; 595 Old Cobblestone Drive, Atlanta, GA 30350 (US). **KEEFE, Robert, Paul** [US/US]; 300 Newcastle Drive, Alpharetta, GA 30004 (US). **ZAKAS, Marietta, Edmunds** [US/US]; 365 Peachtree Battle Avenue, Atlanta, GA 30305 (US). **BARKER, C., Robert** [US/US]; 4779 Sedberry Hill Court, Atlanta, GA 30339 (US).(74) Agents: **REMENICK, James et al.**; Remenick, PLLC,
1025 Thomas Jefferson Street, NW, Suite 175, Washing-
ton, DC 20007 (US).(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ,
CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO,
DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP,
KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD,
ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI,
NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD,
SE, SG, SK, SL, SM, ST, SV, SY, TJ, TM, TN, TR, TT,
TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ,
TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

(54) Title: INFRASTRUCTURE MONITORING SYSTEM AND METHOD




FIG. 1

(57) Abstract: An infrastructure monitoring system and method that comprises multiple monitoring devices and/or multiple output devices. Each monitoring device includes at least one sensor for collecting data, a data storage device for storing the data, a processor for analyzing the data, and a communications device for transmitting and receiving data. The system may also include an operations center for controlling and receiving data from the plurality of devices.

WO 2010/051287 A1

INFRASTRUCTURE MONITORING SYSTEM AND METHOD

Reference to Related Applications

This application claims priority to U.S. provisional application Ser. No.
 5 61/108770, filed October 27, 2008, entitled "WATER SUPPLY INFRASTRUCTURE
 MONITORING SYSTEM AND METHOD," and U.S. provisional application Ser. No.
 61/180600 filed May 22, 2009, entitled "WATER SUPPLY INFRASTRUCTURE
 MONITORING SYSTEM AND METHOD".

10 **Background**

1. Field of the Invention

The invention is directed systems and methods of monitoring and controlling an
 infrastructure such as, but not limited to the supply and use of commercial, industrial or
 residential water, gas and/or electric, and, in particular, to methods and systems for
 15 monitoring and controlling a municipality and alerting a user to potential faults.

2. Background of the Invention

Municipalities administer and/or outsource numerous safety systems within each
 municipality. Such systems are usually complex infrastructures and include but are not
 limited to water distribution, gas distribution, electricity distribution, waste management,
 20 traffic control, fire departments, police departments, and emergency response
 departments. Each of these systems needs to be monitored for use (authorized or
 unauthorized), faults, tampering, events, leaks, contamination, and/or other issues.

Often to obtain an understanding of the state of any one system, or for billing or
 repair purposes, personnel must be sent into the municipality to manually check for
 25 problems within the system. This is slow, labor-intensive process can lead to overlooked
 problems. Furthermore, preferred aspects of the system may only be evaluated
 irregularly or infrequently, thereby allowing a problem to go unchecked for long periods
 of time. For example, a leak in a water main may cost a water company a significant
 amount of money in lost water, energy usage, and chemical treatment, particularly if the
 30 leak is not discovered for a long period of time. Furthermore, a leak can lead to
 underground structural erosion.

Another problem and disadvantage associated with current systems is the lack of property rights sufficient to maintain a network of monitors and device controllers capable of creating a transmission infrastructure that can adapt to multiple monitors and controllers and form an information network for providing information about the system to the utility monitoring the network. For example, some networks require new polls or towers to be erected for placement of the communication devices.

Furthermore, an issue in one system may cause an issue in another system. For example, a fire reported to the fire department may require the gas company to shut off gas flow to the vicinity of the fire and require the water company to redirect water or additional water pressure to the vicinity. However, current systems are not interoperable. Therefore, it is desirable to have a single system that can monitor different aspects of at least one municipality system continuously and communicate with several entities at the same time.

Summary of the Invention

The present invention overcomes the problems and disadvantages associated with current strategies and systems and provides new systems and methods of monitoring municipality infrastructure.

One embodiment of the invention is directed to an infrastructure monitoring system. The system includes an operations center, and a number of monitoring devices in communication with the operations center. Each monitoring device has at least one sensor sensing at least one condition within an infrastructure, a data storage device storing data sensed by the sensors, a communications device to transmit and receive data, and a processor in communication with a sensor, the data storage device, and/or the communications device. At least one monitoring device monitors a first aspect of the infrastructure and at least one monitoring device monitors a second aspect of the infrastructure.

In preferred embodiments, the operations center and the monitoring devices are in wireless communication. In other embodiments, at least one output device is in communication with the operations center. Each output device has a communications device to receive and/or transmit data, at least one output port, and a processor in communication with the communications device and/or the at least one output port.

In preferred embodiments, the operations center and at least one output device are in wireless communication. Each monitoring device and each output device can be adapted to receive transmissions for a second monitoring device or output device and retransmit the transmission to the second monitoring device or monitoring device. 5 Additionally, each monitoring device and each output device can be adapted to receive transmissions for the operations center and retransmit the transmission to the operations center.

In preferred embodiments, at least one output device is connected to an actuator control device, an alarm, a Radio-Frequency Identification device and/or a tamper prevention device. In preferred embodiments, a monitoring device and an output device are contained within the same unit. In such embodiments, the monitoring device and the output device can share a power source, a communications device, and/or a processor. 10

In preferred embodiments, the infrastructure is at least one of a water distribution system, an electricity distribution system, a gas distribution system, a traffic control system, and an emergency response system. In preferred embodiments, the monitoring device can monitor for at least one of use of a commodity, tampering, leaks, GPS location, proximity, tilt, smoke, temperature, rust, corrosion, fluid flow, pressure, water quality, air quality, and motion. The system can produce an alert when the at least one monitoring device registers an event. The monitoring device can be coupled to a camera. 15 20

In preferred embodiments, there are multiple operations centers. Each operations center can be uniquely located. Each operations center monitors a number of infrastructures concurrently. The infrastructures of are selected from the group including water systems, electrical systems, gas systems, emergency response systems, traffic control systems, and combinations thereof. 25

Another embodiment of the invention is directed to a method of disseminating information. The method includes the steps of obtaining information about at least one infrastructure from an infrastructure monitoring system, evaluating the information, and disseminating the information. The infrastructure monitoring system includes an operations center and a number of monitoring devices in communication with the operations center. Each monitoring device has at least one sensor sensing at least one 30

condition within the infrastructure, a data storage device storing data sensed by the sensor, a communications device to transmit and receive data, and a processor in communication with the sensor, the data storage device, and/or the communications device. At least one monitoring device monitors a first aspect of the infrastructure and at least one monitoring device monitors a second aspect of the infrastructure.

In preferred embodiments, the information is disseminated to at least one of an emergency responder, a utility repair crew, and a dispatcher. The information can be disseminated to two or more entities. In preferred embodiments, the information obtained relates to at least one of commodity use, tampering, leaks, location, proximity, tilt, smoke, temperature, rust, corrosion, fluid flow, pressure, water quality, air quality, and motion.

In preferred embodiments, the infrastructure is selected from the group consisting of water systems, electrical systems, gas systems, emergency response systems, traffic control systems, and combinations thereof. The information can be obtained from a number of infrastructures concurrently. In the preferred embodiment, the information is transmitted over a wireless network. The wireless network is preferably a telecommunications network and the information is disseminated to at least one portable device.

In the preferred embodiment, the information is evaluated to determine if an aspect of the infrastructure exceeds a predetermined threshold. In the preferred embodiment, information is transmitted from the at least one sensor to the operations center.

Other embodiments and advantages of the invention are set forth in part in the description, which follows, and in part, may be obvious from this description, or may be learned from the practice of the invention.

Description of the Drawings

The invention is described in greater detail by way of example only and with reference to the attached drawings, in which:

Figure 1 is a schematic of one embodiment of the system of the invention.

Figure 2 is a schematic of one embodiment of the monitoring device of the invention.

Figure 3 is a schematic of one embodiment of a control device of the invention.

Description of the Invention

As embodied and broadly described herein, the disclosures herein provide detailed embodiments of the invention. However, the disclosed embodiments are merely
5 exemplary of the invention that may be embodied in various and alternative forms. Therefore, there is no intent that specific structural and functional details should be limiting, but rather the intention is that they provide a basis for the claims and as a representative basis for teaching one skilled in the art to variously employ the present invention.

10 A problem in the art capable of being solved by the embodiments of the present invention is monitoring and maintaining an infrastructure. It has surprisingly been discovered that monitoring devices with one or two way communication abilities can be used to detect faults in the municipality's systems and provide on-demand, real time, or near real time device status, maintenance, and control over the systems.

15 A network of monitoring devices of the invention is capable of providing a system administrator with a full picture of the current state of the system. The network preferably includes an array of different monitoring devices each capable of sensing at least one condition. The monitoring devices may be capable of sending and receiving data to and from at least one operations center. Communication may be from the remote
20 monitoring device to a central monitoring facility, to one of a number of regional monitoring centers, to a user, and/or to a research facility. Furthermore, the system preferably includes at least one control device. Each control device is adapted to control a different aspect of the system. The control devices may be part of the monitoring devices or may be separate units. Communication is preferably over the Internet, but
25 may be over a private network, a local area network, or a wide area network. Preferably the communication involves a wireless component, such as from the remote monitoring device and/or control device to a regional monitoring facility, or to distributed monitors. Also preferably, the communications are secured or encrypted such that the communications system cannot be monitored by another unknown party. Preferably
30 access to the system is granted through user names and passwords, although additional and/or alternate encryption methods can be employed.

One embodiment of the invention is directed to water infrastructure systems. In such systems, monitoring devices can be located throughout the system, for example, as attachments to component parts, for feedback to a network that can provide real-time information to the utility operating the network. The network operators can use the information transmitted to activate controlling devices on the network, or to dispatch repair or other services as directed by the information provided by the network. For example, if water pressure monitors on a water meter indicate a variance between locations, a water leak can be reported using the network, and controlling devices can divert water. Pressure meters can be attached to fire hydrants to monitor and report pressure losses throughout the system, providing real-time information to benefit the users of the fire hydrants (fire departments who need to be assured of adequate pressure), the users of the system (water consumers who will be affected by lower pressure), and the operators of the system (who suffer asset loss as a result of lack of real-time information about losses).

Figure 1 depicts a system 100 of the invention for monitoring, controlling, and communicating with at least one monitoring device and/or at least one control device. System 100 includes an operations center 105 in communication with at least one monitoring device 110 and/or one control device 111. In the preferred embodiment, there is bi-directional communication between operations center 105 and devices 110 and 111. Communications can be simplex or duplex. Communication can occur over any communications network 115 known in the art, including but not limited to wired networks, wireless networks, Zigbee networks, Bluetooth networks, Z-wave networks, WiFi networks, WiMax networks, RF networks, local area networks (LAN), internet networks, wide area networks (WAN), cellular telephone network, hardwired telephone networks, 900 MHz wireless networks, and satellite networks. In the preferred embodiment, the network is a fixed network. For example, the fixed network can be a mesh network or a star network. Additionally, devices 110 and 111 and operations center 105 can be in direct communication or can communicate through an intermediary device, such as a relay or a gateway.

Each monitoring device 110 of the invention preferably monitors at least one aspect of the infrastructure. The monitored aspect can be one or more of the components

of the infrastructure (e.g. pipe conditions, valve conditions, fire hydrant conditions, service line conditions, meter conditions, power line conditions, and battery conditions), commodity conditions (e.g. fluid or gas flow, fluid or gas pressure, fluid or gas temperature, and fluid or gas contaminants), or combinations thereof. Additionally, the monitors can be self monitoring. For example the monitors preferably determine if there is a loss of communication, low battery levels, and/or internal damage (e.g. short circuits due to water damage). Additionally, each monitoring device 110 can be structurally stable (e.g. fixed to a valve, pipe, or meter) or movable (e.g. allowed to move with or within the flow of water or gas in the pipes).

Each node in the network of the invention preferably detects errors in transmissions. Error detection can use cyclic redundancy codes using a table based on a defined polynomial or any other method of error detection. In preferred embodiments, transmissions can be rerouted if the primary route is blocked or otherwise unavailable. Furthermore, devices 110 and 111 can confirm receipt of a message, e.g. via a hand shake protocol. In instances where confirmation is not received the message can be resent along the same route or rerouted.

In preferred embodiments, each monitoring device 110 and each control device 111 is assigned a unique identifier. The unique identifier can be related to the devices' geographical locations, street addresses, order of installation, or any other method of identifying the devices. Furthermore, different types of devices 110 and 111 can have identifiers that are unique to that type of device. For example, the identifier for all water meters can start with a WM, while the identifier for all leak detectors can start with a LD. Each communication to and from a device 110 and 111 can include the unique identifier so that the message is received by the correct device 110 or 111, or operations center 105 can determine where the message was sent from.

Each monitoring device 110 and each control device 111 can be retrofitted to an existing system or device, can be coupled to a new system or device, or can be integrated into a new system or device. For example, the system can be connected to, work with, or work independently of a Supervisory control and data acquisition (SCADA) network. In preferred embodiments, each monitoring device 110 and each control device 111 has a

set of adapters to facilitate coupling the monitoring device 110 or control device 111 to a new or existing system or device.

In preferred embodiments, system 100 is divided into sectors with each sector having at least one monitoring device 110 and/or at least one control device 111. Each sector can communicate directly with operations center 105 or each sector can have at least one intermediary communications device that is in communication with the monitoring device 110 and/or control device 111 and operations center 105. In the preferred embodiment, the sectors are divided up by geographical location. For example, all of the devices in one neighborhood can be in a single sector and there is one sector for each neighborhood. In preferred embodiments, one intermediary communications device can service multiple sectors.

In preferred embodiments, each monitoring device 110 and/or control device 111 can communicate with adjacent monitoring devices 110 and/or control devices 111. In such embodiments, each device 110 and/or 111 can act as a transceiver or relay by receiving messages intended for another device or for the operations center 105 and forwarding the message. In embodiments where the system 100 is divided into sectors, monitoring devices 110 and control devices 111 can only communicate within their sector. In other embodiments, monitoring device 110 and control device 111 can communicate with devices 110 and/or 111 in other sectors. Each remote monitoring device 110 and/or the operations center 105 may be able to determine if a transmitted message was received by the intended device and, if not, may be able to reroute the message until the message is properly received. Additionally, relay devices can be implemented in the system to further extend the range of communications. For example, relay devices can be placed on telephone poles, on municipal buildings, within fire hydrants, and/or under manhole covers. In preferred embodiments, devices 110 and 111 communicate over a mesh network. In the mesh network, devices 110 and 111 can communicate with other devices 110 and 111 within the mesh network. Operations center 105 can set specified communications pathways derived from routing tables.

Operations center 105 can be located at a municipality office, a private or public company, a fire station, a police station, or any other entity that monitors operations center 105. In other embodiments, operations center 105 can be a remotely hosted

operations center accessible by a device capable of accessing the Internet. In such embodiments, operations center 105 can take advantage of cloud computing (e.g. a network of remotely hosted computers, servers, and data storage devices). Compared to non-remotely hosted computer networks, cloud computing can increase ease of use, increase access, increase security, decrease costs, be custom tailored, and provide an unrestricted expansion of storage space. Additionally, in preferred embodiments, there is a plurality of operations centers 105. One or more operations centers can be located at different entities and each control center can monitor a different aspect of system 100. For example, in embodiments where one monitoring device monitors water usage and another monitors gas leaks, the water usage aspect can be monitored by a water utility company and the gas leaks can be monitored by the gas utility company and/or the fire department. In preferred embodiments, there are redundant operations centers 105, where at least two operations centers 105 monitor the same aspect of system 100. Operations center 105, in preferred embodiments, can send transmissions to update the firmware of devices 110 and 111.

Figure 2 is a schematic of a monitoring device unit 200. Monitoring device unit 200 includes a processor 205. Processor 205 is coupled to at least one input port 210 for receiving data from sensors 215. Processor 205 is also coupled to a transceiver 220 for sending and receiving signals. In preferred embodiments, processor 205 is coupled to a data storage unit 230. Data storage unit 230 can hold a predetermined amount of data received from the sensors 215. For example, data storage unit 230 can hold data for a predetermined amount of time (e.g. one day, one week, or one month), can hold a predetermined number of readings (e.g. 10 readings, 100 readings, 1000 readings), or can hold data until directed to purge the data by the operations center. Additionally, data storage unit 230 can hold instructions for processor 205 to execute upon prompting from the operations center. In the preferred embodiments, processor 205 compiles at least some of the data stored in data storage unit 230 for transmitting to the operations center.

Each remote monitoring device 200 may collect data and/or transmit data continuously, at specific intervals, or randomly. In embodiments where the monitoring device 200 collects and transmits data in a non-continuous configuration, monitoring device 200 may turn off or reduce power consumption during the non-data collecting

periods to save energy. In preferred embodiments, processor 205 is coupled to a power source 235. Power source 235 can be a device capable of powering processor 205 and devices attached to processor 205. For example, power source 235 can be a battery, solar panel array, wind turbine, water turbine, electrical lines, or combinations thereof. In preferred embodiments, there is also a backup power source, such as a battery. In preferred embodiments, the power may derive from the operation of the infrastructure system.

In the preferred embodiment, processor 205 is coupled to at least one sensor 215 that monitors at least one condition associated with the monitoring device. In preferred embodiments, sensors 215 can determine the status of a device. Sensors 215 can be directly wired to processor 205 or can use wireless communication to send and receive signals from processor 205. Sensors 215 can be positioned within the monitoring device or be external to the monitoring device. In preferred embodiments, sensors 215 are positioned remote from the monitoring device. For example a sensor can be positioned on a nearby building or telephone pole. In the embodiments, where sensors 215 and processor 205 communicate wirelessly, the same communications protocol can be used in the sensor/processor communication as in the processor/operations center communication, or different communications protocols can be used in the sensor/processor communication as in the processor/control center communication. For example, the sensor/processor communications can use RF protocols while the processor/control center communications can be over a wired network.

In preferred embodiments, sensor 215 is a use monitor. In such embodiments, the use monitor records the amount of water, gas, electricity, or other commodity that is used by a customer over a specified period of time. The use monitor can continuously record the amount of the commodity used or the use monitor can provide a signal to processor 205 that the commodity is in use. Processor 205 can transmit a signal to the operations control to alert the operations center that the monitoring device is being used and/or how much of the commodity is flowing through the sensor. In preferred embodiments, the operations center can request a reading from the use monitor on demand. In preferred embodiments, the processor or the operations center can determine based on the use, if there is unauthorized use of the commodity. Upon detection of unauthorized use, at least

one of processor 205 or the operations center can generate an alarm that there is unauthorized use. For example, in embodiments where the use monitor is coupled to a fire hydrant, if the use monitor indicates that the fire hydrant is in use, however no fire is reported, the operations center can disseminate an alert that there is potential misuse of
5 the fire hydrant.

In preferred embodiments, at least one sensor 215 is a tamper sensor. The tamper sensor can be a motion detector, a contact sensor, a rotation sensor, a touch sensor, a proximity sensor, a biofeedback sensor, a temperature sensor, a capacitance sensor, a resistance sensor, or any other sensor that is able to detect the presence of an object. The
10 tamper sensor can send a message to processor 205 when the tamper sensor detects an event. The processor 205 will then evaluate the event to determine if a device being monitored is being tampered with or will relay the message to the operations center for evaluation. The monitored device can be a fire hydrant, utility meter, valve, manhole cover, pump, or any other device that may be tampered with. Upon detection of a tamper
15 event, at least one of processor 205 and the operations center can generate an alarm that the device is being tampered with. In preferred embodiments, the monitoring device may activate a tamper prevention device (described below). In preferred embodiments, the operations center will send a transmission to processor 205 telling processor 205 to disregard messages from the tamper sensor for a predetermined period of time or until
20 another message is received from the operations center telling processor 205 to resume monitoring for tamper events. For example, if a fire department needs to use a fire hydrant, the operations center will send a message to processor 205 to temporarily disregard any tamper events. Once the fire department is finished using the fire hydrant the operations center will send a message to processor 205 to start monitoring for tamper
25 events again.

In preferred embodiments at least two of sensors 215 are leak detectors. Each leak detector can include an in-pipe leak detector and/or an exterior leak detector. In gas applications, the leak detectors are preferably vapor sensors. While in liquid applications, preferably the leak detectors use acoustic monitoring to determine presence
30 and location of a leak. The energy generated from a leak is transmitted within a pipe through the commodity as well as through the pipe wall. Each leak detector can detect

the vibrations made by the leak in the commodity or the pipe wall, joint or service line. To determine the location of a leak, at least two detectors must detect the same leak. Based on the velocity of the sound traveling along the pipe (V), the distance between the two detectors (D) and the delay between the times each detector detects the sound (T), the
5 location of the leak (L) can be determined by the following equation:

$$L = (D - (V \times T))/2$$

When using the above equation, the typical velocity of sound in water is about 1500 m/s while the typical speed of sound through an iron pipe is 5100 m/s. The velocity can be measured empirically. For example, if the leak is exactly midway between the two
10 detectors the sound would reach both detectors at the same time. Each detector may monitor continuously or at predetermined periods of time. The leak detectors can send a message to processor 205 when the leak detectors detect an event. The processor 205 can then evaluate the event to determine if there is a leak and how severe the leak is or can relay the message to the operations center for evaluation. Upon detection of a leak event,
15 at least one of processor 205 or the operations center can generate an alert that there is a leak if the leak is determined to be severe enough to warrant attention.

In preferred embodiments, at least one sensor 215 is a smoke detector. The smoke detector can be a photoelectric detector, an ionization detector, or any other device that can detect the presence of smoke. The smoke detector can be located within the
20 monitoring device or exterior to the monitoring device. In the preferred embodiment, the smoke detector monitors continuously for smoke. The smoke detector can send a message to processor 205 when the smoke detector detects an event. The processor 205 can then evaluate the event to determine if there is smoke or can relay the message to the operations center for evaluation. Upon detection of smoke, at least one of processor 205
25 or the operations center can generate an alert that there is smoke.

In preferred embodiments, at least one sensor 215 is a temperature sensor. The temperature sensor can be a contact sensor (e.g. thermocouples, thermistors, liquid-in-glass thermometers, resistance temperature detectors, filled system thermometers, bimetallic thermometers, semiconductor temperature sensors, and phase change
30 indicators) or a non-contact sensor (e.g. radiation thermometers, thermal imagers, ratio thermometers, optical pyrometers, and fiber optic thermometers). The temperature

sensor can be located within the monitoring device or exterior to the monitoring device. In the preferred embodiment, the temperature sensor monitors continuously for the temperature to rise above or drop below a predetermined threshold. The temperature sensor can send a message to processor 205 when the temperature sensor detects a
5 temperature beyond the thresholds. The processor 205 can then evaluate the event to determine if there the temperature is a problem (such as freezing pipes or fire) or can relay the message to the operations center for evaluation. Upon detection of undesirable temperatures, at least one of processor 205 or the operations center can generate an alert that there is an undesirable temperature condition.

10 In preferred embodiments, at least one sensor 215 is a rust and/or corrosion sensor. The sensor can detect rust and/or corrosion using any method known in the art, including but not limited to liquid penetration inspection, magnetic particle inspection, radiographic inspection, visual inspection, eddy current inspection, ultrasonic inspection, and thermographic inspection. The sensor can send a message to processor 205 when the
15 sensor detects a rust or corrosion beyond a threshold value. The processor 205 can then evaluate the rust or corrosion to determine if there is a problem or can relay the message to the operations center for evaluation. Upon detection of undesirable rust or corrosion, at least one of processor 205 or the operations center can generate an alert that there is an undesirable amount of rust or corrosion.

20 In preferred embodiments, at least one sensor 215 is a fluid flow sensor. Fluid flow sensor can be used either in gas systems or liquid systems. The fluid flow sensor can detect direction of the flow, turbidity of the flow, velocity of the flow, density of the flow, viscosity of the flow, and/or any other aspect of the flow. The fluid flow sensor may be a velocimeter, a laser-based interferometer, a vane, a rotary potentiometer, a Hall
25 effect sensor, a device to measure heat transfer caused by the flowing fluid, or any other device know in the art to measure the flow of fluid. The sensor can send a message to processor 205 when the sensor detects a flow anomaly. The processor 205 can then evaluate the event to determine if the anomaly is a problem or can relay the message to the operations center for evaluation. Upon detection of an anomaly, at least one of
30 processor 205 and the operations center can generate an alert that there is an anomaly.

In preferred embodiments, at least one sensor 215 is a pressure sensor. In the preferred embodiment, the pressure sensor is positioned within the flow of fluid or area in which the pressure is being sensed. For example, the pressure sensor can be positioned at the base of a fire hydrant and in the water to determine the water pressure within water system, in a pipe to determine gas or water pressure within a gas or water system, or in a room to determine air pressure within the room. The pressure sensor can be a piezoresistive strain gauge, a capacitive gauge, an electromagnetic gauge, a piezoelectric device, or any other device known in the art to measure pressure. The sensor can send a message to processor 205 when the sensor detects a pressure anomaly. The processor 205 can then evaluate the event to determine if the anomaly is a problem or can relay the message to the operations center for evaluation. Upon detection of an anomaly, at least one of processor 205 or the operations center can generate an alert that there is an anomaly.

In preferred embodiments, at least one sensor 215 is a water quality monitor. The water quality monitor can monitor a single aspect of water flowing through the system or multiple aspects of the water. For example, the water quality monitor can monitor one or more of the water's bacteria levels, pharmaceutical levels, alkalinity, chlorine and/or chloramine levels, hardness, pH levels, peroxide content, iron levels, nitrate levels, nitrite levels, arsenic levels, pollution levels, oxygen levels, biomass levels, and/or any of the other contaminants regulated by the Environmental Protection Agency (EPA). In embodiments where there are multiple monitoring devices, all the devices can monitor the same aspects, each device can monitor a different aspect, or a combination thereof. In the preferred embodiment, the water quality monitors test the water continuously, however, in preferred embodiments, the water quality monitors test the water at predetermined time intervals (e.g. once a hour, once a day, once a week, etc.). Each water quality monitor relays data to processor 205. Processor 205 can store the data on database 230 or transmit the data to the operations center. Either processor 205 or the operations center can monitor the data received from the water quality monitors to determine if there is a change in the levels of the contaminants or if the levels of the contaminants rise above a threshold level. Upon detection of unsafe contamination

levels, at least one of processor 205 or the operations center can generate an alert that there is contamination in the water system.

In the embodiments where at least two monitoring devices are monitoring the same aspect of the water, the operations center can determine if there is a change in the aspect of the water from the location of one monitoring device to the location of the other. If there is a change, the operations center can generate an alert that there is a change in the water system and output the approximate location of the change in the aspect of the water.

In preferred embodiments, at least one sensor 215 is an air quality monitor. The air quality monitor can monitor a single aspect of the air or multiple aspects of the air. Furthermore, the air quality monitor can monitor the air within a facility or ambient air. For example, the air quality monitor can monitor one or more of the air's benzene levels, carbon disulfide levels, urethane levels, formaldehyde levels, phosphorus levels, naphthalene levels, parathion levels, quinoline levels, trifluralin levels, and/or any of the other contaminants whose acceptable levels have been set by the Environmental Protection Agency. In embodiments where there are multiple monitoring devices, all the devices can monitor the same aspects or each device can monitor a different aspect, or a combination thereof. In the preferred embodiment, the air quality monitors test the air continuously, however, in preferred embodiments, the air quality monitors test the air at predetermined time intervals (e.g. once a hour, once a day, once a week, etc.). Each air quality monitor relays data to processor 205. Processor 205 can store the data on database 230 or transmit the data to the operations center. Either processor 205 or the operations center can monitor the data received from the air quality monitors to determine if there is a change in the levels of the contaminants or if the levels of the contaminants rise above a threshold level. Upon detection of unsafe contamination levels, at least one of processor 205 or the operations center can generate an alert that there is contamination in the air.

In the embodiments where at least two monitoring devices are monitoring the same aspect of the air, the operations center can determine if there is a change in the aspect of the air from the location of one monitoring device to the location of the other. If there is a change, the operations center can generate an alert that there is a change in

the air and output the approximate location of the change in the aspect of the air. Furthermore, in embodiments where there is a time stamp associated with each reading, the control center can determine the approximate direction and speed at which the contaminant is moving.

5 In preferred embodiments, at least one sensor 215 is a motion detector. The motion detector can be a radar-based motion detector, a photo-sensor motion detector, a passive infrared motion detector, a magnetic motion detector, a pressure sensitive motion detector, or any other device capable of detection the motion of objects. The motion detector can be used, for example, to count the number of cars passing through an
10 intersection to control a traffic light, for tamper prevention as described above, for security purposes, and/or to control street lights. The motion detector can be placed within the monitoring device or exterior to the monitoring device. Upon detecting motion, the motion detector can relay the detection to processor 205. Processor 205 can save the detection on database 230 or transmit a message regarding the detection to the
15 operations center. Processor 205 or the operations center can evaluate the detection and act in accordance with the purpose of the motion detector. For example, if the motion detector detects a predetermined number of vehicles have passed the monitoring device, processor 205 or the operations center can cause a traffic light to switch from green to red. As a second example, if the motion detector detects a motion after a
20 predetermined time, e.g. after sunset, processor 205 or the operations center can cause the street lights near the monitoring device to illuminate for a predetermined period of time.

 In preferred embodiments, at least one sensor 215 is a tiltmeter. The tiltmeter can be a pendulum, a water tube, a bubble-level meter, and/or a MEMS electronic meter. The tiltmeter can be located on devices within the system, such as, but not limited to,
25 pipes, fire hydrants, meters, valves, telephone poles, manhole covers, and light posts. The sensor can send a message to processor 205 when the sensor detects a tilt beyond a threshold value. The processor 205 can then evaluate the tilt to determine if there is a problem or can relay the message to the operations center for evaluation. Upon detection of undesirable tilt, at least one of processor 205 or the operations center can generate an
30 alert that there is an undesirable tilt. For example, if a telephone pole is struck by a car, the tiltmeter will indicate that the telephone pole is tilting at an undesirable level and the

operations center can alert the municipality to send out a repair crew to assess the situation and repair the telephone pole.

In preferred embodiments, at least one sensor 215 is a proximity sensor. The proximity sensor can use electromagnetic technology, electrostatic technology, infrared technology, or a touch switch. The proximity sensor can detect if devices are properly closed or if devices are improperly touching. The sensor can send a message to processor 205 when the sensor detects proximity beyond a threshold value. The processor 205 can then evaluate the proximity to determine if there is a problem or can relay the message to the operations center for evaluation. Upon detection of undesirable proximity, at least one of processor 205 or the operations center can generate an alert that there is an undesirable proximity. For example, if a valve is improperly closed, the proximity sensor will indicate that the valve is not closed and processor 205 can alert the municipality to take proper actions to close the valve.

In preferred embodiments, at least one sensor 215 is a camera. The camera can be an infrared camera, a video camera, a still camera, a digital camera, a film camera, combinations thereof, or any other device capable of acquiring an image. In a preferred embodiment, the camera is a digital video camera that takes video images continuously. In another preferred embodiment, the camera is a digital still camera that takes still images at regular intervals or upon command from processor 205. In preferred embodiments, the camera can be a traffic camera and take a picture when instructed to by processor 205, for example upon determination that a vehicle is running a red light. In other embodiments, the camera is be use to perform visual inspections of the systems infrastructure. For example, the field of view of the camera can include a device within the system that is apt to corrode and the camera can provide an easy method to visually inspect any degradation of the device. The camera can send image data to processor 205 where the data is stored on database 230 or is transmitted to the operations center. In preferred embodiments, image data is streamed continuously from the camera to processor 205 and from processor 205 to the operations center. The data stream can either be live or delayed. The camera can be located on the monitoring device, near the monitoring device, or within the monitoring device with a portion of the camera extending outside the monitoring device or with a hole in the monitoring device through

which the camera can obtain images. In preferred embodiments, the camera is positioned on an actuator. The actuator can move to reposition the field of view of the camera. The actuator can move upon demand from processor 205 or can move autonomously. In the embodiments where the actuator moves autonomously, the movement can be continuous or sporadic.

In preferred embodiments, at least one sensor 215 is a Global Positioning System (GPS) receiver. In the preferred embodiment, the GPS receiver is located on devices within the system, such as, but not limited to, pipes, fire hydrants, meters, valves, telephone poles, manhole covers, and light posts. The sensor can send a message to processor 205 indicating the sensor location. The processor 205 can then relay the message to the operations center for evaluation, conformation, and documenting. Upon detection of unexpected location, at least one of processor 205 or the operations center can generate an alert that the sensor has moved, possibly indicating that the device has been dislodged, tampered with, or stolen. Additionally, the GPS location can be used, for example, by emergency responders to locate fire hydrants, or repair crews to determine the location of a buried device. In such embodiments, the operations center can disseminate information to the emergency responders or repair crews to easily locate the device. The dissemination can occur by any method, including but not limited to, verbally, over a telecommunications network (e.g. to a smart phone or portable computer), or over a shortwave radio. In embodiments where the monitoring device is moving with the flow of fluid, the sensor can provide updated locations of the monitoring device to track, for example, the flow or contamination levels within the flow.

Other possible sensors 215 connected to monitoring device 200 can include, but are not limited to, flow rate meters, backflow meters, system status monitors, and power level monitors.

Figure 3 is a schematic of a control device 300. Control device 300 includes a processor 305. Processor 305 is coupled to at least one output port 310 for controlling an output device 340. Processor 305 is also coupled to a transceiver 320 for sending and receiving signals. Processor 305 is communicatively coupled to output port 310. Output port 310 is connected to at least one output device 340. Each output device can 340 have the same purpose or each output device 340 can have a different purpose, or

combinations thereof. Output devices 340 can be located within control device 300 or external to control device 300, as shown. Furthermore, output devices 340 can be attached to control device 300 or can be remote from control device 300. Output devices 340 communicate with output port 310 through wired or wireless communication channels. In preferred embodiments, output devices 340 are capable of bidirectional communication. In preferred embodiments, control device 300 is an integral part of a monitoring device. In such embodiments, the control device and the monitoring device can share the same processor and/or transceiver.

In preferred embodiments, processor 305 is coupled to a data storage unit 330. Data storage unit 330 may store instructions for processor 305 of how to control output devices 340. In preferred embodiments, processor 305 is coupled to a power source 335. Power source 335 can be any device capable of powering processor 305 and any devices attached to processor 305. For example, power source 335 can be a battery, solar panel array, wind turbine, water turbine, electrical lines, or combinations thereof. In preferred embodiments, there is also a backup power source, such as a battery.

In preferred embodiments, at least one output device 340 is an actuator control device. The actuator control device can control any type of actuator, including but not limited to, a tamper prevention device, a locking device, a camera motion device, a fire hydrant nut opening device, or a valve. The actuator control device can control the actuator autonomously or upon demand from processor 305. For example, upon receiving a signal that a particular event has been sensed, processor 305 may send a command to the actuator control device to act in a particular manner. Likewise, in preferred embodiments the control signal may come from the operations center. The actuator can be mechanical, electrical, or a combination thereof.

In preferred embodiments, at least one output device 340 is an alarm. The alarm can be a visual alarm, an audible alarm, a tactile (i.e. vibration) alarm, or a combination thereof. The alarm can be located within the monitoring device, exterior to the monitoring device, at the operations center, remote from the system, or any other location to alert people. Furthermore, there can be more than one alarm at different locations. For example, in the embodiments where there is a smoke detector, there can be an audible alarm located within the fire detector to alert people around the monitoring device of a

potential fire, there can be an audible alarm at the fire station to alert the fire department of the potential fire, and there can be a visual alarm at the gas utility company to indicate that the flow gas in the vicinity of the potential fire should be shut off. In preferred embodiments the alarm is controlled by the processor 305, while in other embodiments
5 the alarm is controlled by the operations center. In preferred embodiments, the alarm has an on/off switch controllable locally.

In preferred embodiments, at least one output device 340 is a tamper prevention device. The tamper prevention device can be a mechanical lock, an alarm, a light, an electrical shock generator, a retaining device, an electrical lock, or any other device
10 capable of preventing tampering. The tamper prevention device may merely deter tampering or may incapacitate a person who is trying to tamper with the device, depending on the level of security. In preferred embodiments the tamper prevention device is controlled by the processor 305, while in other embodiments the tamper prevention device is controlled by the operations center.

In preferred embodiments, at least one output device 340 is a Radio-Frequency Identification (RFID) device. The RFID device can broadcast information about the device it is attached to. For example, the RFID device may broadcast manufacturer information, location information, last service date, device information (e.g. make, model, and/or year), current status (e.g. a valve can broadcast if it is open or closed), etc.
15 In preferred embodiments the RFID device is updateable by the processor 305 or by the operations center. The RFID device can be either an active (e.g. battery powered) or passive (e.g. require an external source to provoke signal transmission) device.
20

Examples:

A system of the invention is monitoring a water distribution infrastructure. The
25 system is used to automatically control the water pressure within the system. Such a system includes a number of water meters disbursed throughout the infrastructure relaying real time use information to a control center. Upon a determination by the operations center that there is low usage of the system (e.g. at night) based on information received by a predetermined number of the water meters, the operations
30 center causes pumps supplying pressure within the system to reduce or cease pumping. Thereby cutting down on the electricity used by the pumps while maintaining enough

pressure throughout the infrastructure to satisfy any water needs. The determination to reduce or cease pumping can be also based on information received from pressure sensors disbursed throughout the infrastructure. For example, if the pressure within the infrastructure exceeds a threshold value, the operations center causes the pumps to reduce
5 or cease pumping.

In another example, the system is used to assist in maintaining the infrastructure. Water pipes and valves are often buried underground making it difficult to locate, assess the status of the devices, and repair them if necessary. Using an example of the above described system, each device is equipped with a monitoring the device. The monitoring
10 device, for example, may monitor for corrosion using a corrosion monitor, geographical location using a GPS receiver, and leaks using a leak detector. Upon detection of corrosion and/or a leak, the monitoring device sends a message to the operations center where the information is analyzed. The operations center is able to make a determination if the corrosion and/or leak is severe enough to warrant fixing, if the corrosion and/or
15 leak should be watched to determine if it worsens, or if the corrosion and/or leak can be ignored. The operations center will also alert a person of the situation for further assessment.

If it is determined that the corrosion and/or leak should be fixed, the operations center disseminates information to a repair crew and redirects water flow away from the
20 device. Such information can include location of the device, based on data received the GPS receiver, problem associated with the device, device information (e.g. make, model, and/or year), etc. The monitoring device can also be equipped with a RFID transmitter, which transmits at least some of the above information. The repair crew receives the information on a smart phone, a portable computer, or other device capable of receiving
25 such information. Upon completion of the repair, the operations center updates the system to indicate a new last repaired date for the device.

In another Example, the system is monitored by several entities within a municipality at the same time. For example, a fire department, a gas utility, a water utility, an electric utility, and traffic control center all monitor the system concurrently.
30 Upon detection of smoke by a monitoring device, the control center alerts each entity of a potential fire. The location of the potential fire is determined by cross-referencing the ID

number of the monitoring device with a lookup table or based on information received from a GPS receiver. The fire department uses the location information to send out emergency response personnel to the vicinity of the potential fire. The gas utility uses the location information to divert or shut off gas flow to the vicinity of the potential fire. The water utility uses the location information to divert water to or increase water pressure in the vicinity of the potential fire as well as determines if any fire hydrants in the vicinity of the potential fire are potentially damaged (e.g. are tilted at an unusual angle, are receiving no or little water pressure, or have been tampered with) based on information received from monitoring devices attached to the fire hydrants. The location of the fire hydrants is determined by cross-referencing the ID number of the monitoring device with a lookup table or based on information received from a GPS receiver. The water utility automatically alerts the fire department as to which fire hydrants to use. The water utility also disables any tamper prevention devices associated with the fire hydrants. The electric utility receives a signal that additional pressure may be needed within the water system and provides an increased electrical load to the water pumps. Additionally, the traffic control center adjusts traffic lights en route from the fire station to the vicinity of the potential fire to assist the fire trucks in arriving quickly and safely.

In another example, the system is used to monitor contamination of the fluid flowing through the system. The system includes pressure sensors, leak detectors and contamination detectors. Leaks within the system can cause a pressure drop throughout the system which can lead to contaminants being drawn into the system. For example, if a pipe is under water and the pressure inside the pipe drops below the pressure outside the pipe, the exterior water will flow into the pipe. Therefore, the system has several monitoring devices to check for such potential or actual contamination. The pressure sensors will indicate if the pressure within the system drops below a threshold level at which contaminants can be drawn into the system. The leak detectors will indicate that there is a leak through which contaminants can enter the system. While the contamination detectors will indicate if there is contamination within the system, indicating a possible breach of the infrastructure of the system.

Other embodiments and uses of the invention will be apparent to those skilled in the art from consideration of the specification and practice of the invention disclosed

herein.

It is
intended that the specification and examples be considered exemplary only with the true
scope and spirit of the invention indicated by the following claims. Furthermore, the
5 term “comprising of” includes the terms “consisting of” and “consisting essentially of.”
All examples illustrate embodiments of the invention, but should not be viewed as
limiting the scope of the invention.

CLAIMS

1. An infrastructure monitoring system for use with a fire hydrant and a water distribution system coupled to the fire hydrant, the system comprising:

an operations center; and

a plurality of communications devices communicatively coupled to the operations center,

wherein

at least one communications device of the plurality of communications devices is configured to be coupled to the fire hydrant and comprises a repeater;

at least another communications device of the plurality of communications devices comprises:

 a monitoring device, the monitoring device comprising at least one sensor sensing at least one condition within the water distribution system;

 a data storage device storing data sensed by the at least one sensor;

 a transceiver device adapted to transmit and receive data; and

a processor communicatively coupled to the at least one sensor, the data storage device, and the transceiver device, the processor configured to:

receive the data sensed by the at least one sensor;

determine, based on the data sensed by the at least one sensor, if there is a problem with the at least one condition within the water distribution system that the at least one sensor is sensing;

upon determining that there is a problem with the at least one condition within the water distribution system that the at least one sensor is sensing, transmit a message to the operations center via the transceiver device, and

periodically compile sensing data stored in the data storage device and transmit the compiled sensing data to the operations center via the transceiver device,

the monitoring device, in use

is positioned remotely from the at least one communications device;

moves with a flow of water within the water distribution system; and

transmits the compiled sensing data to the operations center via the repeater.

2. The system of claim 1, wherein the one communications device further comprises one of a monitoring device or an output device.
3. The system of claim 1, wherein the one communications device is configured for placement within one of a nozzle cap, a pumper nozzle, a hose nozzle, a fire truck hookup, and a bonnet of the fire hydrant.




FIG. 1




FIG. 2




FIG. 3

