



US006363587B1

(12) **United States Patent**  
**Richter et al.**

(10) **Patent No.:** **US 6,363,587 B1**  
(45) **Date of Patent:** **Apr. 2, 2002**

- (54) **PERFORATED RELEASE TAPE**
- (75) Inventors: **Gerhard Ludwig Richter**, Erkelenz (DE); **Randall Lynn Alberg**, Maplewood, MN (US)
- (73) Assignee: **3M Innovative Properties Company**, St. Paul, MN (US)
- (\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

EP	0 853 935 A2	7/1998
EP	0 894 448 A1	2/1999
EP	0 927 550	7/1999
EP	0 941 730	9/1999
JP	8-2365	1/1996
JP	10-137008	5/1998
WO	WO 96/12464	5/1996
WO	WO 97/28774	8/1997

*Primary Examiner*—James R. Brittain  
(74) *Attorney, Agent, or Firm*—Gary L. Griswold; Robert W. Sprague; William J. Bond

- (21) Appl. No.: **09/499,135**
- (22) Filed: **Feb. 7, 2000**
- (51) **Int. Cl.<sup>7</sup>** ..... **A61F 13/56**
- (52) **U.S. Cl.** ..... **24/306**; 604/391
- (58) **Field of Search** ..... 24/304, 306, 442, 24/DIG. 11; 604/391

(57) **ABSTRACT**

There is provided a mechanical fastener tape tab laminate comprising a tape tab backing having at least a first distal end portion, an inner tab portion and second distal end portion, the second distal end portion provided with a mechanical fastener material. The first distal end portion is provided with an adhesive layer for attachment to a disposable absorbent article. The tape tab backing further has a folded tape portion comprising a backing having an adhesive layer on an outer face and having at least an inner leg portion and an outer leg portion. The outer leg portion has an exposed adhesive provided for attachment to the disposable absorbent article. The inner and outer leg portions are separated by at least one fold. The folded tape portion backing has a line of weakness along the at least one fold. The line of weakness is provided on a portion of the tape tab backing spaced from the first distal end portion. This line of weakness keeps the tab laminate from flagging prior to use and is easily severable to allow the tab to be extended for use.

(56) **References Cited**


**U.S. PATENT DOCUMENTS**

3,848,594 A	11/1974	Buell	128/284
4,726,971 A	2/1988	Pape et al.	428/40
5,176,670 A	1/1993	Roessler et al.	604/391
5,256,231 A	10/1993	Gorman et al.	156/178
5,926,926 A	7/1999	Kato	24/442

**FOREIGN PATENT DOCUMENTS**

EP	0 321 232 B1	5/1993
EP	0 818 188 A2	1/1998
EP	0 832 631 A2	1/1998

**60 Claims, 7 Drawing Sheets**






Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16



**PERFORATED RELEASE TAPE****BACKGROUND AND FIELD OF INVENTION**

The present invention relates to a mechanical fastener closure tape tab laminate for use on disposable articles, generally a disposable absorbent diaper.

Closure tape tab laminates utilizing mechanical fasteners are known in the art with the mechanical fastener generally located on a tape tab backing. The mechanical fastener is attached generally by the use of adhesives. The opposite end of the tab is generally permanently attached to one face of the disposable article with the mechanical fastener extending out beyond a side edge of the absorbent article for use in forming a closure with a mating attachment provided on a opposite end of the disposable article. Generally when the diaper or the like is packaged prior to use, it is preferred that the tab be folded back into the main body of the diaper. Otherwise the tab will extend out beyond the edge of the diaper and create problems such as inadvertently attaching to substrates as well as making it difficult to fold the article into a form suitable for an easily packaged product. As such, it is preferred that the mechanical fastener "free end" be folded back onto the opposite face of the diaper prior to use. The problem of an unattached tab extending out beyond the edge of the diaper is generally known as flagging. The conventional approach to solving this flagging problem has been to provide a pressure sensitive adhesive somewhere on the tape tab laminate which would allow the tape tab free end to releasably adhere to a suitable surface on the diaper. The end user would then grasp a fingerlift on the tab and break this adhesive bond and extend the tab for use. Such an adhesive anti-flagging configuration is disclosed, for example, in European Patent No. 321,232, where the adhesive is adjacent the mechanical fastener on the tab. European Patent Application No. 894,448 discloses providing pressure sensitive adhesive on the tops of mechanical fastener hook heads for anti-flagging. Japanese Patent Application No. 8-2365 provides adhesive on the extended portion of the tab, which adhesive then transfers to the diaper such that there is no exposed adhesive on the free end of the tab when in use. The use of an exposed adhesive for anti-flagging is also taught in PCT Patent Application No. W097/28774. Although effective, the use of an exposed pressure sensitive adhesive is undesirable in many instances with a mechanical fastening system. For example there are many exposed fibrous surfaces on absorbent articles with mechanical fasteners, which fibrous surfaces can cause fiber contamination of the adhesive. Also there is undesirable reaction on the part of some customers to the use of exposed adhesives in mechanical fastener systems of this type. For these reasons and others there has been considerable work on a non-adhesive solution to the flagging problem.

The use of a non-adhesive approach to the flagging problem is proposed, for example, in European Patent Application No. 818,188. This patent document proposes releasably welding the tab free end to an inner surface of a diaper. Although effective, this is problematic in that it requires an on-line welding during the diaper manufacturing process, which can slow diaper production. Japanese Patent Application No. 10-137008 and U.S. Pat. No. 5,926,926 disclose the use of a separate small patch of loop material, which can engage with the hooks. These loop patches are generally placed where the anti-flagging adhesive would be placed. The small loop patches suggested in these patents are unlikely to be entirely effective in providing for a reliable connection. Also these loops add significant bulk to the tabs

creating the possibility of hard bands in the packaged diapers and making it difficult to provide long yardage rolls of pre-laminated mechanical fastener tape tabs. European Patent Application No. 832,631 proposes a complicated structure involving a splittable nonwoven material. This would have similar issues as the use of loop patches and be difficult to manufacture. European Patent Application No. 853,935 discloses a complicated laminated tab structure, which comprises a tape tab backing having two adhesive coated portions with an adhesive free region separating them and a separate carrier for the hook. The hook carrier has a separate adhesive attachment zone and is perforated in an adhesive free zone. The carrier perforation is separable which allows the tab to be maintained in a folded condition prior to use and broken or torn to allow the tab to be extended. Although effective in maintaining a tab in a folded condition, this construction does not allow for a conventional Y-bond to provide a secure attachment to both faces of the diaper side edge and requires two complicated zone adhesive coatings on the tape tab backing and the carrier.

Although there are many varied techniques taught in the art to maintain a fastening tab laminate in a folding condition around the edge of a diaper prior to use, there still remains the need for an effective way of providing such an arrangement for a mechanical fastener tape tab laminate which provides for a combination of ease of construction, a reliable and secure attachment that is easily releasable by the user and which does not rely on exposed pressure sensitive adhesives and preferably in a construction that allows the possibility of providing a secure Y-bond to the edge of the diaper.

**BRIEF DESCRIPTION OF THE DRAWINGS**

FIG. 1 is a perspective view of a diaper using a tape tab in accordance with the invention.

FIG. 2 is a perspective view of a diaper roll of a pre-laminated mechanical fastener tape tab of the invention.

FIG. 3 is an exploded view of the first embodiment of a mechanical fastener tape tab laminate of the invention.

FIG. 4 is an assembled view of the first embodiment mechanical fastener tape tab laminate.

FIG. 5 is an assembled view of the first embodiment mechanical fastener tape tab laminate when initially attached to an article.

FIG. 6 is an assembled view of the first embodiment mechanical fastener tape tab laminate when fully attached to an article.

FIG. 7 is an assembled view of the first embodiment mechanical fastener tape tab laminate in a use form.

FIG. 8 is an exploded view of a second embodiment of a mechanical fastener tape tab laminate of the invention.

FIG. 9 is an assembled view of the second embodiment of a mechanical fastener tape tab laminate of the invention.

FIG. 10 is an assembled view of the second embodiment of a mechanical fastener tape tab laminate of the invention when initially attached to an article.

FIG. 11 is an assembled view of the second embodiment of a mechanical fastener tape tab laminate of the invention when fully attached to an article.

FIG. 12 is an assembled view of the second embodiment of a mechanical fastener tape tab laminate of the invention in a use form.

FIG. 13 is a third embodiment of a mechanical fastener tape tab laminate of the invention.

FIG. 14 is an assembled view of fourth embodiment of a mechanical fastener tape tab laminate of the invention.

FIG. 15 is an assembled view of fifth embodiment of a mechanical fastener tape tab laminate of the invention.

FIG. 16 is an assembled view of sixth embodiment of a mechanical fastener tape tab laminate of the invention.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to FIG. 1, a conventional diaper construction 1 is shown comprising a liquid permeable topsheet 2 and a liquid impermeable backsheet 3. Between the topsheet 2 and the backsheet 3 would be an absorbent pad structure (not shown). The liquid permeable topsheet 2 would generally be a nonwoven web or like permeable structure which would allow the passage of liquids to the absorbent pad. The liquid impermeable backsheet 3 conventionally is a film or a laminate of a film with a nonwoven. The backsheet film is generally a polyolefin thermoplastic film, which can be provided with breathability. The nonwoven laminated to such a film would be on the outer surface of the diaper to provide a soft texture and cloth-like feel. The nonwoven can also provide a surface that could allow a hook material to engage, in certain circumstances, to allow for closure attachment and/or disposability of the diaper following use. At least a first corner 6 at a first end 7 of the diaper chassis 1 has a mechanical fastener tab 10 designed to adhere to a mating mechanical fastener element 4, and/or the fibrous backsheet 3, at a second end 8 of the diaper chassis 1. When the diaper is worn, i.e., when the invention mechanical fastener closure tab is in use, the first corner 6 at the first end 7 of the disposable diaper overlap with a corresponding opposing corner 6 at the opposing end 8 of the diaper so that the corner positions of first end 7 and second end 8 of the diaper overlap. Generally mechanical fastening hooks engage with a loop structure and/or possibly the backsheet so that there is a continuous engagement with the waist of the wearer, encircling the torso.

The liquid permeable topsheet would comprise a conventional material known for this use. These materials include spunbond webs, melt blown webs, carded webs, and the like. These webs are conventionally formed of thermoplastic and hydrophobic polymer fibers, such as polyolefin or polyester fibers.

The backsheet 3 is a generally liquid impermeable web, optionally an air permeable web or film and conventionally uses a thin polyolefin polymer film generally less than 1 to 2 mils thick. For use in a mechanical fastener closure system, the backsheet 3 is preferably a laminate of a substantially liquid impermeable film with a woven, nonwoven, knitted or stitch bonded or like fibrous web, which fibrous web is suitably engageable with the mechanical fastener hooks 11 on the mechanical fastening tab 10. Adhesive lamination, pattern heat bonding or extrusion lamination of the web with the liquid impermeable film can form this laminate.

The loop material can be any conventional loop fabric such as disclosed, for example, in U.S. Pat. Nos. 5,176,670 or 5,256,231, the substance of which are incorporated herein by reference. The loop fabric can be a conventional fibrous structure such as a nonwoven, a knitted material, a stitch bonded material or the like, formed of natural or synthetic fibers, which fibers can be either continuous or discontinuous and/or bonded. Generally, the loop material must have sufficient available fibers and loft to allow penetration of the mechanical fastening 11 into the loop structure but still have enough fibers available to engage with the individual hooks.

The mechanical fastener of the invention would generally comprise a tape backing 13 having a hook element 11 where the backing is provided with a distal finger-lift region 12. The backing 13 would further include a release tab 15 that would preferably cover an inner tab portion 14 of the tape tab backing and is preferably also bonded to the topsheet 2 at the corner portion 6 at the first end 7 of the diaper. Mechanical fastener tape tab laminates 10 of the invention can be provided in a roll form as is generally shown in FIG. 2. This roll is generally provided with a mechanical fastener tape tab laminate having a finger lift 22, a mechanical fastener portion 21 and a release tab 25. Individual tab elements 23 can be cut from the roll and attached to the diaper in a manner which will become clear upon discussion of the further specific embodiments below.

A first embodiment of the invention mechanical fastener tape tab laminate is shown in the expanded view of FIG. 3. The tape tab backing 33 is provided with a pressure-sensitive adhesive layer 36, which adhesive layer allows for attachment of the mechanical fastener material 31 and the release tab 35. Optionally, a further adhesive layer 38 can be provided on the mechanical fastener material 31. The tape tab backing 33 is separated into three distinct portions. The first distal end portion 37 is provided with an exposed portion of the adhesive layer 36, which exposed adhesive is used for permanent attachment of the assembled tab to one face of the diaper chassis 1. An inner tab portion 34 is attached to the release tab 35 using the adhesive layer, 36 and 44. A second distal end portion 39 of the tape tab backing 33 is provided with the releasably fastenable mechanical fastener material 31 and optionally a finger lift 32. The mechanical fastener material 31 is attached using adhesive layer 36 and/or an adhesive layer 38 on the mechanical fastener element 31. Generally, the tape tab backing 33 is provided with a continuous pressure-sensitive adhesive layer 36 for ease of manufacturability. However, the inner tab portion 34 and the second distal end portion 39 need not be provided with pressure-sensitive adhesive provided that the mechanical fastener material 31 and/or the release tab 35 are provided with suitable adhesives or other conventional attachment means to attach to the backing 33. Generally, pressure-sensitive adhesives are preferred for attachment of the mechanical fastener material 31 and release tab 35, however, other suitable conventional adhesives could be used if suitable. In the preferred embodiment, the mechanical fastener material 31 is a hook element 11 generally provided with upstanding hook elements for engagement with a mating loop surface provided on the outside of the diaper, generally, the loop fastener element 4. Although generally not economically viable, alternatively, a loop fastening material could be used in place of the hook element 11 as the mechanical fastener material 31, provided a suitable hook material was provided on the front portion of the diaper 1. Other known mechanical fastening structures could also be suitable for the invention laminates such as self-mating fasteners.

The release tab 35 generally comprises a backing 47 provided with a pressure-sensitive adhesive layer 44 on the outer face. The opposite inner face 46 of the backing can be provided with a suitable release layer or treatment, however such a release layer or treatment is optional. The release tab 35 in the FIG. 3 embodiment is folded into a circular form provided with an inner fold 41 and an outer fold 42. The inner fold 41 would be adjacent the edge on a diaper 1 when the tab portion first distal end 37 is attached to the diaper (e.g., backsheet 3). Generally, the release tab 35 comprises

5

a flat film, or like web, folded into a circular form having ends 45. These ends 45 meet to form the circular form on the side of the folded structure directly attached to the tape tab backing 33. Thus, both ends 45 are attached to the tape tab backing 33. This ensures that the release tab backing is a substantially continuous uninterrupted circular structure when the release tab is attached to the backing 33 in the laminate. Specifically, the release tab 35 is a substantially continuous (no gaps that would allow the release tab 35 to be opened or unfolded) structure, from the inner fold 41 to the outer fold 42 and back again, when the release tab 35 is attached to the tape tab backing 33 as shown in FIG. 4. The circular structure of the release tab when attached to the backing 33 has an outer leg 52 and an inner attached leg 51. The outer fold 42 is provided with a weakened zone 43 which allows the release tab to be easily broken at this point. Generally, this line of weakness is provided by suitably cutting the release tab backing 47 intermittently along the line 43 along the width dimension of the release tab backing. The backing 47 remains continuous and attached along this line of weakness to allow the release tab to be folded and remain folded and continuous prior to use. The line of weakness could also be formed by scoring, partially cutting through backing 47, or otherwise weakening backing 47 along line 43 across substantially the entire width of the backing 47.

FIG. 4 shows the assembled laminate as shown in the expanded view of FIG. 3, where like numerals indicate identical elements. The second distal end portion 39 of the tape tab backing 33 has been folded over onto itself to provide a finger lift portion 32 and the mechanical fastener material 31 and the release tab 35 are in substantially abutting relationship. This allows the mechanical fastener material 31 and the release tab 35 to cover the entire adhesive layer 36 on the second distal end portion 39 and the inner tab portion 34. Alternatively, the mechanical fastener material 31 and the release tab 35 could be spaced from each other if there is substantially no exposed adhesive in the gap formed, for example if there is no adhesive layer 36 on second distal end portion 39 and/or the inner tab portion 34 of the tape tab backing 33.

The first embodiment of the tape tab laminate 40 is shown partially attached to a diaper chassis 1 in FIG. 5. The tape tab backing 33 first distal end portion 37 is attached to the diaper corner 6 by the pressure-sensitive adhesive layer 36. The edge 5 of the diaper corner portion 6 substantially abuts the release tab inner fold 41 as shown, however this is not necessary. It is generally sufficient that the first tab distal end portion 37 has sufficient adhesive surface area in contact with the diaper corner 6 so as to provide a secure engagement. The available surface area of adhesive layer 36 and the first end portion 37 is attached to the diaper when the diaper edge 5 is close to or abutting the release tab inner fold 41.

FIG. 5 depicts an intermediate step in the attachment of the mechanical fastener tape tab laminate 40 to the diaper chassis 1. The completed attachment of the laminate 40 to a diaper is shown in FIG. 6 where the tape tab backing 33 is folded over back onto itself on the opposite side of the corner portion 6 so that the pressure-sensitive adhesive 44 on the outer leg 52 of the release tab attaches to the opposite face of the corner portion 6 securing the mechanical fastener tape tab laminate 40 in the folded condition. The mechanical fastener tape tab laminate 40 remains in this folded condition up to the point in time that the diaper is used. When the diaper is used, the folded over portion of the tape tab laminate 40, comprising the second distal end portion 39 and the inner tab portion 34, is extended from its folded condi-

6

tion at the corner 6 of the diaper by breaking the release tab 35 along the weakened line. The mechanical fastener material 31 is then exposed for use as shown in FIG. 7 without any exposed adhesive 36. Generally, to ensure that the laminate is maintained in its folded over condition prior to use, the line of weakness is located at least 10 mm, preferably at least 15 mm, from where the tape tab laminate is folded 49 back onto itself.

In the embodiment of FIGS. 3-7 the second distal end portion 39 of the tape tab backing 33 is effectively bonded to both faces of the diaper 1 at the diaper corner portion 6 by attachment of the first distal end portion 37 of tape tab backing 33 and by attachment of the outer leg 52 of the release tab 35 to the opposite face of the diaper corner portion 6. The shear forces exerted by attachment of the mechanical fastener material 31 to the loop or opposing mechanical fastener material on the diaper chassis are transferred to both faces of the diaper by the attachment of both the release tab 35 and the backing 33 to the diaper. These forces are transferred from the backing 33 to the release tab 53 via the continuous inner fold 41, which provides what is generally called a "Y-bond". The use of a Y-bond fold 49 and its advantages are described, for example, in U.S. Pat. Nos. 3,848,594 and 4,726,971 and PCT Appln. No. WO/96/12464, the substance of which are substantially incorporated herein by reference. The Y-bond fold 49 provides a very secure, permanent attachment of the mechanical fastener tape tab laminate 40 to the diaper chassis 1 minimizing or eliminating the risk of detachment and providing an even distribution of the attachment forces to both faces of the corner portion 6 of the diaper 1.

A second embodiment of the invention mechanical fastener tape tab laminate 50 is shown in FIGS. 8-12. An expanded view of the second embodiment of mechanical fastener tape tab laminate 50 is shown in FIG. 8. The tape tab backing 53 is provided with a pressure-sensitive adhesive layer 56 that allows for attachment of the mechanical fastener material 31, which mechanical fastener material 31 can optionally contain a further adhesive layer 38, and the release tab 55. The tape tab backing 53 is separated into four portions. The first portion is the first distal end portion 57 which is provided with an exposed portion of the adhesive layer 56 for permanent attachment to the diaper chassis 1. The second portion is an inner tab portion 54 which is attached to the release tab 55. The third portion is the second distal end portion 59 of the tape tab backing 53 which is provided with the releasably fastenable mechanical fastener material 31. The fourth portion is the finger lift portion 52, which also has an exposed portion of the adhesive layer 56.

Generally, the tape tab backing 53 is provided with a continuous pressure-sensitive adhesive layer 56 for ease of manufacturability. However, the inner tab portion 54 and the second distal end portion 59 need not be provided with pressure-sensitive adhesive provided that the mechanical fastener material 31 and/or the release tab 55 are provided with suitable adhesive or other conventional means to attach to the backing 53. The adhesive layer 56 could be intermittently provided on the tape tab backing 53 only in those areas where it is needed. The mechanical fastener material 31 is generally provided with upstanding hook elements suitable for engagement to the mating surface provided on the outside of the diaper, generally, the loop fastener element 4.

The release tab 55 generally comprises a backing 75 provided with a pressure-sensitive adhesive layer 58 an outer face 76. The opposite inner face 77 of the backing can be provided with a suitable release layer or treatment,

however such is optional. The release tab **55** is folded into a C-shape provided with an inner fold **60** and an open end **61**. The inner fold **60** would generally be adjacent the edge **5** on a diaper when the first distal end portion **57** is attached to the diaper corner portion **6**. Generally, the release tab **55** backing **75** comprises, a flat film or like web having ends **62**, which ends **62** can terminate adjacent the mechanical fastener material **31**. Generally only the bottom leg **72** of the C-fold release tab **55** needs to terminate near or adjacent the mechanical fastener material **31** of the inner tab portion **54** when there is an underlying pressure sensitive adhesive layer **56**. If pressure sensitive adhesive layer **56** is not provided in the inner tab portion, the location of the release tab **55** ends **62** is not critical as no adhesive needs to be covered, and in certain embodiments release tab **55** could be eliminated or be a flat unfolded film only covering the inner tab portion **54**. The tape tab backing **53** in the finger lift portion **52** is folded back onto itself in a Z-shape providing an outer top leg **74**, having an exposed portion of adhesive layer **56**, and an inner leg **73**. The bottom leg of the Z-shape is the unfolded main portion of the tape tab backing **53**. The inner leg **73** is created by a first fold **64** of the backing **53**. The second outer leg **74** is created by a second fold **65** of the inner leg **73**. The outer leg **74** is designed to attach to a surface of the diaper by the exposed portion of adhesive layer **56** as shown in FIG. **11**. The outer fold **65** is provided with a weakened zone **66**, which allows the Z fold finger lift **52** to be easily broken at this point. Generally, this line of weakness is provided by suitably cutting the tape tab backing intermittently along the line **66** or as otherwise discussed relative to the first embodiment. FIG. **9** shows the assembled laminate shown in the expanded view, where like numerals indicate identical elements.

The second embodiment of the tape tab laminate **50** is shown partially attached to a diaper chassis **1** in FIG. **10**. The tape tab backing **53** first distal end portion **57** is attached to the diaper corner **6** by the pressure-sensitive layer **56**. The edge **5** of the diaper corner portion **6** substantially abuts the release tab fold **60**. However, again it is generally only sufficient that the first distal end portion **57** has sufficient adhesive surface area in contact with the diaper corner **6** so as to provide a secure engagement.

FIG. **10** is an intermediate step in the process of attaching the tape tab laminate **50** to the diaper chassis **1**. The completed attachment of the second embodiment tape tab laminate **50** is shown in FIG. **11** where the tape tab backing **53** is folded over back onto itself on the opposite side of the corner portion **6** so that the pressure-sensitive adhesive **67** on the finger lift **52** attaches to the opposite face of the corner portion **6** securing the laminate **50** in the folded condition. The mechanical fastener tape tab laminate is provided in this folded condition up to the point in time that the diaper is used. When the diaper is used, the folded over portion of the tape tab laminate comprising the inner tab portion **54** the second distal end portion **59** and the fingerlift portion, are separated from the corner **6** of the diaper by breaking the finger lift portion **52** along the weakened line **66**. The mechanical fastener material **31** is then exposed for use as shown in FIG. **12**. The outer leg **74** remains attached to the diaper but with the adhesive not exposed during use of the mechanical fastening tab laminate **50**.

Again, in the embodiment of FIGS. **8-12**, the second distal end portion **59** of the tape tab backing **53** is effectively bonded to both faces of the diaper **1** at the corner portion **6** in a Y-bond **68**, by attachment of both the first distal end tab portion **57** of a tape tab backing and outer leg portion **71** of the release tab **55**. The shear forces exerted by attachment of

the mechanical fastener element **31** to the loop or opposing mechanical fastener on the diaper chassis are transferred to both faces of the diaper as the release tab **55** is attached to both the backing **53** and the diaper by the inner fold **60** which provides a Y-bond **68**. The forces from the tape tab backing **53** are transferred to the diaper from the inner leg **72**, attached to the backing **53**, to the outer leg **71**, attached to the diaper.

A third embodiment of the invention mechanical fastener tape tab laminate **80** is shown in FIG. **13**. The tape tab backing **83** is provided with a pressure sensitive adhesive layer **86** which allows for the attachment of the mechanical fastener material **31**, which can optionally contain a further adhesive layer **38**, and the release tab laminate **95**. The tape tab backing **83** is separated into three portions. The first portion is the first distal tab end portion **87** which is provided with an exposed portion of the adhesive layer **86** for permanent attachment to one face of the diaper chassis **1**. The second portion is an inner tab portion **84** which is attached to the release tab **95**. The third portion is the second distal end portion **89** of the tape tab backing **83** which is provided with the releasably attachable mechanical fastening material **31**. A separately attached web layer **99** attached to the adhesive layer **86** of the tape tab backing **83** provides the optional finger lift **82**. The release tab of the embodiment of FIG. **13** differs from the first embodiment of the invention, shown in FIGS. **3-7**, in that the release tab backing **97** is folded into a C-fold shape having a first inner leg **91** and a second outer leg **92** on opposite sides of a C-fold **94**. The first inner leg **91** of the C-folded release tab is attached to the diaper tape tab backing **83**. The second outer leg **92** is not attached to the tape tab backing. The release tab laminate **95** then forms an inner fold **98** by use of a separately attached unifying web **96** forming a tape tab laminate. The unifying web **96** is attached at one face to the second outer leg **92** of the release tab at a terminal end portion of this second outer leg **92**, and attached to tape tab backing **83** on an opposite face of the unifying web **96**. Between the two points of attachment, the unifying web **96** is folded into a C-shape providing an inner fold **98**. This inner fold **98** creates a Y-bond as described in the first embodiment of U.S. Pat. No. 4,726,971, the substance of which is incorporated by reference in its entirety. A. In the FIG. **13** embodiment the release tab **95** laminated with unifying web **96** is a substantially continuous structure from the inner fold **98** provided by the unifying web **96** to the outer C-fold **94** provided by the release tab. The outer C-fold **94** is provided with a weakened zone **93** which allows the release tab to be easily broken at this point after assembled into a diaper as shown in FIG. **1**, and the first embodiment FIG. **7**.

A fourth embodiment of the invention mechanical fastener tape tab laminate **100** is shown in FIG. **14**. The tape tab backing **103** is provided with a pressure sensitive adhesive layer **106** that allows for attachment of the mechanical fastener material **31**, which can optionally contain a further adhesive layer **38**, and the release tab **105**. The tape tab laminate **100** is provided with four portions. The first portion is the first distal end portion **107** which is provided with an exposed adhesive portion of the adhesive layer **106** for a permanent attachment to one face of the diaper chassis **1**. The second portion is an inner tab portion **104** which is attached to the release tab **105**. The third portion is the second distal end portion **109** of the tape tab backing **103** which is provided with the releasably fastenable mechanical fastener material **31**. The fourth portion is a fingerlift portion **112** provided with the breakable line of weakness **113** providing the invention antifflogging feature.

The finger lift portion **112** is provided with a C-folded tape element **118**. The C-folded tape element **118** comprises a backing **116** having a first inner leg **111** and a second outer leg **117** separated by fold **115**. The second outer leg **117** has an exposed adhesive **114** and the fold **115** is provided with a weakened zone **113**, which allows the C-folded tape element **118** to be easily broken at this point. The exposed adhesive layer **114** on the C-folded tape element **118** allows attachment to the opposite face of the diaper corner portion **6** securing the laminate **100** in a folded condition such as shown in the second embodiment of the invention. An adhesive-free fingerlift is provided by web **99** as in the FIG. **13** embodiment. The mechanical fastener tape tab laminate **100** is provided in this folded condition up to the point in time that the diaper is used. When the diaper is used the folded over portion of the tape tab laminate comprising the inner tab portion **104**, the second distal end portion **109** and the fingerlift portion **112** are separated from the corner **6** of a diaper by breaking the C-fold tape element **118** along the weakened line **113**. The mechanical fastener material **31** is then exposed for use. In this embodiment a Y-bond is not formed in that the release tab **105** is attached only to the tape tab backing **103**. The C-folded tape element **118** could also be arranged in the opposite direction such that the open end of the C-fold faces out towards the free fingerlift. Also the first inner leg **111** could be formed by the unfolded tape tab backing **103**.

The embodiment of FIG. **15** is a variation of the second embodiment of the invention where a Y-bond is not created in that a release tab **105** is provided only to cover exposed adhesive on the inner tab portion of the tape tab backing in this embodiment. Like numbers specify identical features of the second embodiment of FIGS. **8–12**.

A sixth embodiment of the invention is shown in FIG. **16**. In this embodiment the release tab **125** is provided in a C-fold. An inner leg **122** is attached to the tape tab backing **33** and folded along fold **126** to an outer leg **121**, which is provided with an exposed adhesive **127** for attachment to an opposing face of the diaper corner **6**. The fold **126** is provided with a line of weakening **123**. In this embodiment a Y-bond will not be created in that when the line of weakening **123** is broken the outer leg portion **121** of the release tab would be attached only to the inner face of the diaper and not to the tape tab backing **33**.

The above detailed description of the invention is made with respect to certain preferred embodiments of the invention mechanical fastener tape tab closure laminate as used on a conventional disposable diaper chassis. However, it would be apparent to one of skill in the art that the preferred embodiments of the invention mechanical fastener tape tab closure laminate could be equally applicable to other articles such as hospital gowns, caps, incontinent garments and other diaper designs and the like.

We claim:

**1.** A mechanical fastener tape tab laminate comprising a tape tab backing having at least a first distal end portion, an inner tab portion and second distal end portion, the second distal end portion provided with a mechanical fastener material, the first distal end portion provided with an adhesive layer for attachment to a disposable absorbent article, the tape tab backing further having a folded tape portion comprising a backing having an adhesive layer on an outer face and having at least an inner leg portion and an outer leg portion, the outer leg portion having an exposed adhesive provided for attachment to the disposable absorbent article, the inner and outer leg portions separated by at least one fold, the folded tape portion backing having a line of

weakness along the at least one fold, wherein the line of weakness is provided on a portion of the tape tab backing spaced from the first distal end portion.

**2.** The mechanical fastener tape tab laminate of claim **1** wherein the inner leg portion is attached to the tape tab backing.

**3.** The mechanical fastener tape tab laminate of claim **2** wherein the line of weakness extends across the entire width of the folded tape portion backing.

**4.** The mechanical fastener tape tab laminate of claim **3** wherein the line of weakness is provided at least 10 mm from the first distal end portion to be attached to the disposable absorbent article.

**5.** The mechanical fastener tape tab laminate of claim **4** wherein the second distal portion is provided with a hook fastener element.

**6.** The mechanical fastener tape tab laminate of claim **5** wherein the hook fastener element is attached to an adhesive layer provided on the tape tab backing.

**7.** The mechanical fastener tape tab laminate of claim **5** wherein the hook fastener element is provided with an adhesive layer for attachment to the tape tab backing.

**8.** The mechanical fastener tape tab laminate of claim **5** wherein the folded tape portion comprises a release tab provided on the inner tab portion having at least the inner leg attached to the inner tab portion.

**9.** The mechanical fastener tape tab laminate of claim **8** wherein the folded release tab at least one fold is located adjacent to the second distal end portion of the tape tab backing.

**10.** The mechanical fastener tape tab laminate of claim **9** wherein the folded release tab is in the form of a C-fold having at least one terminal end on the outer leg portion which is unattached to the tape tab backing and a second terminal end on the inner leg portion.

**11.** The mechanical fastener tape tab laminate of claim **10** wherein the two terminal ends end at the approximately same location on the tape tab backing.

**12.** The mechanical fastener tape tab laminate of claim **11** wherein the inner leg portion of the release tab attached to the inner tab portion is longer than the outer leg portion of the release tape tab.

**13.** The mechanical fastener tape tab laminate of claim **10** wherein the line of weakening is formed by intermittent slitting of the release tab backing.

**14.** The mechanical fastener tape tab laminate of claim **13** wherein the release tab backing has an adhesive layer on its outer face.

**15.** The mechanical fastener tape tab laminate of claim **14** wherein the release tab backing has a release surface on face forming the inner face of the C-fold.

**16.** The mechanical fastener tape tab laminate of claim **8** wherein the release tab is in the form of a circle having two fold lines, an inner fold adjacent the first distal end portion of the tape tab backing end and an outer fold adjacent the second distal end portion of the tape tab backing, which outer fold is provided with the line of weakness.

**17.** The mechanical fastener tape tab laminate of claim **16** wherein the release tab is formed of a continuous backing.

**18.** The mechanical fastener tape tab laminate of claim **17** wherein the release tab backing has two terminal ends both of which terminal ends are attached to the tape tab backing forming at least in part the inner leg portion.

**19.** The mechanical fastener tape tab laminate of claim **16** wherein the release tab is in the form of a laminate.

**20.** The mechanical fastener tape tab laminate of claim **19** wherein the release tab laminate is formed of a release tab

tape backing formed into a C-fold having an outer leg and an inner leg and a unifying strip, also formed into a C-fold and having an outer leg and an inner leg, wherein the outer leg of the unifying strip is attached to the outer leg of the release tab and the inner leg of the unifying strip is attached to the tape tab backing, the C-fold release tab forming an outer fold having the line of weakness and the unifying strip forming an inner fold.

21. The mechanical fastener tape tab laminate of claim 1 wherein the folded tape portion inner leg portion and the outer leg portion are provided on a fingerlift portion of the tape tab backing.

22. The mechanical fastener tape tab laminate of claim 21 wherein the inner leg portion and outer leg portion are formed of the tape tab backing having at least one fold.

23. The mechanical fastener tape tab laminate of claim 22 wherein the tape tab backing has at least two folds forming a Z-fold having an inner fold and an outer fold at least one of which is provided with the line of weakness.

24. The mechanical fastener tape tab laminate of claim 23 wherein the outer fold of the Z-fold has the line of weakness.

25. The mechanical fastener tape tab laminate of claim 24 wherein the outer leg adhesive layer is provided by the tape tab backing adhesive layer.

26. The mechanical fastener tape tab laminate of claim 21 wherein the folded tape portion is formed of a separate adhesive coated backing attached to the tape tab backing.

27. The mechanical fastener tape tab laminate of claim 26 wherein the folded tape portion comprises a release tab having the inner leg attached to the tape tab backing.

28. The mechanical fastener tape tab laminate of claim 27 wherein the folded tape portion is in the form of a C-fold.

29. The mechanical fastener tape tab laminate of claim 28 wherein the C-fold having the line of weakness is located adjacent the second distal end portion of the tape tab backing.

30. The mechanical fastener tape tab laminate of claim 28 wherein the C-fold having the line of weakness is located adjacent a terminal end of the tape tab backing.

31. A disposable absorbent article having a mechanical fastener tape tab laminate, the disposable absorbent article having an outer face and an inner face at least one edge having a mechanical fastener tape tab laminate at one terminal end, said mechanical fastener tape tab laminate comprising a tape tab backing having at least a first distal end portion, an inner tab portion and second distal end portion, the second distal end portion provided with a mechanical fastener material, the first distal end portion provided with an adhesive layer for attachment to a disposable absorbent article, the tape tab backing further having a folded tape portion comprising a backing having an adhesive layer on an outer face and having at least an inner leg portion and an outer leg portion, the outer leg portion having an exposed adhesive provided for attachment to the disposable absorbent article, the inner and outer leg portions separated by at least one fold, the folded tape portion backing having a line of weakness along the at least one fold, wherein the line of weakness is provided on a portion of the tape tab backing spaced from the first distal end portion.

32. The disposable absorbent article of claim 31 wherein the inner leg portion is attached to the tape tab backing.

33. The disposable absorbent article of claim 32 wherein the line of weakness extends across the entire width of the folded tape portion backing.

34. The disposable absorbent article of claim 33 wherein the line of weakness is provided at least 10 mm from the first distal end portion to be attached to the disposable absorbent article.

35. The disposable absorbent article of claim 34 wherein the second distal portion is provided with a hook fastener element.

36. The disposable absorbent article of claim 35 wherein the hook fastener element is attached to an adhesive layer provided on the tape tab backing.

37. The disposable absorbent article of claim 35 wherein the hook fastener element is provided with an adhesive layer for attachment to the tape tab backing.

38. The disposable absorbent article of claim 35 wherein the folded tape portion comprises a release tab provided on the inner tab portion having at least the inner leg attached to the inner tab portion.

39. The disposable absorbent article of claim 38 wherein the folded release tab at least one fold is located adjacent to the second distal end portion of the tape tab backing.

40. The disposable absorbent article of claim 39 wherein the folded release tab is in the form of a C-fold having at least one terminal end on the outer leg portion which is unattached to the tape tab backing and a second terminal end on the inner leg portion.

41. The disposable absorbent article of claim 40 wherein the two terminal ends end at the approximately same location on the tape tab backing.

42. The disposable absorbent article of claim 41 wherein the inner leg portion of the release tab attached to the inner tab portion is longer than the outer leg portion of the release tab portion.

43. The disposable absorbent article of claim 40 wherein the line of weakening is formed by intermittent slitting of the release tab backing.

44. The disposable absorbent article of claim 43 wherein the release tab backing has an adhesive layer on its outer face.

45. The disposable absorbent article of claim 44 wherein the release tab backing has a release surface on face forming the inner face of the C-fold.

46. The disposable absorbent article of claim 38 wherein the release tab is in the form of a circle having two fold lines, an inner fold adjacent the first distal end portion of the tape tab backing and an outer fold adjacent the second distal end portion of the tape tab backing, which outer fold is provided with the line of weakness.

47. The disposable absorbent article of claim 46 wherein the release tab is formed of a continuous backing.

48. The disposable absorbent article of claim 47 wherein the release tab backing has two terminal ends both of which terminal ends are attached to the tape tab backing forming at least in part the inner leg portion.

49. The disposable absorbent article of claim 46 wherein the release tab is in the form of a laminate.

50. The disposable absorbent article of claim 49 wherein the release tab laminate is formed of a release tab tape backing formed into a C-fold having an outer leg and an inner leg and a unifying strip, also formed into a C-fold and having an outer leg and an inner leg, wherein the outer leg of the unifying strip is attached to the outer leg of the release tab and the inner leg of the unifying strip is attached to the tape tab backing, the C-fold release tab forming an outer fold having the line of weakness and the unifying strip forming an inner fold.

51. The disposable absorbent article of claim 31 wherein the folded tape portion inner leg portion and the outer leg portion are provided on a fingerlift portion of the tape tab backing.

52. The disposable absorbent article of claim 51 wherein the folded tape portion is formed of a separate adhesive coated backing attached to the tape tab backing.

**13**

**53.** The disposable absorbent article of claim **52** wherein the folded tape portion comprises a release tab having the inner leg attached to the tape tab backing.

**54.** The disposable absorbent article of claim **53** wherein the folded tape portion is in the form of a C-fold.

**55.** The disposable absorbent article of claim **54** wherein the C-fold having the line of weakness is located adjacent the second distal end portion of the tape tab backing.

**56.** The disposable absorbent article of claim **55** wherein the C-fold having the line of weakness is located adjacent a terminal end of the tape tab backing.

**57.** The disposable absorbent article of claim **31** wherein the inner leg portion and outer leg portion are formed of the tape tab backing having at least one fold.

**14**

**58.** The disposable absorbent article of claim **57** wherein the tape tab backing has at least two folds forming a Z-fold having an inner fold and an outer fold at least one of which is provided with the line of weakness.

**59.** The disposable absorbent article of claim **58** wherein the outer fold of the Z-fold has the line of weakness.

**60.** The disposable absorbent article of claim **59** wherein the outer leg adhesive layer is provided by the tape tab backing adhesive layer.

\* \* \* \* \*

UNITED STATES PATENT AND TRADEMARK OFFICE  
**CERTIFICATE OF CORRECTION**

PATENT NO. : 6,363,587 B1  
DATED : April 2, 2002  
INVENTOR(S) : Richter, Gerhard L.

Page 1 of 1

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Column 1,

Line 22, delete "end"be" and insert in place thereof -- "end" be --.

Column 8,

Line 65, delete "3 1." and insert in place thereof -- 31. --.

Column 11,


Line 25, delete "tap e" and insert in place thereof -- tape --.

Line 25, delete "form e d" and insert in place thereof -- formed --.

Signed and Sealed this

Nineteenth Day of November, 2002

*Attest:*

A handwritten signature in black ink, appearing to read "James E. Rogan", written over a horizontal line.

*Attesting Officer*

JAMES E. ROGAN  
*Director of the United States Patent and Trademark Office*