




(86) Date de dépôt PCT/PCT Filing Date: 2011/10/05  
 (87) Date publication PCT/PCT Publication Date: 2012/04/12  
 (45) Date de délivrance/Issue Date: 2020/07/14  
 (85) Entrée phase nationale/National Entry: 2013/05/08  
 (86) N° demande PCT/PCT Application No.: US 2011/054979  
 (87) N° publication PCT/PCT Publication No.: 2012/048040  
 (30) Priorités/Priorities: 2010/10/05 (US61/389,960);  
 2011/01/07 (US61/430,641); 2011/03/24 (US61/467,097);  
 2011/06/20 (US61/498,954);  
 2011/06/30 (US PCT/US2011/042637)

(51) Cl.Int./Int.Cl. *G01N 33/50* (2006.01),  
*G01N 21/17* (2006.01), *G01N 27/26* (2006.01),  
*G01N 33/52* (2006.01)  
 (72) Inventeurs/Inventors:  
 YU, CHRIS CHANG, US;  
 DU, XUEDONG, CN  
 (73) Propriétaire/Owner:  
 ANPAC BIO-MEDICAL SCIENCE CO., LTD., VG  
 (74) Agent: BLANEY MCMURTRY LLP

(54) Titre : DISPOSITIFS MICROSCOPIQUES DESTINES A DETECTER DES MALADIES  
 (54) Title: MICRO-DEVICES FOR DISEASE DETECTION



(57) Abrégé/Abstract:

Among others, the present invention provides piezo-electric micro-devices for detecting at the microscopic level an electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, physical, bio-chemical, bio-physical, physical-chemical, bio-physical-chemical, bio-mechanical, bio-electro-mechanical, electro-mechanical, or mechanical property of the biologic subject.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau(10) International Publication Number  
**WO 2012/048040 A3**(43) International Publication Date  
12 April 2012 (12.04.2012)

## (51) International Patent Classification:

G01N 33/50 (2006.01) G01N 33/52 (2006.01)  
G01N 27/26 (2006.01) G01N 21/17 (2006.01)

## (21) International Application Number:

PCT/US2011/054979

## (22) International Filing Date:

5 October 2011 (05.10.2011)

## (25) Filing Language:

English

## (26) Publication Language:

English

## (30) Priority Data:

61/389,960	5 October 2010 (05.10.2010)	US
61/430,641	7 January 2011 (07.01.2011)	US
61/467,097	24 March 2011 (24.03.2011)	US
61/498,954	20 June 2011 (20.06.2011)	US
PCT/US2011/042637	30 June 2011 (30.06.2011)	US

(71) Applicant (for all designated States except US): **ANPAC BIO-MEDICAL SCIENCE CO., LTD.**; Shrm Trustees (BVI) Limited Of Trinity Chambers, P.O. Box 4301, Road Town, Tortola (VG).

## (72) Inventors; and

(75) Inventors/Applicants (for US only): **YU, Chris, Chang** [US/US]; 4369 State Highway 198, Conneautville, PA 16406 (US). **DU, Xuedong** [CN/CN]; Room 702, Lane 358, Qingtong Road, Pudong District, Shanghai, 201203 (CN).

(74) Agent: **RAO, Weisun**; Miller, Canfield, Paddock And Stone, P.L.C., 225 W. Washington St., Suite 2600, Chicago, IL 60606 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

## Published:

— with international search report (Art. 21(3))

[Continued on next page]

(54) Title: MICRO-DEVICES FOR DISEASE DETECTION




FIGURE 1

(57) Abstract: Among others, the present invention provides piezo-electric micro-devices for detecting at the microscopic level an electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, physical, bio-chemical, bio-physical, physical-chemical, bio-physical-chemical, bio-mechanical, bio-electro-mechanical, electro-mechanical, or mechanical property of the biological subject.

WO 2012/048040 A3

**WO 2012/048040 A3** 

---

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*

**(88) Date of publication of the international search report:**  
21 June 2012

## MICRO-DEVICES FOR DISEASE DETECTION

[1]

### **Background of the Invention**

[2] Many serious diseases with high morbidity and mortality, including cancer and heart diseases, are very difficult to diagnose early and accurately. Current disease diagnosis technologies typically rely on macroscopic data and information such as body temperature, blood pressure, and scanned images of the body. To detect serious diseases such as cancer, many of the diagnosis apparatus commonly used today are based on imaging technologies, including x-ray, CT scan, and nuclear magnetic resonance (NMR). While they provide various degrees of usefulness in disease diagnosis, most of them cannot provide accurate, totally safe, and cost-effective diagnosis of such serious diseases as cancer at an early stage. Further, many of the existing diagnosis techniques and related apparatus are invasive and sometimes not readily accessible, especially in remote regions or rural areas.

[3] Even the newly emerged DNA tests have not been proven effective in diagnosing a wide range of diseases in a rapid, reliable, accurate, and cost-effective manner. In recent years, there have been some efforts in using nano technologies for various biological applications, with most of the work focused on gene mapping and moderate developments in the field of disease detection. For instance, Pantel et al. discussed the use of a MicroElectroMechanical Systems (MEMS) sensor for detecting cancer cells in blood and bone marrow *in vitro* (see, e.g., Klaus Pantel et al., *Nature Reviews*, 2008, 8, 329); Kubena et al. disclose in U.S. Patent Number 6,922,118 the deployment of MEMS for detecting biological agents; and Weissman et al. disclose in U.S. Patent Number 6,330,885 utilizing MEMS sensor for detecting accretion of biological matter.

[4] However, to date, most of the above described technologies have been limited to isolated examples for sensing, using systems of relatively simple constructions and large dimensions but often with limited functions, and lack sensitivities and specificities. Further, some existing technologies utilizing nano-particles and biological approaches have the drawbacks of requiring complicated sample preparation procedures (such as using chemical or biological markers), difficulty in data interpretation, and too much reliance on visual and color change as means of diagnosis (which is subjective and of limited resolution), making them unsuitable for early stage disease detection, e.g., for such serious diseases as cancer, and particularly for routine hospital screening and/or regular physical check-up examinations.

[5] These drawbacks call for novel solutions that not only overcome them but also bring enhanced accuracy, specificity, efficiency, non-invasiveness, practicality, simplicity, and speed in early-stage disease detection at reduced costs.

#### **Summary of the Invention**

[6] The present invention in general relates to a class of innovative disease detection apparatus which utilizes novel micro-devices (or functionalities) integrated onto them for carrying out diagnosis at microscopic levels, *in vivo* or *in vitro*, on a single cell, a single biological molecular (e.g., DNA, RNA, or protein), a single biological subject (e.g., a single virus), or other sufficiently small unit or fundamental biological composition. This class of apparatus can be made by using state-of-the-art micro-device fabrication technologies and novel process flows such as integrated circuit fabrication technologies. As used herein, the term “disease detection apparatus” can be interchanged with such terms as disease detection device or apparatus integrated with micro-devices, or any other similar terms of the same meaning. Apparatus of this invention containing multiple micro-devices can detect multiple parameters of a biological sample to be analyzed. These disease detection apparatus are capable of detecting diseases at their early stages with a high degree of sensitivity, specificity, speed, simplicity, practicality, convenience (e.g., reduced apparatus size), or affordability (e.g., reduced costs).

[7] One key component of the detection apparatus is a class of novel micro-devices and their inventive fabrication processes which enable these novel micro-devices to perform at a much higher level than those of conventional disease detection apparatus or technologies, due to much improved detection sensitivity, specificity, simplicity, practicality, and speed. Examples of

fabrication techniques that can be used to make the micro-devices described herein include but not limited to mechanical, chemical, physical-chemical, chemical mechanical, bio-physical, bio-physical mechanical, electro-mechanical, bio-electro-mechanical, micro-electro-mechanical, electro-chemical-mechanical, electro-bio-chemical-mechanical, nano-fabrication techniques, integrated circuit and semiconductor manufacturing techniques and processes. For a general description of some of the applicable fabrication technologies, see, e.g., R. Zaouk et al., *Introduction to Microfabrication Techniques*, in *Microfluidic Techniques* (S. Minteer, ed.), 2006, Humana Press; *Microsystem Engineering of Lab-on-a-chip Devices*, 1st Ed. (Geschke, Klank & Telleman, eds.), John Wiley & Sons, 2004. Micro-device functionalities would at least include sensing, detecting, measuring, diagnosing, monitoring, and analyzing for disease diagnosis. Multiple micro-devices can be integrated onto a piece of detection apparatus to make the apparatus more advanced and sophisticated for further enhanced measurement sensitivity, specificity, speed and functionalities, with ability to measure the same parameter or a set of different parameters.

[8] Optional components of the apparatus includes means to perform at least the function of addressing, controlling, forcing, receiving, amplifying, manipulating, or storing information from each probe. Such means can be, e.g., a central control unit that includes a controlling circuitry, an addressing unit, an amplifier circuitry, a logic processing circuitry, a memory unit, an application specific chip, a signal transmitter, a signal receiver, or a sensor.

[9] Specifically, one aspect of this invention provides apparatus for detecting a disease, each comprising a first micro-device and a first substrate supporting the first micro-device, wherein the first micro-device contacts a biological subject to be analyzed and is capable of measuring at the microscopic level an electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, electro-mechanical, electro-chemical, electro-chemical-mechanical, bio-chemical, bio-mechanical, bio-electro-mechanical, bio-electro-chemical, bio-electro-chemical-mechanical, physical, or mechanical property of the biologic material. The apparatus can further optionally include a device for reading the data from measuring the property.

[10] In some embodiments, the difference in the measured property of the tested biologic material and that of a biologic sample from a subject free of the disease is indicative of the possible occurrence of the disease in early stage.

[11] In some other embodiments, the electrical property is surface charge, surface potential, oscillation in electrical signal (e.g., oscillation in ions, pulsing electrical field, pulsing surface charge, pulsing voltage), electrical field, electrical field distribution, electrical charge distribution, or impedance; the thermal property is temperature; the chemical property is pH value, ionic strength, bonding strength; the physical property is density; and the mechanical property is hardness, shear strength, elongation strength, fracture stress, adhesion, elasticity, or density.

[12] In some embodiments, the probing and detecting device applies to the biological subject a voltage ranging from about 1 mV to about 10 V, or from about 1 mV to about 1.0 V.

[13] In some embodiments, the first micro-device comprises a conductive material, an electrically insulating material, a biological material, or a semiconductor material.

[14] In some other embodiments, each of the apparatus further comprises at least one or more additional micro-devices. In these embodiments, each of the micro-devices contained in the apparatus comprises a conductive material, an electrically insulating material, or a semiconductor material; and each of the micro-devices can comprise the same or different material(s) and can measure the same or different properties at the same or different time.

[15] In some embodiments, the probing device and the micro-devices are placed with a desired distance between each other. These multiple micro-devices can be spaced out, e.g., with a distance of at least 10 angstroms on the substrate, or with a distance ranging from about 5 microns to about 100 microns.

[16] The multiple micro-devices integrated in a disease detection apparatus can sequentially and/or simultaneously measure various parameters from a biological subject being detected at macroscopic and/or microscopic levels. Sometimes, in an apparatus with multiple micro-devices, some micro-devices can act as probing devices to disturb the biological subject and trigger a response from the biological subject, while other micro-devices in the apparatus can act as detection devices to measure the triggered response by the biological subject.

[17] In some other embodiments, each of the micro-devices has the size ranging from about 1 angstrom ( $\text{\AA}$ ) to about 5 millimeter (e.g., from 5  $\text{\AA}$  to 1 millimeter).

[18] In some other embodiments, the apparatus comprises one or more additional substrates on which the micro-devices are placed. Each of the substrates can comprise the same or a different material (e.g., a conductive material or an insulator) and can be in the same or a different shape (e.g., a slab or a tube), and each substrate can be a two- or three-dimensional

object. They can take the form of cylinder, rectangle, cube, slabs, or any other desired shapes and configurations, in order to further improve their measurement sensitivity, specificity, speed, sample size, and reduce cost and size.

[19] In terms of detection apparatus to integrate micro-devices, in one novel detection apparatus design, to increase measurement sensitivity, micro-devices mounted on two slabs separated by a small spacing with sample to be measured between the two said slabs can be used to detect disease with improved speed, with micro-devices measuring cells, DNAs, and desired items in the sample in parallel. The surface area of the slabs can be maximized in order to have maximum number of micro-devices placed on the slabs and enhance measurement efficiency and speed. Optionally, multiple micro-devices integrated on the surface of the slabs can be closely spaced with their spacing matching that of cells, DNAs, and items to be measured.

[20] In another novel configuration, a detection apparatus integrated with micro-devices is shaped in the form of a cylinder, with multiple micro-devices with detection probes integrated/mounted in the inter surfaces of the cylinder and with sample to be measured (such as blood) flowing through the cylinder.

[21] In yet another innovative configuration, a detection apparatus with integrated micro-devices is shaped in the form of a rectangular pipe, with multiple micro-devices with detection probes integrated/mounted in the inter surfaces of the pipe and with sample to be measured (such as blood) flowing through the rectangular pipe.

[22] In another aspect, the invention provides another set of apparatus for detecting a disease in a biological subject, comprising a system for delivering the biological subject to be detected and a probing and detecting device for probing and detecting the biological subject.

[23] The difference in the measured property of the detected biologic material and of a standard biologic sample is indicative of the possible occurrence of the disease.

[24] In some embodiments, the probing and detecting device comprises a first micro-device and a first substrate supporting the first micro-device, the first micro-device contacts the biologic subject to be detected and is capable of measuring at the microscopic level an electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, electro-mechanical, electro-chemical, electro-chemical-mechanical, bio-chemical, bio-chemical-physical, bio-mechanical, bio-electro-mechanical, bio-electro-chemical, bio-electro-chemical-mechanical, physical, or mechanical property of the biologic subject. For example, the electrical property can be surface



charge, surface potential, resting potential, electrical current, electrical field distribution, electric dipole, electric quadruple, three-dimensional electrical or charge cloud distribution, electrical properties at telomere of DNA and chromosome, or impedance; the thermal property can be temperature, or vibrational frequency of biological item or molecules; the optical property can be optical absorption, optical transmission, optical reflection, optical-electrical property, brightness, or fluorescent emission; the chemical property can be pH value, chemical reaction, bio-chemical reaction, bio-electro-chemical reaction, reaction speed, reaction energy, oxygen concentration, oxygen consumption rate, ionic strength, catalytic behavior, or bonding strength; the physical property can be density or geometric size; the acoustic property is frequency, speed of acoustic waves, acoustic frequency and intensity spectrum distribution, acoustic intensity, acoustical absorption, or acoustical resonance; and the mechanical property is internal pressure, hardness, shear strength, elongation strength, fracture stress, adhesion, mechanical resonance frequency, elasticity, plasticity, or compressibility.

[25] In some embodiments of the apparatus, the probing and detecting device applies to the biological subject a voltage ranging from about 1 mV to about 10 V, or from about 1 mV to about 1.0 V.

[26] In some embodiments of the apparatus, the first micro-device comprises a conductive material, an electrically insulating material, a biological material, or a semiconductor material.

[27] In some embodiments of the apparatus, the first micro-device has a size ranging from about 1 angstrom to about 5 millimeter.

[28] In some embodiments of the apparatus, the probing and detecting device further comprises one or more additional micro-devices, each of which is also capable of measuring at the microscopic level an electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, electro-mechanical, electro-chemical, electro-chemical-mechanical, bio-chemical, bio-mechanical, bio-electro-mechanical, bio-electro-chemical, bio-electro-chemical-mechanical, physical, or mechanical property of the biologic entity. The electrical property can be surface charge, surface potential, resting potential, electrical current, electrical field distribution, electric dipole, electric quadruple, three-dimensional electrical or charge cloud distribution, electrical properties at telomere of DNA and chromosome, or impedance; the thermal property can be temperature, or vibrational frequency of biological item or molecules; the optical property can be optical absorption, optical transmission, optical reflection, optical-

electrical property, brightness, or fluorescent emission; the chemical property can be pH value, chemical reaction, bio-chemical reaction, bio-electro-chemical reaction, reaction speed, reaction energy, oxygen concentration, oxygen consumption rate, ionic strength, catalytic behavior, or bonding strength; the physical property can be density or geometric size; the acoustic property can be frequency, speed of acoustic waves, acoustic frequency and intensity spectrum distribution, acoustic intensity, acoustical absorption, or acoustical resonance; and the mechanical property can be internal pressure, hardness, shear strength, elongation strength, fracture stress, adhesion, mechanical resonance frequency, elasticity, plasticity, or compressibility.

[29] In some embodiments of the apparatus, each of the additional micro-devices comprises a conductive material, an electrically insulating material, a biological material, or a semiconductor material. Further, each of the additional micro-devices comprises a material that is the same as or different from the material of the first micro-device and is capable of measuring the same or different property of the biologic subject as the first-micro-device does.

[30] In some embodiments of the apparatus, the first micro-device and each of the additional micro-devices are capable of measuring the surface charge, surface potential, resting potential, electrical current, electrical field distribution, electric dipole, electric quadruple, three-dimensional electrical or charge cloud distribution, electrical properties at telomere of DNA and chromosome, impedance, temperature, vibrational frequency, optical absorption, optical transmission, optical reflection, optical-electrical property, brightness, fluorescent emission, pH value, chemical reaction, bio-chemical reaction, bio-electro-chemical reaction, reaction speed, reaction energy, oxygen concentration, oxygen consumption rate, ionic strength, catalytic behavior, bonding strength, density, geometric size, frequency, speed of acoustic waves, acoustic frequency and intensity spectrum distribution, acoustic intensity, acoustical absorption, acoustical resonance, internal pressure, hardness, shearing strength, elongation strength, fracture stress, adhesion, mechanical resonance frequency, elasticity, plasticity, or compressibility. They can measure the same or different properties at the same or different times.

[31] In some embodiments of the apparatus, the probing device and the micro-devices are placed with a desired distance between each other.

[32] In some embodiments of the apparatus, each of the additional micro-devices has a size ranging from about 1 angstrom to about 5 millimeter.

[33] In some embodiments of the apparatus, the micro-devices are spaced out on the substrate by a distance of at least 10 angstroms (e.g., from about 5 microns to about 100 microns).

[34] In some embodiments of the apparatus, the substrate is in the shape of a slab, a rectangle, a cube, a tube, or an array of tubes; or the substrate is a three-dimensional object.

[35] In some embodiments of the apparatus, the probing and detecting device further comprises a second substrate of the same or different material as the first substrate.

[36] In some embodiments, the apparatus further comprises a device for reading the data from measuring the property by the probing and detecting device.

[37] In some embodiments, the apparatus each further comprises a system for delivering a fluid, which comprises a pressure generator, a pressure regulator, a throttle valve, a pressure gauge, and distributing kits. The pressure generator can include a motor piston system and a bin containing compressed gas; the pressure regulator can down-regulate or up-regulate the pressure to a desired value; the pressure gauge feeds back the measured value to the throttle valve, which then regulates the pressure to approach the target value.

[38] The fluid to be delivered in the apparatus can be a liquid or gas. Examples of the liquid include blood, urine, saliva, tear, saline, and sweat; whereas examples of the gas include nitrogen, argon, helium, neon, krypton, xenon, or radon.

[39] In some embodiments of the apparatus, the probing and detecting device further comprises a system controller which comprises a pre-amplifier, a lock-in amplifier, an electrical meter, a thermal meter, a switching matrix, a system bus, a nonvolatile storage device, a random access memory, a processor, or a user interface. The interface may include a sensor which can be, e.g., a thermal sensor, a flow meter, an optical sensor, or a sensor comprising one or more piezo-electric materials.

[40] In some embodiments, the apparatus may further include a biological interface, a system controller, or at least one system for reclaiming or treatment medical waste. Reclaiming and treatment of medical waste is performed by the same system or by two different systems.

[41] In some embodiments, the apparatus further include a testing sample delivery system, a testing sample distribution system, a distribution channel, a pre-processing unit, a detection device, a global positioning system, a motion device, a signal transmitter, a signal receiver, a sensor, a memory storage unit, a logic processing unit, an application specific chip, a testing sample recycling and reclaiming unit, a micro-electro-mechanical device, a multi-functional

device, or a micro-instrument to perform surgery, cleaning, or medical function. Such additional components each may be fabricated by methods known in the art, e.g., as described in PCT/US2010/041001, PCT/US2011/024672, U.S. Application No. 12/416,280, and PCT/US2011/042637.

**[42]** In some embodiments of the apparatus, the system for delivering the biological subject comprises at least one channel inside which the biological subject to be detected travels in a certain direction; the probing and detecting device comprises at least one probing micro-device and at least one detecting micro-device, at least one probing micro-device is located before at least one detecting micro-device relative to the direction in which the biological subject travels, and the probing micro-device and the detecting micro-device can be attached to the interior or exterior wall of the channel.

**[43]** In some embodiments, the probing and detecting device comprise at least two detecting micro-devices capable of measuring at the micro-level the same or different properties of the biological subject.

**[44]** In some further embodiments, the detecting micro-devices are capable of measuring at the microscopic level the surface charge, surface potential, resting potential, action potential, electrical voltage, electrical current, electrical field distribution, electrical charge distribution, electric dipole, electric quadruple, three-dimensional electrical or charge cloud distribution, electrical properties at telomere of DNA and chromosome, dynamic changes in electrical properties, dynamic changes in potential, dynamic changes in surface charge, dynamic changes in current, dynamic changes in electrical field, dynamic changes in electrical voltage, dynamic changes in electrical distribution, dynamic changes in electronic cloud distribution, impedance, temperature, vibrational frequency, optical absorption, optical transmission, optical reflection, optical-electrical property, brightness, fluorescent emission, pH value, chemical reaction, bio-chemical reaction, bio-electro-chemical reaction, reaction speed, reaction energy, speed of reaction, oxygen concentration, oxygen consumption rate, ionic strength, catalytic behavior, bonding strength, density, geometric size, frequency, speed of acoustic waves, acoustic frequency and intensity spectrum distribution, acoustic intensity, acoustical absorption, acoustical resonance, internal pressure, hardness, shear strength, elongation strength, fracture stress, adhesion, mechanical resonance frequency, elasticity, plasticity, or compressibility.

[45] In some embodiments of the apparatus, the shapes and sizes of different sections of the channel can be the same or different; the width of the channel ranges from about 1 nm to about 1 mm; the channel can be straight, curved, or angled; the interior wall of the channel defines a circular, oval, or polygon space; the interior wall of the channel defines a circular or rectangular space; the channel is a circular carbon nano-tube.

[46] In some embodiments of the apparatus, the carbon nano-tube has a diameter ranging from about 0.5 nm to about 100 nm and a length ranging from about 5.0 nm to about 10 mm.

[47] In some embodiments of the apparatus, the interior wall of the channel has at least one concave that may be in the same section as a probing or detecting micro-device. The concave groove can be a cubic space or an angled space; the concave groove can have a depth ranging from about 10 nm to about 1 mm.

[48] In some embodiments of the apparatus, a distribution fluid is injected into the channel, either before or after the biological subject passes a probing micro-device, to aid the traveling or separation of the biological subject inside the channel. The distribution fluid can be injected into the channel through a distribution fluid channel connected to an opening in the channel wall.

[49] In some yet other innovative embodiments, a cleaning fluid can be used to clean the apparatus, particularly narrow and small spaces in the apparatus where biological residues and deposits (such as dried blood and protein when they are used in or as a sample) likely accumulate and block such spaces. Desired properties of such a cleaning fluid include, e.g., low viscosity and ability to dissolve the biological residues and deposits.

[50] The apparatus can be for detecting the diseases of more than one biological subjects and the channel comprises a device located therein for separating or dividing the biological subjects based on different levels of a same property of the biological subjects. The separating or dividing device can be, e.g., a slit, and separates or divides biological subjects based on their properties such as surface charges.

[51] The apparatus can further include a filtering device for removing irrelevant objects from the biologic subject for detection.

[52] The biological subject can be a DNA, telomere of DNA, RNA, chromosome, cell, cell substructure, protein, tissue, or virus.

[53] In some embodiments, the apparatus may further includes a unit for delivering the biological subject, a channel, a detection unit, a data storage unit, a data analysis unit, a central

control unit, a biological sample recirculation unit, a waste disposal unit; a pre-processing unit, a signal processing unit, or a disposal processing unit. All the additional components can be integrated on a single device or a board along with the delivering system and probing and detecting probe. The pre-processing unit may comprise a sample filtration unit; a delivery unit for delivering a desired ion, a biological component, or a bio-chemical component; a recharging unit; a constant pressure delivery unit; and a sample pre-probing disturbing unit. The sample filtration unit may comprise an entrance channel, a disturbing fluid channel, an accelerating chamber, and a slit. The signal processing unit may comprise an amplifier, a lock-in amplifier, an A/D (analog-to-digital or alternative to direct electric current) converter, a micro-computer, a manipulator, a display, and network connections. The signal processing unit may collect more than one signal, collect multiple signals simultaneously, collect signals simultaneously at different locations, and the signals can be integrated to cancel noise or to enhance the signal to noise ratio. The collected signal(s) may also be processed through one or more lock-in amplifiers to enhance the signal to noise ratio, thereby improving detection sensitivity and repeatability.

[54] In some embodiments of the apparatus, a bio-compatible fluid is injected into the disturbing fluid channel to separate the biological subject, or the bio-compatible fluid is injected from the entrance of the disturbing fluid channel and delivered to an opening in the entrance channel wall. The biocompatible fluid comprises saline, water, an oxygen-rich liquid, or plasma.

[55] In some embodiments of the apparatus, the angle between the entrance channel and the disturbing fluid channel ranges from about 0° to about 180°, from about 30° to about 150°, from about 60° to about 120°, or from about 75° to about 105°, or about 90°; the width of each channel ranges from about 1 nm to about 1 mm; and at least one of the channels comprises one probing device attached to the channel's sidewall, wherein the probing device is capable of measuring at the microscopic level an electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, electro-mechanical, electro-chemical, electro-chemical-mechanical, bio-chemical, bio-mechanical, bio-electro-mechanical, bio-electro-chemical, bio-electro-chemical-mechanical, physical or mechanical property of the biological subject. The sample filtration unit may comprise an entrance channel, a biocompatible micro-filter, or an exit channel.

[56] In some embodiments of the apparatus, the biocompatible micro-filter is capable of filtering the biological subject based on at least one property selected from physical size,

hardness, elasticity, shear strength, weight, surface feature, optical, acoustical, thermal, chemical, mechanical, biological, bio-chemical, electrical, electro-chemical, magnetic, electromagnetic, electro-mechanical, electro-chemical-mechanical, and electro-chemical-biological property.

[57] In some embodiments, at least one of the channels comprises at least two probing devices attached to the channel's sidewalls, and the probing devices are capable of measuring at the microscopic level an electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, electro-mechanical, electro-chemical, electro-chemical-mechanical, bio-chemical, physical-chemical, bio-physical, bio-physical mechanical, bio-mechanical, bio-electro-mechanical, bio-electro-chemical, bio-electro-chemical-mechanical, physical or mechanical property of the biological subject.

[58] In some embodiments of the apparatus, the recharging unit recharges nutrient or respiring gas to the biological subject. The nutrient can include a biocompatible strong or weak electrolyte, amino acid, mineral, ions, oxygen, oxygen-rich liquid, intravenous drip, glucose, or protein; and the respiring gas can include oxygen.

[59] In some embodiments, the biological subject to be tested comprises blood, urine, saliva, tear, saline, or sweat.

[60] In some embodiments, the signal processing unit comprises an amplifier, a lock-in amplifier, an A/D converter, a micro-computer, a manipulator, a display, or a network connection. It can collect more than one signal, and the signals can be integrated to reduce (i.e., cancel out) noise and hence enhance the signal to noise ratio.

[61] In still another aspect, the invention provides alternative apparatus for detecting a disease in a biological subject. The apparatus each comprise a launching chamber to launch a probe object at a desired speed and direction, a detection unit, a probe object, a detection component, a channel for transporting the biological subject to be tested and the probe object.

[62] In some embodiments of these apparatus, the launching chamber comprises a piston for releasing the probe object and a channel for directing the probe object.

[63] In some embodiments, the detection unit or the detection component is capable of measuring at the microscopic level an electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, electro-mechanical, electro-chemical, electro-chemical-mechanical, bio-chemical, physical-chemical, bio-physical, bio-physical mechanical, bio-

mechanical, bio-electro-mechanical, bio-electro-chemical, bio-electro-chemical-mechanical, physical or mechanical property of the biological subject.

[64] Yet still another set of apparatus for detecting a disease in a biological subject as provided by this invention are those fabricated by a method comprising: providing a substrate; sequentially depositing a first material and a second material as two layers onto the substrate to form a material stack; patterning the second material to form a first desired feature; depositing a third material onto the material stack to cover the second material; optionally patterning the first material and third material to form a second desired feature; and optionally depositing a fourth material onto the material stack; wherein the detection device is capable of interacting with the biological subject to generate a response signal.

[65] In some embodiments, in these methods used for fabricating the apparatus, the second material can be patterned by microelectronic processes.

[66] In some embodiments, in these methods used for fabricating the apparatus, the first material and third material can be the same or different.

[67] In some embodiments, in these methods used for fabricating the apparatus, the first material and third material are patterned by lithography and etch processes selective to the second material to form at least one type of trench feature in the layers of the third material and first material.

[68] In some embodiments, in these methods used for fabricating the apparatus, the fabrication method may further comprise capping the top of the material stack to form an enclosed trench. The enclosed trench can, e.g., be used to observe and record features and behaviors of the biological subject. The capping can comprise, e.g., placing a second device on the top of the material stack, and the second device can be a device identical to the detection device being capped, a piece of glass or crystal, or a functional device selected from the group consisting of an imaging device, an optical sensor, a memory storage, a signal transmission, a logic processing component, a circuit for data storage, signal transmission, signal receiving, and signal processing.

[69] In some embodiments, in these methods used for fabricating the apparatus, the first feature or second feature is selected from the group consisting of partitioned chambers, chambers connected with channels, channels, probe generator (probe), detection probes, electrically connective interconnection lines, optical transmission lines, and piezo-electric lines. For example, the partitioned chambers can be for pre-processing of the biological subject for initial



screening and enhancement of concentration of diseased biological subject for further testing, chambers connected with channels are for pre-processing and detection, channels can be for biological subject to flow through, the probe generator (probe) can be for generating probe and disturb signal onto the biological subject for triggering a response signal, the detection probe can be for measuring properties of the biological subject and the response signal, the electrically connective interconnection lines can be for transmitting signals, the optical transmission lines can be for transmitting signals, and piezo-electric lines can be for using piezo-electric effect to probe biological subjects.

[70] In some embodiments, in these methods used for fabricating the apparatus, the second material is patterned using lithography and etch processes selective to the first material to form a desired component such as a detection probe.

[71] In some embodiments, in these methods used for fabricating the apparatus, the first and third materials are patterned using lithography and etch processes selective to the second material to form at least one type of trench feature in the layers of the third and first materials, with the second material reasonably aligned with the wall of the trench.

[72] In some embodiments, in these methods used for fabricating the apparatus, the thickness of the fourth material is thinner than that of the third material.

[73] In some embodiments, the second and the fourth materials form detection probes.

[74] In some embodiments, the second and the fourth materials form a probe and a detector, respectively.

[75] In some embodiments, the apparatus may further include an imaging device for observing and recording properties and behaviors of the biological subject.

[76] In some embodiments, the apparatus may further include a pre-processing unit with chambers for pre-screening and enhancing a diseased biological subject for further testing, channels for carrying fluidic sample to flow through, probes for probing and disturbing the biological subject being tested for generating response signals, detection probes for measuring properties and response signals of the biological subject, and an imaging device, a camera, a viewing station, an acoustic detector, a thermal detector, an ion emission detector, or a thermal recorder for observing and recording properties and behaviors of the biological subject.

[77] In some embodiments, the apparatus may further include a memory storage unit, a signal transmission component, a logic processing component, or a circuit for data storage, signal

transmission, signal receiving, or signal processing. These additional devices can be fabricated by microelectronics processes on the substrate where the first material is deposited.

[78] In some embodiments, the apparatus may have typical channel dimensions ranging from about 2 microns  $\times$  2 microns to about 100 microns  $\times$  100 microns in cross sectional area for a square-shaped channel, a rectangle-shaped channel, a radius ranging from about 1 micron to about 20 microns in cross sectional area for a circular shaped channel, and a typical probe dimension ranging from about 0.5 micron  $\times$  0.5 micron to about 20 microns  $\times$  20 microns in cross sectional area for a square-shaped probe.

[79] In some embodiments, the apparatus may have typical channel dimensions ranging from about 6 microns  $\times$  6 microns to about 14 microns  $\times$  14 microns in cross sectional area for a square-shaped channel, a radius ranging from about 3 microns to about 8 microns in cross sectional area for a circular shaped channel, and a typical probe dimension ranging from about 0.5 micron  $\times$  0.5 micron to about 10 microns  $\times$  10 microns in cross sectional area for a square shaped probe.

[80] In some embodiments, the first material and the fourth material each comprise un-doped oxide ( $\text{SiO}_2$ ), silicon nitride, doped oxide, a polymer material, glass, or an insulating material.

[81] In some embodiments, the second material and third material each comprise an electrically conductive material, aluminum, an aluminum alloy, copper, a copper alloy, tungsten, a tungsten alloy, gold, a gold alloy, silver, a silver alloy, or a piezo-electric material. Examples of the piezo-electric material include, but are not limited to, quartz, berlinite, gallium, orthophosphate,  $\text{GaPO}_4$ , tourmaline, ceramics, barium, titanate,  $\text{BaTiO}_3$ , lead zirconate, titanate PZT, zinc oxide, aluminum nitride, and a polyvinylidene fluoride.

[82] In yet some other embodiments, the second material and fourth material each comprise an electrically conductive material or a piezo-electric material. Examples of the electrically conductive material include, but are not limited to, aluminum, an aluminum alloy, copper, a copper alloy, tungsten, a tungsten alloy, gold, a gold alloy, silver, a silver alloy; whereas examples of the piezo-electric material include, but are not limited to, quartz, berlinite, gallium, orthophosphate,  $\text{GaPO}_4$ , tourmaline, ceramics, barium, titanate,  $\text{BaTiO}_3$ , lead zirconate, titanate PZT, zinc oxide, aluminum nitride, and a polyvinylidene fluoride.

[83] In some embodiments of the apparatus, the detection device comprises at least one probe, at least one detector, or at least one pair of probe and detector, the probe generates a probing or

disturbing signal onto the biological subject to give a response signal, and the detector measures the response signal thus generated.

[84] In some embodiments of the apparatus, the second material is patterned by microelectronic processes to form a first desired feature; the first material and third material are optionally patterned by microelectronic processes to form a second desired feature; and the first material and third material can be the same or different.

[85] In some embodiments, the methods for fabricating the apparatus further include capping the top of the material stack to form an enclosed trench, with such trench used for test sample transportation or detection site.

[86] One of the key novel aspects of this patent application is the design and fabrication process flows of micro-devices and methods of using the micro-devices for contacting and measuring properties, at microscopic levels and in a three dimensional space, of a biological subject (e.g., a single cell or a single biological molecule such as DNA or RNA). The micro-devices have micro-probes arranged in a three dimensional manner with feature sizes as small as a cell, a DNA, and a RNA and capable of trapping, sorting, probing, measuring, manipulating, or modifying biological subjects.

[87] Another aspect of this invention relates to methods for fabricating a micro-device. The methods include depositing various materials on a substrate and, in the interims of depositing every two materials, pattern the materials by microelectronic technology and associated processes, wherein the micro-device is capable of measuring at the microscopic level the electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, physical, physical-chemical, bio-chemical, bio-physical, mechanical, bio-chemical mechanical, bio-electro-mechanical, bio-electro-chemical mechanical, electro-chemical mechanical, micro-electro-mechanical property of a biologic subject that the micro-device is to contact.

[88] Still another aspect of this invention relates to methods for fabricating a micro-device, which include depositing a first material on the substrate, patterning the first material by a microelectronic process to give rise to at least one patterned residual and leaving part of the substrate surface uncovered by the first material, depositing a second non-conductive material atop the processed first material and the substrate, creating an opening in the second material and exposing part of the patterned residual of the first material, filling up the opening in the second

material with a third material. In some embodiments, the microelectronic process comprises thin film deposition, photolithography, etching, cleaning, or chemical mechanical polishing.

[89] Yet in still another aspect, the invention provides methods for fabricating a micro-device, which include the first step of depositing a first material onto a substrate; the second step of depositing a second material onto the first material and then patterning the second material with a microelectronic technology or process; and repeating the second step at least once with a material that can be the same as or different from the first or second material. The materials used in the repeated steps can be the same as or different from the first or second material. In some embodiments, at least one of the materials used in fabricating the micro-device is a piezo-electric material or a conductive material.

[90] In some embodiments, multiple fabricated micro-devices can be coupled, joined, connected, and integrated by physical or electrical method to constitute the more advanced devices.

[91] In some embodiments, the apparatuses of this invention can be integrated on a single device (e.g., by using a semiconductor processing technology) or assembled on a board (e.g., by using a computer packaging technology).

[92] In some embodiments, patterning of a material is done by a microelectronic process (e.g., chemical vapor deposition, physical vapor deposition, or atomic layer deposition to deposit various materials on a substrate as an insulator or conductor; lithography or etch to transfer patterns from design to structure; chemical mechanical planarization, chemical cleaning for particle removal, thermal spiking anneal to reduce the crystal defects, diffusion or ion implantation for doping elements into specific layers). In some embodiments, patterning is planarization by chemical polishing, mechanical polishing, or chemical mechanical polishing.

[93] In some other embodiments, the methods further include removal of a stack of multiple layers of materials by wet etch, plasma etch, or by vapor etch.

[94] In some embodiments, the micro-device can move in any direction. For instance, two micro-devices can move in opposite directions.

[95] In some embodiments, the micro-device thus fabricated is so patterned that it is capable of trapping, sorting, probing, measuring, or modifying a biological subject; or that it can piece through the membrane of a cell.

[96] Still another aspect of the invention relates to methods for fabricating a device or apparatus for detecting disease in a biological subject, which include providing a substrate, sequentially depositing a first material and a second material as two different layers onto the substrate to form a material stack, patterning the second material by microelectronic processes to form a first desired feature, depositing a third material onto the material stack, optionally patterning the first and third materials by microelectronic processes to form a second desired feature, and optionally depositing a fourth material onto the material stack.

[97] In some embodiments, the methods further include steps of fabricating (utilizing processes including but not limited to depositing, patterning, polishing, and cleaning) additional components onto the substrate before sequentially depositing the first material and the second material as layers onto the substrate, wherein the additional components comprise a data storage component, a signal processing component, a memory storage component, a signal transmitting component, a logic processing component, or an RF (radio-frequency) component.

[98] In some other embodiments, the methods further include steps of fabricating at least a circuit onto the substrate before sequentially depositing the first material and the second material as layers onto the substrate, wherein the circuit comprises a data storage circuit, a signal processing circuit, a memory storage circuit, a signal transmitting circuit, or a logic processing circuit.

[99] In still some other embodiments, the methods of this invention further include a step of planarizing the third material using chemical mechanical polishing process or an etch back process, after the step of depositing the third material onto the material stack and before the step of patterning the first and the third materials.

[100] Examples of the suitable microelectronic processes include, but are not limited to, thin film deposition, lithography, etch, polishing, cleaning, ion implantation, diffusion, and packaging as typically used in microelectronics.

[101] The first and third materials can be the same or different. They can be, for example, electrically insulating material, such as oxide, doped oxide, silicon nitride, or a polymer.

[102] The second material can be an electrically conductive material, a piezo-electric material, a semiconductor material, a thermal sensitive material, an optical material, a pressure sensitive material, an ion emission sensitive material, or any combination thereof. For example, the second material can be copper, aluminum, tungsten, gold, silver, glass, an aluminum alloy, a

copper alloy, a tungsten alloy, a gold alloy, a silver alloy, quartz, berlinite, gallium, orthophosphate,  $\text{GaPO}_4$ , tourmaline, ceramics, barium, titanate,  $\text{BaTiO}_3$ , lead zirconate, titanate PZT, zinc oxide, aluminum nitride, and a polyvinylidene fluoride.

[103] In some embodiments, the first desired feature can be a probe, whereas the second desired feature can be a recessed form, or a trench form in the layers of the first and third materials.

[104] In yet some other embodiment, the methods of this invention further comprise depositing a fourth material onto the material stack and then patterning the fourth material to form a recessed area such as a hole at a selected location.

[105] In still another embodiment, the methods of this invention further comprise a step of removing the third material from the material stack by wet or vapor etch to form a detection chamber between the fourth material and the substrate. Furthermore, they may also include a step of removing the first material from the material stack by wet or vapor etch to form a channel. The channel can connect the formed detection chamber with additional chambers.

[106] In yet still another embodiment, the methods of this invention further include a step of sealing or capping the top of the material stack to form an enclosed trench. In one example of this step, the top of the material stack is sealed or capped with an additional device onto the material stack. Examples of such an additional device include, but are not limited to, an imaging device, a communication device, and a detecting probe. The above said device on top of the material stack comprises of optical device, imaging device, camera, viewing station, acoustic detector, thermal detector, ion emission detector, and thermal recorder.

[107] In yet another aspect, the present invention provides methods for fabricating a device for detecting disease in a biological subject, which include providing a substrate, sequentially depositing a first and a second materials as layers onto the substrate to form a material stack, patterning the second material by lithography and etch process to form a recessed area in the layer of the second material, depositing a third material onto the material stack, removing a portion of the third material above the second material by etch back or polishing process, patterning the third material by lithography and etch to form at least a portion of recessed area in the layer of the third material, depositing a fourth material onto the material stack, and removing the portion of the fourth material above the third material by etch back or polishing process to keep at least a portion of the second and fourth material in the same layer.

[108] If desired, more layers of different materials can be deposited, patterned, cleaned, or planarized to form additional structures with more features, functionalities, and complexities.

[109] The first and third materials used in the methods of this invention can be the same or different. In some embodiments, they are the same. They can be, e.g., an electrically insulating material. Examples of the first and third materials include, but are not limited to, oxide, doped oxide, silicon nitride, or a polymer.

[110] In some embodiments, following the deposition and processing of the third or fourth material, at least one more material is deposited and processed to form a top layer with a detection chamber or channels formed underneath.

[111] Examples of the second material include, but are not limited to, electrically conductive materials, piezo-electric materials, semiconductor materials, thermal sensitive materials, a pressure sensitive material, an ion emission sensitive material, optical materials, or any combinations thereof.

[112] In some embodiments, a novel detection apparatus comprising a detection chamber and/or channels for test sample transport is formed by methods that include the steps of: depositing a first material, patterning the first material ("material A") to form at least a recessed area, depositing a second material ("material B"), removing the second material ("material B") from areas above the first material ("material A") by using polishing and/or etch back processes, leaving the second material ("material B") in the recessed area in the first material layer, depositing a third material ("material C") to cover the first material ("material A") and the second material ("material B"), patterning the third material ("material C") to form at least a hole smaller than the recessed area(s) in the third material layer and above it, removing the second material ("material B") optionally by using vapor etch or wet etch, forming an enclosed cavity in the first material layer.

[113] In addition to novel micro-devices and manufacturing process for fabricating them, packaging of such devices are also critical (a) in ensuring its proper function and (b) how to incorporate (transport it into the micro-device) biological sample into the micro-device for detection, probing, communicating, and possibly manipulating, modifying and treating such biological subjects. Specifically, after being fabricated, the micro-devices typically need to be packaged for protection from outside environment and for configuration for connection with the outside world (e.g., by electrical connection).

[114] In this application, a set of novel designs, configurations, processes, and materials are disclosed, with the goals of protecting the micro-devices, connecting to the outside world, and transporting biological samples into the micro-devices properly and effectively. In some embodiments relating to this aspect, after being fabricated, a micro-device can be wrapped with a packaging material that forms a protective or packaging layer around the micro-device. The packaging process may also allow for forming lead pins on the packaging material for connections (e.g., magnetic or electric connection) with outside devices, e.g., for data transmissions and instruction communications. The packaging material can be an organic polymeric material, an inorganic polymeric material, or a molding compound.

[115] In some other embodiments, a novel cavity can be formed in the packaging or protective layer, which has at least one opening connecting to the inlet of the micro-device and at least one other opening connecting to an outside device such as an injection device. In this way, a biological sample can be injected into the cavity through the opening (e.g., by connecting to an injector) and transported into the micro-device through the other opening connecting to the micro-device inlet.

[116] In still some other applications, an outside device such as an injection device can be directly connected to an inlet of, or fitted into, the micro-device for transporting a biological sample. In this case, it is important that the inlet is leak free at both ends connected to the micro-device and to the outside device (such as an injector). To achieve this, a first material with substantially high viscosity can be used first to seal seams and cracks between the inlet and the micro-device, or between the outside device and the micro-device. It could be a solid material or a material with very high viscosity. To secure its stability and resolve possible adhesion issues with the first material and the device, a second material (e.g., a material that has a lower viscosity and is sticky in nature, when melt or solution) can be applied. Examples of such a material include epoxies, adhesives, and glues. To speed up the drying process of the second material when it is in a solution, heat can be applied (for example, an air flow at a temperature of 40 °C or higher).

[117] In yet some other embodiments, a novel detection apparatus can be integrated with at least one micro-injector and at least one detector, in which the micro-injector can inject a desired object into the biological subject to be tested to generate a response by the biological subject and the detector detects the response thus generated by the biological subject.



[118] The invention further provides methods for detecting a biological subject's dynamic response to a signal. These methods include providing an apparatus comprising two micro-devices of which one is a probing micro-device and the other is a detecting micro-device and positioned with a distance from the probing micro-device; contacting the biological subject with the probing micro-device whereby the probing micro-device measures a property of the biological subject at the microscopic level or sends a stimulating signal to the biological subject; and the detecting micro-device measures the response of the biological subject through measuring properties of the biological subject at the microscopic level. Optionally, the detecting micro-device contacts the biological subject during the measurements.

[119] In some embodiments, the signal is an electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, electro-mechanical, electro-chemical, electro-chemical-mechanical, bio-chemical, bio-mechanical, bio-electro-mechanical, bio-electro-chemical, bio-electro-chemical-mechanical, physical, or mechanical signal.

[120] In some other embodiments, the property at the microscopic level is an electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, electro-mechanical, electro-chemical, electro-chemical-mechanical, bio-chemical, bio-chemical-physical, bio-mechanical, bio-electro-mechanical, bio-electro-chemical, bio-electro-chemical-mechanical, physical, or mechanical property.

[121] Examples of the electrical properties include, but are not limited to, surface charge, surface potential, resting potential, electrical current, electrical field distribution, electric dipole, electric quadrupole, three-dimensional electrical and/or charge cloud distribution, electrical properties at telomere of DNA and chromosome (also called sticky end or DNA end) or impedance. Examples of the thermal properties include temperature, and vibrational frequency of biological item and molecules. Examples of the optical properties include optical absorption, optical transmission, optical reflection, optical-electrical properties, brightness, and fluorescent emission. Examples of the chemical properties include pH value, chemical reaction, bio-chemical reaction, bio-electro-chemical reaction, reaction speed, reaction energy, speed of reaction, oxygen concentration, oxygen consumption rate, ionic strength, catalytic behavior, and bonding strength. Examples of the physical properties include density and geometric size. Examples of the acoustic properties include frequency, speed of acoustic waves, acoustic frequency and intensity spectrum distribution, acoustic intensity, acoustical absorption, and

acoustical resonance. Examples of the mechanical property include internal pressure, hardness, shear strength, elongation strength, fracture stress, adhesion, mechanical resonance frequency, elasticity, plasticity, and compressibility. The data from measuring one or more of the properties at the microscopic level can be used for detecting diseases, e.g., cancer at its early stage, or for estimating the life expectancy of the carrier of the biological subject.

[122] In some other embodiments, the apparatus further includes a third micro-device that is different from the probing micro-device and the detecting micro-device; and the third micro-device measures the same or a different property of the biological subject as the probing micro-device and the detecting micro-device do.

[123] In still some other embodiments, the apparatus further includes a clock micro-device that is different from the probing micro-device and the detecting micro-device; and the type of clock micro-device is placed at a fixed distance before the probing micro-devices and detecting micro-devices with a distinctive signal when a biological subject passes it and acts as a clock device.

[124] Yet still in some embodiments, the data recorded by the detecting micro-device is filtered by a phase lock-in technology to remove noise unsynchronized to the clock signal in order to enhance signal to noise ratio and improve measurement sensitivity.

[125] Another aspect of this invention relates to methods for detecting disease in a biological subject, comprising providing an apparatus comprising a channel, a detection probe, imaging device, a memory storage component, a signal transmitting component, a signal receiving component, or a logic processing component, pre-processing the biological subject to enhance its concentration, measuring the properties of the biological subject, optionally contacting the biological subject with the probing component (probing micro-device or probing tip) through the channel to trigger or result in a response signal, using the detection probe (e.g., detection micro-device or detection component) to detect the response signal from the biological subject, optionally separating diseased biological subject from healthy biological subject based on the response signal, optionally sending the separated, suspected diseased biological subject on for further tests, and analyzing the response signal and reaching a diagnosis conclusion. The biological subject can be a DNA, a sub-structure in a cell, a cell, or a protein.

[126] In some embodiments, the methods of this invention further include detection of the response signal and behaviors of interaction or events occurred between at least two biological subjects or at least one biological subject with at least one non-biological subject. The at least

two biological subject can be different or identical, in type of composition. Examples of interactions or events occurred between at least two biological subjects include, but are not limited to, a DNA colliding with another DNA, a cell smashing into another cell, a DNA crashing into a cell, a protein colliding with another protein, or a DNA crashing into a protein. Examples of interactions or events occurred between at least one biological subject with at least one non-biological subject include, but not limited to, an inorganic particle colliding with a biological subject, an organic particle colliding with a biological subject, or a composite particle colliding with a biological subject.

[127] Examples of the response signals include, but are not limited to, an electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, electro-mechanical, electro-chemical, electro-chemical-mechanical, bio-chemical, bio-chemical-physical, bio-mechanical, bio-electro-mechanical, bio-electro-chemical, bio-electro-chemical-mechanical, physical, and mechanical signal.

[128] Another aspect of the current invention relates to methods for detecting disease in a biological subject. The methods include providing an apparatus comprising a pre-processing unit, at least one detection device, a partitioned chamber with channels connecting them, and an injection device (for, e.g., injecting a probe material into the biological subject to be tested), and measuring response signals from the biological subject, wherein the probe material comprises an organic particle, an inorganic particle, a biological subject, or a composite-based object.

[129] Yet another aspect of the current invention relates to methods for detecting a disease in a biological subject by interacting it with a probe object, comprising providing an apparatus comprising a launching chamber, a detection unit, and channels, launching a probe object onto the biological subject, causing a collision between the probe object and the biological subject to give rise to a response signal, recording and detecting the response signal during and after the collision. The probe object may comprise an organic particle, an inorganic particle, a biological subject, or a composite-based object.

[130] Still another aspect of this invention relates to methods for detecting a disease in early stage in a biological subject. These methods include the steps of collecting a first sample (including a cell or a biological molecule) of the biological subject's tissue or organ potentially carrying the disease, collecting a second sample of the same tissue or organ from a second subject free of the disease, separately contacting the first and second samples with a disease

detection apparatus of this invention, and comparing the data from the measurements of the first and second samples. As mentioned above, a disease detection apparatus of this invention includes a micro-device and a substrate supporting the micro-device, wherein the micro-device is capable of measuring at the microscopic level the electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, physical, or mechanical property of a biological sample.

**[131]** Still a further aspect of this invention relates to a method of cellular communication. The micro-device can generate artificial microscopic calcium (or other elements) oscillations which simulate the intracellular biological communications. This artificial signal can be coded to interact with cellular proteins, nucleus, and eventually regulates cell's determination or fate, which in turn can result in communication, probing, modifying, manipulating, or control of a biological subject at the cellular level, hence giving rise to diagnose or cure of diseases at the cellular level or in their early stage.

**[132]** Yet still a further aspect of this invention relates to methods for determining cellular or molecular response to a signal. The methods include the step of contacting a cell or biological molecule with a disease detection apparatus of this invention – which includes a first micro-device, a second micro-device, and a first substrate supporting the first micro-device and second micro-device. The first micro-device in the apparatus is capable of measuring at the microscopic level an electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, electro-mechanical, electro-chemical, electro-chemical-mechanical, bio-chemical, bio-mechanical, bio-electro-mechanical, bio-electro-chemical, bio-electro-chemical-mechanical, physical, or mechanical property of the cell; and the second micro-device contacts the cell or biological molecule and stimulates it with a signal.

**[133]** In some embodiments of these methods, the apparatus further comprises a third micro-device that is capable of measuring at the microscopic level the same electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, electro-mechanical, electro-chemical, electro-chemical-mechanical, bio-chemical, bio-mechanical, bio-electro-mechanical, bio-electro-chemical, bio-electro-chemical-mechanical, physical, or mechanical property of the cell or biological molecule as the first micro-device is.

**[134]** In some other embodiments, the cell contacts the first micro-device, second micro-device, and third micro-device in the order.

[135] In some further embodiments, the signal is an electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, electro-mechanical, electro-chemical, electro-chemical-mechanical, bio-chemical, bio-mechanical, bio-electro-mechanical, bio-electro-chemical, bio-electro-chemical-mechanical, physical, or mechanical signal.

[136] In some embodiments of the apparatus of this invention, the system for delivering the biological subject includes at least one channel inside which the biological subject to be detected travels in a certain direction; the probing and detecting device includes at least one probing micro-device and at least one detecting micro-device, at least one probing micro-device is located before at least one detecting micro-device relative to the direction in which the biological subject travels, and the probing micro-device and the detecting micro-device can be attached to the interior or exterior wall of the channel. In some other embodiments, multiple channels with different geometries are utilized.

[137] In some examples of these embodiments, the probing and detecting device includes at least two detecting micro-devices capable of measuring at the micro-level the same or different properties of the biological subject. Examples of the electrical properties include, but are not limited to, surface charge, surface potential, resting potential, electrical current, electrical field distribution, electric dipole, electric quadrupole, three-dimensional electrical and/or charge cloud distribution, electrical properties at telomere of DNA and chromosome or impedance; examples of the thermal properties include temperature, and vibrational frequency of biological item and molecules; examples of the optical properties include optical absorption, optical transmission, optical reflection, optical-electrical properties, brightness, and fluorescent emission; examples of the chemical properties include pH value, chemical reaction, bio-chemical reaction, bio-electro-chemical reaction, reaction speed, reaction energy, speed of reaction, oxygen concentration, oxygen consumption rate, ionic strength, catalytic behavior, and bonding strength; examples of the physical properties include density and geometric size; examples of the acoustic properties include frequency, speed of acoustic waves, acoustic frequency and intensity spectrum distribution, acoustic intensity, acoustical absorption, and acoustical resonance; and examples of the mechanical property include internal pressure, hardness, shear strength, elongation strength, fracture stress, adhesion, mechanical resonance frequency, elasticity, plasticity, and compressibility. For instance, the detecting micro-devices are capable of measuring at the

microscopic level the surface charge, electric potential, brightness, fluorescent emission, geometric size, shape, frequency, internal pressure, or temperature of the biological subject.

[138] In some other embodiments, the shapes and sizes of different sections of the channel can be the same or different; the width of the channel can be about 1 nm ~ 1 mm (e.g., 1 ~ 750 nm, 1 ~ 600 nm; 100 ~ 800 nm, 200 ~ 750 nm, or 400 ~ 650 nm); the channel can be straight, curved, or angled; the interior wall of the channel defines a circular, oval, or polygon (e.g., rectangular) space.

[139] An example of a suitable channel is a circular carbon nano-tube, which can have a diameter of, e.g., about 0.5 ~ 100 nm, or a length of, e.g., about 5.0 nm ~ 10 mm.

[140] In some embodiments, the interior wall of the channel has at least one concave that may be in the same section as a probing or detecting micro-device. The concave groove can be, e.g., a cubic space or an angled space. It can have a depth of, e.g., about 10 nm ~ 1 mm.

[141] In some other embodiments, a distribution fluid can be injected into the channel, either before or after the biological subject passes a probing micro-device, to aid the traveling or separation of the biological subject inside the channel. A suitable distribution fluid is a biocompatible liquid or solution, e.g., water or saline. The distribution fluid can be injected into the channel through a distribution fluid channel connected to an opening in the channel wall. Utilizing such a distribution fluid allows, among others, preparation of the surface of the channel (in which the biological subject travels), cleaning of the channel, disinfection of the apparatus, and enhancing the measurement sensitivity of the apparatus.

[142] In yet some other embodiments, a cleaning fluid can be used to clean an apparatus of this invention, particularly narrow and small spaces in the apparatus wherein biological residues and deposits (e.g., dried blood or protein when it is used as or contained in a sample to be tested by the apparatus) are likely to accumulate and block such spaces. Desired properties of such a cleaning fluid include low viscosity and ability to dissolve the biological residues and deposits. For example, when an apparatus of this invention is used for detecting a disease, certain biological samples, such as blood, could result in blockage to narrow, small spaces in the apparatus such as narrow channels when the blood is allowed to dry. The cleaning solution is expected to address this issue by dissolve the biological samples.

[143] In still some other embodiments, the apparatus of this invention can be for detecting the diseases of more than one biological subject, and the channel comprises a device located therein

for separating or dividing the biological subjects based on different levels of a same property of the biological subjects. An example of such a separating or dividing device is a slit that can, e.g., separate or divide biological subjects based on their surface charges, their density, their size, or other properties such as electrical, thermal, optical, chemical, physical, magnetic, electromagnetic, and mechanical properties. Examples of the electrical properties include, but are not limited to, surface charge, surface potential, resting potential, electrical current, electrical field distribution, electric dipole, electric quadrupole, three-dimensional electrical and/or charge cloud distribution, electrical properties at telomere of DNA and chromosome or impedance; examples of the thermal properties include temperature, and vibrational frequency of biological item and molecules; examples of the optical properties include optical absorption, optical transmission, optical reflection, optical-electrical properties, brightness, and fluorescent emission; examples of the chemical properties include pH value, chemical reaction, bio-chemical reaction, bio-electro-chemical reaction, reaction speed, reaction energy, speed of reaction, oxygen concentration, oxygen consumption rate, ionic strength, catalytic behavior, and bonding strength; examples of the physical properties include density and geometric size; examples of the acoustic properties include frequency, speed of acoustic waves, acoustic frequency and intensity spectrum distribution, acoustic intensity, acoustical absorption, and acoustical resonance; and examples of the mechanical property include internal pressure, hardness, shear strength, elongation strength, fracture stress, adhesion, mechanical resonance frequency, elasticity, plasticity, and compressibility.

[144] In yet still some other embodiments, the apparatus of this invention can further include a filtering device for removing irrelevant objects from the biologic subject for detection.

[145] In another aspect, the invention provides methods for obtaining dynamic information of a biologic material, each comprising contacting the biological subject (e.g., including but not limited to a cell, substructure of a cell such as cell membrane, a DNA, a RNA, a protein, or a virus) with an apparatus comprising a first micro-device, a second micro-device, and a first substrate supporting the first micro-device and second micro-device, wherein the first micro-device is capable of measuring at the microscopic level an electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, physical, or mechanical property of the biological subject, and the second micro-device contacts the biological subjects and stimulates it with a signal.

[146] In yet another embodiment, the micro-device in the detection apparatus can communicate with biological subjects such as cells, DNA, RNA, virus, or protein. Further, the micro-device can trap, sort, analyze, treat, and modify biological subjects such as cells, DNA, RNA, blood cells, protein, or virus. Specifically, an array of micro-devices arranged in a desired manner can trap, sort, detect, and modify DNA structures.

[147] In some embodiments, the apparatus further comprising a third micro-device that is capable of measuring at the microscopic level the same electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, bio-chemical, physical, or mechanical property of the cell as the first micro-device is. In some other embodiments, the cell contacts the first micro-device, second micro-device, and third micro-device in the order. In still some other embodiments, the signal is an electric signal, a magnetic signal, an electromagnetic signal, a thermal signal, an optical signal, an acoustical signal, a biological signal, a chemical signal, a physical signal, or a mechanical electric signal.

[148] In another aspect, this invention provides alternative methods for detecting a biological subject's dynamic information. The methods each include providing an apparatus comprising a clock micro-device, a probing micro-device, and a first detection micro-device, with the probing micro-device being placed between the clock micro-device and the detection micro-device; contacting the biological subject with the clock micro-device whereby the clock micro-device registers the arrival of the biological subject, and optionally measures a property of the biological subject at the microscopic level; contacting the biological subject with the probe device with a periodic probe signal delivered onto the biological subject; using the detecting micro-device to detect response signal from the biological subject; and processing the detected signal by the detection micro-device using phase lock-in technology to filter out signal components unsynchronized to the frequency of the probe signal, and amplify the signal synchronized to the probe signal.

[149] In some embodiments of these methods, there is a distance of at least 10 angstroms between the clock micro-device and the first detecting micro-device.

[150] In some other embodiments, the response signal is an electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, electro-mechanical, electro-chemical, electro-chemical-mechanical, bio-chemical, bio-mechanical, bio-electro-mechanical, bio-electro-chemical, bio-electro-chemical-mechanical, physical, or mechanical signal.



[151] In some other embodiments, the first probing micro-device optionally measures the same property of the biological subject at the microscopic level as the first detecting micro-device does.

[152] In still some other embodiments, the apparatus used in the methods further comprises a second probing micro-device capable of sending a stimulating signal to the biological subject that is different from the signal sent by the first probing micro-device.

[153] In still some other embodiments, the apparatus used in the methods further comprise a second detecting micro-device capable of measuring the same property of the biological subject at the microscopic level as the first detecting micro-device does.

[154] In yet still some other embodiments, the electrical property is surface charge, surface potential, resting potential, electrical current, electrical field distribution, electric dipole, electric quadruple, three-dimensional electrical or charge cloud distribution, electrical properties at telomere of DNA and chromosome, or impedance; the thermal property is temperature, or vibrational frequency of biological item or molecules; the optical property is optical absorption, optical transmission, optical reflection, optical-electrical property, brightness, or fluorescent emission; the chemical property is pH value, chemical reaction, bio-chemical reaction, bio-electro-chemical reaction, reaction speed, reaction energy, oxygen concentration, oxygen consumption rate, ionic strength, catalytic behavior, or bonding strength; the physical property is density or geometric size; the acoustic property is frequency, speed of acoustic waves, acoustic frequency and intensity spectrum distribution, acoustic intensity, acoustical absorption, or acoustical resonance; and the mechanical property is internal pressure, hardness, shear strength, elongation strength, fracture stress, adhesion, mechanical resonance frequency, elasticity, plasticity, or compressibility.

[155] In some embodiments, the data recorded by the first detecting micro-device is filtered by a phase lock-in technology to remove noise unsynchronized to the data recorded by the first probing micro-device or the clock micro-device. The filtered data may have a higher signal to noise data ratio.

[156] Another innovative aspect of the present invention is the use of micro-devices for obtaining real time data and information at the cellular structure level, such as using a micro voltage comparator, four-point probe and other circuitry designs to measure cell surface or bulk electrical properties including resting potential and surface charge for differentiating normal cells

and cancer cells.. The cell surface charge differentiation can be an important factor in deciding the healthy or unhealthy status of a cell and, accordingly, the proper treatment thereof.

[157] For example, in a time of flight approach to obtain dynamic information on a biological subject (e.g., a cell, a substructure of a cell, a DNA or RNA molecule, or a virus), a first micro-device is first used to send a signal to perturb the biological subject to be diagnosed, and then a second micro-device is employed to accurately measure the response from the biological subject. In one arrangement, the first micro-device and the second device are positioned at a desired distance  $L$  apart, with a biological subject to be measured flowing from the first micro-device towards the second micro-device. When the biological subject sample passes the first micro-device, the micro-device sends a signal to the passing biological sample, and then the second micro-device detects the response or retention of the perturbation signal on the entity. From the distance between the two micro-devices, time interval, the nature of perturbation by the first micro-device, and measured changes on the biological subject during the time of flight, microscopic and dynamic properties of the biological subject can be measured and data obtained. In another arrangement, a first micro-device is used to probe the biological subject by first applying a signal (such as a charge) and then detecting the response from the biological subject with a second micro-device as a function of time.

[158] Another novel area of this application is the invention of micro-indentation probes and micro-probes for measuring a range of physical properties (such as mechanical properties) of biological subjects. Examples of such physical properties include but not limited to hardness, shear strength, elongation strength, fracture stress, and properties related to cell membranes as the membranes may be a critical component in disease diagnosis.

[159] Still yet another aspect of this invention is the design, fabrication, and integration of the various components in the disease detection apparatus. These components include, e.g., a sample containment and delivery unit; an array of sample delivery channels; a central disease detection unit comprising multiple detection probes, a central control unit comprising a logic processing unit, a memory unit, a sensor, a signal transmitter, a signal receiver, and an application specific chip; and a waste sample treatment unit in which used sample can be treated, recycled, processed for reuse, or disposed.

[160] Another key novel aspect of the current application is the design, integration, and fabrication process flow of micro-devices capable of making highly sensitive and advanced

measurements on very weak signals in biological systems for disease detection under complicated environment with very weak signal and relatively high noise background. Those novel capabilities using the class of micro-devices disclosed in this invention for disease detection include, e.g., making dynamic measurements, real time measurements (such as time of flight measurements, and combination of using probe signal and detecting response signal), phase lock-in technique to reduce background noise, and 4-point probe techniques to measure very weak signals, and unique and novel probes to measure various electronic, electromagnetic and magnetic properties of biological samples at the single cell, biological subject (e.g., virus) or molecule (e.g., DNA or RNA) level.

[161] Finally, another aspect of this invention relates to apparatus for detecting disease in a biological subject. The apparatus includes a detection device fabricated by a method comprising: providing a substrate; sequentially depositing a first material and a second material as two layers onto the substrate to form a material stack; patterning the second material by microelectronic processes to form a first desired feature; depositing a third material onto the material stack to cover the second material; optionally patterning the first and third materials by microelectronic processes to form a second desired feature; and optionally depositing a fourth material onto the material stack. The first material and third material can be the same or different. The detection device is capable of probing the biological subject to be detected and giving rise to a response signal.

[162] In some embodiments, the fabrication method further comprises capping the top of the material stack to form an enclosed trench.

[163] In some other embodiments, the capping comprises sealing or capping the top of the material stack with an imaging device onto the material stack.

[164] In still some other embodiments, the apparatus further includes a pre-processing unit (chambers) for pre-screening and enhancing a diseased biological subject for further testing, channels for carrying fluidic sample to flow through, probes for probing and disturbing the biological subject being tested for generating response signals, detection probes for measuring properties and response signals of the biological subject, or an imaging device for observing and recording properties and behaviors of the biological subject.

[165] In yet some other embodiments, the detection device has typical channel dimensions ranging from about 2 microns  $\times$  2 microns to about 100 microns  $\times$  100 microns in cross sectional

area for a square-shaped channel, a radius ranging from about 1 micron to about 20 microns in cross sectional area for a circular shaped channel, and a typical probe dimension ranging from about 0.5 micron x 0.5 micron to about 20 microns x 20 microns in cross sectional area for a square-shaped probe. Alternatively, the detection device has typical channel dimensions ranging from about 6 microns x 6 microns to about 14 microns x 14 microns in cross sectional area for a square-shaped channel, a radius ranging from about 3 microns to about 8 microns in cross sectional area for a circular shaped channel, and a typical probe dimension ranging from about 0.5 micron x 0.5 micron to about 10 microns x 10 microns in cross sectional area for a square shaped probe.

[166] In yet still some embodiments, the first and the fourth materials each comprise un-doped oxide ( $\text{SiO}_2$ ), doped oxide, silicon nitride, a polymer material, glass, or an electrically insulating material; the second and third materials each comprise an electrically conductive material, aluminum, an aluminum alloy, copper, a copper alloy, tungsten, a tungsten alloy, gold, a gold alloy, silver, a silver alloy, an optical material, an thermal sensitive material, a magnetic material, a pressure sensitive material, a mechanical stress sensitive material, an ion emission sensitive material, and a piezo-electric material.

[167] In yet still some other embodiments, where the second and fourth materials can be fabricated at the same level as detectors, or as probes and detectors, the first and the third materials each comprise un-doped oxide ( $\text{SiO}_2$ ), doped oxide, silicon nitride, a polymer material, glass, or an electrically insulating material; the second and fourth materials each comprise an electrically conductive material (e.g., aluminum, an aluminum alloy, copper, a copper alloy, tungsten, a tungsten alloy, gold, a gold alloy, silver, or a silver alloy), an optical material (e.g., anisotropic optical material, glass, glass-ceramic, laser gain media, nonlinear optical material, phosphor and scintillator, transparent material), an thermal sensitive material, a magnetic material, a pressure sensitive material, a mechanical stress sensitive material, an ion emission sensitive material, and a piezo-electric material (e.g., quartz, berlinite, gallium, orthophosphate,  $\text{GaPO}_4$ , tourmaline, ceramics, barium, titanate,  $\text{BaTiO}_3$ , lead zirconate, titanate PZT, zinc oxide, aluminum nitride, and a polyvinylidene fluoride).

[168] In further embodiments, the detection device comprises at least one probe, at least one detector, at least one pair of probe and detector in which the probe generates a probing or

disturbing signal onto the biological subject to give a response signal and the detector measures the response signal thus generated.

[169] In other aspects, the present invention provides methods for fabricating micro-devices or micro-detectors of this invention by microelectronic process which may include deposition, lithography, etch, cleaning, direct writing, molecular self assembly, laser ablation, electron beam writing, x-ray writing, diffusion, ion implantation, cleaning, polishing, planarization, or packaging.

[170] In some embodiments, the methods fabricating a micro-device or micro-detector include depositing various materials on a substrate and, in the interims of depositing every two materials, patterning some or all of the deposited materials by a microelectronic process. The micro-device or micro-detector thus fabricated is capable of measuring at the microscopic level an electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, electro-mechanical, electro-chemical, electro-chemical-mechanical, bio-chemical, bio-physical, bio-physical-chemical, physical-chemical, bio-mechanical, bio-electro-mechanical, bio-electro-chemical, bio-electro-chemical-mechanical, physical, or mechanical property of a biologic subject with which the micro-device or micro-detector is to contact.

[171] The electrical property may include surface charge, surface potential, resting potential, action potential, electrical voltage, electrical current, electrical field distribution, electrical charge distribution, electric dipole, electric quadruple, three-dimensional electrical or charge cloud distribution, electrical properties at telomere of DNA and chromosome, dynamic changes in electrical properties, dynamic changes in potential, dynamic changes in surface charge, dynamic changes in current, dynamic changes in electrical field, dynamic changes in electrical voltage, dynamic changes in electrical distribution, dynamic changes in electronic cloud distribution, or impedance; the thermal property may include temperature, or vibrational frequency of biological item or molecules; the optical property may include optical absorption, optical transmission, optical reflection, optical-electrical property, brightness, or fluorescent emission; the chemical property may include pH value, chemical reaction, bio-chemical reaction, bio-electro-chemical reaction, reaction speed, reaction energy, speed of reaction, oxygen concentration, oxygen consumption rate, ionic strength, catalytic behavior, or bonding strength; the physical property may include density or geometric size; the acoustic property may include frequency, speed of acoustic waves, acoustic frequency and intensity spectrum distribution, acoustic intensity,

acoustical absorption, or acoustical resonance; and the mechanical property may include internal pressure, hardness, shear strength, elongation strength, fracture stress, adhesion, mechanical resonance frequency, elasticity, plasticity, or compressibility.

[172] In some other embodiments, the fabrication methods each include the steps of:

providing a substrate;

depositing a first material onto the substrate;

depositing a second material onto the first material and then patterning the second material by a microelectronic process; and

repeating the second step at least once with a material that can be the same as or different from any of the previously deposited materials.

[173] The methods may further include removal of a stack of multiple layers of materials by wet etch, dry etch, or vapor etch.

[174] In these methods, the materials used in the repeated steps can be the same as or different from the first or second material. At least one of the materials used in fabricating the micro-device is a biological material, a polymer, a piezo-electric material, a semiconductor material, an electrically insulating material, or an electrically conductive material.

[175] The micro-device thus fabricated can have one or more characters or functions of the following: moving in any direction; being capable of sorting, probing, measuring, communicating, or modifying a biological subject.

[176] Still, the methods may further include one or more of the following steps:

depositing a third material on the second material and then patterning the third material by a planarization process;

depositing a fourth material on the third material and patterning the fourth material by microelectronic processes;

patterning the third material using a microelectronic process with the fourth material serving as a hardmask;

coupling two devices that are thus fabricated and symmetric to form a detecting device with channels or to form a probing device capable to sending a signal to a biological subject and result in a response;

integrating three or more micro-devices to give an enhanced device with an array of the channels.

[177] Still further, the methods may include the steps of:

before depositing the second material, patterning the first material by a microelectronic process to give rise to at least one patterned residual and leaving part of the substrate surface uncovered by the first material;

creating an opening in the second material to expose part of the patterned residual of the first material; and

filling up the opening in the second material with a third material; wherein the second material is a non-electrically conductive material.

[178] The micro-device thus obtained may include a micro-trench (or channel) having sidewalls and a probe embedded in the micro-trench or channel's sidewalls. Each channel's entrance may be optionally bell-mouthed; the shape of each channel's cross-section is rectangle, ellipse, circle, or polygon. The dimension of the micro-trench may range from about 0.1  $\mu\text{m}$  to about 500  $\mu\text{m}$ .

[179] The micro-trench of the micro-device can be capped with a flat panel or coupling two micro-trenches to form one or more channels. The flat panel may comprise silicon, SiGe, SiO<sub>2</sub>, Al<sub>2</sub>O<sub>3</sub>, acrylate polymer, AgInSbTe, synthetic alexandrite, arsenic triselenide, arsenic trisulfide, barium fluoride, CR-39, cadmium selenide, caesium cadmium chloride, calcite, calcium fluoride, chalcogenide glass, gallium phosphide, GeSbTe, germanium, germanium dioxide, glass code, hydrogen silsesquioxane, Iceland spar, liquid crystal, lithium fluoride, lumicera, METATOY, magnesium fluoride, magnesium oxide, negative index metamaterials, neutron super mirror, phosphor, picarin, poly(methyl methacrylate), polycarbonate, potassium bromide, sapphire, scotophor, spectralon, speculum metal, split-ring resonator, strontium fluoride, yttrium aluminum garnet, yttrium lithium fluoride, yttrium orthovanadate, ZBLAN, zinc selenide, or zinc sulfide.

[180] In some other embodiments, the methods for fabricating a micro-device or micro-detector of this invention include the steps of:

providing a substrate;

sequentially depositing a first material and a second material as two layers onto the substrate to form a material stack;

patterning the second material by microelectronic processes to form a first desired feature; depositing a third material onto the material stack to cover the second material and optionally the first material;

optionally patterning the first and third materials by microelectronic processes to form a second desired feature; and

optionally depositing a fourth material onto the material stack.

**[181]** They may further include:

fabricating at least an additional component onto the substrate before sequentially depositing the first material and the second material as layers onto the substrate, wherein the additional component comprises a data storage component, a signal processing component, a memory storage component, a signal receiver, a signal transmitting component, a logic processing component, or an RF component; or

fabricating at least an integrated circuit onto the substrate before sequentially depositing the first material and the second material as layers onto the substrate, wherein the integrated circuit comprises a data storage circuit, a signal processing circuit, a memory storage circuit, a signal transmitting circuit, a sensor, or a logic processing circuit.

**[182]** In some instances, the first material and the third material are the same; the first material and the third material are electrically insulating (e.g., an oxide, doped oxide, silicon nitride, or a polymer); the first material and the fourth material are the same; the first material and the fourth material are electronically insulating; the second material or the third material is an electrical conductive material, a magnetic material, an electro-magnetic material, an optical material, a thermal sensitive material, a pressure sensitive material, an ion emission sensitive material, or a piezo-electric material.

**[183]** In some other instances, the second material is an electrically conductive material, a piezo-electric material, a semiconductor material, a thermal sensitive material, a magnetic material, a pressure sensitive material, a mechanical stress sensitive material, an ion emission sensitive material, an optical material, or a combination thereof. For example, it may include copper, aluminum, tungsten, gold, silver, the alloys thereof, or glass.

**[184]** The detector thus fabricated may be capable of probing or disturbing a biological subject to be measured; and it may have a recessed form, or a trench form in the layers of the third and first materials. In the detector, the second material may be aligned with the wall of the trench form in the layers of the third and first materials.

**[185]** In some instances, the methods may further include the step of capping the top of the material stack to cover the third material and form an enclosed trench. As an example, the



capping may include sealing or capping the top of the material stack with a layer of material, an imaging device, a camera, a viewing station, an acoustic detector, a thermal detector, an ion emission detector, or a thermal recorder onto the material stack.

**[186]** In some other instances, the methods may still further include one or more of the following steps:

- fabricating at least one integrated circuit onto the substrate before sequentially depositing the first material and the second material as layers onto the substrate, wherein the circuit comprises a data storage circuit, a signal processing circuit, a memory storage circuit, a sensor, a signal transmitting circuit, a sensor, or a logic processing circuit;

- planarizing the third material using a chemical mechanical polishing process or an etch back process after depositing the third material onto the material stack and before patterning the first and the third materials;

- planarizing the third material using a chemical mechanical polishing process or an etch back process to form a detector capable of detecting a response signal from the biological subject;

- patterning the fourth material to form a hole at a selected location after depositing the fourth material onto the material stack;

- removing the third material from the material stack by wet or vapor etch to form a detection chamber between the fourth material and the substrate;

- removing the first material from the material stack by wet or vapor etch to form a channel;

- capping the top of the material stack to form an enclosed trench or channel;

- sealing or capping the top of the material stack with a fifth material to form an enclosed channel capable of observing and recording the biological subject; or

- sealing or capping the top of the material stack with an imaging device, a detector, an optical sensor, a camera, a viewing station, an acoustic detector, a thermal detector, an electrical detector, an ion emission detector, or a thermal recorder onto the material stack.

**[187]** In still some embodiments, the methods for fabricating a micro-device of this invention include the steps of:

- providing a substrate;

- sequentially depositing a first material and a second material as layers onto the substrate to form a material stack;

patterning the second material by microelectronic processes to form at least a portion of a recessed area in the second material (e.g., to form a probe, a detector or an integrated unit with sub-component for detection);

depositing a third material onto the material stack to cover the second material, and removing the portion of the third material above the second material by etch back or polishing process;

patterning the third material by lithography and etch processes to remove at least a portion of the third material;

depositing a fourth material onto the material stack to cover the second and third material, and removing the portion of the fourth material above the second and third material by etch back or polishing process; and

optionally, depositing a fifth material and repeating the above process sequence used for the third material.

[188] In some instances, they may further include one or more steps of the following:

fabricating at least an additional component onto the substrate before sequentially depositing the first material and the second material as layers onto the substrate, wherein the additional component comprises a data storage component, a signal processing component, a memory storage component, a signal transmitting component, a logic processing component, or an RF component; and

fabricating at least one integrated circuit onto the substrate before sequentially depositing the first material and the second material as layers onto the substrate, wherein the integrated circuit comprises a data storage circuit, a signal processing circuit, a memory storage circuit, a signal transmitting circuit, a sensor, or a logic processing circuit.

[189] The substrate can be silicon, polysilicon, silicon nitride, or polymer material; the first material is oxide, doped oxide, silicon nitride, or polymer material. The second and the fourth materials can be the same (e.g., both being an electrical conductive material, semiconductor material, piezo-electric material, thermal sensitive material, an ion emission sensitive material, a magnetic material, a pressure sensitive material, a mechanical stress sensitive material, or optical material). Specific examples of suitable materials include aluminum, copper, tungsten, gold, silver, the alloys thereof, quartz, berlinite, gallium, orthophosphate, GaPO<sub>4</sub>, tourmalines,

ceramics, barium, titanate,  $\text{BaTiO}_3$ , lead zirconate, titanate PZT, zinc oxide, aluminum nitride, and polyvinylidene fluoride.

[190] In still a further aspect, the invention provides piezo-electric micro-detectors. Each of these micro-detectors comprises a substrate, a piezo-electric material, an electronically conductive material, a material that is neither piezo-electric nor electronically conductive, wherein the piezo-electric material is placed between the electronically conductive material and the material that is neither piezo-electric nor electronically conductive, and the material that is neither piezo-electric nor electronically conductive is placed between the substrate and the piezo-electric material, wherein the micro-detector is capable of detecting, at the microscopic level, a property of an object to be detected.

[191] In some embodiments, a portion of the piezo-electric material is projecting out of the other part of the micro-detector and is not supported or surrounded by the other materials in the micro-detector. The projecting piezo-electric material can be, e.g., in the shape of a layer or a stick and can have a minimum length of one angstrom.

[192] In some embodiments, the projecting piezo-electric material has an axis that is essentially parallel to the surface of the substrate.

[193] The projecting piezo-electric material is capable of detecting, at the microscopic level, a property of the object to be detected. The property can be an electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, electro-mechanical, electro-chemical, electro-chemical-mechanical, bio-chemical, bio-mechanical, bio-electro-mechanical, bio-electro-chemical, bio-electro-chemical-mechanical, physical, or mechanical property of the object to be detected. For example, the electrical property can be surface charge, surface potential, resting potential, electrical current, electrical field distribution, electric dipole, electric quadrupole, three-dimensional electrical or charge cloud distribution, electrical properties at telomere of DNA and chromosome, or impedance; the thermal property can be temperature, or vibrational frequency of biological item or molecules; the optical property can be optical absorption, optical transmission, optical reflection, optical-electrical property, brightness, or fluorescent emission; the chemical property can be pH value, chemical reaction, bio-chemical reaction, bio-electro-chemical reaction, reaction speed, reaction energy, oxygen concentration, oxygen consumption rate, ionic strength, catalytic behavior, or bonding strength; the physical property can be density or geometric size; the acoustic property can be frequency, speed of acoustic waves, acoustic

frequency and intensity spectrum distribution, acoustic intensity, acoustical absorption, or acoustical resonance; and the mechanical property can be internal pressure, hardness, shear strength, elongation strength, fracture stress, adhesion, mechanical resonance frequency, elasticity, plasticity, or compressibility.

[194] In some embodiments, the electronically conductive material is connected to the piezo-electric material and capable of delivery signal from the piezo-electric material to a measuring or recording device.

[195] In some embodiments, the piezo-electric material expands when it detects an electric property from the object to be tested, or the piezo-electric material gives rise to an electric currency when it detects a mechanical stress.

[196] The piezo-electric material comprises a crystal, a ceramics, zinc oxide, aluminum nitride, polyvinylidene fluoride, lithium tantalite, lanthanum gallium silicate, or potassium sodium tartrate. Examples of suitable crystals include tourmaline, quartz, Rochelle salt, Berlinite, and gallium orthophosphate; while examples of suitable ceramics include BaTiO<sub>3</sub>, KNbO<sub>3</sub>, Ba<sub>2</sub>NaNb<sub>5</sub>O<sub>15</sub>, LiNbO<sub>3</sub>, SrTiO<sub>3</sub>, Pb(ZrTi)O<sub>3</sub>, Pb<sub>2</sub>KNb<sub>5</sub>O<sub>15</sub>, LiTaO<sub>3</sub>, BiFeO<sub>3</sub>, and Na<sub>x</sub>WO<sub>3</sub>.

[197] In some embodiments, the electronically conductive material comprises an electric conductor or semiconductor. The electric conductor may include a metal or graphite, and the semiconductor may include a crystal or a ceramics.

[198] In some embodiments, the material that is neither piezo-electric nor electronically conductive, is a wet etching stop material.

[199] The piezo-electric micro-detectors described above can be fabricated by a process comprising microelectronics technologies. Accordingly, the invention further provides methods for fabricating a piezo-electric micro-detector. Each method includes the following steps:

- providing a substrate;
- depositing a first material onto the substrate;
- optionally planarizing the first material;
- depositing a second material onto the optionally planarized first material; wherein the second material is neither piezo-electric nor electrically conductive;
- patterning the second material to create at least one recessed area in the second material;

depositing a third, piezo-electric material on the second material to fill its recessed area in the second material and cover the second material;

patterning the third, piezo-electric material to create at least one recessed area in the piezo-electric material;

depositing a fourth material onto the third, piezo-electric material to fill its recessed area and optionally to cover the third, piezo-electric material; wherein the fourth material can be the same as or different from the second material, and the fourth material is neither piezo-electric nor electrically conductive;

optionally patterning the fourth material to give it a certain configuration;

optionally depositing a fifth material onto the optionally patterned fourth material, wherein the fifth material can be the same as or different from the second material, the fifth material is different from the fourth material, and the fifth material is neither piezo-electric nor electrically conductive;

patterning the fourth material and optional fifth material to create an opening that exposes the third, piezo-electric material;

depositing a sixth, electrically conductive material to fill the opening in the fourth material and optional fifth material, and optionally covering part of the fifth material; and

patterning all the materials above the substrate to expose all the materials, and

patterning the second and fourth materials sandwiching the piezo-electric material to expose at least part of the piezo-electric material.

**[200]** If desired, additional material layers (e.g., seventh material layer, or seventh and eighth material layers) can be deposited, patterned, cleaned, or planarized to form additional structures with more features, functionalities, and complexities.

**[201]** In some embodiments, the second material or the fifth material is a wet etch stop material.

**[202]** In some embodiments, the patterning process comprises lithography and etching.

**[203]** In some embodiments, a portion of the patterned piezo-electric material is projecting from the other material(s) with which it is connected, and the projecting piezo-electric material is in the shape of a layer or a stick. For example, the projecting piezo-electric material has an axis that is essentially parallel to the surface of the substrate.

**[204]** Yet in another aspect, the invention provides methods for detecting, at the microscopic level, a mechanical or electric property of a biological subject. Each method includes the steps

of: providing a piezo-electric micro-detector comprising a substrate, a piezo-electric material, an electronically conductive material, a material that is neither piezo-electric nor electronically conductive, wherein the piezo-electric material is placed between the electronically conductive material and the material that is neither piezo-electric nor electronically conductive, and the material that is neither piezo-electric nor electronically conductive is placed between the substrate and the piezo-electric material; contacting the piezo-electric micro-detector with the biological subject to be detected, wherein the piezo-electric micro-detector detects the mechanical or electric property of the biological subject upon the contact and converts the mechanical or electric property to generate an electric or mechanical property, and transferring the electric or mechanical property thus generated through the electrically conductive material to a recording device.

**[205]** As used herein, the term “or” is meant to include both “and” and “or”. It may be interchanged with “and/or.”

**[206]** As used herein, a singular noun is meant to include its plural meaning. For instance, a micro device can mean either a single micro device or multiple micro-devices.

**[207]** As used herein, the term “patterning” means shaping a material into a certain physical form or pattern, including a plane (in which case “patterning” would also mean “planarization.”)

**[208]** As used herein, the term “a biological subject” or “a biological sample” for analysis or test or diagnosis refers to the subject to be analyzed by a disease detection apparatus. It can be a single cell, a single biological molecular (e.g., DNA, RNA, or protein), a single biological subject (e.g., a single cell or virus), any other sufficiently small unit or fundamental biological composition, or a sample of a subject’s organ or tissue that may having a disease or disorder.

**[209]** As used herein, the term “disease” is interchangeable with the term “disorder” and generally refers to any abnormal microscopic property or condition (e.g., a physical condition) of a biological subject (e.g., a mammal or biological species).

**[210]** As used herein, the term “subject” generally refers to a mammal, e.g., a human person.

**[211]** As used herein, the term “microscopic level” refers to the subject being analyzed by the disease detection apparatus of this invention is of a microscopic nature and can be a single cell, a single biological molecular (e.g., DNA, RNA, or protein), a single biological subject (e.g., a single cell or virus), and other sufficiently small unit or fundamental biological composition.

[212] As used herein, a “micro-device” or “micro device” can be any of a wide range of materials, properties, shapes, and degree of complexity and integration. The term has a general meaning for an application from a single material to a very complex device comprising multiple materials with multiple sub units and multiple functions. The complexity contemplated in the present invention ranges from a very small, single particle with a set of desired properties to a fairly complicated, integrated unit with various functional units contained therein. For example, a simple micro-device could be a single spherical article of manufacture of a diameter as small as 100 angstroms with a desired hardness, a desired surface charge, or a desired organic chemistry absorbed on its surface. A more complex micro device could be a 1 millimeter device with a sensor, a simple calculator, a memory unit, a logic unit, and a cutter all integrated onto it. In the former case, the particle can be formed via a fumed or colloidal precipitation process, while the device with various components integrated onto it can be fabricated using various integrated circuit manufacturing processes.

[213] A micro device used in the present invention can range in size (e.g., diameter) from on the order of about 1 angstrom to on the order of about 5 millimeters. For instance, a micro-device ranging in size from on the order of about 10 angstroms to on the order of 100 microns can be used in this invention for targeting biological molecules, entities or compositions of small sizes such as cell structures, DNA, and bacteria. Or, a micro-device ranging in size from on the order of about one micron to the order of about 5 millimeters can be used in the present invention for targeting relatively large biological matters such as a portion of a human organ. As an example, a simple micro device defined in the present application can be a single particle of a diameter less than 100 angstroms, with desired surface properties (e.g., with surface charge or a chemical coating) for preferential absorption or adsorption into a targeted type of cell.

[214] The present invention further provides an apparatus for detecting a disease in a biological subject, which comprises a pre-processing unit, a probing and detecting unit, a signal processing unit, and a disposal processing unit.

[215] In some embodiments of the apparatus, the pre-processing unit includes a sample filtration unit, a recharging unit, a constant pressure delivery unit, and a sample pre-probing disturbing unit. This increases the contraction ratio of certain substance of interests (such as cancer cells) and therefore makes the apparatus more effective and efficient in detecting the targeted biological subject (such as cancer cells).

[216] In some embodiments, the filtration unit can filter off unwanted substance by physical filtration (e.g., based on the electronic charge or size of the substance) or separation by chemical reaction (thereby completely removing the undesirable substances), biochemical reaction, electro-mechanical reaction, electro-chemical reaction, or biological reaction.

[217] In some embodiments, the sample filtration unit can include an entrance channel, a disturbing fluid channel, an accelerating chamber, and a slit. The slit and the interior walls of the entrance channel define two channels (e.g., a top channel and a bottom channel) wherein the biological subject can be separated due to the differences in its property (e.g., electric or physical property).

[218] In some embodiments, a bio-compatible fluid can be injected into the disturbing fluid channel to separate the biological subject. For example, the bio-compatible fluid can be injected from the entrance of the disturbing fluid channel and deliver to an opening in the entrance channel wall. The bio-compatible fluid can be liquid or semi-liquid, and can include saline, water, plasma, an oxygen-rich liquid, or any combination thereof.

[219] In some other embodiments, the angle between the entrance channel and the disturbing fluid channel ranges from about 0° to about 180° (e.g., from about 30° to about 150°, from about 60° to about 120°, or from about 75° to about 105°, or about 90°).

[220] In some other embodiments, the width of each channel can range from about 1 nm to about 1 mm (e.g., from about 2 nm to about 0.6 mm or from about 10 nm to about 0.2 mm).

[221] In some other embodiments, at least one of the channels comprises one probing device attached to the channel's sidewall, and the probing device is capable of measuring at the microscopic level an electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, electro-mechanical, electro-chemical, electro-chemical-mechanical, bio-chemical, bio-mechanical, bio-electro-mechanical, bio-electro-chemical, bio-electro-chemical-mechanical, physical or mechanical property of the biological subject. Examples of the electrical property include surface charge, surface potential, resting potential, electrical current, electrical field distribution, electric dipole, electric quadruple, three-dimensional electrical or charge cloud distribution, electrical properties at telomere of DNA and chromosome, and impedance. Examples of the thermal property include temperature and vibrational frequency. Examples of the optical property include optical absorption, optical transmission, optical reflection, optical-electrical property, brightness, and fluorescent emission. Examples of the chemical property



include pH value, chemical reaction, bio-chemical reaction, bio-electro-chemical reaction, reaction speed, reaction energy, speed of reaction, oxygen concentration, oxygen consumption rate, ionic strength, catalytic behavior, and bonding strength. Examples of the physical property include density and geometric size. Examples of the acoustic property include frequency, speed of acoustic waves, acoustic frequency and intensity spectrum distribution, acoustic intensity, acoustical absorption, and acoustical resonance. Examples of the mechanical property include internal pressure, hardness, shear strength, elongation strength, fracture stress, adhesion, mechanical resonance frequency, elasticity, plasticity, and compressibility.

**[222]** In some embodiments, at least one of the channels comprises at least two probing devices attached to the channel's sidewalls, and the probing devices are capable of measuring at the microscopic level an electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, electro-mechanical, electro-chemical, electro-chemical-mechanical, bio-chemical, bio-mechanical, bio-electro-mechanical, bio-electro-chemical, bio-electro-chemical-mechanical, physical or mechanical property of the biological subject. The probing devices measure the same or different properties at the same time or different times.

**[223]** The two or more probing devices can be placed with a desired distance between each other (at least 10 angstroms). Examples of the desired distance include from about 10 nm to about 100 mm, from about 100 nm to about 10 mm, from about 1 mm to about 10 mm.

**[224]** In some embodiments, the micro-device of this invention comprises at least one probe and at least one detector. The probe can be utilized to launch a probing signal to probe the biological subject, and the detector can detect the biological subject's response (signal) to the probing signal. As an example, a micro-device with at least one acoustic probe (such as an acoustic transducer or microphone) and at least one detector (such as an acoustic signal receiver) is utilized for biological subject detection, wherein the acoustic probe and detector may be constructed with, among others, one or more piezo-electric materials. In this example, an acoustic signal is first launched, and scanned across its frequency range (e.g., from sub Hz to over MHz) by the probe. The response signal to the launched acoustic signal by the probe is then collected by the detector, and subsequently recorded, amplified (e.g., by a lock-in amplifier), and analyzed. The response signal contains characteristic information of a biological subject that is tested. For example, depending on certain properties of the tested biological subject, the detected acoustic resonant frequency, intensity, frequency versus intensity spectrum, or intensity

distribution by the detector may indicate characteristic information about the tested biological subject. Such information includes density, density distribution, absorption properties, shape, surface properties, and other static and dynamic properties of the biological subject.

[225] In some embodiments, the sample filtration unit can include an entrance channel, a biocompatible filter, an exit channel, or any combination thereof. When a biological subject passes through the entrance channel toward the exit channel, the biological subject of a size larger than the filter hole will be blocked against the exit channel, resulting in the smaller biological subject being flushed out through the exit channel. A biocompatible fluid is injected from the exit to carry the biological subject accumulated around the filter and flush out from the channel. The biological subject with a large size is then filtered for further analysis and detection in the detecting component or unit of the apparatus.

[226] In some embodiments, the sample pre-probing disturbing unit can include one micro-device with a channel, a slit located inside the channel, and optionally two plates outside the channel. The two plates can apply a signal, e.g., an electronic voltage, to the biological subject traveling through the channel and separates it based on the electronic charge the biological subject carries. The slit and the interior channels of the channel define two channels where the separated biological subjects enter and optionally are detected for its property at the microscopic level.

[227] In some embodiments, the sample pre-probing disturbing unit applies to the biological subject an electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, electro-mechanical, electro-chemical, electro-chemical-mechanical, bio-chemical, bio-mechanical, bio-electro-mechanical, bio-electro-chemical, bio-electro-chemical-mechanical, physical or mechanical signal. The signal can be applied, e.g., with the two plates described above or in other means (depending on the nature of the signal). The signal as applied can be pulsed or constant.

[228] In some embodiments, the recharging unit recharges nutrient or respiring gas (such as oxygen) to the biological subject. Alternatively, it can also clean up the metabolite of the biological subject. With such a recharging unit, the life stability of the biological subject in the sample is sustained and its use is extended, thereby giving more accurate and reliable detecting results. Examples of nutrient include biocompatible strong or weak electrolyte, amino acid, mineral, ions, oxygen, oxygen-rich liquid, intravenous drip, glucose, and protein. Another

example of the nutrient is a solution containing nano-particles that can be selectively absorbed by certain biological subjects (e.g., cells or viruses).

[229] The recharging system can be separate from and outside of the other components of the apparatus. Alternatively, it can also be installed within one of the other components, e.g., the probing and detecting unit or the disposal processing unit.

[230] In some other embodiments, the signal processing unit comprises an amplifier (e.g., a lock-in amplifier), an A/D (alternate/direct electric current or analog to digital) converter, a micro-computer, a manipulator, a display, and network connections.

[231] In some instance, the signal processing unit collects more than one signal (i.e., multiple signals), and the multiple signals can be integrated to cancel out noise or to enhance the signal to noise ratio. The multiple signals can be signals from multiple locations or from multiple times.

[232] Biological subjects that can be detected by the apparatus include, e.g., blood, urine, saliva, tear, and sweat. The detection results can indicate the possible occurrence or presence of a disease (e.g., one in its early stage) in the biological subject.

[233] As used herein, the term “absorption” typically means a physical bonding between the surface and the material attached to it (absorbed onto it, in this case). On the other hand, the word “adsorption” generally means a stronger, chemical bonding between the two. These properties are very important for the present invention as they can be effectively used for targeted attachment by desired micro devices for measurement at the microscopic level.

[234] As used herein, the term “contact” (as in “the first micro-device *contacts* a biologic entity”) is meant to include both “direct” (or physical) contact and “non-direct” (or indirect or non-physical) contact. When two subjects are in “direct” contact, there is generally no measurable space or distance between the contact points of these two subjects; whereas when they are in “indirect” contact, there is a measurable space or distance between the contact points of these two subjects.

[235] As used herein, the term “probe” or “probing,” in addition to its dictionary meaning, could mean applying a signal (e.g., an electrical, acoustic, magnetic or thermal signal) to a subject and thereby stimulating the subject and causing it to have some kind of intrinsic response.

[236] As used herein, the term “electric property” refers to surface charge, surface potential, electrical field, charge distribution, electrical field distribution, resting potential, action potential, or impedance of a biological subject to be analyzed.

[237] As used herein, the term “magnetic property” refers to diamagnetic, paramagnetic, or ferromagnetic.

[238] As used herein, the term “electromagnetic property” refers to property that has both electric and magnetic dimensions.

[239] As used herein, the term “thermal property” refers to temperature, freezing point, melting point, evaporation temperature, glass transition temperature, or thermal conductivity.

[240] As used herein, the term “optical property” refers to reflection, optical absorption, optical scattering, wave length dependent properties, color, luster, brilliance, scintillation, or dispersion.

[241] As used herein, the term “acoustical property” refers to the characteristics found within a structure that determine the quality of sound in its relevance to hearing. It can generally be measured by the acoustic absorption coefficient. See, e.g., United States Patent No. 3,915,016, for means and methods for determining an acoustical property of a material; T.J. Cox et al., *Acoustic Absorbers and Diffusers*, 2004, Spon Press.

[242] As used herein, the term “biological property” is meant to generally include chemical and physical properties of a biological subject.

[243] As used herein, the term “chemical property” refers to pH value, ionic strength, or bonding strength within the biological sample.

[244] As used herein, the term “physical property” refers to any measurable property the value of which describes a physical system’s state at any given moment in time. The physical properties of a biological sample may include, but are not limited to absorption, albedo, area, brittleness, boiling point, capacitance, color, concentration, density, dielectric, electric charge, electrical conductivity, electrical impedance, electric field, electric potential, emission, flow rate, fluidity, frequency, inductance, intrinsic impedance, intensity, irradiance, luminance, luster, malleability, magnetic field, magnetic flux, mass, melting point, momentum, permeability, permittivity, pressure, radiance, solubility, specific heat, strength, temperature, tension, thermal conductivity, velocity, viscosity, volume, and wave impedance.

[245] As used herein, the term “mechanical property” refers to strength, hardness, toughness, elasticity, plasticity, brittleness, ductility, shear strength, elongation strength, fracture stress, or adhesion of the biological sample.

[246] As used herein, the term “conductive material” (or its equivalent “electric conductor”) is a material which contains movable electric charges. A conductive material can be a metal (e.g.,

copper, silver, or gold) or non-metallic (e.g., graphite, solutions of salts, plasmas, or conductive polymers). In metallic conductors, such as copper or aluminum, the movable charged particles are electrons (see electrical conduction). Positive charges may also be mobile in the form of atoms in a lattice that are missing electrons (known as holes), or in the form of ions, such as in the electrolyte of a battery.

[247] As used herein, the term “electrically insulating material” (also known as “insulator” or “dielectric”) refers to a material that resists the flow of electric current. An insulating material has atoms with tightly bonded valence electrons. Examples of electrically insulating materials include glass or organic polymers (e.g., rubber, plastics, or Teflon).

[248] As used herein, the term “semiconductor” (also known as “semiconducting material”) refers to a material with electrical conductivity due to electron flow (as opposed to ionic conductivity) intermediate in magnitude between that of a conductor and an insulator. Examples of inorganic semiconductors include silicon, silicon-based materials, and germanium. Examples of organic semiconductors include such aromatic hydrocarbons as the polycyclic aromatic compounds pentacene, anthracene, and rubrene; and polymeric organic semiconductors such as poly(3-hexylthiophene), poly(p-phenylene vinylene), polyacetylene and its derivatives. Semiconducting materials can be crystalline solids (e.g., silicon), amorphous (e.g., hydrogenated amorphous silicon and mixtures of arsenic, selenium and tellurium in a variety of proportions), or even liquid.

[249] As used herein, the term “biological material” has the same meaning of “biomaterial” as understood by a person skilled in the art. Without limiting its meaning, biological materials or biomaterials can generally be produced either in nature or synthesized in the laboratory using a variety of chemical approaches utilizing organic compounds (e.g., small organic molecules or polymers) or inorganic compounds (e.g., metallic components or ceramics). They generally can be used or adapted for a medical application, and thus comprise whole or part of a living structure or biomedical device which performs, augments, or replaces a natural function. Such functions may be benign, like being used for a heart valve, or may be bioactive with a more interactive functionality such as hydroxyl-apatite coated hip implants. Biomaterials can also be used every day in dental applications, surgery, and drug delivery. For instance, a construct with impregnated pharmaceutical products can be placed into the body, which permits the prolonged release of a drug over an extended period of time. A biomaterial may also be an autograft,

allograft, or xenograft which can be used as a transplant material. All these materials that have found applications in other medical or biomedical fields can also be used in the present invention.

[250] As used herein, the term “microelectronic technology or process” generally encompasses the technologies or processes used for fabricating micro-electronic and optical-electronic components. Examples include lithography, etching (e.g., wet etching, dry etching, or vapor etching), oxidation, diffusion, implantation, annealing, film deposition, cleaning, direct-writing, polishing, planarization (e.g., by chemical mechanical polishing), epitaxial growth, metallization, process integration, simulation, or any combinations thereof. Additional descriptions on microelectronic technologies or processes can be found in, e.g., Jaeger, Introduction to Microelectronic Fabrication, 2<sup>nd</sup> Ed., Prentice Hall, 2002; Ralph E. Williams, Modern GaAs Processing Methods, 2<sup>nd</sup> Ed., Artech House, 1990; Robert F. Pierret, Advanced Semiconductor Fundamentals, 2<sup>nd</sup> Ed., Prentice Hall, 2002; S. Campbell, The Science and Engineering of Microelectronic Fabrication, 2<sup>nd</sup> Ed., Oxford University Press, 2001.

[251] As used herein, the term “selective” as included in, e.g., “patterning material B using a microelectronics process *selective* to material A”, means that the microelectronics process is effective on material B but not on material A, or is substantially more effective on material B than on material A (e.g., resulting in a much higher removal rate on material B than on material A and thus removing much more material B than material A).

[252] As used herein, the term “carbon nano-tube” generally refers to as allotropes of carbon with a cylindrical nanostructure. See, e.g., Carbon Nanotube Science, by P.J.F. Harris, Cambridge University Press, 2009, for more details about carbon nano-tubes.

[253] Through the use of a single micro-device or a combination of micro-devices integrated into a disease detection apparatus, the disease detection capabilities can be significantly improved in terms of sensitivity, specificity, speed, cost, apparatus size, functionality, and ease of use, along with reduced invasiveness and side-effects. A large number of micro-device types capable of measuring a wide range of microscopic properties of biological sample for disease detection can be integrated and fabricated into a single detection apparatus using micro-fabrication technologies and novel process flows disclosed herein. While for the purposes of demonstration and illustration, a few novel, detailed examples have been shown herein on how microelectronics or nano-fabrication techniques and associated process flows can be utilized to

fabricate highly sensitive, multi-functional, and miniaturized detection devices, the principle and general approaches of employing microelectronics and nano-fabrication technologies in the design and fabrication of high performance detection devices have been contemplated and taught, which can and should be expanded to various combination of fabrication processes including but not limited to thin film deposition, patterning (lithography and etch), planarization (including chemical mechanical polishing), ion implantation, diffusion, cleaning, various materials, and various process sequences and flows and combinations thereof.

#### **Brief Descriptions of the Figures**

[254] Figure 1 (a) is a perspective illustration of a disease detection apparatus of this invention in which a biological sample placed in it or moving through it can be tested. Figure 1(b) and Figure 1(c) illustrate the apparatus which comprises multiple individual detection micro-devices.

[255] Figure 2 (a) is a perspective, cross-sectional illustration of a disease detection apparatus of this invention with multiple micro-devices. A biological sample is placed in the apparatus or moving through it while one or more microscopic properties of this biological sample are measured with the multiple micro-devices. Figures 2(b)-2(l) are perspective illustration of the novel process flow for fabricating the micro-device. Figures 2(m)-2(n) are cross-sectional views of an apparatus comprising multiple individual micro-devices.

[256] Figure 3 is a perspective, cross-sectional illustration of a disease detection apparatus of this invention with multiple micro-devices of different detection probes. A biological sample is placed in the apparatus or moving through it and one or more microscopic properties of this sample are measured with the multiple micro-device.

[257] Figure 4 is a perspective illustration of a disease detection apparatus of this invention. It includes two slabs separated by a narrow spacing with a biological sample to be analyzed placed between the slabs, with multiple micro-devices placed at the inner surfaces of the slabs to measure one or more desired parameters of the sample at microscopic levels.

[258] Figure 5 illustrates a novel process flow for fabricating a disease detection apparatus of this invention utilizing microelectronics technologies.

[259] Figure 6 is a perspective illustration of a disease detection apparatus fabricated by a method of this invention. The apparatus is capable of probing a single cell and measuring its microscopic properties.

[260] Figure 7 is a perspective, cross-sectional illustration of a disease detection apparatus of this invention with multiple micro-devices placed at a desired distance for time of flight measurements with enhanced sensitivity, specificity, and speed, including time dependent or dynamic information.

[261] Figure 8 is a perspective illustration of a novel set of microscopic probes, included in a disease detection apparatus of this invention, for detecting various electronic or magnetic states, configurations, or other properties of a biological sample (e.g., a cell, a DNA or RNA molecule, a telomere of DNA or chromosome, a virus, or a tissue sample).

[262] Figure 9 is a perspective illustration of a novel four-point probe, included in a disease detection apparatus of this invention, for detecting weak electronic signal in a biological sample (e.g., a cell, a DNA or RNA molecule, a telomere of DNA or chromosome, a virus, or a tissue sample).

[263] Figure 10 illustrates a novel process flow for fabricating a class of micro-devices capable of trapping, sorting, probing, measuring, and modifying a biological subject (e.g., a cell, a DNA or RNA molecule, a telomere of DNA or chromosome, a virus, or a tissue sample) at the microscopic level and in a three-dimensional space.

[264] Figure 11 illustrates a novel process flow for fabricating a class of micro-devices capable of measuring physical properties of a biological subject (e.g., a cell, a DNA or RNA molecule, a telomere of DNA or chromosome, a virus, or a tissue sample) such as mechanical properties (e.g., hardness, shear strength, elongation strength, fracture stress) and other properties related to cell membrane.

[265] Figure 12 illustrates how a micro-device with two micro-probes capable of moving in opposite directions when a force is applied can be utilized to probe properties of a biological subject (e.g., mechanical properties of a cell membrane).

[266] Figure 13 illustrates a novel time of flight detection arrangement for disease detection applications, in which both clock signal generator and signal detection probes are used, along with schematically recorded clock signal, probe signal (signal detected by probing micro-device), and processed and enhanced signal after signal filtering using phase lock-in processing technique to enhance the detected signal.

[267] Figure 14 illustrates yet another time of flight disease detection arrangement in which clock signal generators, a probe signal generator, and signal detection probes are used, along



with schematically recorded clock signal, detected signal by probing micro-device in response to probe signal, and processed and enhanced signal after signal filtering using phase lock-in processing technique to enhance the detected signal showing detected response signal as a function of time (response signal delays over time in this case).

[268] Figure 15 illustrates another novel time of flight disease detection application, in which a set of novel micro-filters are utilized to detect biological subjects via separation of biological subjects by their various, specific properties such as size, weight, shape, electrical properties, or surface properties.

[269] Figure 16 illustrates a fluid delivery system, which is a pretreatment part for the disease detection apparatus, and it delivers a sample or auxiliary material at a desired pressure and speed into a device.

[270] Figures 17(b)-17(c) illustrate a novel device which can engage in cellular communications at the single cell level by simulating cellular signals and receiving the cell's responses which can be a signal of electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, electro-mechanical, electro-chemical, electro-chemical-mechanical, bio-chemical, bio-mechanical, bio-electro-mechanical, bio-electro-chemical, bio-electro-chemical-mechanical, physical, or mechanical property. Figure 17(a) illustrates how the signal is processed and responded in a single cell.

[271] Figure 18 illustrates a system block diagram of a disease detection apparatus, comprising various functional modules.

[272] Figure 19 illustrates a micro-device capable of communicating, trapping, sorting, analyzing, treating, or modifying a DNA and measuring the DNA's various properties (e.g., electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, electro-mechanical, electro-chemical, electro-chemical-mechanical, bio-chemical, bio-mechanical, bio-electro-mechanical, bio-electro-chemical, bio-electro-chemical-mechanical, physical, or mechanical properties).

[273] Figure 20 illustrates an apparatus of this invention that can detect the surface charge on biological subjects and separate them by a slit based on the charge.

[274] Figure 21 illustrates another apparatus of this invention that can detect the optical properties of the biological subject with a set of optical sensors.

- [275] Figure 22 illustrates another apparatus of this invention that can separate biological subjects of different geometric size and detect their properties respectively.
- [276] Figure 23 illustrates an apparatus of this invention that can measure the acoustic property of a biological subject.
- [277] Figure 24 illustrates an apparatus of this invention that can measure the internal pressure of a biological subject.
- [278] Figure 25 illustrates an apparatus of this invention that has concaves between the probe couples, in the bottom or ceiling of the channel.
- [279] Figure 26 illustrates another apparatus of this invention that has concaves of a different shape from those illustrated in Figure 25.
- [280] Figure 27 illustrates an apparatus of this invention that has a stepped channel.
- [281] Figure 28 illustrates an apparatus of this invention that has a set of thermal meters.
- [282] Figure 29 illustrates an apparatus of this invention that includes a carbon nano-tube as the channel with DNA contained therein.
- [283] Figure 30 illustrated an integrated apparatus of this invention that includes a detecting device and an optical sensor.
- [284] Figure 31 illustrated an integrated apparatus of this invention that includes a detecting device and a logic circuitry.
- [285] Figure 32 illustrates an apparatus of this invention that includes a detecting device and a filter.
- [286] Figure 33 illustrates how micro-devices of this invention can be used to measure the geometric factors of DNA.
- [287] Figure 34 illustrates a process for fabricating a micro-device of this invention with a cover atop the trench to form a channel.
- [288] Figure 35 is a diagram of an apparatus of this invention for detecting a disease in a biological subject.
- [289] Figure 36 shows an example of a sample filtration unit.
- [290] Figure 37 shows another example of a sample filtration unit.
- [291] Figure 38 is a diagram of a pre-processing unit of an apparatus of this invention.
- [292] Figure 39 is a diagram of an information processing unit of an apparatus of this invention.

[293] Figure 40 shows the integration of multiple signals which results in cancellation of noise and enhancement of signal/noise ratio.

[294] Figure 41 shows one embodiment of the fabrication process of this invention for manufacturing a detection device with at least one detection chamber and at least one detector.

[295] Figure 42 shows another embodiment of a process of this invention for manufacturing a detection device with enclosed detection chambers, detectors, and channels for transporting biological samples such as fluidic samples.

[296] Figure 43 shows a novel disease detection method in which at least one probe object is launched at a desired speed and direction toward a biological subject, resulting in a collision.

[297] Figure 44 illustrates a novel fabrication process of this invention for forming multiple components with different materials at the same device level.

[298] Figure 45 shows a process of this invention for detecting a biological subject using a disease detection device.

[299] Figure 46 shows another embodiment of disease detection process wherein diseased and healthy biological subjects are separated and the diseased biological subjects are delivered to further test.

[300] Figure 47 is an arrayed biological detecting device wherein a series of detecting devices are fabricated into an apparatus.

[301] Figure 48 shows another embodiment of a disease detection device of the current invention including inlet and outlet of the device, the channel where the biological subject passes through, and detection devices aligned along the walls of the channel.

[302] Figure 49 shows a schedule for fabricating a piezo-electric micro-detector of this invention.

[303] Figure 50 shows an example of the micro-device of this invention packaged and ready for use.

[304] Figure 51 shows another example of the micro-device of this invention that is packaged and ready for use.

[305] Figure 52 shows yet another example of the micro-device of this invention that is packaged and ready for use.

### **Detailed Description of the Invention**

[306] One aspect of the present invention relates to apparatus for detecting disease in a biological subject in vivo or in vitro (e.g., human being, an organ, a tissue, or cells in a culture). Each apparatus includes a biological fluid delivering system and a probing and detecting device. The apparatus is capable of measuring microscopic properties of a biological sample. By the constant pressure fluid delivery system, microscopic biological subjects can be delivered onto or into the diagnostic micro-device of the apparatus. Compared to traditional detection apparatus or technologies, the apparatus provided by this invention are advantageous in providing enhanced detection sensitivity, specificity, and speed, with reduced costs and size. The apparatus can further include a biological interface, a probing controlling and data analysis circuitry, or a system reclaiming or treating medical waste. Additional micro-devices, e.g., a second detection device, can also be included or integrated into the apparatus for enhanced detection capabilities.

[307] As a key component of the apparatus, the micro-device should include means to perform at least the function of addressing, controlling, forcing, receiving, amplifying, or storing information from each probing address. As an example, such means can be a central control unit that includes a controlling circuitry, an addressing unit, an amplifier circuitry, a logic processing circuitry, a memory unit, an application specific chip, a signal transmitter, a signal receiver, or a sensor.

[308] In some embodiments, the fluid delivering system comprises a pressure generator, a pressure regulator, a throttle valve, a pressure gauge, and distributing kits. As examples of these embodiments, the pressure generator can include a motor piston system and a bin containing compressed gas; the pressure regulator (which can consist of multiple regulators) can down-regulate or up-regulate the pressure to a desired value; the pressure gauge feeds back the measured value to the throttle valve which then regulates the pressure to approach the target value.

[309] The biological fluid to be delivered can be a sample of a biological subject to be detected for disease or something not necessarily to be detected for disease. In some embodiment, ; the fluid to be delivered is liquid (e.g., a blood sample, a urine sample, or a saline) or gas (e.g., nitrogen, argon, helium, neon, krypton, xenon, or radon). The pressure regulator can be a single pressure regulator or multiple pressure regulators which are placed in succession to either down-regulate or up-regulate the pressure to a desired level, particularly when the initial pressure is

either too high or too low for a single regulator to adjust to the desired level or a level that is acceptable for an end device or target.

[310] In some other embodiments, the system controller includes a pre-amplifier, a lock-in amplifier, an electrical meter, a thermal meter, a switching matrix, a system bus, a nonvolatile storage device, a random access memory, a processor, or a user interface. The interface can include a sensor which can be a thermal sensor, a flow meter, a piezo-meter, or another sensor.

[311] In still some other embodiments, apparatus of this invention further include a biological interface, a system controller, a system for reclaiming or treatment medical waste. The reclaiming and treatment of medical waste can be performed by the same system or two different systems.

[312] Another aspect of this invention provides apparatus for interacting with a cell, which include a device for sending a signal to the cell and optionally receiving a response to the signal from the cell.

[313] In some embodiments, the interaction with the cell can be probing, detecting, communicating with, treating, or modifying with a coded signal that can be an electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, electro-mechanical, electro-chemical, electro-chemical-mechanical, bio-chemical, bio-mechanical, bio-electro-mechanical, bio-electro-chemical, bio-electro-chemical-mechanical, physical, or mechanical signal, or a combination thereof.

[314] In some other embodiments, the device contained in the apparatus can include multiple surfaces coated with one or more elements or combinations of elements, and a control system for releasing the elements. In some instances, the control system can cause release of the elements from the device surface via thermal energy, optical energy, acoustic energy, electrical energy, electro-magnetic energy, magnetic energy, radiation energy, or mechanical energy in a controlled manner. The energy can be in the pulsed form at desired frequencies.

[315] In some other embodiments, the device contained in the apparatus include a first component for storing or releasing one element or a combination of elements onto the surface of the cell or into the cell; and a second component for controlling the release of the elements (e.g., a circuitry for controlling the release of the elements). The elements can be a biological component, a chemical compound, Ca, C, Cl, Co, Cu, H, I, Fe, Mg, Mn, N, O, P, F, K, Na, S, Zn, or a combination thereof. The signal, pulsed or constant, can be in the form of a released

element or combination of elements, and it can be carried in a liquid solution, gas, or a combination thereof. In some instances, the signal can be at a frequency ranging from about  $1 \times 10^{-4}$  Hz to about 100 MHz or ranging from about  $1 \times 10^{-4}$  Hz to about 10 Hz, or at an oscillation concentration ranging from about 1.0 nmol/L to about 10.0 mmol/L. Also, the signal comprises the oscillation of a biological component, a chemical compound, Ca, C, Cl, Co, Cu, H, I, Fe, Mg, Mn, N, O, P, F, K, Na, S, Zn, or a combination thereof, e.g., at desired oscillating frequencies.

[316] In some embodiments, the signal to be sent to the cell can be in the form of oscillating element, compound, or an oscillating density of a biological component, and a response to the signal from the cell is in the form of oscillating element, compound, or an oscillating density of a biological component.

[317] In some embodiments, the device can be coated with a biological film, e.g., to enhance compatibility between the device and the cell.

[318] In some other embodiments, the device can include components for generating a signal to be sent to the cell, receiving a response to the signal from the cell, analyzing the response, processing the response, and interfacing between the device and the cell.

[319] Still another aspect of this invention provides devices each including a micro-filter, a shutter, a cell counter, a selector, a micro-surgical kit, a timer, and a data processing circuitry. The micro-filter can discriminate abnormal cells by a physical property (e.g., e.g., dimension, shape, or velocity), mechanical property, electric property, magnetic property, electromagnetic, thermal property (e.g., temperature), optical property, acoustical property, biological property, chemical property, or bio-chemical property. The devices each can also include one or more micro-filters. Each of these micro-filters can be integrated with two cell counters, one of which is installed at the entrance of each filter well, while the other is installed at the exit of each filter well. The shape of the micro-filter's well is rectangle, ellipse, circle, or polygon; and the micro-filter's dimension ranges from about 0.1  $\mu\text{m}$  to about 500  $\mu\text{m}$  or from about 5  $\mu\text{m}$  to about 200  $\mu\text{m}$ . As used herein, the term "dimension" means the physical or feature size of the filter opening, e.g., diameter, length, width, or height. The filter can be coated with a biological or bio-compatible film, e.g., to enhance compatibility between the device and the cell.

[320] In some embodiments of these devices, the shutter sandwiched by two filter membranes can be controlled by a timer (thus time shutter). The timer can be triggered by the cell counter. For instance, when a cell passes through the cell counter of the filter entrance, the clock is

triggered to reset the shutter to default position, and moves at a preset speed towards the cell pathway, and the timer records the time as the cell pass through the cell counter at the exit.

[321] Still a further aspect of this invention provides methods for fabricating a micro-device with micro-trench and probe embedded in the micro-trench's sidewalls. A micro-trench is an unclosed tunnel (see, e.g., Figure 2(i), 2030), which can be coupled with another upended symmetric trench (see, e.g., Figure 2(k), 2031) to form a closed channel (see, e.g., Figure 2(l), 2020). The method may include chemical vapor deposition, physical vapor deposition, or atomic layer deposition to deposit various materials on a substrate; lithography or etch to transfer patterns from design to structure; chemical mechanical planarization for surface planarization, chemical cleaning for particle removal, diffusion or ion implantation for doping elements into specific layers; or thermal anneal to reduce the crystal defects and activate diffused ions. An example of such method includes: depositing a first material onto a substrate; depositing a second material onto the first material and patterning the second material by a microelectronic process (e.g., lithography or etch) to form a detecting tip; depositing a third material on the second material and then patterning the second material by a planarization process; depositing a fourth material on the third material and patterning the fourth material first by a microelectronic process (e.g., lithography or etch) and then by a microelectronic process (e.g., another etch) in which the fourth material serves as a hardmask. A hardmask generally refers to a material (e.g., inorganic dielectric or metallic compound) used in semiconductor processing as an etch mask in lieu of polymer or other organic "soft" materials.

[322] In some embodiments, the method further includes coupling two devices that are thus fabricated and symmetric (i.e., a flipped mirror) to form a detecting device with channels. The entrance of each channel can be optionally bell-mouthed, e.g., such that the size of channel's opening end (the entrance) is larger than the channel's body, thereby making it easier for a cell to enter the channel. The shape of each channel's cross-section can be rectangle, ellipse, circle, or polygon. The micro-trenches of the coupled two micro-devices can be aligned by the module of alignment marks designed on the layout of the micro-device. The dimension of the micro-trench can range from about 0.1  $\mu\text{m}$  to about 500  $\mu\text{m}$ .

[323] Alternatively, the method can also include covering the micro-trench of the micro-device with a flat panel. Such a panel can comprise or be made with silicon, SiGe, SiO<sub>2</sub>, Al<sub>2</sub>O<sub>3</sub>, or other optical materials. Examples of other potentially suitable optical materials include acrylate

polymer, AgInSbTe, synthetic alexandrite, arsenic triselenide, arsenic trisulfide, barium fluoride, CR-39, cadmium selenide, caesium cadmium chloride, calcite, calcium fluoride, chalcogenide glass, gallium phosphide, GeSbTe, germanium, germanium dioxide, glass code, hydrogen silsesquioxane, Iceland spar, liquid crystal, lithium fluoride, lumicera, METATOY, magnesium fluoride, magnesium oxide, negative index metamaterials, neutron super mirror, phosphor, picarin, poly(methyl methacrylate), polycarbonate, potassium bromide, sapphire, scotophor, spectralon, speculum metal, split-ring resonator, strontium fluoride, yttrium aluminum garnet, yttrium lithium fluoride, yttrium orthovanadate, ZBLAN, zinc selenide, and zinc sulfide.

[324] In other embodiments, the method can further include integrating three or more micro-devices thus fabricated to yield an enhanced device with an array of the channels.

[325] Yet still another aspect of this invention relates to micro-devices each including a micro-trench, a probe embedded aside the trench's side walls or bottom floor, a supporting structure to move the probe, and a controlling circuitry, wherein the micro-device is capable of trapping, sorting, or modifying a DNA and measuring its properties (e.g., electrical, thermal, or optical properties). The micro-trench can be utilized to encase the DNA double helix.

[326] In some embodiments, the width of the micro-trench ranges from about 1 nm to about 10  $\mu\text{m}$ , the depth of the micro-trench ranges from about 1 nm to about 10  $\mu\text{m}$ , or the length of the micro-trench ranges from about 1 nm to about 10 mm. The probe can include or be made of a conductive material and, optionally, a flexible supporting structure to extend or contract the probe. The probe can also have a tip aside the trench and the tip matches spatially with either a major groove or a minor groove of the DNA. The tip can match spatially with interlaced grooves of the DNA, which can be variable. The tip of can also match the end of each strand of the DNA helix. In some examples, the tip's diameter can range from about 1 angstrom to about 10  $\mu\text{m}$ .

[327] In some other embodiments, the micro-device can further include an array of trenches, e.g., to enhance the efficiency.

[328] Another aspect of this invention relates to a set of novel process flows for fabricating micro-devices (including micro-probes and micro-indentation probes) for their applications in disease detection by measuring microscopic properties of a biological sample. The micro-devices can be integrated into a disease detection apparatus of this invention to measure one or more properties at microscopic levels.



[329] Another aspect of this invention is to involve in cellular communications and regulate cellular decision or response (such as differentiation, dedifferentiation, cell division and cell death) with fabricated signals. This could be further employed to detect and treat diseases.

[330] To further enhance measurement capabilities, multiple micro-devices can be implemented into a piece of detection apparatus employing the time of flight technique, in which at least one probing micro-device and one sensing micro-device placed at a preset, known distance. The probing micro-device can apply a signal (e.g., a voltage, a charge, an electrical field, a laser beam, or an acoustic wave) to the biological sample to be measured, and the detection (sensing) micro-device can measure response from or of the biological sample after the sample has traveled a known distance and a desired period of time. For instance, a probing micro-device can apply an electrical charge to a cell first, and then a detection (sensing) micro-device subsequently measures the surface charge after a desired period of time ( $T$ ) has lapsed and the cell has traveled a certain distance ( $L$ ).

[331] The micro-devices contained in the apparatus of this invention can have a wide range of designs, structures, functionalities, and applications due to their diverse properties, high degree of flexibilities, and ability of integration and miniaturization. They include, e.g., a voltage comparator, a four point probe, a calculator, a logic circuitry, a memory unit, a micro cutter, a micro hammer, a micro shield, a micro dye, a micro pin, a micro knife, a micro needle, a micro thread holder, micro tweezers, a micro optical absorber, a micro mirror, a micro wheeler, a micro filter, a micro chopper, a micro shredder, micro pumps, a micro absorber, a micro signal detector, a micro driller, a micro sucker, a micro tester, a micro container, a signal transmitter, a signal generator, a friction sensor, an electrical charge sensor, a temperature sensor, a hardness detector, an acoustic wave generator, an optical wave generator, a heat generator, a micro refrigerator and a charge generator.

[332] Further, it should be noted that advancements in manufacturing technologies have now made fabrications of a wide range of micro-devices and integration of various functions onto the same device highly feasible and cost effective. The typical human cell size is about 10 microns. Using state-of-the-art integrated circuit fabrication techniques, the minimum feature size defined on a micro-device can be as small as 0.1 micron or below. Thus, it is ideal to utilize the disclosed micro-devices for biological applications.

[333] In terms of materials for the micro-devices, the general principle or consideration is the material's compatibility with a biological subject. Since the time in which a micro-device is in contact with a biological sample (e.g., a cell; a biological molecule such as DNA, RNA, or protein; or a tissue or organ sample) may vary, depending on its intended application, a different material or a different combination of materials may be used to make the micro-device. In some special cases, the materials may dissolve in a given pH in a controlled manner and thus may be selected as an appropriate material. Other considerations include cost, simplicity, ease of use and practicality. With the significant advancements in micro fabrication technologies such as integrated circuit manufacturing technology, highly integrated devices with minimum feature size as small as 0.1 micron can now be made cost-effectively and commercially. One good example is the design and fabrication of micro electro mechanical devices (MEMS), which now are being used in a wide variety of applications in the integrated circuit industry.

[334] Set forth below are several illustrations or examples of apparatus of this invention containing a class of innovative micro-devices that are integrated into the disease detection apparatus of this invention, and of their fabrication process.

[335] Figure 1 is a perspective illustration of a disease detection apparatus of this invention **111** in which a biological sample **211** such as a blood sample placed in it or moving through it is tested. In this figure, an example of disease detection apparatus **111** is in the form of a cylinder, in which a biological sample **211** flowing through it (from the left side to the right side in the figure) can be tested for one or more properties at the microscopic levels.

[336] To enhance detection speed and sensitivity, a large number of micro-devices can be integrated into a single disease detection apparatus of this invention, such as the apparatus illustrated in Figure 1(b) and Figure 1(c) with the micro-devices spaced to measure a large number of desired entities (such as cells, DNAs, RNAs, proteins, etc.) in the biological sample. To achieve the above requirements, the detection apparatus should be optimized with its surface area maximized to contact the biological sample and with large number of micro-devices integrated on the maximized surface.

[337] Figure 2 (a) is a perspective, cross-sectional illustration of a disease detection apparatus of this invention **122** with multiple identical micro-devices **311**. A biological sample such as a blood sample **211** placed in it or moving through it can be tested for one or more properties at the microscopic levels including, e.g., electrical properties (such as surface charge, surface potential,

current, impedance, other electrical properties), magnetic properties, electromagnetic properties, mechanical properties (such as density, hardness, shear strength, elongation strength, fracture stress, and adhesion), biological features, chemical properties (e.g., pH or ionic strength), biochemical properties, thermal properties (e.g., temperature), and optical properties.

[338] Instead of measuring a single property of a biological subject for disease diagnosis, various micro-devices can be integrated into a detection apparatus to detect multiple properties. Figure 3 is a perspective, cross-sectional illustration of a disease detection apparatus of this invention **133** with multiple micro-devices **311**, **312**, **313**, **314**, and **315**, of different detection probes in which a sample **211** such as a blood sample placed in it or moving through it can be tested for multiple properties including but not limited to electrical properties (e.g., surface charge, surface potential, and impedance), magnetic properties, electromagnetic properties, mechanical properties (e.g., density, hardness and adhesion), thermal properties (e.g., temperature), biological properties, chemical properties (e.g., pH), physical properties, acoustical properties, and optical properties.

[339] Figures 2(b)-2(n) illustrate a process flow of this invention for fabricating micro-devices for trapping, sorting, probing, measuring, and modifying biological subjects (e.g., a single cell, a DNA or RNA molecule). First, a material **2002** (e.g., a non-conducting material) and another material **2003** (e.g., a conducting material) are sequentially deposited on a substrate **2001** (see Figure 2(b) and Figure 2(c)). The first material **2003** is then subsequently patterned by the lithography and etch processes (see Figure 2(d)). Another material **2004** is then deposited (as shown in Figure 2(e)) and planarized (as shown in Figure 2(f)). Another layer of material **2005** is deposited (as shown in Figure 2(g)) and patterned as a hard mask (as shown in Figure 2(h)), then followed by etch (as shown in Figure 2(j)), which is stopped on the substrate **2001**. Figure 2(i) is a perspective illustration of the device, while Figure 2(j) is a vertical illustration of the device.

[340] As shown in Figure 2(k), the device **2080** and a mirrored or symmetric device **2081** can be coupled together (as shown in Figure 2(l)). As such, the apparatus having the pathway with probe embedded in the sidewall is fabricated.

[341] As illustrated in Figure 2(m) and Figure 2(n), a large number of detection micro-devices can be integrated together to enhance the detection efficiency.

[342] As illustrated herein, it is desirable to optimize the detection apparatus design to maximize measurement surface area, since the greater the surface area, the greater number of micro-devices that can be placed on the detection apparatus to simultaneously measure the sample, thereby increasing detection speed and also minimizing the amount of sample needed for the test. Figure 4 is a perspective illustration of a disease detection apparatus of this invention 144. It includes two slabs separated by a narrow spacing with a sample such as a blood sample to be measured placed between the slabs, with multiple micro-devices placed at the inner surfaces of the slabs to measure one or more properties of the sample at microscopic levels.

[343] Yet another aspect of this invention relates to a set of novel fabrication process flows for making micro-devices for disease detection purposes. Figure 5 illustrates a novel process flow for fabricating a disease detection apparatus utilizing microelectronics technologies and processes. First, a material 412 is deposited on a substrate 411 (Figure 5(a)). It is then patterned by photolithography and etching processes (Figure 5(b)). Following the deposition, material 413 is planarized using chemical mechanical polishing as shown in Figure 5(d). Recessed areas, in the form of hole pattern, are next formed in material 413 using photolithography and etch processes, as shown in Figure 5(e), followed by the deposition of material 414 (Figure 5(f)). Material 414 above the surface of material 413 is removed by chemical mechanical polishing (Figure 5(g), followed by deposition of material 415. Material 415 is next patterned using photolithography and etching processes (Figure 5(i)). Material 414 is next deposited and its excess material above its substrate 415 is removed by chemical mechanical polishing (Figure 5(j) and (k)). Finally, a light etch or short chemical mechanical polishing to material 415 is carried out to recess material 415, selective to material 414 (Figure 5(l)), resulting in slight protruding of material 414. Material 412 can be a piezo-electric material. When a voltage is applied to it in the right direction, it will expand and push up, resulting in upward motion in middle tip in material 414. Thus, a micro-device with two probes capable of measuring a range of properties (including mechanical and electrical properties) of biological samples is fabricated, using the above novel fabrication process flow.

[344] Detection apparatus integrated with micro-devices disclosed in this application is fully capable of detecting pre-chosen properties on a single cell, a single DNA, a single RNA, or an individual, small sized biological matter level. Figure 6 is a perspective illustration of a micro-device 555 fabricated by a novel process flow disclosed in this patent application (e.g., novel

process flow illustrated in Figure 5 above) and how such a device is capable of probing a single cell 666 and measuring the cell for collecting intended parameters. Figure 6(a) illustrated a perspective, cross-section of a micro-device 555 with a pair of micro probes 531 and 520, where micro probe 531 is in the form of a tip and micro probe 520 is in the form of a ring. Both of micro probes 531 and 520 can be conductive and they can serve as a pair of probes to measure electrical properties of a biological sample. Micro probe 531 is in contact with a base 518 which can be a piezo-electric material. When a voltage is applied to the base 518 made of a piezo-electric material, the base 518 can expand and push micro probe tip 531 upward, which can be useful in measuring various properties of a biological sample such as a single cell. In Figure 6(b), micro-device 555 is shown to measure a single cell 666, using probe tip 531 penetrating through cell membrane 611 and into the cell's inner space 622, while probe ring 520 making contact with cell membrane 611 at the outside surface of the membrane. This way, the micro-device 555 can make various measurements on the cell, including its electrical properties (e.g., electrical potential, current across the cell membrane, surface charge on the membrane, and impedance), mechanical properties (e.g., hardness when probe tip 531 is designed as a micro-indentation probe), thermal properties (e.g., temperature), physical properties, and chemical properties (e.g., pH).

[345] In another further aspect, the invention provides the design, integration, and fabrication process flow of micro-devices capable of making highly sensitive and advanced measurements on very weak signals in biological systems for disease detection under complicated environment with very weak signal and relatively high noise background. Those novel capabilities using the class of micro-devices disclosed in this invention for disease detection include but not limited to making dynamic measurements, real time measurements (such as time of flight measurements, and combination of using probe signal and detecting response signal), phase lock-in technique to reduce background noise, and 4-point probe techniques to measure very weak signals, and unique and novel probes to measure various electronic, electromagnetic and magnetic properties of biological samples at the single cell (e.g., a telomere of DNA or chromosome), single molecule (e.g., DNA, RNA, or protein), single biological subject (e.g., virus) level.

[346] For example, in a time of flight approach to obtain dynamic information on the biological sample (e.g., a cell, a substructure of a cell, a DNA, a RNA, or a virus), a first micro-device is first used to send a signal to perturb the biological subject to be diagnosed, and then a second

micro-device is employed to accurately measure the response from the biological subject. In one embodiment, the first micro-device and the second micro-device are positioned with a desired or pre-determined distance  $L$  apart, with a biological subject to be measured flowing from the first micro-device towards the second micro-device. When the biological subject passes the first micro-device, the first micro-device sends a signal to the passing biological subject, and then the second micro-device detects the response or retention of the perturbation signal on the biological subject. From the distance between the two micro-devices, time interval, the nature of perturbation by the first micro-device, and measured changes on the biological subject during the time of flight, microscopic and dynamic properties of the biological subject can be obtained. In another embodiment, a first micro-device is used to probe the biological subject by applying a signal (e.g., an electronic charge) and the response from the biological subject is detected by a second micro-device as a function of time.

[347] To further increase detection sensitivity, a novel detection process for disease detection is used, in which time of flight technique is employed. Figure 7 is a perspective, cross-sectional illustration of detection apparatus **155** with multiple micro-devices **321** and **331** placed at a desired distance **700** for time of flight measurements to attain dynamic information on biological sample **211** (e.g., a cell) with enhanced measurement sensitivity, specificity, and speed. In this time of flight measurement, one or more properties of the biological sample **211** are first measured when the sample **211** passes the first micro-device **321**. The same properties are then measured again when the sample **211** passes the second micro-device **331** after it has travelled the distance **700**. The change in properties of sample **211** from at micro-device **321** to at micro-device **331** indicates how it reacts with its surrounding environment (e.g., a particular biological environment) during that period. It may also reveal information and provide insight on how its properties evolve with time. Alternatively, in the arrangement shown in Figure 7, micro-device **321** could be used first as a probe to apply a probe signal (e.g., an electrical charge) to sample **211** as the sample passes the micro-device **321**. Subsequently, the response of the sample to the probe signal can be detected by micro-device **331** as the sample passes it (e.g., change in the electrical charge on the sample during the flight). Measurements on biological sample **211** can be done via contact or non-contact measurements. In one embodiment, an array of micro-devices can be deployed at a desired spacing to measure properties of the biological subject over time.

[348] The utilization of micro-devices (e.g., made by using the fabrication process flows of this invention) as discussed above and illustrated in Figure 7 can be helpful for detecting a set of new, microscopic properties of a biological sample (e.g., a cell, a cell substructure, or a biological molecule such as DNA or RNA or protein) that have not been considered in existing detection technologies. Such microscopic properties can be electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, electro-mechanical, electro-chemical, electro-chemical-mechanical, bio-chemical, bio-mechanical, bio-electro-mechanical, bio-electro-chemical, bio-electro-chemical-mechanical, physical, or mechanical properties of a biological sample that is a single biological subject (such as a cell, a cell substructure, a biological molecule – e.g., DNA, RNA, or protein – or a sample of a tissue or organ). It is known that biological matters includes from basic bonding such as OH, CO, and CH bonding, to complex, three dimensional structures such as DNA and RNA. Some of them have a unique signature in terms of its electronic configuration. Some of them may have unique electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, electro-mechanical, electro-chemical, electro-chemical-mechanical, bio-chemical, bio-mechanical, bio-electro-mechanical, bio-electro-chemical, bio-electro-chemical-mechanical, physical, or mechanical properties and configurations. Normal biological subject and diseased biological subject may carry different signatures with respective to the above said properties. However, none of the above stated parameters or properties have been routinely used as a disease detection property. Using a disease detection apparatus including one or more micro-devices of this invention, those properties can be detected, measured, and utilized as useful signals for disease detection, particularly for early stage detection of serious diseases such as cancer.

[349] Figure 8 is a perspective illustration of a novel set of microscopic probes 341, 342, 343, 344, 345, 346, and 347 designed and configured to detect various electronic, magnetic, or electromagnetic states, configurations, or other properties at microscopic level on biological samples 212, 213, 214, and 215, which can be a single cell, DNA, RNA, and tissue or sample. As an example, in terms of measuring electronic properties, the shapes of biological samples 212, 213, 214, and 215 in Figure 8 may represent electronic monopole (sample 212), dipole (samples 213 and 214), and quadruple (sample 215). The micro-devices 341, 342, 343, 344, 345, 346, and 347 are optimized to maximize measurement sensitivity of those said parameters including but not limited to electronic states, electronic charge, electronic cloud distribution, electrical field,

and magnetic and electromagnetic properties, and the micro-devices can be designed and arranged in three dimensional configurations. For some diseases such as cancer, it is likely that electronic states and corresponding electronic properties differ between normal and cancerous cells, DNA, RNA, and tissue. Therefore, by measuring electronic, magnetic and electromagnetic properties at microscopic levels including at cell, DNA, and RNA levels, disease detection sensitivity and specificity can be improved.

[350] In addition to the above examples in measuring electrical properties (e.g., charge, electronic states, electronic charge, electronic cloud distribution, electrical field, current, and electrical potential, and impedance), mechanical properties (e.g., hardness, density, shear strength, and fracture strength) and chemical properties (e.g., pH) in a single cell, and in Figure 8 for measuring electrical, magnetic or electromagnetic states or configurations of biological samples at cell and biological molecular (e.g., DNA, RNA, and protein) levels, other micro-devices are disclosed in this application for sensitive electrical measurements.

[351] Figure 9 is a perspective illustration of a four-point probe for detecting weak electronic signal in a biological sample such as a cell, where a four point probe 348 is designed to measure electrical properties (impedance and weak electrical current) of a biological sample 216.

[352] One of the key aspects of this invention is the design and fabrication process flows of micro-devices and methods of use the micro-devices for catching and/or measuring biological subjects (e.g., cells, cell substructures, DNA, and RNA) at microscopic levels and in three dimensional space, in which the micro-devices have micro-probes arranged in three dimensional manner with feature sizes as small as a cell, DNA, or RNA, and capable of trapping, sorting, probing, measuring, and modifying biological subjects. Such micro-devices can be fabricated using state-of-the-art microelectronics processing techniques such as those used in fabricating integrated circuits. Using thin film deposition technologies such as molecular epitaxy beam (MEB) and atomic layer deposition (ALD), film thickness as thin as a few monolayers can be achieved (e.g., 4 Å to 10 Å). Further, using electron beam or x-ray lithography, device feature size on the order of nanometers can be obtained, making micro-device capable of trapping, probing, measuring, and modifying a biological subject (e.g., a single cell, a single DNA or RNA molecule) possible.

[353] Figure 10 illustrates a process flow of this invention for fabricating micro-devices for trapping, sorting, probing, measuring, and modifying biological subjects (e.g., a single cell, a



DNA or RNA molecule). In this process flow, microelectronics processes are utilized to fabricate micro-devices designed to achieve the above stated unique functions. Specifically, a first material **712** (typically a conducting material) is first deposited on a substrate **711** (Figure 10(a) and Figure 10(b)). The first material **712** is subsequently patterned by using lithography and etch processes (Figure 10(c)). A second material **713** is then deposited and planarized using chemical mechanical polishing process to remove overburden of the second material **713** above the first material **712** (as shown in Figure 10(e)). Another layer of material **714** is deposited and patterned, followed by deposition and planarization by chemical mechanical polishing of another layer of **712** (Figure 10(f)). Next, a third material **715** is deposited and patterned, using lithography and etch processes (Figure 10(g) and Figure 10(h)), followed by deposition and planarization of a fourth material **716**, typically a sacrificial material (Figure 10(i) and Figure 10(j)). Repeating the process flow of deposition of patterning material **712** or material **715** alternatively, and deposition of material **716** and planarization by chemical mechanical polishing (Figure 10(k)-(m)), a film stack featuring multiple layers with alternating material **712** (e.g., a conducting material) and material **715** (e.g., an insulating material) in at least portions of the device is formed. Finally, material **716** between film stacks **771** and **772** is removed by wet etch, dry etch (which may require lithography process), or vapor etch, selective to all other materials (Figure 10(n)). As illustrated in Figure 10(o), in the case of **712** being a conductive material connected to an electrical circuit or an electrical source (e.g., a charge source), each probe tip formed by **712** on the stack (e.g., **781** and **782**) can have a charge or an electrical field at the surface (e.g., **781** and **782**), which (each probe tip) can be selected to have a positive charge or a negative charge, or a positive electrical field or negative electrical field. Conversely, such probe tip can also sense various properties of biological subject being measured (e.g., electronic cloud, field, charge, or temperature when the probe tip is a thermal detector, or light emission when the probe tip is an optical sensor). Using electrical circuit or electrical source, various combinations of electrical charge distribution or electrical field can be placed on the micro-device, as shown in Figure 10(o) and Figure 10(p), which can be used to sort and trap various biological subjects such as a cell and a DNA molecule. For instance, a biological subject with a charge distribution inverse of that in Figure 10(p) can be trapped by the micro-device shown in Figure 10(p). An array of micro-devices with various charge distributions or electrical field distributions can trap their respective biological subjects in a high speed, which can serve as a sorting device. Figure

10(q) illustrates the use of a micro-device capable of trapping a DNA or measuring various properties (e.g., electrical, thermal, or optical properties) of a DNA, with each probe tip matched up spatially with either a major groove or minor groove of a double helix DNA. Figure 10(r) illustrates how the probe tips are connected to electrical circuit, where only electrical wiring is shown. It should be noted that the micro-device shown in this example can be integrated onto a single chip with one billion or more such micro-devices to trap and/or sort cells, DNAs, RNAs, proteins, and other biological subject in a high speed.

[354] Another aspect of this invention relates to micro-indentation probes and micro-probes for measuring a range of physical properties (such as mechanical properties) of biological subjects. Examples of the mechanical properties include hardness, shear strength, elongation strength, fracture stress, and other properties related to cell membrane which is believed to be a critical component in disease diagnosis.

[355] Figure 11 illustrates a novel fabrication process flow for micro-devices capable of probing a range of properties of biological subjects, such as mechanical properties of cell membrane (e.g., mechanical strength of a cell membrane). In this process flow, a material **812** is first deposited onto a substrate **811**, followed by the deposition of another material **813** (Figure 11(a)). Following patterning of material **813** using lithography and etch processes, a material **814** is deposited (Figure 11(b)) and planarized (Figure 11(c)). Another layer of material **813** is next deposited and patterned using lithography and etch processes to remove portions of the material **813**, followed by the deposition and planarization of a material **815** (which can be a piezo-electric material and can serve as a driver) (Figure 11(d)). A layer of material **813** is next deposited, followed by deposition and patterning of yet another layer of **813**, and deposition and planarization of material **816** (Figure 11(e)). Next, material **816** is etched back to a reduced thickness, and patterned, followed by patterning of triple- layer of material **813** (Figure 11(f)). Another layer of **814** is deposited (Figure 11(g)) and planarized by chemical mechanical polishing (Figure 11(h)), and patterned (Fig 11(i)). Finally, multiple layers of **813** are removed by wet etch, plasma etch, or vapor etch (Figure 11(j)). Figure 11(k) is a perspective, cross-sectional illustration of the micro-device in a plane perpendicular to that in Figure 11(j) (90-degree rotation from Figure 11(j)). Figure 11(l) illustrates a micro-device with two micro-tips **871** and **872** which can move in opposite directions when a voltage is applied to piezo-electric drivers **881** and **882**, which can be used to probe biological subjects such as cells.

[356] Figure 12 is an illustration of how micro-devices fabricated using the novel manufacturing process shown in Figure 11 work. In Figure 12, a micro-device 850 with two micro-probes 866 and 855 can move in opposite directions upon a force being applied (Figure 12(a)). When the tips of the two probes are penetrated into a cell 870, as the distance between the two micro-probes is increased with the increasing applied force, the cell is stretched. Finally, as the applied force is reached a critical value, the cell is broken into two pieces (Figure 12(b)). The dynamic response of the cell to the applied force provides information on the cell, particularly on the mechanical properties (e.g., elasticity) of cell membrane. The force at the point in which the cell is torn apart reflects the strength of the cell and it may be called a breaking point: the greater the mechanical strength of the cell membrane is, the greater the force is at the breaking point.

[357] Another novel approach provided by this invention is the use of phase lock-in measurement for disease detection, which reduces background noise and effectively enhances signal to noise ratio. Generally, in this measurement approach, a periodic signal is used to probe the biological sample and response coherent to the frequency of this periodic probe signal is detected and amplified, while other signals not coherent to the frequency of the probe signal is filtered out, which thereby effectively reduces background noise. In one of the embodiments in this invention, a probing micro-device can send a periodic probe signal (e.g., a pulsed laser beam, a pulsed thermal wave, or an alternating electrical field) to a biological subject, response to the probe signal by the biological subject can be detected by a detecting micro-device. The phase lock-in technique can be used to filter out unwanted noise and enhance the response signal which is synchronized to the frequency of the probe signal. The following two examples illustrate the novel features of time of flight detection arrangement in combination with phase lock-in detection technique to enhance weak signal and therefore detection sensitivity in disease detection measurements.

[358] Figure 13 is an illustration of a novel time of flight detection arrangement for disease detection applications. Specifically, Figure 13(a) shows a set-up for measuring biological subject 911 using detection probe 933 and clock generator 922, and Figure 13(b) contains recorded signal 921 due to structure 922, signal 931 recorded by signal probe 933, and processed signal 941 using a phase lock-in technique to filter out noise in recorded signal 931, where only response synchronized to clock signal 921 is retained. In the setup shown in Figure 13(a), when

a biological subject such as a cell **911** passes a structure **922**, it triggers a clear signal (e.g., a light scattering signal if **922** is a light source, or a sharp increase in voltage if **922** is an orifice structure in a resistor). Therefore, **922** can be used to register the arrival of the biological subject, and as a clock when multiple structures of **922** are placed at a periodic distance as shown in recorded signal trace **921** in Figure 13(b). In addition, when **922** is placed at a known distance in front of a probe **933**, it marks the arrival of a biological subject coming towards **933** and signal response recorded at **933** is delayed by a time  $t$  from the signal triggered by **922** where  $t$  equals distance between **922** and **933** divided by traveling speed of the biological subject. As illustrated in Figure 13(b), signal **921** due to structure **922** is clear and periodic with periodicity proportional to distance between structure **922**s, while signal measured by probe **933** has a high noise level and relatively weak signal related to the biological subject. With the utilization of phase lock-in technique to filter out noise in recorded signal **931** by the detection probe **933** un-synchronized to clock signal **921**, signal to noise ratio can be greatly enhanced as shown in processed signal **941** in Figure 13(b).

[359] Figure 14 illustrates yet another time of flight disease detection arrangement in which a clock signal generator **922**, a probe signal generator **944**, and a signal detection probe **955** are used, along with schematically recorded clock signal **921**, total recorded response signal **951** (except clock signal), and processed signal **952** using phase lock-in technique. In this arrangement, a probe signal generator **944** is used to perturb the biological subject **911** (e.g., heating **911** up using an optical beam, or adding an electrical charge to **911**), and response to the probe signal is subsequently measured as a function of time using an array of detection probes **955**. The filtered signal in **952** shows dynamic response to probe signal by **944** as it decays over time. Since normal cell and abnormal cell may respond differently to the probe signal, this arrangement with proper micro-probes can be utilized to detect diseases such as cancer. In another embodiment utilizing this set-up (shown in Figure 14), the probe signal generator **944** can send a periodic signal to the biological subject **911**, detected response signal from the biological subject by the detection probe **955** can be processed using the phase lock-in technique, with noise un-synchronized to the frequency of the probe signal filtered out and signal synchronized to the probe signal frequency amplified.

[360] Figure 15 is a perspective illustration of the novel multi-property micro-filter. A timed shutter **1502** is sandwiched between 2 pieces of filter membrane **1501** with wells. When a

biological subject **1511** moves through the pathway of the well, it is first detected by the counter **1512**, which triggers the clock of the barrier panel **1502**. Then the larger cells will be filtered out, or blocked, by the filter's holes **1001**, while only the specific subjects with enough speed are able to get through the pathway **1503** before the timed shutter **1502** closes the filter pathway (see Figure 15(b)). Otherwise it will be held back as the timed shutter **1502** moves to block the pathway as shown in Figure 15(c).

[361] Figure 16 illustrates a fluid delivery system that includes a pressure generator, a pressure regulator, a throttle valve, a pressure gauge, and distributing kits. The pressure generator **1605** sustains fluid with desired pressure, and the pressure is further regulated by the regulator **1601** and then accurately manipulated by the throttle valve **1602**. Meanwhile, the pressure is monitored at real time and fed back to the throttle valve **1602** by the pressure gauge **1603**. The regulated fluid is then in parallel conducted into the multiple devices where a constant pressure is needed to drive the fluid sample.

[362] Figure 17 illustrates how a micro-device in a disease detection apparatus of this invention can communicate, probe, detect, and optionally treat and modify biological subjects at a microscopic level. Figure 17(a) illustrates the sequence of cellular events from signal recognition to cell fates determination. First, as the signals **1701** are detected by receptors **1702** on the cell surface, the cell will integrate and encode the signals into a biologically comprehensible message, such as calcium oscillation **1703**. Consequently, corresponding proteins **1704** in the cell will interact with the message, then be modified and transform into ion-interacted proteins **1705** accordingly. Through the translocation, these modified proteins **1705** will pass the carried message to the nuclear proteins, and the controlled modification on nuclear proteins will modulate the expression of gene **1707** which includes transcription, translation, epigenetic processes, and chromatin modifications. Through messenger RNA **1709**, the message is in turn passed to specific proteins **1710**, thereby changing their concentration – which then determines or regulates a cell's decision or activities, such as differentiation, division, or even death.

[363] Figure 17(b) illustrates an apparatus of this invention which is capable of detecting, communicating with, treating, modifying, or probing a single cell, by a contact or non-contact means. The apparatus is equipped with micro-probes and micro-injectors which are addressed

and modulated by the controlling circuitry **1720**. Each individual micro-injector is supplied with a separate micro-cartridge, which carries designed chemicals or compounds.

[364] To illustrate how an apparatus of this invention can be used to simulate an intracellular signal, calcium oscillation is taken as an example mechanism. First, a  $\text{Ca}^{2+}$ -release-activated channel (CRAC) has to be opened to its maximal extent, which could be achieved by various approaches. In an example of the applicable approaches, a biochemical material (e.g., thapsigargin) stored in the cartridge **1724** is released by an injector **1725** to the cell, and the CRAC will open at the stimulus of the biological subject. In another example of the applicable approaches, the injector **1724** forces a specific voltage on cell membrane, which causes the CRAC to open as well.

[365] The  $\text{Ca}^{2+}$  concentration of a solution in the injector **1728** can be regulated as it is a desirable combination of a  $\text{Ca}^{2+}$ -containing solution **1726**, and a  $\text{Ca}^{2+}$  free solution **1727**. While the injector **1730** contains a  $\text{Ca}^{2+}$  free solution, then injectors **1728** and **1730** are alternately switched on and off at a desired frequency. As such, the  $\text{Ca}^{2+}$  oscillation is achieved and the content inside the cell membrane are then exposed to a  $\text{Ca}^{2+}$  oscillation. Consequently, the cell's activities or fate is being manipulated by the regulated signal generated by the apparatus.

[366] Meanwhile, the cell's response (e.g., in the form of an electric, magnetic, electromagnetic, thermal, optical, acoustical, or mechanical property) can be monitored and recorded by the probes integrated in this apparatus.

[367] Figure 17(c) illustrates another design of apparatus which is able to setup communication with a single cell. The apparatus is equipped with micro-probes which are coated with biologically compatible compounds or elements, e.g., Ca, C, Cl, Co, Cu, H, I, Fe, Mg, Mn, N, O, P, F, K, Na, S, or Zn. These probes can generate oscillating chemical signals with such an element or compound to interact with the cell, and results into a response that affects the cell's activities or eventual fate as describe above. Likewise, this apparatus can probe and record the cell's response (e.g., in the form of an electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, electro-mechanical, electro-chemical, electro-chemical-mechanical, bio-chemical, bio-mechanical, bio-electro-mechanical, bio-electro-chemical, bio-electro-chemical-mechanical, physical, or mechanical property) as well.

[368] Figure 18 illustrates the system block diagram of a disease detection apparatus of this invention. This example includes a fluid delivering system **1801**, biological interface **1802**, a

probing and detecting device **1803**, a system controller **1805**, a medical waste reclaiming and treating system **1804**. A biological sample or material is transported to the interface **1802** by the fluid delivery system **1801**, meanwhile the fluid parameters (or properties) are reported to the system controller **1805** which comprises a logic processing unit, a memory unit, an application specific chip, a sensor, a signal transmitter, and a signal receiver; and then the system controller **1805** can give further command to the system. The interface **1802** is an assembly which bridges a fluid sample and the detecting device, and further monitors the parameters or properties of the biological sample (e.g., pressure, temperature, stickiness, or flow rate) and then reports the data to the system controller **1805** while distributing the biological sample to the probing and detecting device **1803** with a specified speed or pressure (which can be commanded by the system controller **1805**).

[369] The system controller **1805** is the central commander and monitor of the entire system (or apparatus), where all the parameters and information from various modules is processed and exchanged and the instructions are given out, and where the command is dispatched. The system controller **1805** can include, e.g., a pre-amplifier, an electrical meter, a thermal meter, a switching matrix, a system bus, a nonvolatile storage device, a random access memory, a processor, and a user interface through which the user of the apparatus can manipulate, configure the apparatus, and read the operating parameters and final result. The pre-amplifier can process the raw signal to a recognizable signal for the meters. The meters can force and measure corresponding signals which can be, e.g., electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, electro-mechanical, electro-chemical, electro-chemical-mechanical, bio-chemical, bio-mechanical, bio-electro-mechanical, bio-electro-chemical, bio-electro-chemical-mechanical, physical, or mechanical signals, or combinations thereof. The switching matrix can switch the testing terminals of different arrays of the probe sub-apparatus. The user interface includes input and output assemblies and is an assembly which seals the fluid delivery system and the probing and detecting device together.

[370] The probing and detecting device **1803** is the core functional module of the disease detection apparatus of this invention as it is the unit that probes the biological sample and collects related cellular signals (or responses). The waste reclaiming and treating system **1804** reclaims the waste biological sample to protect the privacy of its biological host, and keeps it away from polluting the environment.

[371] Figures 19(b)-(n) illustrate a process flow for fabricating a micro-device for trapping, sorting, probing, measuring, treating, or modifying a biological subject (e.g., a single cell, a DNA or RNA molecule). A first material **1902** (e.g., a piezo-electric conducting material) and a second material **1903** (e.g., a conducting material) are sequentially deposited on a substrate **1901** (see Figures 19(b) and 19(c)). The second material **1903** is subsequently patterned by lithography and etch processes (see Figure 19(d)). A third material **1904** is next deposited (as shown in Figure 19(e)) and planarized (see Figure 19(f)). A layer of a fourth material **1905** is subsequently deposited (see Figure 19(g)) and patterned as a hard mask (see Figure 19(h)), followed by etch to remove the third and first materials from desired areas, which stops on the substrate **1901**. Figure 19(i) is a perspective illustration of the device, while Figure 19(j) is a vertical illustration of the same device.

[372] Figure 19 (k) illustrates the use of a micro-device capable of trapping a DNA **1920** and measuring various properties (e.g., electrical, magnetic, physical, thermal, chemical, biological, bio-chemical, or optical properties) of a DNA. Each probe tip **1912** matches up spatially with either a major groove or minor groove of a double helix DNA. Meanwhile, two probes (**1911** and **1910**) configured at the end of the trench can force or measure signals to each strand end of the DNA's double helix. The probes can be made of a conducting material with optionally a piezo-electric support structure, which can stretch forward and backward at a desired distance. All the probes are numbered, addressed, and controlled by a controlling circuitry.

[373] Figure 19(l) shows a simplified form of the device illustrated in Figure 19(k). In this device, probe tips match spatially with interlaced grooves of a double helix DNA. The number of groove intervals between the adjacent probes is variable. If required, either DNA can be moved (for example, by pulling by probes 1910 and 1911) or the probes can move along the trench direction, mapping out properties in a full or partial DNA.

[374] Figure 20 illustrates an apparatus of this invention that is capable of detecting or measuring the surface charge of a biological subject **2010**. It includes a channel, a pair of plates **2022**, and a slit **2030** which separates the channel into a top channel **2041** and a bottom channel **2051**. When a biological subject **2010** carrying a surface charge (positive charge shown in Figure 20(a)) passes through the channel, under the influence of the voltage applied on the plates **2022** (with positive voltage at the top plate and negative at the bottom plate), it will move towards the bottom plate as shown in Figure 20(b). Thus, the biological subject **2010** will pass



through the bottom channel **2051** when it reaches slit **2030**. (If the biological subject **2010** carries a negative charge, it would pass through the top channel **2041**.) This way, a biological subject with unknown charge type (negative or positive) can be determined by using this apparatus.

[375] This device comprises at least 2 parts of channel, one of which is channel **2060** where the biological subject is charged or modified, and the other comprises at least one plate or slit to separate the biological subjects (e.g., where the biological subjects are separated).

[376] As surface charge will affect the shape of a biological subject, by using novel and multiple plates, information on the shape and charge distribution of biological subjects can be obtained. The general principle and design of the micro-device can be extended to a broader scope, thereby making it possible to obtain other information on the biological subject via separation by applying other parameters such as ion gradient, thermal gradient, optical beam, or another form of energy.

[377] Figure 21 illustrates another apparatus of this invention for detecting or measuring microscopic properties of a biological subject **2110** by utilizing a micro-device that includes a channel, a set of probes **2120**, and a set of optical sensors **2132** (see, Figure 21(a)). The detected signals by probes **2120** can be correlated to information including images collected by the optical sensors **2132** to enhance detection sensitivity and specificity. The optical sensors can be, e.g., a CCD camera, a fluorescence light detector, a CMOS imaging sensor, or any combination.

[378] Alternatively, a probe **2120** can be designed to trigger optical emission such as fluorescence light emission **2143** in the targeted biological subject such as diseased cells, which can then be detected by an optical probe **2132** as illustrated in Figure 21(c). Specifically, biological subjects can be first treated with a tag solution which can selectively react to diseased cells. Subsequently, upon reacting (contact or non-contact) with probe **2120**, optical emissions from diseased cells occur and can be detected by optical sensors **2132**. This novel process using the micro-devices of this invention is more sensitive than such conventional methods as traditional fluorescence spectroscopy as the emission trigger point is directly next to the optical probe and the triggered signal **2143** can be recorded in real time and on-site, with minimum loss of signal.

[379] Figure 22 illustrates another embodiment of the apparatus of this invention, which can be used to separate biological subjects of different geometric size and detect their properties

respectively. It includes at least an entrance channel **2210**, a disturbing fluid channel **2220**, an accelerating chamber **2230**, and two selecting channels **2240** and **2250**. The angle between **2220** and **2210** is between  $0^\circ$  and  $180^\circ$ . The biological subject **2201** flows in the x-direction from **2210** to **2230**. The biocompatible distribution fluid **2202** flows from **2220** to **2230**. Then the fluid **2202** will accelerate **2201** in y-direction. However, the acceleration correlates with the radius of the biological subjects and the larger ones are less accelerated than the small ones. Thus, the larger and smaller subjects are separated into different channels. Meanwhile, probes can be optionally assembled aside the sidewall of **2210**, **2220**, **2230**, **2240**, and **2250**. They could detect electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, physical, or mechanical properties at the microscopic level. In the mean time, if desired, a cleaning fluid can also be injected into the system for dissolving and/or cleaning biological residues and deposits (e.g., dried blood and protein) in the narrow and small spaces in the apparatus, and ensuring smooth passage of a biological subject to be tested through the apparatus.

[380] The channel included in the apparatus of this invention can have a width of, e.g., from 1 nm to 1 mm. The apparatus should have at least one inlet channel and at least two outlet channels.

[381] Figure 23 shows another apparatus of this invention with an acoustic detector **2320** for measuring the acoustic property of a biological subject **2301**. This apparatus includes a channel **2310**, and at least an ultrasonic emitter and an ultrasonic receiver installed along the sidewall of the channel. When the biological subject **2301** passes through the channel **2310**, the ultrasonic signal emitted from **2320** will be received after carrying information on **2301** by the receiver **2330**. The frequency of the ultrasonic signal can be, e.g., from 2 MHz to 10 GHz, and the trench width of the channel can be, e.g., from 1 nm to 1 mm. The acoustic transducer (i.e., the ultrasonic emitter) can be fabricated using a piezo-electric material (e.g., quartz, berlinite, gallium, orthophosphate,  $\text{GaPO}_4$ , tourmalines, ceramics, barium, titanate,  $\text{BaTiO}_3$ , lead zirconate, titanate PZT, zinc oxide, aluminum nitride, and polyvinylidene fluorides).

[382] Figure 24 shows another apparatus of this invention that includes a pressure detector for biological subject **2401**. It includes at least one channel **2410** and whereon at least one piezo-electric detector **2420**. When the biologic subject **2401** passes through the channel, the piezo-electric detector **2420** will detect the pressure of **2401**, transform the information into an electrical signal, and send it out to a signal reader. Likewise, the trench width in the apparatus

can be, e.g., from 1 nm to 1 mm, and the piezo-electric material can be, e.g., quartz, berlinite, gallium, orthophosphate,  $\text{GaPO}_4$ , tourmalines, ceramics, barium, titanate,  $\text{BaTiO}_3$ , lead zirconate, titanate PZT, zinc oxide, aluminum nitride, or polyvinylidene fluorides.

[383] Figure 25 shows another apparatus of this invention that include a concave groove **2530** between a probe couple, in the bottom or ceiling of the channel. When a biological subject **2510** passes through, the concave **2530** can selectively trap the biological subject with particular geometric characteristics and makes the probing more efficiently. The shape of concave's projection can be rectangle, polygon, ellipse, or circle. The probe could detect electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, physical, or mechanical properties. Similarly, the trench width can be, e.g., from 1 nm to 1 mm. Figure 25(a) is an up-down view of this apparatus, Figure 25(b) is a side view, whereas Figure 25(c) is a perspective view.

[384] Figure 26 is another apparatus of this invention that also includes concave grooves **2630** (of a different shape from those shown in Figure 25) on the bottom or ceiling of the channel. When a biological subject **2610** passes through, the concave grooves **2630** will generate a turbulent fluidic flow, which can selectively trap the micro-biological subjects with particular geometric characteristics. The probe could detect electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, physical, or mechanical properties. The depth of the concave groove can be, e.g., from 10 nm to 1 mm, and the channel width can be, e.g., from 1 nm to 1 mm.

[385] Figure 27 illustrated an apparatus of this invention with a stepped channel **2710**. When a biological subject **2701** passes through the channel **2710**, probe couples of different distances can be used to measure different microscopic properties, or even the same microscopic at different sensitivity at various steps (**2720**, **2730**, **2740**) with probe aside each step. This mechanism can be used in the phase lock-in application so that signal for the same microscopic property can be accumulated. The probes can detect or measure microscopic electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, physical, or mechanical properties.

[386] Figure 28 illustrates another apparatus of this invention with thermal meters **2830**. It includes a channel, a set of probes **2820**, and a set of thermal meters **2830**. The thermal meters **2830** can be an infrared sensor, a transistor sub-threshold leakage current tester, or thermister.

[387] Figure 29 illustrates a specific apparatus of this invention which includes carbon a nano-tube **2920** with a channel **2910** inside, probes **2940** which can detect microscopic electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, physical, or mechanical properties. The carbon nano-tube **2920** as shown contains a double-helix DNA molecule **2930**. The carbon nano-tube can force and sense electrical signals by the probes **2940** aside. The diameter of the carbon nano tube diameter can be, e.g., from 0.5 nm to 50 nm, and its length can range from, e.g., 5 nm to 10 mm.

[388] Figure 30 shows an integrated apparatus of this invention that includes a detecting device (shown in Figure 30(a)) and an optical sensor (shown in Figure 30(b)) which can be, e.g., a CMOS image sensor (CIS), a Charge-Coupled Device (CCD), a florescence light detector, or another image sensor. The detecting device comprises at least a probe and a channel, and the image device comprises at least 1 pixel. Figure 30(c-1) and Figure 30(c-2) illustrate the device with the detecting device and optical sensor integrated. As illustrated in Figure 30(d), when biological subjects **3001**, **3002**, **3003** pass through, the probe **3010** in the channel **3020**, its electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, physical, or mechanical property could be detected by the probe **3010** (see Figure 30(e)), meanwhile its image could be synchronously recorded by the optical sensor (Figure 30(f)). Both the probed signal and image are combined together to provide a diagnosis and enhanced detection sensitivity and specificity. Such a detecting device and an optical sensing device can be designed in a system-on-chip or be packaged into one chip.

[389] Figure 31 shows an apparatus with a detecting micro-device (Figure 31(a)) and a logic circuitry (Fig 31(b)). The detecting device comprises at least a probe and a channel, and the logic circuitry comprises an addressor, an amplifier, and a RAM. When a biological subject **3101** passes through the channel, its property could be detected by the probe **3130**, and the signal can be addressed, analyzed, stored, processed, and plotted in real time. Figure 31(c-1) and Figure 31(c-2) illustrate the device with detecting device and Circuitry integrated. Similarly, the detecting device and the integrated circuit can be designed in a System-on-Chip or be packaged into one chip.

[390] Figure 32 shows an apparatus of this invention that comprises a detecting device (Figure 32(a)) and a filter (Figure 32(b)). When a biological subject **3201** passes through the device, a filtration is performed in the filter, and irrelevant objects can be removed. The remaining

subjects' property can then be detected by the probe device (Figure 31(a)). The filtration before probing will enhance the precision of the device. The width of the channel can also range, e.g., from 1 nm to 1 mm.

[391] Figure 33 shows the geometric factors of DNA **3330** such as spacing in DNA's minor groove (**3310**) have an impact on spatial distribution of electrostatic properties in the region, which in turn may impact local biochemical or chemical reactions in the segment of this DNA. By probing, measuring, and modifying spatial properties of DNA (such as the spacing of minor groove) using the disclosed detector and probe **3320**, one may detect properties such as defect of DNA, predict reaction/process at the segment of the DNA, and repair or manipulate geometric properties and therefore spatial distribution of electrostatic field/charge, impacting biochemical or chemical reaction at the segment of the DNA. For example, tip **3320** can be used to physically increase spacing of minor groove **3310**.

[392] Figure 34 shows the fabrication process for a micro-device of this invention that has a flat cover atop of trench to form a channel. This will eliminate the need for coupling two trenches to form a channel, which can be tedious for requiring perfect alignment. The cover can be transparent and allow observation with a microscope. It can comprise or be made of silicon, SiGe, SiO<sub>2</sub>, various types of glass, or Al<sub>2</sub>O<sub>3</sub>.

[393] Figure 35 is a diagram of an apparatus of this invention for detecting a disease in a biological subject. This apparatus includes a pre-processing unit, a probing and detecting unit, a signal processing, and a disposal processing unit.

[394] Figure 36 shows an example of a sample filtration sub-unit in the pre-processing unit, which can separate the cells with different dimensions or sizes. This device comprises at least one entrance channel **3610**, one disturbing fluid channel **3620**, one accelerating chamber **3630**, and two selecting channels (**3640** and **3650**). The angle **3660** between **3620** and **3610** ranges from 0° to 180°.

[395] The biological subject **3601** flows in the x direction from the entrance channel **3610** to the accelerating chamber **3630**. A bio-compatible fluid **3602** flows from disturbing fluid channel **3620** to the accelerating chamber **3630**, it then accelerates the biological subject **3601** in the y-direction. The acceleration correlates with the radius of the biological subject and the larger ones are less accelerated than the smaller ones. Then, the larger and smaller subjects are separated into different selecting channels. Meanwhile, probes can be optionally assembled on the

sidewalls of the channels **3610**, **3620**, **3630**, **3640**, and **3650**. The probes could detect, at the microscopic level, electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, biochemical, electro-mechanical, electro-chemical, electro-chemical-mechanical, physical, or mechanical properties.

[**396**] Figure 37 is a diagram of another example of a sample filtration unit in the apparatus of this invention. **3701** represents small cells, while **3702** represents large cells. When a valve **3704** is open and another valve **3703** is closed, biological subjects (**3701** and **3702**) flow towards exit A. Large cells that have larger size than the filtration hole are blocked against exit A, while small cells are flushed out through exit A. The entrance valve **3704** and exit A valve **3707** are then closed, and a bio-compatible fluid is injected through the fluid entrance valve **3706**. The fluid carries big cells are flushed out from exit B. The larger cells are then analyzed and detected in the detection part of the invention.

[**397**] Figure 38 is a diagram of a pre-processing unit of an apparatus of this invention. This unit includes a sample filtration unit, a recharging unit or system for recharging nutrient or gas into the biological subject, a constant pressure delivery unit, and a sample pre-probing disturbing unit.

[**398**] Figure 39 is a diagram of an information or signal processing unit of an apparatus of this invention. This unit includes an amplifier (such as a lock-in amplifier) for amplifying the signal, an A/D converter, and a micro-computer (e.g., a device containing a computer chip or information processing sub-device), a manipulator, a display, and network connections.

[**399**] Figure 40 shows the integration of multiple signals which results in cancellation of noise and enhancement of signal/noise ratio. In this figure, a biological **4001** is tested by Probe 1 during  $\Delta t$  between **t1** and **t2**, and by Probe 2 during  $\Delta t$  between **t3** and **t4**. **4002** is **4001**'s tested signal from Probe 1, and **4003** is from Probe 2. Signal **4004** is the integration result from signal **4002** and **4003**. The noise cancels out each other in certain extent and results in an improved signal strength or signal/noise ratio. The same principle can be applied to data collected from more than more than 2 micro-devices or probing units.

[**400**] Figure 41 shows one embodiment of the fabrication processes flow of this invention for manufacturing a detection device with at least one detection chamber and at least one detector. In this example, following an optional process flow of fabricating data storage, data processing and analyzing components (including transistors, memory devices, logic circuits, and RF

devices), a material **4122** is first deposited onto a substrate **4111**, followed by the deposition of another material **4133** (material for future detectors). Material **4133** can be selected from electrically conductive materials, piezo-electric materials, semiconductor materials, thermal sensitive materials, ion emission sensitive materials, pressure sensitive materials, mechanical stress sensitive materials, or optical materials. Optionally, it can also consist of composite materials or a desired material stack. If required, an integrated detector with a set of sub-components can be placed at this level. Material **4133** is next patterned using lithography and etch processes, forming a set of desired features shown in Figure 41(c). Another material **4144** is subsequently deposited, which can be the same as or different from material **4122**. Material **4122** can be an electrically insulating material such as oxide (SiO<sub>2</sub>), doped oxide, silicon nitride, or polymer material. Next, the material **4144** is optionally planarized using polishing (e.g., using chemical mechanical polishing) or etch back process. The material stack is then patterned using lithography and etch processes, stopping on substrate **4111**. Finally, as shown in Figure 41(g), a capping layer or the surface of another component **4155** is placed on top of the material stack (thereby sealing or capping it), forming an enclosed detection chamber **4166** with detector **4177** for biological sample detection.

[401] Figure 42 illustrates another embodiment of the fabricating method of this invention for manufacturing a detection device with enclosed detection chambers, detectors, and channels for transporting biological samples such as fluidic samples. In this embodiment, following an optional process flow of fabricating data storage, data processing and analyzing components (including transistors, memory devices, logic circuits, and RF devices), a material **4222** is first deposited onto a substrate **4211**, followed by the deposition of another material **4233** (material for future detectors). Material **4233** can be selected from electrical conductive materials, piezo-electric materials, semiconductor materials, thermal sensitive materials, ion emission sensitive materials, pressure sensitive materials, mechanical stress sensitive materials, or optical materials. Optionally, it can also include composite materials or a desired material stack. If required, an integrated detector with a set of sub-components can be placed at this level.

[402] Materials **4222** and **4233** are subsequently patterned using lithography and etch processes (Figure 42(c)). These two layers (**4222** and **4233**) can be patterned in separate patterning processes sequentially, or can be patterned in the same process, pending on device design, types of materials and etch chemistries. Substrate **4211** is next etched as shown in Figure 42(d),

forming a recessed area (cavity) in **4211**, in which stacks **4222** and **4233** can be used as a hard mask during the etch process.

[403] A material **4244** is deposited into the recessed area, and the portion of the material **4244** above the material **4233** is removed using a polishing (chemical or mechanical) or etch back process. Material **4244** can be selected from oxide, doped oxide, silicon nitride, and polymer materials. A layer **4255** is then deposited onto material **4244** and patterned to form small holes at selected locations. A wet or vapor etch is utilized next to remove material **4244**, forming an enclosed detection chamber **4266**.

[404] Optionally, as shown in Figure 42(i), the material **4222** is also removed using wet or vapor etch process, forming channels **4288** connecting various detection chambers, thus forming detection chambers with a detector **4277** lined with the walls of the detection chamber and with gaseous or fluidic biological samples flowing through the chambers. Finally, the top surface of the detection chamber is sealed with another layer of material (e.g., **4255**).

[405] Figure 43 shows a novel disease detection method of this invention in which at least one probe object is launched at a desired speed and direction toward a biological subject, resulting in a collision. The response(s) by the biological subject during and/or after the collision is detected and recorded, which can provide detailed and microscopic information on the biological subject such as weight, density, elasticity, rigidity, structure, bonding (between different components in the biological subject), electrical properties such as electrical charge, magnetic properties, structural information, and surface properties. For example, for a same type of cell, it is expected that a cancerous cell will experience a smaller traveling distance after the collision than that of a normal cell due to its denser, greater weight, and possibly larger volume. As shown in Figure 43(a), a probe object **4311** is launched towards a biological subject **4322**. After the collision with the probe object **4311**, the biological subject **4322** may be pushed (scattered) out a distance depending on its properties as shown Figure 43(b).

[406] Figure 43(c) shows a schematic of a novel disease detection device with a probe object launch chamber **4344**, an array of detectors **4333**, a probe object **4322** and a biological subject to be tested **4311**. In general, a test object can be an inorganic particle, an organic particle, a composite particle, or a biological subject itself. The launch chamber comprises a piston to launch the object, a control system interfaced to an electronic circuit or a computer for instructions, and a channel to direct the object.



[407] Figure 44 illustrates a novel fabrication process for forming multiple components with different materials at the same device level. First, a first material **4422** is deposited onto a substrate **4411** (see Figure 44(a)), followed by the deposition of a second material **4433**. The second material **4433** is next patterned to form at least a portion of recessed area in the layer **4433**, using lithography and etch processes (see Figure 44(c)). A third material **4444** is subsequently deposited. The third material can be the same as or different from the second material **4422**.

[408] The third material directly above the second material is removed via etch back and/or polishing (such as chemical mechanical polishing) processes (see Figure 44(e)). Optionally, the third material is next patterned to form at least a portion of recessed area in layer **4444** (Figure 44(f)). A fourth material **4455** is then deposited. Optionally, the portion of the fourth material **4455** directly above the third material **4444** or above both the second and third materials is removed via etch back and/or polishing (such as chemical mechanical polishing). The above process can keep repeating to form multiple features with the same or different materials at the same device level. Hence, this process flow forms at least two components **4466** and **4477** with different materials or the same materials at the same device level. For example, in one embodiment, one component can be used as a prober and the other can be used as a detector.

[409] Figure 45 illustrates a method for detecting a disease in a biological subject. A biological subject **4501** passes through the channel **4531** at a speed  $v$ , and probe **4511** is a probe which can grossly detect the properties of the biological subject at high speed.

[410] Probe **4512** is a fine probing device which is coated by a piezo-electric material. There is a distance  $\Delta L$  between probe **4511** and probe **4512**.

[411] When the biological subjects are tested when getting through **4511**, if the entity is identified to be a suspected abnormal one, the system would trigger the piezo-electric probe **4512** to stretch into the channel and probe particular properties after a time delay of  $\Delta t$ . And probe **4512** retracts after the suspected entity passed through.

[412] The probing device is capable of measuring at the microscopic level an electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, electro-mechanical, electro-chemical, electro-chemical-mechanical, bio-chemical, bio-mechanical, bio-electro-mechanical, bio-electro-chemical, bio-electro-chemical-mechanical, physical or mechanical property of the biological subject.

[413] The width of the micro-channel can range from about 1 nm to about 1 mm.

[414] Figure 46 shows a process of detecting a disease in a biological subject. A biological subject **4601** passes through the channel **4631** at a speed  $v$ . Probe **4611** is a probe which can grossly detect the properties of the biological subject at high speed. **4621** and **4622** are piezo-electric valves to control the micro-channel **4631** and **4632**. **4612** is a fine probing device which can probe biological properties more particularly. **4631** is flush channel to rush out normal biological subjects. **4632** is detection channel where the suspected entities are fine detected in this channel.

[415] When a biological subject is tested while getting through **4611**, if it is normal, the valve **4621** of the flush channel is open, while the detection channel valve **4622** is closed, the biological subject is flushed out without a time-consuming fine detection.

[416] When the biological subject is tested while getting through **4611**, if it is suspected to be abnormal or diseased, the valve **4621** of the flush channel is closed, while the detection channel valve **4622** is open, the biological subject is conducted to the detection channel for a more particular probing.

[417] The width of the micro-channel can range from about 1 nm to about 1 mm.

[418] The probing device is capable of measuring at the microscopic level an electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, electro-mechanical, electro-chemical, electro-chemical-mechanical, bio-chemical, bio-mechanical, bio-electro-mechanical, bio-electro-chemical, bio-electro-chemical-mechanical, physical or mechanical property of the biological subject.

[419] Figure 47 illustrates an arrayed biological detecting device. As shown in Figure 47(a), **4701** are arrayed micro-channels which can get through the fluidics and biological subjects. **4702** are probing devices embedded aside the channels. The sensors are wired by bit-lines **4721** and word-lines **4722**. The signals are applied and collected by the decoder R\row-select **4742** and decoder column select **4741**. As illustrated in Figure 47(b), the micro-channel arrayed biological detecting device **4700** can be embedded in a macro-channel **4701**. The micro-channel's dimension ranges from about 1  $\mu\text{m}$  to about 1 mm. The shape of the micro-channel can be rectangle, ellipse, circle, or polygon.

[420] The probing device is capable of measuring at the microscopic level an electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, electro-mechanical, electro-

chemical, electro-chemical-mechanical, bio-chemical, bio-mechanical, bio-electro-mechanical, bio-electro-chemical, bio-electro-chemical-mechanical, physical or mechanical property of the biological subject.

[421] Figure 48 illustrates a device of the current invention for disease detection. 4801 is inlet of the detecting device, and 4802 is the outlet of the device. 4820 is the channel where the biological subjects pass through. 4811 is the optical component of the detecting device.

[422] As illustrated in Figure 48(b), the optical component 4811 consists of an optical emitter 4812 and an optical receiver 4813. The optical emitter emits an optical pulse (e.g. laser beam pulse), when the biological subject 4801 passing through the optical component, and the optical sensor detects the diffraction of the optical pulse, then identify the morphology of the entity.

[423] Figure 49 shows a schedule for fabricating a piezo-electric micro-detector of this invention. Particularly, in Figure 49(a), a substrate 4901 is deposited sequentially with a wet etching stop layer 4902 of material A, and with a sacrificial layer 4903 of material B. The sacrificial layer 4903 is then patterned by the lithography and etching processes. Shown in Figure 49(b), a layer 4904 of piezo-electric material C is then deposited onto the surface of the sacrificial layer 4903, and then planarized. As shown in Figure 49 (c), the layer 4904 is then patterned by lithography and etching processes. A second sacrificial layer 4905 (which can be the same as or different from material B) and a second wet etching stop layer 4906 (which can be the same as or different from material A) are subsequently deposited, as shown in Figure 49(d) and Figure 49(e). A patterning process using lithography and etching is performed through layers 4906 and 4905, and etching is stopped on the piezo-electric layer 4904. It is followed by depositing a conductive layer 4907 of material D is deposited, and then patterning the conductive layer. See Figure 49(g). A patterning process is then followed and the etching stopped on the substrate, thereby forming a trench. See Figure 49(h). An isotropic wet etch selective to material B is then followed, giving rise to a piezo-electric probe (a cantilever) 4908. See Figure 49(i).

[424] Figure 50 shows an example of the micro-device of this invention packaged and ready for integration with a sample delivery system and data recording device. As illustrated in Figure 50(a), the device 5001 is fabricated by micro-electronics processes described herein and has at least a micro-trench 5011, a probe 5022, and a bonding pad 5021. The surface of the device's top layer can include SixOyNz, Si, SixOy, SixNy, or a compound containing the elements of Si,

O, and N. Component **5002** is a flat glass panel. In Figure 50(b), the flat panel **5002** is shown to be bonded with micro-device **5001** on the side of micro-trench. The bonding can be achieved by a chemical, thermal, physical, optical, acoustical, or electrical means, or any combination thereof. Figure 50(c) shows a conductive wire being bonded with the bonding pad from the side of the pads. As illustrated in Figure 50(d), the device **5001** is then packaged in a plastic cube with only conducting wires exposed. In Figure 50(e), a conical channel **5020** is carved through packaging material and connecting the internal channel of the device. As illustrated in Figure 50(f), the larger opening mouth of the conical channel makes it operational and convenient to mount a sample delivery injector with the device, thereby better enabling the delivery of sample from an injector with relatively large size of injector needle into device with relatively small channels.

[425] Figure 51 shows another example of the micro-device of this invention packaged and ready for integration with a sample delivery system and data recording device. As shown in Figure 51(a), a micro-device **5100** is fabricated by one or more micro-electronics processes as described in International Application No. PCT/US2011/042637, entitled "Apparatus for Disease Detection." The micro-device **5100** has at least a micro-trench **5104**, a probe **5103**, a connecting port **5102**, and a bonding pad **5105**. On the top of the micro-device **5100**, the surface layer comprises SixOyNz, Si, SixOy, SixNy, or a compound consisting of Si, O, and N. The surface layer can be covered, and thus the micro-device **5100** is mounted, with a flat glass panel **5101**. See Figure 51(b). The mounting can be by a chemical, thermal, physical, optical, acoustical, or electrical means. As shown in Figure 51(c), the conductive wire is bonded with bonding pad from the side of the pads. Figure 51(d) illustrates that the micro-device **5100** can then be packaged in a cube with only conducting wires exposed. The packaging cube can comprise a packaging material such as plastic, ceramic, metal, glass, or quartz. As shown in Figure 51(e), a tunnel **5141** is then drilled into the cube until the tunnel reaches the connecting port **5102**. Further, as shown in Figure 51(f), the tunnel **5141** is then being connected to other pipes which can delivery a sample to be tested into the micro-device **5100**, and flush out the sample after the sample is tested.

[426] Figure 52 shows yet another example of the micro-device of this invention packaged and ready for integration with a sample delivery system and data recording device. As illustrated in Figure 52(a), device **5200** is a micro-fluidic device which has at least one micro-channel **5201**. **5203** is a pipe that conducts a fluidic sample. The micro-channel **5201** and the conducting pipe

5203 are aligned and submerged in a liquid, for example, water. Figure 52(b) illustrates that, when the temperature of the liquid in which the micro-device and conducting pipe are submerged, is decreased to its freezing point or lower, the liquid solidifies into a solid 5204. As illustrated in Figure 52(c), while the temperature of the liquid is maintained below the freezing point, the combination (including the solid 5204, the conducting pipe 5203, and the device 5200) is enclosed into a packaging material 5205 whose melting temperature is higher than that of the solid 5204, with only the conducting pipe exposed. Figure 52(d) shows that, after the temperature is increased above the melting point of the solid 5204, the solid material 5204 melts and becomes a liquid and is then exhausted from the conducting pipe 5203. The space 5206 wherein the solid material 5204 once filled is now available or empty, and the channel 5201 and the conducting pipe 5203 are now connected through and sealed in the space 5206.

[427] While for the purposes of demonstration and illustration, the above cited novel, detailed examples show how microelectronics and/or nano-fabrication techniques and associated process flows can be utilized to fabricate highly sensitive, multi-functional, powerful, and miniaturized detection devices, the principle and general approaches of employing microelectronics and nano-fabrication technologies in the design and fabrication of high performance detection devices have been contemplated and taught, which can and should be expanded to various combination of fabrication processes including but not limited to thin film deposition, patterning (lithography and etch), planarization (including chemical mechanical polishing), ion implantation, diffusion, cleaning, various materials, combination of processes and steps, and various process sequences and flows. For example, in alternative detection device design and fabrication process flows, the number of materials involved can be fewer than or exceed four materials (which have been utilized in the above example), and the number of process steps can be fewer or more than those demonstrated process sequences, depending on specific needs and performance targets. For example, in some disease detection applications, a fifth material such as a biomaterial-based thin film can be used to coat a metal detection tip to enhance contact between the detection tip and a biological subject being measured, thereby improving measurement sensitivity.

[428] Applications for the detection apparatus and methods of this invention include detection of diseases (e.g., in their early stage), particularly for serious diseases like cancer. Since cancer cell and normal cell differ in a number of ways including differences in possible microscopic properties such as electrical potential, surface charge, density, adhesion, and pH, novel micro-

devices disclosed herein are capable of detecting these differences and therefore applicable for enhanced capability to detect diseases (e.g., for cancer), particularly in their early stage. In addition micro-devices for measuring electrical potential and electrical charge parameters, micro-devices capable of carrying out mechanical property measurements (e.g., density) can also be fabricated and used as disclosed herein. In mechanical property measurement for early stage disease detection, the focus will be on the mechanical properties that likely differentiate disease or cancerous cells from normal cell. As an example, one can differentiate cancerous cells from normal cells by using a detection apparatus of this invention that is integrated with micro-devices capable of carrying out micro-indentation measurements.

[429] Although specific embodiments of this invention have been illustrated herein, it will be appreciated by those skilled in the art that any modifications and variations can be made without departing from the spirit of the invention. The examples and illustrations above are not intended to limit the scope of this invention. Any combination of detection apparatus, micro-devices, fabrication processes, and applications of this invention, along with any obvious their extension or analogs, are within the scope of this invention. Further, it is intended that this invention encompass any arrangement, which is calculated to achieve that same purpose, and all such variations and modifications as fall within the scope of the appended claims.

[430] All the features disclosed in this specification (including any accompanying claims, abstract and drawings) may be replaced by alternative features serving the same, equivalent or similar purpose, unless expressly stated otherwise. Thus, unless expressly stated otherwise, each feature disclosed is one example of a generic series of equivalent or similar features.

#### **Other Embodiments**

[431] It is to be understood that while the invention has been described in conjunction with the detailed description thereof, the foregoing description is intended to illustrate and not limit the scope of the invention, which is defined by the scope of the appended claims. Other aspects, advantages, and modifications are within the scope of the following claims

**What Is Claimed Is:**

1. A micro-device comprising a piezo-electric material part of which forms a probe with a supporting point in the micro-device, an electronically conductive material, a material that is neither piezo-electric nor electronically conductive, wherein the piezo-electric material is placed between the electrically conductive material and the material that is neither piezo-electric nor electronically conductive, and the micro-device is configured to detect, at the microscopic level, a property of a biological subject to be detected.
2. The micro-device of claim 1, wherein a portion of the piezo-electric probe is extending out of the supporting point and the extending part is substantially free and surrounded, without contact, by the other materials in the micro-device.
3. The micro-device of claim 2, wherein the extending piezo-electric probe is in the shape of a layer or a stick with a minimum length of one angstrom.
4. The micro-device of claim 2, wherein the extending piezo-electric probe has an axel that is essentially parallel to the surface of the substrate.
5. The micro-device of claim 2, wherein the extending part of the piezo-electric probe detects, at the microscopic level, a property of the biological subject to be detected; optionally the piezo-electric probe expands when it detects an electric property from the biological subject to be tested or it is applied with a desired voltage, or the piezo-electric probe gives rise to an electric currency when it detects a mechanical stress.
6. The micro-device of claim 1, wherein the electronically conductive material is connected to the piezo-electric material and is configured to deliver a signal from the piezo-electric probe to a measuring or recording device connected to the micro-device.
7. The micro-device of claim 1, wherein the piezo-electric probe stretches or contracts when it is applied with a desired voltage.
8. The micro-device of claim 1, wherein the piezo-electric probe converts a mechanical force applied on it into an electric signal proportional to the strength of the force.
9. The micro-device of claim 1, wherein the piezo-electric material comprises a crystal, ceramics, zinc oxide, aluminum nitride, polyvinylidene fluoride, lithium tantalite, lanthanum gallium silicate, or potassium sodium tartrate.
10. The micro-device of claim 9, where the crystal comprises tourmaline, topaz, quartz, Rochelle salt, Berlinite, or gallium orthophosphate.

11. The micro-device of claim 9, wherein the ceramics comprises BaTiO<sub>3</sub>, KNbO<sub>3</sub>, Ba<sub>2</sub>NaNb<sub>5</sub>O<sub>5</sub>, LiNbO<sub>3</sub>, SrTiO<sub>3</sub>, Pb(ZrTi)O<sub>3</sub>, Pb<sub>2</sub>KNb<sub>5</sub>O<sub>15</sub>, LiTaO<sub>3</sub>, BiFeO<sub>3</sub>, or Na<sub>x</sub>WO<sub>3</sub>.
12. The micro-device of claim 1, wherein the electronically conductive material comprise an electric conductor or semiconductor.
13. The micro-device of claim 12, wherein the electric conductor comprises a metal, or graphite; and the semiconductor comprises a single crystal, poly crystal, or ceramics.
14. The micro-device of claim 1, wherein the material that is neither piezo-electric nor electronically conductive, is a wet etching stop material which has relatively slower etch rate than that of the material intended to be removed.
15. The micro-device of claim 1, wherein the micro-device is fabricated by a process comprising microelectronics technologies.
16. The micro-device of claim 15, wherein the micro-device has at least one channel that has at least a first end and a second end, is defined by the walls of one or more of the materials constituting the micro-device, and is formed as a result of the fabrication process; and the biological subject to be tested travels through the channel from its first end to its second end.
17. The micro-device of claim 16, further comprising a packaging or protective material which wraps around the other materials constituting the micro-device, the packaging or protective has at least an inlet and an outlet, the inlet connects with the first end of the channel, and the outlet connects with the second end of the channel.
18. The micro-device of claim 17, wherein the inlet comprises at least one opening defined by the inner wall of the packaging or protective material for transporting the biological subject to be tested from an outside injector into the micro-device.
19. The micro-device of claim 18, wherein the inlet has a tapering figure with a bigger end and a smaller end, the bigger end is on the external surface of the packaging material and connected to the outside injector of the biological subject, the smaller end is connected to first end of the channel of micro-device.
20. The micro-device of claim 19, wherein the inlet is sealed by a process comprising:
  - applying a first sealing material with a substantially high viscosity to seal seams and cracks between the smaller end of the inlet and the first end of the channel of the micro-device;
  - applying a second sealing material with a lower viscosity on top of the first sealing material and its surrounding area; and



optionally heating the first and second sealing materials to facilitate the sealing process.

21. The micro-device of claim 20, wherein the first sealing material is a solid.
22. The micro-device of claim 20, wherein the second sealing material comprises a polymeric material, an epoxy, a glue film, or a solution thereof.
23. The micro-device of claim 20, wherein heating causes the temperature of the first and second sealing materials to be above 40 °C.
24. The micro-device of claim 16, further comprising conductive wires or cables that are connecting the piezo-electric probe and an external data processor, through one or more of the materials constituting the micro-device.
25. The micro-device of claim 24, wherein the one or more materials connecting the piezo-electric probe and the external data process comprise  $\text{SixOyNz}$ , Si,  $\text{SixOy}$ ,  $\text{SixNy}$ , or a compound comprising the chemical elements of Si, O, and N.
26. The micro-device of claim 16, further comprising a flat panel atop of the channel, wherein the flat panel is part of the defining walls of the channel, and the flat panel comprises silicon, SiGe,  $\text{SiO}_2$ ,  $\text{Al}_2\text{O}_3$ , acrylate polymer, AgInSbTe, synthetic alexandrite, arsenic triselenide, arsenic trisulfide, barium fluoride, CR-39, cadmium selenide, caesium cadmium chloride, calcite, calcium fluoride, chalcogenide glass, gallium phosphide, GeSbTe, germanium, germanium dioxide, glass code, hydrogen silsesquioxane, Iceland spar, liquid crystal, lithium fluoride, lumicera, METATOY, magnesium fluoride, agnesium oxide, negative index metamaterials, neutron super mirror, phosphor, picarin, poly(methyl methacrylate), polycarbonate, potassium bromide, sapphire, scotophor, spectralon, speculum metal, split-ring resonator, strontium fluoride, yttrium aluminum garnet, yttrium lithium fluoride, yttrium orthovanadate, ZBLAN, zinc selenide, or zinc sulfide.
27. The micro-device of claim 16, wherein the packaging or protecting material is applied to the micro-device by using a polymeric casing.
28. The micro-device of claim 1, wherein the biologic subject to be tested comprises blood, sweat, urine, saliva, cells, protein, DNA, RNA, or a biological tissue sample.
29. The micro-device of claim 1, wherein the micro-device further comprises one detector.
30. The micro-device of claim 29, wherein the detector is an acoustic signal receiver and is configured to detect an acoustic signal.

31. The micro-device of claim 29, wherein the micro-device further comprises an additional probe that can be piezo-electric or non piezo-electric.
32. The micro-device of claim 31, wherein the additional probe is an acoustic transducer and is configured to generate an acoustic signal.
33. The micro-device of claim 31, wherein the additional probe contacts the biological subject to be tested and causes the biological subject to respond by generating a signal.
34. The micro-device of claim 33, wherein the signal generated by the biological is delivered to and detected by the detector.
35. The micro-device of claim 29, wherein the micro-detector comprises a sensor that detects, at the microscopic level, an electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, physical, or mechanical property of the object to be detected.
36. The micro-device of claim 35, wherein the electrical property is surface charge, surface potential, resting potential, electrical current, electrical field distribution, electric dipole, electric quadruple, three-dimensional electrical or charge cloud distribution, electrical properties at telomere of DNA and chromosome, or impedance.
37. The micro-device of claim 35, wherein the thermal property is temperature, or vibrational frequency of a biological item or molecules.
38. The micro-device of claim 35, wherein the optical property is optical absorption, optical transmission, optical reflection, optical-electrical property, brightness, or fluorescent emission.
39. The micro-device of claim 35, wherein the chemical property is pH, acidity, chemical reaction, bio-chemical reaction, bio-electro-chemical reaction, reaction speed, reaction energy, oxygen concentration, oxygen consumption rate, ionic strength, catalytic behavior, or bonding strength.
40. The micro-device of claim 35, wherein the physical property is density or geometric size.
41. The micro-device of claim 35, wherein the acoustic property is frequency, speed of acoustic waves, acoustic frequency and intensity spectrum distribution, acoustic intensity, acoustical absorption, or acoustical resonance.
42. The micro-device of claim 35, wherein the mechanical property is internal pressure, hardness, shear strength, elongation strength, fracture stress, adhesion, mechanical resonance frequency, elasticity, plasticity, or compressibility.

**43.** A method for detecting a mechanical or electric property of a biological subject, comprising:

providing a piezo-electric micro-device comprising a piezo-electric material forming a probe with a supporting point in the micro-device, an electronically conductive material, a material that is neither piezo-electric nor electronically conductive, wherein the piezo-electric material is placed between the electronically conductive material and the material that is neither piezo-electric nor electronically conductive; and

contacting the piezo-electric micro-device with the biological subject to be detected, wherein the piezo-electric micro-device detects the mechanical, acoustical, or electric property of the biological subject upon contacting it and converts the mechanical, acoustical, or electric property to generate an electric or mechanical response, and transferring the electric, acoustical, or mechanical response thus generated through the electrically conductive material to a recording device or data analyzer.

**44.** The method of claim 43, further comprising using a cleaning fluid to remove biological residues or deposits of the biological subject.

**45.** The method of claim 43, wherein the micro-device further comprises one detector.

**46.** The method of claim 45, wherein the detector is an acoustic signal receiver and is configured to detect an acoustic signal.

**47.** The method of claim 45, wherein the micro-device further comprises an additional probe that can be piezo-electric or non piezo-electric.

**48.** The method of claim 47, wherein the additional probe is an acoustic transducer and is configured to generate an acoustic signal.

**49.** The method of claim 48, wherein the additional probe contacts the biological subject to be tested and causes the biological subject to respond by generating a signal.

**50.** The method of claim 49, wherein the signal generated by the biological is delivered to and detected by the detector.

**51.** The method of claim 47, further comprising the following steps:

applying an input signal to the probe to generate an acoustic signal;  
scanning the frequency range of the acoustic signal;

contacting the probe with the biological subject, thereby launching the acoustic signal to the biological subject and causing the biological subject to generate a response signal which is then detected by the detector;

recording the response signal detected by the detector as a function of the frequency of the acoustic signal launched by the probe;

optionally amplifying the recorded signal by the detector;

optionally amplifying the recorded signal by the detector using a lock-in amplifier;

optionally filtering out noise in the recorded signal by the detector unsynchronized to the input acoustic signal by the probe;

optionally analyzing the recorded signal; and

reaching a diagnosis conclusion.

**52.** The method of claim 51, wherein the input signal is a pulsed or modulated acoustic signal.

**53.** The method of claim 51, wherein the response signal is recorded for its resonant frequency or acoustic intensity, or frequency versus intensity spectrum of the biological system and its immediate surrounding.

**54.** A method for fabricating a piezo-electric micro-device, comprising:

providing a substrate;

depositing a first material onto the substrate;

optionally planarizing the first material;

depositing a second material onto the first material; wherein the second material is neither piezo-electric nor electrically conductive;

patterning the second material to create at least one recessed area in the second material;

depositing a third, piezo-electric material on the second material to fill its recessed area in the second material and cover the second material;

patterning the third, piezo-electric material to create at least one recessed area in the piezo-electric material;

depositing a fourth material onto the third, piezo-electric material to fill its recessed area and optionally to cover the third, piezo-electric material; wherein the fourth material can be the same as or different from the second material, and the fourth material is neither piezo-electric nor electrically conductive;

optionally patterning the fourth material to give it a certain configuration;

optionally depositing a fifth material onto the optionally patterned fourth material, wherein the fifth material can be the same as or different from the first material, the fifth material is different from the fourth material, and the fifth material is neither piezo-electric nor electrically conductive;

patterning the fourth material and the optional fifth material to create an opening that exposes the third, piezo-electric material thus forming a piezo-electric probe;

depositing a sixth, electrically conductive material to fill the opening in the fourth material and optional fifth material, and optionally covering part of the fifth material;

patterning all the materials above the substrate to expose all the materials, and

patterning the second and fourth materials sandwiching the piezo-electric material to expose at least part of the piezo-electric material.

**55.** The method of claim 54, further comprising depositing, patterning, cleaning, or planarizing one or more additional materials to form additional features, structures, and functionalities, wherein each of the additional materials can be the same or different from one of the earlier deposited materials, provided that the two materials that are deposited consecutively are not the same.

**56.** The method of claim 54, wherein the first material is a wet etch stop material.

**57.** The method of claim 54, wherein the fifth material is a wet etch stop material.

**58.** The method of claim 54, wherein the patterning process comprises lithography and etching processes.

**59.** The method of claim 54, wherein one end of the patterned piezo-electric probe is supported and connected to the body of the micro-device and the remainder of the piezo-electric probe is extending away from the support.

**60.** The method of claim 59, wherein the extending piezo-electric probe can be in the shape of cylinder, slab, rectangle, cone, cube, or cuboid.

**61.** The method of claim 59, wherein the extending piezo-electric probe has an axis that is essentially parallel to the surface of the substrate.

**62.** The method of claim 54, wherein the piezo-electric material stretches when it is applied with an electric voltage, or gives rise to an electric signal when it is disturbed with a mechanical force.

- 63.** The method of claim 54, wherein the piezo-electric material comprises a crystal, ceramics, zinc oxide, aluminum nitride, polyvinylidene fluoride, lithium tantalite, lanthanum gallium silicate, or potassium sodium tartrate.
- 64.** The method of claim 63, where the crystal comprises tourmaline, topaz, quartz, Rochelle salt, Berlinite, or gallium orthophosphate.
- 65.** The method of claim 63, wherein the ceramics comprises  $\text{BaTiO}_3$ ,  $\text{KNbO}_3$ ,  $\text{Ba}_2\text{NaNb}_5\text{O}_{15}$ ,  $\text{LiNbO}_3$ ,  $\text{SrTiO}_3$ ,  $\text{Pb}(\text{ZrTi})\text{O}_3$ ,  $\text{Pb}_2\text{KNb}_5\text{O}_{15}$ ,  $\text{LiTaO}_3$ ,  $\text{BiFeO}_3$ , or  $\text{Na}_x\text{WO}_3$ .
- 66.** The method of claim 54, wherein the electronically conductive material comprises an electric conductor or semiconductor.
- 67.** The method of claim 66, wherein the electric conductor comprises a metal or graphite, and the semiconductor comprises a crystal, poly crystal, or ceramics.
- 68.** A method for fabricating a micro-device, comprising depositing various materials on a substrate and, in the interims of depositing every two materials, patterning some or all of the deposited materials by a microelectronic process, wherein at least one of the various materials is a piezo-electric material, the two materials that are consecutively deposited are different, and the micro-device is configured to measure at the microscopic level an electric, magnetic, electromagnetic, thermal, optical, acoustical, biological, chemical, electro-mechanical, electro-chemical, electro-chemical-mechanical, bio-chemical, bio-physical, bio-physical-chemical, physical-chemical, bio-mechanical, bio-electro-mechanical, bio-electro-chemical, bio-electro-chemical-mechanical, physical, or mechanical property of a biologic subject with which the micro-device is to contact.
- 69.** The method of claim 68, wherein the microelectronic process comprises deposition, lithography, etch, cleaning, direct-writing, diffusion, ion implantation, cleaning, polishing, planarization, or packaging.




FIGURE 1




FIGURE 2






FIGURE 2 (Cont.)





FIGURE 3



**FIGURE 4**




FIGURE 5




FIGURE 5 (Cont.)




FIGURE 6




FIGURE 7




FIGURE 8






FIGURE 9




FIGURE 10





FIGURE 10 (Cont.)



**FIGURE 11**




FIGURE 11 (Cont.)




FIGURE 12




FIGURE 13




FIGURE 14







FIGURE 15



**FIGURE 15 (Cont.)**




FIGURE 16




FIGURE 17-a




FIGURE 17-b




FIGURE 17-c




FIGURE 18




FIGURE 19






FIGURE 19 (Cont.)




FIGURE 20





FIGURE 21





**FIGURE 23**




FIGURE 24






FIGURE 25




**FIGURE 26**





**FIGURE 27**



**FIGURE 28**




FIGURE 29




FIGURE 30




FIGURE 30 (Cont.)




FIGURE 31




FIGURE 32





FIGURE 33





Detecting device covered with transparent panel

FIGURE 34




FIGURE 35




FIGURE 36







FIGURE 37



**FIGURE 38**



**FIGURE 39**






FIGURE 41






FIGURE 42





FIGURE 42 (Cont.)



(a)

(b)



(c)

FIGURE 43




FIGURE 44




FIGURE 45







FIGURE 47




FIGURE 48






FIGURE 49







FIGURE 49



**FIGURE 50**



**FIGURE 50**



**FIGURE 50**





FIGURE 51



**FIGURE 51**




FIGURE 51








FIGURE 52




(c)




(d)


FIGURE 52



(a)



(b)



(c)