

(12) **UK Patent Application** (19) **GB** (11) **2 348 566** (13) **A**

(43) Date of A Publication **04.10.2000**

(21) Application No **9907319.9**

(22) Date of Filing **31.03.1999**

(71) Applicant(s)
**International Business Machines Corporation
(Incorporated in USA - New York)
Armonk, New York 10504, United States of America**

(72) Inventor(s)
Jeremy Guy Sanders

(74) Agent and/or Address for Service
**IBM United Kingdom Limited
Intellectual Property Department, Mail Point 110,
Hursley Park, WINCHESTER, Hampshire, SO21 2JN,
United Kingdom**

(51) INT CL⁷
H04M 1/27 7/00

(52) UK CL (Edition R)
H4K KBNJ KF42 KOA


(56) Documents Cited
GB 2331197 A GB 2328114 A GB 2317782 A

(58) Field of Search
UK CL (Edition Q) **H4K KBNJ KFH KF42 KF50X KOA**
INT CL⁶ **H04M 1/27 3/42 3/50 7/00**
ONLINE: WPI; EPODOC; JAPIO

(54) Abstract Title
Computer network telephony

(57) A method and apparatus for connecting computer network ip telephones using a voice recognition engine and a ip address database on an Internet server. The method comprises opening a voice channel from an ip phones to a voice recognition server; determining the name of the addressee from a speech input sent over the voice channel to the voice recognition server by the caller; determining an ip address from an ip address database corresponding to the determined addressee's name; opening a data channel from the database and transmitting the ip address to one or other of said telephones; and routing logic on said one or other ip phones using the ip address to establish a connection with the other ip phone. This allows the ip phones to access remote resources of voice recognition and a large database thereby taking advantage of more powerful resources that would be available locally. This is particularly advantageous for pervasive computing devices which have limited resources for storage of ip addresses.

GB 2 348 566 A



1/2

Figure 1




Figure 2

COMPUTER NETWORK TELEPHONY

FIELD OF INVENTION

5 This invention relates to computer network telephony. In particular it relates to making connections between network telephones on a computer network.

BACKGROUND OF INVENTION

10 Although originally intended for the transmission of computer data, more recently computer networks and specifically the Internet has been exploited to provide real time telephony communications. The primary attraction of the Internet for telephony communications is the low charge compared with conventional telephony or the plain old telephone system (POTS). Many Internet users have a dial-up connection to an access provider over a local telephone line, and therefore such users pay only local telephone charges when logged on. Some access providers charge a monthly description, whilst others charge on the basis of connection time (some may do both). However, there is generally no charge associated with actual data transfer over the network. As a result, the effective cost of an international call over the Internet may be no more than that of a local call of the same duration to the access provider. In addition, the fully digital nature of the Internet may potentially offer a richer functionality (e.g. in terms of conference calling) than conventional telephone networks. Internet phones are surveyed in the article "Dial 1-800-Internet" in Byte Magazine, February 1996, pages 83-88 and in the article "Nattering On", in New Scientist, 2 March 1996, pages 38-40.

30 The transmission of voice signals over a packet network is described for example in "Using Local Area Networks for Carrying Online Voice" by D. Cohen, pages 13-21, in "Voice Transmission over an Ethernet Backbone" by P. Ravasio, R. Marcogliese, and R. Novarese, pages 39-65, both in "Local Computer Networks" (edited by P. Ravasio, G. Hopkins, and N. Naffah; North Holland, 1982) and also in GB 2283252. The basic principles of such a scheme are that a first computer digitally samples a voice input signal at a regular rate (eg 8 kHz). A number of samples are then assembled into a data packet for transmission over the network to a second terminal, which then feeds the samples to a loudspeaker or equivalent device for play out, again at a constant 8 kHz rate. Voice transmission over the Internet is substantially similar to transmission over a LAN (which may indeed provide part of the Internet transmission path), but there tends to be less spare bandwidth available on the Internet. As a result, Internet phones normally compress the voice

signal at the transmitting end, and then decompress it at the receiving end.

5 Voice directories for POTS are known. Wildfire is an "Advanced
Voice-Controlled Electronic Assistant". It has various capabilities,
including acting as a "voice dialler" - wherein the user can speak a
telephone number they wish to call into a phone which has a connection to
the Wildfire system - the Wildfire system can perform a transfer to the
10 telephone number requested. Users can also set up to 150 "nicknames" for
commonly used numbers such as "work", "home", "bill", etc. and just ask
Wildfire to "call Bill", for example. Wildfire is not an IP telephony
based product and does not allow for very large numbers of names in a
directory. Furthermore it is an internal company directory which uses a
private branch switch to make connections. For further info, check out
15 <http://www4.wildfire.com>.

Another POTS voice directory, ViaVoice Directory Dialler, prompts
callers for a person's name, requests further information when duplicate
names are encountered and transfers the call to the number which equates
20 with that person's name. It currently has support for up to 250,000
names. It is not an IP telephony based product and uses a private branch
switch based in the company or internal telephone network. For further
info, see [http://www.software.ibm.com/speech/overview/business/
direct.html](http://www.software.ibm.com/speech/overview/business/direct.html).

25 An ip address is a unique identification and uses several bytes of
memory, more memory to store than a nick name or abbreviated address.
This can cause a problem with thin devices with reduced memory capacity.
This problem will become more prominent as the number of telephony
30 addresses in the world rises at the current rate. Furthermore in a few
years time the number of unique address will be reaching a limit and a
new unique format may have to be used using far more numbers and memory.
This is not such a problem for POTS telephones which may use local
telephone numbers or extensions to request connections from switches.
35

Internet telephony uses a transient network of computers to send
discrete packets of data between destinations. Unlike POTS telephones,
the route the voice data take may vary over the course of a conversation,
it is necessary that the network phones themselves have the full address
40 information of the destination available.

SUMMARY OF INVENTION

45 According to one aspect of the invention there is provided a method
of connecting computer network ip telephones: opening a voice channel
from one of said ip phones to a voice recognition server; determining a

name from a speech input sent over the voice channel to the voice
recognition server; determining an ip address from an ip address database
corresponding to the determined name; opening a data channel from the
database and transmitting the ip address to one or other of said
5 telephones; and routing logic on said one or other ip phones using the ip
address to establish a connection with the other ip phone.

This allows the ip phones to access remote resources of voice
recognition and a large database thereby taking advantage of more
10 powerful resources than would be available locally. This is particularly
advantageous for pervasive computing devices which have limited
resources.

The network phone differs from a normal phone in the following
15 manner: it only has a single multipurpose button, has no numeric
identification on it, and plugs into a data network rather than a
telephone line connected to a switch. It may be a virtual device on a
screen rather than an actual physical device. The device has the
capability to set up a voice stream ("telephone call") to another similar
20 device (virtual or physical) on the same data network. The device
receives the address (not number) of the other device from a directory
dialler, to which it will set up a connection whenever the single
multipurpose button is pressed, so that the caller can declare the name
(not number) of the person to whom a call is required and the directory
25 dialler can supply the address to which a connection is to be made. Hence
the addressing logic resides in the directory dialler, but the "switching
logic" lies in the phone itself, which is to say that whereas a telephone
connected to a switch always makes a connection through the switch, the
Numberless LAN phone only makes a connection of its own initiative
30 through the data network. This is already achieved by Internet phones
(e.g., CoolTalk for Netscape). The product may make calls to devices
(phones, Internet phones, other Numberless LAN phones) outside of the
network in which it is able to make connections of its own initiative by
using the directory dialler as a gateway - however this ability is
35 unlikely to effectively differentiate the product, as it is really a
property of the directory dialler/gateway.

Advantageously the voice channel to the voice recognition server is
opened immediately on activation of the said one ip phone. This can be
40 achieved when the phone is taken off the hook. An ip socket is opened
through the voice over ip interface to the remote voice recognition
server. Since no buttons need be pressed by a caller all buttons may be
removed from the phone interface increasing the ease of use and lowering
manufacturing costs.

The voice recognition server may send a voice message requesting the name of the other ip phone or user be spoken into the ip phone. The caller responds and the spoken name transmitted to the voice recognition functionality on the remote server.

5

According to another aspect of the invention there is provided a computer network telephone comprising: voice recognition functionality; a network address database functionality; and a routing module; wherein the voice recognition functionality will determine a name from a spoken name, an ip address will be determined from the database using the name, and the routing logic module will use the ip address to establish a connection with another network telephone.

10

15

Preferably the routing logic module is an integral part of the network telephone and allows the ip phone to route calls directly to other ip phones give their ip address.

20

The voice recognition engine may be provided in a remote server and also the ip address database maybe provided in a remote server. More preferably the ip address database and the voice recognition functionality are provided in the same remote server so that there is minimum communication time between the two functions.

25

30

According to a further aspect of the invention there is provided a network server comprising: a voice recognition engine; an Internet telephony database; a network interface; and a routing module; wherein the voice recognition engine is adapted to perform recognition on a spoken name corresponding to a second network phone, said spoken name is received through the network interface from a first network telephone; an ip address corresponding to the recognised name is located in the Internet telephony database and sent back to the first network phone through the routing module so that a connection may be established between the first and second network phones.

35

40

The intention of the at least the embodiment of the invention is to facilitate the elimination of long telephone numbers, diverse and inflexible numbering plans, and potentially telephone switches themselves. Furthermore is it hoped that telephones with numbered dialpads will eventually be replaced by telephones without a dialpad.

BRIEF DESCRIPTION OF DRAWINGS

45

In order to promote a fuller understanding of this and other aspects of the present invention, an embodiment will now be described, by way of example only, with reference to the accompanying drawings in which:

Figure 1 is a schematic representation of two computer network telephones connected by a computer network; and

Figure 2 shows the method used to connect the network telephones.

5 DETAILED DESCRIPTION OF PREFERRED EMBODIMENT

10 The embodiment comprises a first and second network telephone 13A,B connected to the server 10 via a computer network 11 (see Figure 1). The preferred network is the Internet but the network can be a wide area network or a local area network. The server 10 is connected to the Internet via a network adapter or via an Internet gateway, for example in another server on the LAN. In the embodiment the first and second network telephones 13A,B are connected independently to the Internet.

15 A personal computer set up as a network telephone typically has a microprocessor, semiconductor memory (ROM/RAM), hard disk, and a bus over which data is transferred (not shown). Other components of the computer are a display, keyboard and mouse (not shown). The computer maybe any conventional workstation, such as an Aptiva computer, available from IBM Corporation. Alternatively, any other form of suitable network access device, including the new generation of low-cost systems ('network computers' or 'thin clients' - effectively sub-PCs) which are currently being developed, maybe employed as the client telephone terminal.

25 Each network telephone is equipped with a network adapter card and accompanying software including a routing logic interface 14A,B, voice over ip interface 16A,B and Internet protocol interface 18A,B. The network adapter provides the hardware layer interface directly to the LAN or Internet gateway. Alternatively the Internet is accessed using a modem via an Internet provider. The operation of a network adapter card or modem to provide Internet access is well-known, and so will not be described in detail. The routing logic module 14 provides the mechanism to select the server and other network telephones to receive Internet messages. The voice over ip interface 16A,B provides the mechanism to convert voice signals to and from Internet messages. The Internet protocol module provides the mechanism to set up Internet connections between the server and the network phone to send Internet messages via the connections. Button 24A,B is linked to the routing logic interface 14A,B. On activation of the button 24A, an Internet message is sent between the routing logic module 14A and the directory server 10.

40 An audio card (not shown), for example MWave from IBM Corporation, is connected to the bus and to a headset including microphone 20A,B and earphone 22A,B for audio input and output respectively. Alternatively the network phone may have a loudspeaker, and built-in microphone, but

the use of a headset is preferred to optimise the quality of the audio signal produced and actually heard.

5 The network server 10 is based on a conventional computer work station having a display screen, keyboard, microprocessor, ROM/RAM, disk storage (not shown). The RISC system/6000 workstation, available from the IBM Corporation, is an example. The network server 10 is connected to the Internet via routing logic module 14C, voice over IP interface module 16C and internet protocol interface 18C. The server 10 comprises voice
10 processing functionality 25 and a IP address database 26.

The network phone 13A requires routing information from the directory server 10. When the button 13A is depressed a data message is sent (step 102 - see Figure 2) to check the server 10 is ready. The ip
15 address of the directory server is permanently stored in network phone 13A memory and selected by the routing logic interface 14A so that the IP interface 18A can set up the data channel. Once it is established that the directory server 10 is ready the voice-over ip interface can set up
20 voice channels between the speaker 22A and microphone 20A of the network phone and the directory server 10 (step 104). The caller speaks the name of the recipient intended for the call, i.e. the user of network phone 13B (step 106). The directory server 10 performs speech recognition on the caller's voice to determine the destination of the call (step 108). The server 10 then looks up the address of the recipient (step 110) and
25 passes the address back to phone 13 along the data channel (step 112).

Network phone 13A first "pings" network phone 13B to check that it is available (step 114) , the "ping" is to check that network phone 13B is not already on a call and then connecting to network phone 13B via
30 Voice-over IP (step 116). Network phone 13B rings, and the user of network 13B can accept the call by pressing the button on network phone 13B. The respective users may now have a communication over network phones 13A,B as per a normal POTS call (step 118).

35 Another situation arises when network phone 13A (or B) makes another request to the Directory Server 10 such as a transfer to another phone - "transfer [name of user of network phone 13B] to [another user's name]". This would temporarily leave phone 13B "waiting" for the reconnection of phone 1 (or another user), or the Directory Server if a
40 transfer is to be made to Phones outside the network. If the request is "hang up" (or some shorthand agreed for this such as "ok") then phone 1 is instructed by the Directory Server to send a packet of data to LAN Phone 2 telling it that it has hung up.

45 The Directory Server has a T1/E1 interface 26 to a PBX 28 which is connected to other telephone switches via a POTS telephony network. This

allows network phone users to talk to ordinary telephones using the Directory Server as a Voice-over IP Gateway (the users on ordinary telephones could be referred to by their names if the Directory Server was aware of them, or by their names and telephone numbers if this was the first call to their numbers).

Although the embodiment has been described in terms of the network phone controlling the routing of the connection from the first phone to the second phone, it has been envisaged that the directory server can act as a node in the connection of the first phone to the second phone. In this case the server opens a second channel to the second network phone after the ip address has been located and then connects the first network phone channel with the second network phone channel.

Now that the invention has been described by way of a preferred embodiment, various modifications and improvements will occur to those person skilled in the art. Therefore it should be understood that the preferred embodiment has been provided as an example and not as a limitation.

CLAIMS

1. A method of connecting computer network ip telephones:
opening a voice channel from one of said ip phones to a voice
5 recognition server;
determining a name from a speech input sent over the voice channel
to the voice recognition server;
determining an ip address from an ip address database corresponding
to the determined name;
10 opening a data channel from the database and transmitting the ip
address to one or other of said telephones; and
routing logic on said one or other ip phones using the ip address
to establish a connection with the other ip phone.
- 15 2. A method as claimed in claim 1 whereby the voice channel to the
voice recognition server is opened immediately on activation of the said
one ip phone.
- 20 3. A method as claimed in claim 2 whereby the ip phone is activated
when the phone is taken off the hook.
4. A computer network telephone comprising:
voice recognition functionality;
a network address database functionality; and
25 a routing logic module;
wherein the voice recognition functionality will determine a name
from a spoken name, an ip address will be determined from the database
using the name, and the routing logic module will use the ip address to
establish a connection with another network telephone.
30
5. A computer network telephone as claimed in claim 4 wherein the
routing logic module is an integral part of the network telephone and
allows the ip phone to route calls directly to other ip phones give their
ip address.
35
6. A computer network telephone as claim in claims 4 or 5 wherein the
voice recognition engine is provided in a remote server and also the ip
address database maybe provided in a remote server.
- 40 7. A computer network telephone as claimed in claim 6 wherein the ip
address database and the voice recognition functionality are provided in
the same remote server.
- 45 8. A computer network telephony server comprising:
voice recognition functionality;
network address database functionality; and

routing logic module;

wherein the voice recognition functionality will determine a name from a spoken name sent to the server from a first network telephone, an ip address for a second network phone will be determined from the database using the name, and routing logic will use the ip address to establish a connection between the first and second network telephone.

5



Application No: GB 9907319.9
Claims searched: 1-8

Examiner: Richard Howe
Date of search: 18 May 1999

Patents Act 1977
Search Report under Section 17

Databases searched:

UK Patent Office collections, including GB, EP, WO & US patent specifications, in:

UK Cl (Ed.Q): H4K (KFH, KF42, KBNJ, KF50X, KOA)

Int Cl (Ed.6): H04M (1/27, 3/42, 3/50, 7/00)

Other: Online : wpi; epodoc; japiro

Documents considered to be relevant:

Category	Identity of document and relevant passage	Relevant to claims
A,E	GB 2 331 197 A (Telefonaktiebolaget L M Ericsson) - see abstract	
A	GB 2 328 114 A (Matsushita Electric) - see abstract	
A	GB 2 317 782 A (Matsushita Electric) - see abstract	

X	Document indicating lack of novelty or inventive step	A	Document indicating technological background and/or state of the art.
Y	Document indicating lack of inventive step if combined with one or more other documents of same category.	P	Document published on or after the declared priority date but before the filing date of this invention.
&	Member of the same patent family	E	Patent document published on or after, but with priority date earlier than, the filing date of this application.