



US011020639B2

(12) **United States Patent**
Golden et al.

(10) **Patent No.:** **US 11,020,639 B2**

(45) **Date of Patent:** ***Jun. 1, 2021**

(54) **GOLF CLUB HAVING AN ELASTOMER ELEMENT FOR BALL SPEED CONTROL**

(58) **Field of Classification Search**

CPC A63B 53/0475; A63B 53/0408; A63B 53/0445; A63B 60/54; A63B 53/047
(Continued)

(71) Applicant: **Acushnet Company**, Fairhaven, MA (US)

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,133,129 A 3/1915 Govan
2,111,249 A 3/1938 Plese
(Continued)

(72) Inventors: **Charles E. Golden**, Encinitas, CA (US); **John Morin**, The Woodlands, TX (US); **Oswaldo Gonzalez**, San Jacinto, CA (US); **Jonathan Hebreo**, San Diego, CA (US); **Marni D. Ines**, San Marcos, CA (US); **Gery M. Zimmerman**, Fallbrook, CA (US); **Jason A. Mata**, Carlsbad, CA (US)

FOREIGN PATENT DOCUMENTS

JP H11-192329 5/2001
JP 2001-170222 6/2001
(Continued)

(73) Assignee: **Acushnet Company**, Fairhaven, MA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

This patent is subject to a terminal disclaimer.

Primary Examiner — Sebastiano Passaniti

(74) *Attorney, Agent, or Firm* — Kevin N. McCoy

(21) Appl. No.: **16/833,054**

(57) **ABSTRACT**

(22) Filed: **Mar. 27, 2020**

A golf club head including a club head body including a back portion and a striking face, wherein the striking face comprises a front surface configured to strike a golf ball and a rear surface opposite the front surface, wherein the back portion is spaced from the rear surface, a first deformable member residing between the back portion and the rear surface of the striking face, wherein the first deformable member comprises a front surface in contact with the rear surface of the striking face, and a second deformable member residing between the back portion and the rear surface of the striking face, wherein the second deformable member comprises a front surface in contact with the rear surface of the striking face, wherein the first deformable member has a greater Shore A durometer than the second deformable member.

(65) **Prior Publication Data**

US 2020/0222767 A1 Jul. 16, 2020


Related U.S. Application Data

(63) Continuation-in-part of application No. 16/286,412, filed on Feb. 26, 2019, now Pat. No. 10,625,127, (Continued)

19 Claims, 38 Drawing Sheets

(51) **Int. Cl.**
A63B 53/04 (2015.01)

(52) **U.S. Cl.**
CPC **A63B 53/0475** (2013.01); **A63B 53/0408** (2020.08); **A63B 53/0445** (2020.08)



Related U.S. Application Data

which is a continuation-in-part of application No. 16/225,577, filed on Dec. 19, 2018, now abandoned, which is a continuation-in-part of application No. 16/158,578, filed on Oct. 12, 2018, now Pat. No. 10,293,226, which is a continuation-in-part of application No. 16/027,077, filed on Jul. 3, 2018, now abandoned, which is a continuation-in-part of application No. 15/220,122, filed on Jul. 26, 2016, now Pat. No. 10,086,244.

(58) **Field of Classification Search**

USPC 473/324-350, 287-292
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,817,522	A	6/1974	Simmons	
4,195,842	A	4/1980	Coleman	
4,398,965	A	8/1983	Campau	
4,754,977	A	7/1988	Sahm	
4,826,172	A	5/1989	Antonious	
4,938,470	A	7/1990	Antonious	
5,121,922	A	6/1992	Harsh, Sr.	
5,184,823	A	2/1993	Desboilles	
5,261,664	A	11/1993	Anderson	
5,290,032	A	3/1994	Fenton	
5,328,184	A	7/1994	Antonious	
5,346,213	A	9/1994	Yamada	
5,398,929	A	3/1995	Kitaichi	
5,403,007	A	4/1995	Chen	
5,464,211	A	11/1995	Atkins, Sr.	
5,492,327	A	2/1996	Biafore, Jr.	
5,499,814	A	3/1996	Lu	
5,505,453	A	4/1996	MacK	
5,529,543	A *	6/1996	Beaumont, Sr.	A63B 60/00 473/290
5,547,194	A	8/1996	Aizawa	
5,628,697	A	5/1997	Gamble	
5,669,829	A	9/1997	Lin	
5,697,855	A *	12/1997	Aizawa	A63B 53/04 473/350
5,888,148	A	3/1999	Allen	
5,890,973	A	4/1999	Gamble	
5,899,821	A	5/1999	Hsu	
6,001,030	A *	12/1999	Delaney	A63B 53/0487 473/329
6,015,354	A	1/2000	Ahn	
6,165,081	A	12/2000	Chou	
6,299,547	B1	10/2001	Kosmatka	
6,299,549	B1	10/2001	Shieh	
6,364,789	B1	4/2002	Kosmatka	
6,595,870	B2	7/2003	Stites	
6,695,715	B1	2/2004	Chikaraishi	
6,832,961	B2	12/2004	Sano	
6,855,066	B2	2/2005	Best	
6,902,495	B2	6/2005	Pergande	
6,921,344	B2 *	7/2005	Gilbert	A63B 60/00 473/334
6,964,620	B2	11/2005	Gilbert	
6,991,559	B2	1/2006	Yabu	
7,056,229	B2	6/2006	Chen	
7,096,558	B2	8/2006	Sano	
7,140,977	B2	11/2006	Atkins, Sr.	
7,160,204	B2	1/2007	Huang	
7,211,006	B2	5/2007	Chang	
7,247,104	B2	7/2007	Poynor	
7,371,190	B2	5/2008	Gilbert	
7,559,853	B2	7/2009	Hirano	

7,575,523	B2	8/2009	Yokota	
7,582,024	B2	9/2009	Shear	
7,588,503	B2	9/2009	Roach	
7,597,633	B2	10/2009	Shimazaki	
7,604,550	B1	10/2009	Currie	
7,686,706	B2	3/2010	Matsunaga	
7,713,141	B2	5/2010	Yamamoto	
7,749,100	B2	7/2010	Tavares	
7,785,212	B2 *	8/2010	Lukasiewicz, Jr.	A63B 53/0466 473/332
7,798,913	B2	9/2010	Noble	
7,871,338	B2 *	1/2011	Nakano	A63B 60/00 473/332
7,935,000	B2	5/2011	Stites	
7,967,700	B2	6/2011	Stites	
8,088,025	B2	1/2012	Wahl	
8,157,673	B2	4/2012	Gilbert	
8,187,116	B2	5/2012	Boyd	
8,210,961	B2	7/2012	Finn	
8,210,965	B2	7/2012	Roach	
8,267,807	B2	9/2012	Takechi	
8,277,337	B2 *	10/2012	Shimazaki	A63B 53/04 473/350
8,328,663	B2	12/2012	Wahl	
8,353,784	B2	1/2013	Boyd	
8,403,771	B1	3/2013	Rice	
8,403,774	B2	3/2013	Stites	
8,517,863	B2	8/2013	Wahl	
8,562,652	B2	10/2013	Biedermann	
8,608,585	B2	12/2013	Stites	
8,753,219	B2	6/2014	Gilbert	
8,753,228	B2	6/2014	Golden	
8,758,159	B2	6/2014	Morin	
8,814,725	B2	8/2014	Wahl	
8,821,307	B2	9/2014	Park	
9,259,629	B2 *	2/2016	Gilbert	A63B 53/0475
9,265,995	B2	2/2016	Wahl	
9,457,241	B2	10/2016	Hebreo	
9,597,562	B2	3/2017	Dipert	
10,086,244	B2	10/2018	Morin	
10,293,226	B2 *	5/2019	Hebreo	A63B 53/047
10,625,127	B2 *	4/2020	Golden	A63B 60/52
2003/0092502	A1 *	5/2003	Pergande	A63B 53/08 473/332
2003/0190975	A1	10/2003	Fagot	
2005/0107183	A1 *	5/2005	Takeda	A63B 53/047 473/326
2005/0277485	A1	12/2005	Hou	
2007/0026961	A1	2/2007	Hou	
2007/0135233	A1	7/2007	Perras	
2008/0004131	A1	1/2008	Lin	
2008/0305888	A1 *	12/2008	Tseng	A63B 53/0475 473/332
2009/0163295	A1	6/2009	Tseng	
2010/0056297	A1	3/2010	Roach	
2010/0273565	A1	10/2010	Stites	
2011/0124432	A1	5/2011	Oldknow	
2011/0250985	A1	10/2011	Stites	
2012/0064997	A1	3/2012	Sato	
2015/0165280	A1	6/2015	Hebreo	
2015/0343281	A1	12/2015	Ban	
2017/0144037	A1	5/2017	Dipert	

FOREIGN PATENT DOCUMENTS

JP	2006-000139	A	1/2006
JP	2007-21171		1/2007
JP	2009-61317		3/2009
JP	2015-517882		6/2015

* cited by examiner




FIG. 1B




FIG. 1A




FIG. 1C




FIG. 2A




FIG. 2B




FIG. 3B




FIG. 3A




FIG. 4B




FIG. 4A




FIG. 4C




FIG. 5A




FIG. 5B




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 6D




FIG. 6E




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 9A




FIG. 9B




FIG. 10




FIG. 11B




FIG. 11A




FIG. 11C




FIG. 11D




FIG. 12A




FIG. 12B




FIG. 13A




FIG. 13B




FIG. 14A




FIG. 14B




FIG. 14C




FIG. 14D




FIG. 14E




FIG. 14F




FIG. 14G




FIG. 14H




FIG. 14I




FIG. 14J




FIG. 14K




FIG. 14L




FIG. 15A




FIG. 15B




FIG. 15C




FIG. 15D




FIG. 16




FIG. 17C




FIG. 17B




FIG. 17A




FIG. 17E

FIG. 17D




FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 24




FIG. 23




FIG. 25

**GOLF CLUB HAVING AN ELASTOMER
ELEMENT FOR BALL SPEED CONTROL**

RELATED APPLICATIONS

This application is a continuation-in-part of application Ser. No. 16/286,412, filed Feb. 26, 2019, which is a continuation-in-part of application Ser. No. 16/225,577, filed Dec. 19, 2018, which is a continuation-in-part of application Ser. No. 16/158,578, filed Oct. 12, 2018, now U.S. Pat. No. 10,293,226, which is a continuation-in-part of application Ser. No. 16/027,077, filed Jul. 3, 2018, which is a continuation-in-part of application Ser. No. 15/220,122, filed Jul. 26, 2016, now U.S. Pat. No. 10,086,244, which are hereby incorporated by reference in their entirety. To the extent appropriate, the present application claims priority to the above-referenced applications.

BACKGROUND

It is a goal for golfers to reduce the total number of swings needed to complete a round of golf, thus reducing their total score. To achieve that goal, it is generally desirable to for a golfer to have a ball fly a consistent distance when struck by the same golf club and, for some clubs, also to have that ball travel a long distance. For instance, when a golfer slightly mishits a golf ball, the golfer does not want the golf ball to fly a significantly different distance. At the same time, the golfer also does not want to have a significantly reduced overall distance every time the golfer strikes the ball, even when the golfer strikes the ball in the “sweet spot” of the golf club.

SUMMARY

One non-limiting embodiment of the present technology includes a golf club head including a club head body including a back portion and a striking face; wherein the striking face comprises a front surface configured to strike a golf ball and a rear surface opposite the front surface; wherein the back portion is spaced from the rear surface; a first deformable member residing between the back portion and the rear surface of the striking face; wherein the first deformable member comprises a front surface in contact with the rear surface of the striking face and a rear surface in contact with the back portion; and a second deformable member residing between the back portion and the rear surface of the striking face; wherein the second deformable member comprises a front surface in contact with the rear surface of the striking face and a rear surface in contact with the back portion; and a coordinate system centered at a center of gravity of the golf club head, the coordinate system including a y-axis extending vertically, perpendicular to a ground plane when the golf club head is in an address position at prescribed loft and lie, an x-axis perpendicular to the y-axis and parallel to the striking face, extending towards a heel of the golf club head, and a z-axis, perpendicular to the y-axis and the x-axis and extending through the striking face, wherein the striking face comprises a plurality of scorelines, wherein the striking face comprises a heel reference plane extending parallel to the y-axis and the x-axis, wherein the heel reference plane is offset 1 millimeter towards the heel from a heel-most extent of the scorelines, wherein the striking face comprises a striking face length measured from the heel reference plane to a toe-most extent of the front surface of the striking face parallel to the x-axis; wherein the rear surface of the striking face comprises a first

supported region, wherein a perimeter of the front surface of the first deformable member defines the first supported region, wherein the first supported region comprises a first geometric center, wherein the first geometric center of the first supported region is located a first supported region offset length toward from the heel reference plane measured parallel to the x-axis; wherein the rear surface of the striking face comprises a second supported region, wherein a perimeter of the front surface of the second deformable member defines the second supported region, wherein the second supported region comprises a second geometric center, wherein the second geometric center of the second supported region is located a second supported region offset length toward from the heel reference plane measured parallel to the x-axis; wherein the first supported region offset length divided by the second supported region offset length is greater than 1.0.

In an additional non-limiting embodiment of the present technology the first supported region offset length divided by the second supported region offset length is greater than 1.5.

In an additional non-limiting embodiment of the present technology the first supported region offset length divided by the second supported region offset length is greater than 2.0.

In an additional non-limiting embodiment of the present technology at least a portion of the striking face comprises a thickness of less than or equal to 2.2 mm.

In an additional non-limiting embodiment of the present technology the front surface of the first deformable member is circular having a front diameter, wherein the rear surface of the first deformable member is circular having a rear diameter, wherein the front diameter is less than the rear diameter and wherein the front surface of the second deformable member is circular having a front diameter, wherein the rear surface of the second deformable member is circular having a rear diameter, wherein the front diameter is less than the rear diameter.

In an additional non-limiting embodiment of the present technology the first deformable member has a greater Shore A durometer than the second deformable member.

In an additional non-limiting embodiment of the present technology the striking face comprises a first density, wherein the back portion comprises a back cover, wherein the back cover comprises a recess, wherein the second deformable member is at least partially retained within the recess, wherein the back cover comprises a second density, wherein the first density is greater than the second density.

In an additional non-limiting embodiment of the present technology the center of gravity of the golf club head is located less than or equal to 20 millimeters above the ground plane, measured parallel to the y-axis, and wherein the golf club head comprises an MOI-Y greater than or equal to 250 kg-mm².

One non-limiting embodiment of the present technology includes a golf club head including a club head body including a back portion and a striking face; wherein the striking face comprises a front surface configured to strike a golf ball and a rear surface opposite the front surface; wherein the back portion is spaced from the rear surface; a first deformable member residing between the back portion and the rear surface of the striking face; wherein the first deformable member comprises a front surface in contact with the rear surface of the striking face; and a second deformable member residing between the back portion and the rear surface of the striking face; wherein the second deformable member comprises a front surface in contact

with the rear surface of the striking face; wherein the first deformable member has a greater Shore A durometer than the second deformable member.

In an additional non-limiting embodiment of the present technology the striking face comprises a first density, wherein the back portion comprises a back cover, wherein the back cover comprises a recess, wherein the second deformable member is at least partially retained within the recess, wherein the back cover comprises a second density, wherein the first density is greater than the second density.

In an additional non-limiting embodiment of the present technology at least a portion of the striking face comprises a thickness of less than or equal to 2.2 mm.

In an additional non-limiting embodiment of the present technology the front surface of the first deformable member is circular having a front diameter, wherein the rear surface of the first deformable member is circular having a rear diameter, wherein the front diameter is less than the rear diameter, wherein the front surface of the second deformable member is circular having a front diameter, wherein the rear surface of the second deformable member is circular having a rear diameter, wherein the front diameter is less than the rear diameter.

In an additional non-limiting embodiment of the present technology the golf club head comprises an interior cavity formed between the back portion and the striking face, wherein an aperture is formed through the back portion, an adjustment driver residing within the aperture, the adjustment driver including a recess adjacent the interior cavity, wherein at least a portion of the first deformable member resides within the recess, wherein the back portion comprises a shelf surrounding the aperture and wherein the adjustment driver comprises a flange, the flange in contact with the shelf.

An additional non-limiting embodiment of the present technology further includes a coordinate system centered at a center of gravity of the golf club head, the coordinate system including a y-axis extending vertically, perpendicular to a ground plane when the golf club head is in an address position at prescribed loft and lie, an x-axis perpendicular to the y-axis and parallel to the striking face, extending towards a heel of the golf club head, and a z-axis, perpendicular to the y-axis and the x-axis and extending through the striking face, wherein the striking face comprises a plurality of scorelines, wherein the striking face comprises a heel reference plane extending parallel to the y-axis and the x-axis, wherein the heel reference plane is offset 1 millimeter towards the heel from a heel-most extent of the scorelines, wherein the striking face comprises a striking face length measured from the heel reference plane to a toe-most extent of the front surface of the striking face parallel to the x-axis, wherein the rear surface of the striking face comprises a first supported region, wherein a perimeter of the front surface of the first deformable member defines the first supported region, wherein the first supported region comprises a first geometric center, wherein the first geometric center of the first supported region is located a first supported region offset length toward from the heel reference plane measured parallel to the x-axis, wherein the rear surface of the striking face comprises a second supported region, wherein a perimeter of the front surface of the second deformable member defines the second supported region, wherein the second supported region comprises a second geometric center, wherein the second geometric center of the second supported region is located a second supported region offset length toward from the heel reference plane measured

parallel to the x-axis, wherein the first supported region offset length divided by the second supported region offset length is greater than 1.5.

One non-limiting embodiment of the present technology includes a golf club head including a club head body including a back portion and a striking face; wherein the striking face comprises a front surface configured to strike a golf ball and a rear surface opposite the front surface; wherein the back portion is spaced from the rear surface; a first deformable member residing between the back portion and the rear surface of the striking face; wherein the first deformable member comprises a front surface in contact with the rear surface of the striking face; and a second deformable member residing between the back portion and the rear surface of the striking face; wherein the second deformable member comprises a front surface in contact with the rear surface of the striking face; wherein the back portion comprises a back cover; wherein the back cover comprises a recess; and wherein the second deformable member is at least partially retained within the recess.

In an additional non-limiting embodiment of the present technology the striking face comprises a first density, wherein the back cover comprises a second density, wherein the first density is greater than the second density.

In an additional non-limiting embodiment of the present technology the first deformable member has a greater Shore A durometer than the second deformable member.

In an additional non-limiting embodiment of the present technology at least a portion of the striking face comprises a thickness of less than or equal to 2.2 mm.

In an additional non-limiting embodiment of the present technology the front surface of the first deformable member is circular having a front diameter, wherein the rear surface of the first deformable member is circular having a rear diameter, wherein the front diameter is less than the rear diameter, wherein the front surface of the second deformable member is circular having a front diameter, wherein the rear surface of the second deformable member is circular having a rear diameter, wherein the front diameter is less than the rear diameter.

In an additional non-limiting embodiment of the present technology the golf club head comprises an interior cavity formed between the back portion and the striking face, wherein an aperture is formed through the back portion, an adjustment driver residing within the aperture, the adjustment driver including a recess adjacent the interior cavity, wherein at least a portion of the first deformable member resides within the recess, wherein the back portion comprises a shelf surrounding the aperture and wherein the adjustment driver comprises a flange, the flange in contact with the shelf.

This summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used to limit the scope of the claimed subject matter.

BRIEF DESCRIPTION OF THE DRAWINGS

Non-limiting and non-exhaustive examples are described with reference to the following Figures.

FIGS. 1A-1B depict section views of a golf club head having an elastomer element.

FIG. 1C depicts a perspective section view of the golf club head depicted in FIGS. 1A-1B.

5

FIGS. 2A-2B depict section views of a golf club head having an elastomer element and a striking face with a thickened center portion.

FIGS. 3A-3B depict section views of a golf club head having an elastomer element and an adjustment mechanism to adjust the compression of the elastomer element.

FIG. 4A depicts a perspective view of another example of a golf club head having an elastomer element and an adjustment mechanism to adjust the compression of the elastomer element.

FIG. 4B depicts a section view of the golf club head of FIG. 4A.

FIG. 4C depicts a section view of another example of a golf club having an elastomer element and an adjustment mechanism to adjust the compression of the elastomer element.

FIG. 5A depicts a stress contour diagram for a golf club head without an elastomer element.

FIG. 5B depicts a stress contour diagram for a golf club head with an elastomer element.

FIG. 6A depicts a front view of the golf club head.

FIG. 6B depicts a toe view of the golf club head of FIG. 6A.

FIG. 6C depicts a section view A-A of the golf club head of FIG. 6A.

FIG. 6D depicts a perspective view of the golf club head of FIG. 6A oriented perpendicular to the striking face.

FIG. 6E depicts a perspective view of the golf club head of FIG. 6A oriented perpendicular to the striking face including the supported region.

FIG. 7A depicts a perspective view of the golf club head.

FIG. 7B depicts an additional perspective view of the golf club head of FIG. 7A.

FIG. 7C depicts a rear view of the golf club head of FIG. 7A.

FIG. 8A depicts a section view B-B of the golf club head of FIG. 7C.

FIG. 8B depicts a section view C-C of the golf club head of FIG. 7C.

FIG. 8C depicts a section view D-D of the golf club head of FIG. 7C.

FIG. 9A depicts an additional section view of the front of the golf club head of FIG. 7A missing the striking face.

FIG. 9B depicts the section view from FIG. 9A with the deformable member removed.

FIG. 10 depicts a perspective view of the golf club head of FIG. 7A oriented perpendicular to the striking face including the supported region.

FIG. 11A depicts a cross sectional view of the golf club head of FIG. 7C including an additional embodiment of an elastomer element.

FIG. 11B depicts a cross sectional view of the golf club head of FIG. 7C including an additional embodiment of an elastomer element.

FIG. 11C depicts a cross sectional view of the golf club head of FIG. 7C including an additional embodiment of an elastomer element.

FIG. 11D depicts a cross sectional view of the golf club head of FIG. 7C including an additional embodiment of an elastomer element.

FIG. 12A depicts the periodogram power spectral density estimate of the golf club head depicted in FIG. 11A.

FIG. 12B depicts the sound power estimate of the golf club head depicted in FIG. 11A.

FIG. 13A depicts the periodogram power spectral density estimate of the golf club head depicted in FIG. 11D.

6

FIG. 13B depicts the sound power estimate of the golf club head depicted in FIG. 11D.

FIG. 14A illustrates a cross sectional view of an elastomer element having a larger rear portion than front portion.

FIG. 14B illustrates a cross sectional view of an elastomer element having a larger rear portion than front portion.

FIG. 14C illustrates a cross sectional view of an elastomer element having a larger rear portion than front portion.

FIG. 14D illustrates a cross sectional view of an elastomer element similar to that of FIG. 14A but includes a first material and a second material.

FIG. 14E illustrates a cross sectional view of an elastomer element similar to that of FIG. 14B but includes a first material and a second material.

FIG. 14F illustrates a cross sectional view of an elastomer element similar to that of FIG. 14C but includes a first material and a second material.

FIG. 14G illustrates a cross sectional view of an elastomer element similar to that of FIG. 14A but the center of the front portion is offset from a center of the rear portion.

FIG. 14H illustrates a cross sectional view of an elastomer element similar to that of FIG. 14B but the center of the front portion is offset from a center of the rear portion.

FIG. 14I illustrates a cross sectional view of an elastomer element similar to that of FIG. 14C but the center of the front portion is offset from a center of the rear portion.

FIG. 14J illustrates a cross sectional view of an elastomer element which necks down in diameter between the front portion and the rear portion.

FIG. 14K illustrates a cross sectional view of an elastomer element which necks down in diameter between the front portion and the rear portion.

FIG. 14L illustrates a cross sectional view of an elastomer element similar to that of FIG. 14J but includes a first material and a second material.

FIG. 15A depicts a rear view of the golf club head.

FIG. 15B depicts a perspective view of the golf club head of FIG. 15A.

FIG. 15C depicts an additional perspective view of the golf club head of FIG. 15A.

FIG. 15D depicts a section view E-E of the golf club head of FIG. 15A.

FIG. 16 depicts the section view E-E of the golf club head of FIG. 15D without the adjustment driver and elastomer element installed.

FIG. 17A depicts a perspective view of the adjustment driver and elastomer element of the golf club head of FIG. 15A.

FIG. 17B depicts an additional perspective view of the adjustment driver and elastomer element of the golf club head of FIG. 15A.

FIG. 17C depicts a side view of the adjustment driver and elastomer element of the golf club head of FIG. 15A.

FIG. 17D depicts a section view of the adjustment driver and elastomer element of FIG. 17A.

FIG. 17E depicts an additional perspective of the section view of the adjustment driver and elastomer element of FIG. 17A.

FIG. 18 depicts a rear view of the golf club head.

FIG. 19 depicts an exploded view of the golf club head of FIG. 18.

FIG. 20 depicts a section view F-F of the golf club head.

FIG. 21 depicts a section view G-G of the golf club head.

FIG. 22 depicts a frontal view of the golf club head of FIG. 18, including the supported regions.

FIG. 23 depicts a perspective view of golf club head and an additional embodiment of the second deformable member.

FIG. 24 depicts the second deformable member illustrated in FIG. 23.

FIG. 25 depicts a section view F-F of the golf club head including the second deformable member illustrated in FIGS. 23 and 24.

DETAILED DESCRIPTION

The technologies described herein contemplate an iron-type golf club head that incorporates an elastomer element to promote more uniform ball speed across the striking face of the golf club. Traditional thin-faced iron-type golf clubs generally produce less uniform launch velocities across the striking face due to increased compliance at the geometric center of the striking face. For example, when a golf club strikes a golf ball, the striking face of the club deflects and then springs forward, accelerating the golf ball off the striking face. While such a design may lead to large flight distances for a golf ball when struck in the center of the face, any off-center strike of golf ball causes significant losses in flight distance of the golf ball. In comparison, an extremely thick face causes more uniform ball flight regardless of impact location, but a significant loss in launch velocities. The present technology incorporates an elastomer element between a back portion of the hollow iron and the rear surface of the striking face. By including the elastomer element, the magnitude of the launch velocity may be reduced for strikes at the center of the face while improving uniformity of launch velocities across the striking face. In some examples, the compression of the elastomer element between the back portion and the striking face may also be adjustable to allow for a golfer or golf club fitting professional to alter the deflection of the striking face when striking a golf ball.

FIGS. 1A-1B depict section views depict section views of a golf club head 100 having an elastomer element 102. FIG. 1C depicts a perspective section view of the golf club head 100. FIGS. 1A-1C are described concurrently. The club head 100 includes a striking face 118 and a back portion 112. A cavity 120 is formed between the striking face 118 and the back portion 112. An elastomer element 102 is disposed in the cavity 120 between the striking face 118 and the back portion 112. A rear portion of the elastomer element 102 is held in place by a cradle 108. The cradle 108 is attached to the back portion 112 of the golf club head 100, and the cradle 108 includes a recess 109 to receive the rear portion of the elastomer element 102. The lip of the cradle 108 prevents the elastomer element 102 from sliding or otherwise moving out of position. The elastomer element 102 may have a generally frustoconical shape, as shown in FIGS. 1A-1B.

In other examples, the elastomer element 102 may have a cylindrical, spherical, cuboid, or prism shape. The recess 109 of the cradle 108 is formed to substantially match the shape of the rear portion of the elastomer element 102. For example, with the frustoconical elastomer element 102, the recess 109 of the cradle 108 is also frustoconical such that the surface of the rear portion of the elastomer element 102 is in contact with the interior walls of the recess 109 of the cradle 108. The cradle 108 may be welded or otherwise attached onto the back portion 112, or the cradle 108 may be formed as part of the back portion 112 during a casting or forging process. The back portion 112 may also be machined to include the cradle 108.

A front portion 103 of the elastomer element 102 contacts the rear surface 119 of the striking face 118. The front portion 103 of the elastomer element 102 may be held in place on the rear surface 119 of the striking face 118 by a securing structure, such as flange 110. The flange 110 protrudes from the rear surface 119 of the striking face 118 into the cavity 120. The flange 110 receives the front portion 103 of the elastomer element 102 to substantially prevent the elastomer element 102 from sliding along the rear surface 119 of the striking face 118. The flange 110 may partially or completely surround the front portion 103 of the elastomer element 102. Similar to the cradle 108, the flange 110 may be shaped to match the shape of the front portion 103 of the elastomer element 102 such that the surface of the front portion 103 of the elastomer element 102 is in contact with the interior surfaces of the flange 110. The flange 110 may be welded or otherwise attached to the rear surface 119 of the striking face 118. The flange 110 may also be cast or forged during the formation of the striking face 118. For instance, where the striking face 118 is a face insert, the flange 110 may be incorporated during the casting or forging process to make the face insert. In another example, the flange 110 and the striking face 118 may be machined from a thicker face plate. Alternative securing structures other than the flange 110 may also be used. For instance, two or more posts may be included on rear surface 119 of the striking face 118 around the perimeter of the front portion 103 of the elastomer element 102. As another example, an adhesive may be used to secure the elastomer element 102 to the rear surface 119 of the striking face 118. In other embodiments, no securing structure is utilized and the elastomer element 102 is generally held in place due to the compression of the elastomer element 102 between the cradle 108 and the rear surface 119 of the striking face 118.

In the example depicted in FIGS. 1A-1C, the elastomer element 102 is disposed behind the approximate geometric center of the striking face 118. In traditional thin face golf clubs, strikes at the geometric center of the striking face 118 display the largest displacement of the striking face 118, and thus the greatest ball speeds. By disposing the elastomer 102 at the geometric center of the striking face 118, the deflection of the striking face 118 at that point is reduced, thus reducing the ball speed. Portions of the striking face 118 not backed by the elastomer element 102, however, continue to deflect into the cavity 120 contributing to the speed of the golf ball. As such, a more uniform distribution of ball speeds resulting from ball strikes across the striking face 118 from the heel to the toe may be achieved. In other examples, the elastomer element 102 may be disposed at other locations within the club head 100.

The elasticity of the elastomer element 102 also affects the deflection of the striking face 118. For instance, a material with a lower elastic modulus allows for further deflection of the striking face 118, providing for higher maximum ball speeds but less uniformity of ball speeds. In contrast, a material with a higher elastic modulus further prevents deflection of the striking face 118, providing for lower maximum ball speeds but more uniformity of ball speeds. Different types of materials are discussed in further detail below with reference to Tables 2-3.

The golf club head 100 also includes a sole 105 having a sole channel 104 in between a front sole portion 114 and a rear sole portion 116. The sole channel 104 extends along the sole 105 of the golf club head 100 from a point near the heel to a point near the toe thereof. While depicted as being a hollow channel, the sole channel 104 may be filled or spanned by a plastic, rubber, polymer, or other material to

prevent debris from entering the cavity 120. The sole channel 104 allows for additional deflection of the lower portion of the striking face 118. By allowing for further deflection of the lower portion of the striking face 118, increased ball speeds are achieved from ball strikes at lower portions of the striking face 118, such as ball strikes off the turf. Accordingly, the elastomer element 102 and the sole channel 104 in combination with one another provide for increased flight distance of a golf ball for turf strikes along with more uniform ball speeds across the striking face 118.

FIGS. 2A-2B depict sections views of a golf club head 200 having an elastomer element 202 and a striking face 218 with a thickened center portion 222. Golf club head 200 is similar to golf club head 100 discussed above with reference to FIGS. 1A-1C, except a thickened portion 222 of the striking face 218 is utilized rather than a flange 110. The thickened portion 222 of the striking face 218 protrudes into the cavity 220. The front portion 203 of the elastomer element 202 contacts the rear surface 219 of the thickened portion 222. The rear portion of the elastomer element 202 is received by a recess 209 in a cradle 208, which is attached to the back portion 212 and substantially similar to the cradle 108 discussed above with reference to FIGS. 1A-1C. Due to the thickened portion 222 of the striking face 218, the elastomer element 202 may be shorter in length than the elastomer element 102 in FIGS. 1A-1C. The golf club head 200 also includes a sole channel 204 disposed between a front sole portion 214 and a rear sole portion 216. The sole channel 204 also provides benefits similar to that of sole channel 104 described in FIGS. 1A-1C and may also be filled with or spanned by a material.

FIGS. 3A-3B depict section views of a golf club head 300 having an elastomer element 302 and an adjustment mechanism to adjust the compression of the elastomer element 302. The golf club head 300 includes a striking face 318 and a back portion 312, and a cavity 320 is formed between the back portion 312 and the striking face 318. Similar to the golf club head 100 described above with reference to FIGS. 1A-1C, a flange 310 is disposed on the rear surface 319 of the striking face 318, and the flange 310 receives the front portion 303 of the elastomer element 302. In the example depicted in FIGS. 3A-3B, the elastomer element 302 has a generally cylindrical shape. In other examples, however, the elastomer element 302 may have a conical, frustoconical, spherical, cuboid, or prism shape.

The golf club head 300 also includes an adjustment mechanism. The adjustment mechanism is configured to adjust the compression of the elastomer element 302 against the rear surface 319 of the striking face 318. In the embodiment depicted in FIGS. 3A-3B, the adjustment mechanism includes an adjustment receiver 306 and an adjustment driver 330. The adjustment receiver 306 may be a structure with a through-hole into the cavity 320, and the adjustment driver 330 may be a threaded element or screw, as depicted. The through-hole of the adjustment receiver 306 includes a threaded interior surface for receiving the threaded element 330. The adjustment receiver 306 may be formed as part of the forging or casting process of the back portion 312 or may also be machined and tapped following the forging and casting process. The threaded element 330 includes an interface 334, such as a recess, that contacts or receives a rear portion of the elastomer element 302. The threaded element 330 also includes a screw drive 332 that is at least partially external to the golf club head 300 such that a golfer can access the screw drive 332. When the threaded element 330 is turned via screw drive 332, such as by a screwdriver, Allen wrench, or torque wrench, the threaded element 330

moves further into or out of the cavity 320. In some examples, the interface 334 that contacts or receives the rear portion of the elastomer element 302 may be lubricated so as to prevent twisting or spinning of the elastomer element 302 when the threaded element 330 is turned. As the threaded element 330 moves further into the cavity 320, the compression of the elastomer element 302 against the rear surface 319 of the striking face 318 increases, thus altering a performance of the elastomer element 302.

A higher compression of the elastomer element 302 against the rear surface 319 of the striking face 318 further restricts the deflection of the striking face 318. In turn, further restriction of the deflection causes more uniform ball speeds across the striking face 318. However, the restriction on deflection also lowers the maximum ball speed from the center of the striking face 318. By making the compression of the elastomer element 302 adjustable with the adjustment mechanism, the golfer or a golf-club-fitting professional may adjust the compression to fit the particular needs of the golfer. For example, a golfer that desires further maximum distance, but does not need uniform ball speed across the striking face 318, can reduce the initial set compression of the elastomer element 302 by loosening the threaded element 330. In contrast, a golfer that desires uniform ball speed across the striking face 318 can tighten the threaded element 330 to increase the initial set compression of the elastomer element 302.

While the adjustment mechanism is depicted as including a threaded element 330 and a threaded through-hole in FIGS. 3A-3B, other adjustment mechanisms could be used to adjust the compression of the elastomer element 302 against the rear surface 319 of the striking face 318. For instance, the adjustment mechanism may include a lever where rotation of the lever alters the compression of the elastomer element 302. The adjustment mechanism may also include a button that may be depressed to directly increase the compression of the elastomer element 302. Other types of adjustment mechanisms may also be used.

The golf club head 300 also includes a sole channel 304 between a front sole portion 314 and a rear sole portion 316, similar to the sole channel 104 discussed above with reference to FIGS. 1A-1C. The sole channel 304 also provides benefits similar to that of sole channel 104 and may also be filled with or spanned by a material.

The golf club head 300 may also be created or sold as a kit. In the example depicted where the adjustment mechanism is a threaded element 330, such as a screw, the kit may include a plurality of threaded elements 330. Each of the threaded elements 330 may have a different weight, such that the golfer can select the desired weight. For example, one golfer may prefer an overall lighter weight for the head of an iron, while another golfer may prefer a heavier weight. The plurality of threaded elements 330 may also each have different weight distributions. For instance, different threaded elements 330 may be configured so as to distribute, as desired, the weight of each threaded element 330 along a length thereof. The plurality of threaded elements 330 may also have differing lengths. By having differing lengths, each threaded elements 330 may have a maximum compression that it can apply to the elastomer element 302. For instance, a shorter threaded elements 330 may not be able to apply as much force onto the elastomer element 302 as a longer threaded elements 330, depending on the configuration of the adjustment receiver 306. The kit may also include a torque wrench for installing the threaded elements 330 into

the adjustment receiver 306. The torque wrench may include preset settings corresponding to different compression or performance levels.

FIG. 4A depicts a perspective view of another example of a golf club head 400A having an elastomer element 402 and an adjustment mechanism to adjust the compression of the elastomer element 402. FIG. 4B depicts a section view of the golf club head 400A. The golf club 400A includes striking face 418 and a back portion 412 with a cavity 420 formed there between. Like the adjustment mechanism in FIGS. 3A-3B, the adjustment mechanism in golf club head 400A includes an adjustment receiver 406 and an adjustment driver 430. In the example depicted, the adjustment receiver 406 is a structure having a threaded through-hole for accepting the adjustment driver 430, and the adjustment driver 430 is a screw. In some embodiments, the adjustment receiver 406 may be defined by a threaded through-hole through the back portion 412, without the need for any additional structure.

The tip of the screw 430 is in contact with a cradle 408A that holds a rear portion of the elastomer element 402. As the screw 430 is turned, the lateral movement of the screw 430 causes the cradle 408A to move towards or away from the striking face 418. Accordingly, in some examples, the screw 430 extends substantially orthogonal to the rear surface 419 of the striking face 418. Because the cradle 408A holds the rear portion of the elastomer element 402, movement of the cradle 408A causes a change in the compression of the elastomer element 402 against the rear surface 419 of the striking face 418. As such, the compression of the elastomer element 402 may be adjusted by turning the screw 430 via screw drive 432, similar to manipulation of the threaded element 330 in golf club head 300 depicted in FIGS. 3A-3B.

FIG. 4C depicts a section view of another example of a golf club 400C having an elastomer element 402 and an adjustment mechanism to adjust the compression of the elastomer element 402. The golf club head 400C is substantially similar to the golf club head 400A depicted in FIGS. 4A-4B, except golf club head 400C includes a larger cradle 408C having a depth D greater than a depth of a comparatively smaller cradle (e.g., the cradle 408A of FIGS. 4A-4B having a depth d). The larger cradle 408C encompasses more the elastomer element 402 than a smaller cradle. By encompassing a larger portion of the elastomer element 402, the cradle 408C further limits the deformation of the elastomer element 402 upon a strike of a golf ball by golf club head 400C. Limitation of the deformation of the elastomer element 402 also may limit the potential maximum deflection of the striking face 418, and therefore may reduce the maximum ball speed for the golf club head 400C while increasing the uniformity of speeds across the striking face 418. The larger cradle 408C does not come into contact with the rear surface 419 of the striking face 418 at maximum deflection thereof. The cradle 408C itself may be made of the same material as the back portion 412, such as a steel. The cradle 408C may also be made from a titanium, a composite, a ceramic, or a variety of other materials.

The size of the cradle 408C may be selected based on the desired ball speed properties. For instance, the cradle 408C may encompass approximately 25% or more of the volume of the elastomer element 402, as shown in FIG. 4C. In other examples, the cradle 408C may encompass between approximately 25%-50% of the volume of the elastomer element 402. In yet other examples, the cradle 408C may encompass approximately 10%-25% or less than approximately 10% of the volume of the elastomer element 402. In still other examples, the cradle 408C may encompass more

than 50% of the volume of the elastomer element 402. For the portion of the elastomer element 402 encompassed by the cradle 408C, substantially the entire perimeter surface of that portion of elastomer element 402 may contact the interior surfaces of the recess 409 of the cradle 408C.

The connection between the cradle 408C and the adjustment driver 430 can also be seen more clearly in FIG. 4C. The tip of the adjustment driver 430, which may be a flat surface, contacts the rear surface 407 of the cradle 408C. Thus, as the adjustment driver 430 moves into the cavity 420, the cradle 408C and the elastomer element 402 are pushed towards the striking face 418. Conversely, as the adjustment driver 430 is backed out of the cavity 420, the cradle 408C maintains contact with the adjustment driver 430 due to the force exerted from the elastomer element 402 resulting from the compression thereof. In some embodiments, the surface of the tip of the screw 430 and/or the rear surface 407 of the cradle 408C may be lubricated so as to prevent twisting of the cradle 408C. In other examples, the tip of the adjustment driver 430 may be attached to the cradle 408C such that the cradle 408C twists with the turning of the adjustment driver 430. In such an embodiment, the elastomer element 402 may be substantially cylindrical, conical, spherical, or frustoconical, and the interior 409 of the cradle 408C may be lubricated to prevent twisting of the elastomer element 402. In another example, the rear surface 419 of the striking face 418 and/or the front surface of the elastomer element 402 in contact with the rear surface 419 of the striking face 418 may be lubricated so as to allow for spinning of the elastomer element 402 against the rear surface 419 of the striking face 418.

While the golf club heads 400A and 400C are depicted with a continuous sole 414 rather than a sole channel like the golf club head 300 of FIGS. 3A-3B, other embodiments of golf club heads 400A and 400C may include a sole channel. In addition, golf club heads 400A and 400C may also be sold as kits with a plurality of screws and/or a torque wrench, similar to the kit discussed above for golf club head 300. An additional back plate may be added to the aft portion of the golf club heads 400A and 400C, while still leaving a portion of the screw exposed for adjustment.

Simulated results of different types of golf club heads further demonstrate ball speed uniformity across the face of the golf club heads including an elastomer element. Table 1 indicates ball speed retention across the face of a golf club head for several different example golf club heads. Example 1 is a baseline hollow iron having a 2.1 mm face thickness with a sole channel. Example 2 is a hollow iron with a 2.1 mm face with a rigid rod extending from the back portion to the striking face, also including a sole channel. Example 3 is a hollow iron with a striking face having a thick center (6.1 mm) and a thin perimeter (2.1 mm), also having a sole channel. Example 4 is a golf club head having an elastomer element similar to golf club head 100 depicted in FIGS. 1A-1C. The "Center" row indicates ball speeds resulting from a strike in the center of the golf club head, the "1/2" Heel" row indicates the loss of ball speed from a strike a half inch from the center of the club head towards the heel, and the "1/2" Toe" row indicates the loss of ball speed from a strike a half inch from the center of the club head towards the toe. All values in Table 1 are in miles per hour (mph).

TABLE 1

Impact Location	Example 1	Example 2	Example 3	Example 4
Center	134.1	132.8	133.8	133.6
1/2" Heel (drop from center)	-1.0	-0.4	-0.9	-0.7
1/2" Toe (drop from center)	-6.9	-6.5	-6.8	-6.7

From the results in Table 1, the golf club head with the elastomer (Example 4) displays a relatively high ball speed from the center of the face, while also providing a reduced loss of ball speed from strikes near the toe or the heel of the golf club.

In addition, as mentioned above, the type of material utilized for any of the elastomer elements discussed herein has an effect on the displacement of the striking face. For instance, an elastomer element with a greater elastic modulus will resist compression and thus deflection of the striking face, leading to lower ball speeds. For example, for a golf club head similar to golf club head 400A, Table 2 indicates ball speeds achieved from using materials with different elasticity properties. All ball speeds were the result of strikes at the center of the face.

TABLE 2

Material	Elastic Modulus (GPa)	Ball Speed (mph)
Material A	0.41	132.2
Material B	0.58	132.2
Material C	4.14	132.0
Material D	41.4	131.0

From the results in Table 2, a selection of material for the elastomer element can be used to fine tune the performance of the golf club. Any of the materials listed in Table 2 are acceptable for use in forming an elastomer element to be used in the present technology.

The different types of materials also have effect on the ball speed retention across the striking face. For example, for a golf club head similar to golf club head 400A, Table 3 indicates ball speeds achieved across the striking face from heel to toe for the different materials used as the elastomer element. The materials referenced in Table 3 are the same materials from Table 2. All speeds in Table 3 are in mph.

TABLE 3

Material	1/2" Toe Impact	Center Impact	1/2" Heel Impact
No Elastomer Element	128.7	132.2	129.4
Material A (0.41 GPa)	128.7	132.2	129.4
Material C (4.1 GPa)	128.7	132.0	129.3
Material D (41 GPa)	127.9	131.0	128.7

From the results in Table 3, materials having a higher elastic modulus provide for better ball speed retention across the striking face, but lose maximum ball speed for impacts at the center of the face. For some applications, a range of elastic moduli for the elastomer element from about 4 to about 15 GPa may be used. In other applications, a range of elastic

moduli for the elastomer element from about 1 to about 40 or about 50 GPa may be used.

As mentioned above with reference to FIGS. 4A-4C, the size of the cradle may also have an impact on the ball speed. For a smaller cradle, such as cradle 408A in FIGS. 4A-4B, and an elastomer element made of a 13 GPa material, a loss of about 0.2 mph is observed for a center impact as compared to the same club with no elastomer element. For a larger cradle that is about 5 mm deeper, such as cradle 408C in FIG. 4C, and an elastomer element also made of a 13 GPa material, a loss of about 0.4 mph is observed for a center impact as compared to the same club with no elastomer element. For the same larger cradle and an elastomer element made of a 0.4 GPa material, a loss of only about 0.2 mph is observed for a center impact as compared to the same club with no elastomer element.

San Diego Plastics, Inc. of National City, Calif. offers several plastics having elastic moduli ranging from 2.6 GPa to 13 GPa that would all be acceptable for use. The plastics also have yield strengths that are also acceptable for use in the golf club heads discussed herein. Table 4 lists several materials offered by San Diego Plastics and their respective elastic modulus and yield strength values.

TABLE 4

	ABS	Tecaform Acetal	PVC	Tecapeek	Tecapeek 30% Carbon Fiber
Thermoplastic Elastic Modulus (GPa)	2.8	2.6	2.8	3.6	13
Thermoplastic Compressive Yield Strength (GPa)	0.077	0.031	0.088	0.118	0.240

The inclusion of an elastomer element also provide benefits in durability for the club face by reducing stress values displayed by the striking face upon impact with a golf ball. FIG. 5A depicts a stress contour diagram for a golf club head 500A without an elastomer element, and FIG. 5B depicts a stress contour diagram for a golf club head 500B with an elastomer element. In the golf club head 500A, the von Mises stress at the center of the face 502A is about 68% of the maximum von Mises stress, which occurs at the bottom face edge 504A. Without an elastomer element, the von Mises stress levels are high and indicate that the club face may be susceptible to failure and/or early deterioration. In the golf club 500B, for an elastomer element having an elastic modulus of 0.41 GPa, the von Mises stress for the face near the edge of the elastomer element 502B is reduced by about 16% and the maximum von Mises stress occurring at the bottom face edge 504B is reduced by about 18%. These von Mises stresses are still relatively high, but are significantly reduced from those of the golf club head 500A. For a golf club head 500B with an elastomer element having an elastic modulus of about 13 GPa, the von Mises stress for the face near the edge of the elastomer element 502B is reduced by about 50% and the maximum von Mises stress occurring at the bottom face edge 504B is reduced by about 56%. Such von Mises stress values are lower and are indicative of a more durable golf club head that may be less likely to fail.

FIGS. 6A-6E depict a golf club head 600 having an elastomer element 602. FIG. 6A depicts a front view of the golf club head 600. FIG. 6B depicts a toe view of the golf club head 600 of FIG. 6A. FIG. 6C depicts a section view

15

A-A of the golf club head 600 of FIG. 6A. FIG. 6D depicts a perspective view of the golf club head 600 of FIG. 6A oriented perpendicular to the striking face 618. FIG. 6E depicts a perspective view of the golf club head 600 of FIG. 6A oriented perpendicular to the striking face 618 including the supported region 642. The golf club head 600 includes a striking face 618 configured to strike a ball, a sole 605 located at the bottom of the golf club head 600, and a back portion 612.

As illustrated in FIGS. 6A and 6B, the golf club head 600 includes a coordinate system centered at the center of gravity (CG) of the golf club head 600. The coordinate system includes a y-axis which extends vertically, perpendicular to a ground plane when the golf club head 600 is in an address position at prescribed lie and loft a. The coordinate system includes an x-axis, perpendicular to the y-axis, parallel to the striking face 618, and extending towards the heel of the golf club head 600. The coordinate system includes a z-axis, perpendicular to the y-axis and x-axis and extending through the striking face 618. The golf club head 600 has a rotational moment of inertia about the y-axis (MOI-Y), a value which represents the golf club head's resistance to angular acceleration about the y-axis.

An elastomer element 602 is disposed between the striking face 618 and the back portion 612. The striking face 618 includes a rear surface 619. The front portion 603 of the elastomer element 602 contacts the rear surface 619 of the striking face 618. As illustrated in FIGS. 6C and 6E, the striking face 618 includes a supported region 642, the portion of the rear surface 619 supported by the elastomer element 602, which is defined as the area inside the supported region perimeter 640 defined by the outer extent of the front portion 603 of the elastomer element 602 in contact with the rear surface 619 of the striking face 618. The supported region 642 is illustrated with hatching in FIG. 6E. The supported region 642 wouldn't normally be visible from the front of the golf club head 600 but was added for illustrative purposes.

The striking face 618 includes a striking face area 652, which is defined as the area inside the striking face perimeter 650 as illustrated in FIG. 6D. As illustrated in FIG. 6C, the striking face perimeter is delineated by an upper limit 654 and a lower limit 656. The upper limit 654 is located at the intersection of the substantially flat rear surface 619 and the upper radius 655 which extends to the top line of the golf club head 600. The lower limit 656 is located at the intersection of the substantially flat rear surface 619 and the lower radius 657 which extends to the sole 605 of the golf club head 600. The striking face perimeter is similarly delineated 658 (as illustrated in FIG. 6D) at the toe of the golf club head 600 (not illustrated in cross section). The heel portion of the striking face perimeter is defined by a plane 659 extending parallel to the y-axis and the x-axis offset 1 millimeter (mm) towards the heel from the heel-most extent of the scorelines 660 formed in the striking face 618. The striking face area 652 is illustrated with hatching in FIG. 6D. The limits 654, 656 of the striking face perimeter have been projected onto the striking face 618 in FIG. 6D for ease of illustration and understanding.

A plurality of golf club heads much like golf club head 600 described herein can be included in a set, each golf club head having a different loft a. Each golf club head can also have additional varying characteristics which may include, for example, MOI-Y, Striking Face Area, Area of Supported Region, and the Unsupported Face Percentage. The Unsupported Face Percentage is calculated by dividing the Area of Supported Region by the Striking Face Area and multiplying

16

by 100% and subtracting it from 100%. An example of one set of iron type golf club heads is included in Table 5 below. The set in Table 5 includes the following lofts: 21, 24, 27, and 30. Other sets may include a greater number of golf club heads and/or a wider range of loft a values, or a smaller number of golf club heads and/or a smaller range of loft a values. Additionally, a set may include one or more golf club heads which include an elastomer element and one or more golf club heads which do not include an elastomer element.

TABLE 5

Loft of Iron (Degrees)	MOI-Y (kg*mm ²)	Striking Face Area (mm ²)	Area of Supported Region (mm ²)	Unsupported Face Percentage (%)
21	270	2809	74	97.37
24	272	2790	74	97.35
27	276	2777	74	97.34
30	278	2742	74	97.30

An example of an additional embodiment of set of iron type golf club heads is included in Table 6 below.

TABLE 6

Loft of Iron (Degrees)	MOI-Y (kg*mm ²)	Striking Face Area (mm ²)	Area of Supported Region (mm ²)	Unsupported Face Percentage (%)
21	272	2897	74	97.45
24	278	2890	74	97.44
27	289	2878	74	97.43
30	294	2803	74	97.36

If all other characteristics are held constant, a larger the MOI-Y value increases the ball speed of off-center hits. For clubs with a smaller MOI-Y, the decrease in off-center ball speed can be mitigated with a greater unsupported face percentage. By supporting a smaller percentage of the face, more of the face is able to flex during impact, increasing off-center ball speed. Thus, for the inventive golf club set described in Table 5 above, the MOI-Y increases through the set as loft a increases and the unsupported face percentage decreases through the set as loft a increases. This relationship creates consistent off-center ball speeds through a set of golf clubs.

A set of golf clubs can include a first golf club head with a loft greater than or equal to 20 degrees and less than or equal to 24 degrees and a second golf club head with a loft greater than or equal to 28 degrees and less than or equal to 32 degrees. In one embodiment, the set can be configured so that the first golf club head has a larger unsupported face percentage than the second golf club head and the first golf club head has a lower MOI-Y than the second golf club head.

More particular characteristics of embodiments described herein are described below. In some embodiments, the area of the supported region can be greater than 30 millimeters². In some embodiments, the area of the supported region can be greater than 40 millimeters². In some embodiments, the area of the supported region can be greater than 60 millimeters². In some embodiments, the area of the supported region can be greater than 65 millimeters². In some embodiments, the area of the supported region can be greater than 70 millimeters². In some embodiments, the area of the supported region can be greater than 73 millimeters².

In some embodiments, the area of the supported region can be less than 140 millimeters². In some embodiments, the area of the supported region can be less than 130 millimeters². In some embodiments, the area of the supported region can be less than 120 millimeters². In some embodiments, the area of the supported region can be less than 110 millimeters². In some embodiments, the area of the supported region can be less than 100 millimeters². In some embodiments, the area of the supported region can be less than 90 millimeters². In some embodiments, the area of the supported region can be less than 85 millimeters². In some embodiments, the area of the supported region can be less than 80 millimeters². In some embodiments, the area of the supported region can be less than 75 millimeters².

In some embodiments, the unsupported face percentage is greater than 70%. In some embodiments, the unsupported face percentage is greater than 75%. In some embodiments, the unsupported face percentage is greater than 80%. In some embodiments, the unsupported face percentage is greater than 85%. In some embodiments, the unsupported face percentage is greater than 90%. In some embodiments, the unsupported face percentage is greater than 95%. In some embodiments, the unsupported face percentage is greater than 96%. In some embodiments, the unsupported face percentage is greater than 97%.

In some embodiments, the unsupported face percentage is less than 99.75%. In some embodiments, the unsupported face percentage is less than 99.50%. In some embodiments, the unsupported face percentage is less than 99.25%. In some embodiments, the unsupported face percentage is less than 99.00%. In some embodiments, the unsupported face percentage is less than 98.75%. In some embodiments, the unsupported face percentage is less than 98.50%. In some embodiments, the unsupported face percentage is less than 98.25%. In some embodiments, the unsupported face percentage is less than 98.00%. In some embodiments, the unsupported face percentage is less than 97.75%. In some embodiments, the unsupported face percentage is less than 97.50%. In some embodiments, the unsupported face percentage is less than 97.25%. In some embodiments, the unsupported face percentage is less than 97.00%.

FIGS. 7A-10 depict a golf club head 700 having an elastomer element 702. FIG. 7A depicts a perspective view of the golf club head 700. FIG. 7B depicts an additional perspective view of the golf club head 700 of FIG. 7A. FIG. 7C depicts a rear view of the golf club head 700 of FIG. 7A. FIG. 8A depicts a section view B-B of the golf club head 700 of FIG. 7C. FIG. 8B depicts a section view C-C of the golf club head 700 of FIG. 7C. FIG. 8C depicts a section view D-D of the golf club head 700 of FIG. 7C. FIG. 9A depicts an additional section view of the front of the golf club head 700 of FIG. 7A missing the striking face. FIG. 9B depicts the section view from FIG. 9A with the elastomer element removed. FIG. 10. Depicts a perspective view of the golf club head 700 of FIG. 7A oriented perpendicular to the striking face 718 including the supported region 742. Please note that the golf club head 700 illustrated in FIGS. 7A-10 is an iron-type cavity back golf club but the inventions described herein are applicable to other types of golf club heads as well.

The golf club head 700 includes a deformable member 702 disposed between the striking face 718 and the back portion 712. In one embodiment, the deformable member 702 is formed from an elastomer. The front portion 703 of the elastomer element 702 contacts the rear surface 719 of the striking face 718. The striking face 718 includes a supported region 742, the portion of the rear surface 719

supported by the elastomer element 702, which is defined as the area inside the supported region perimeter 740 defined by the outer extent of the front portion 703 of the elastomer element 702 in contact with the rear surface 719 of the striking face 718. The supported region 742 wouldn't normally be visible from the front of the golf club head 700 but was added in FIG. 10 for illustrative purposes.

The golf club head 700 illustrated in FIGS. 7A-10 is a cavity back construction and includes a periphery portion 701 surrounding and extending rearward from the striking face 718. The periphery portion 701 includes the sole 705, the toe 706, and the topline 707. The periphery portion 701 can also include a weight pad 710. The golf club head 700 also includes a back portion 712 configured to support the elastomer element 702.

The back portion 712 includes a cantilever support arm 762 affixed to the periphery portion 701. The support arm 762 can include a cradle 708 configured to hold the elastomer element 702 in place. The cradle 708 can include a lip 709 configured to locate the elastomer element 702 on the cradle 708 and relative to the striking face 718. The lip 709 can surround a portion of the elastomer element 702. Additionally, an adhesive can be used between the elastomer element 702 and the cradle 708 to secure the elastomer element 702 to the cradle 708.

The support arm 762 extends from the weight pad 710 located at the intersection of the sole 705 and the toe 706 of the periphery portion 701 towards the supported region 742. The support arm 762 is oriented substantially parallel to the rear surface 719 of the striking face 718. The support arm 762 can include a rib 764 to increase the stiffness of the support arm 762. The rib 764 can extend rearwards from the support arm 762 substantially perpendicularly to the rear surface 719 of the striking face 718. One benefit of a cantilever support arm 762 is it provides a lower CG height than an alternative beam design, such as the embodiment illustrated in FIG. 4A, which supported at both ends by the periphery portion.

In order to provide a low CG height the support arm 762 is cantilevered which means it is only affixed to the periphery portion 701 at one end of the support arm 762. The support arm is designed such that the distance H between the highest portion of the support arm 762 and the ground plane GP when the golf club head 700 is in an address position, as illustrated in FIG. 8C, is minimized, while locating the elastomer element 702 in the optimal position. In one embodiment, H is less than or equal to 50 mm. In an additional embodiment, H is less than 45 mm. In an additional embodiment, H is less than or equal to 40 mm. In an additional embodiment, H is less than or equal to 35 mm. In an additional embodiment, H is less than or equal to 30 mm. In an additional embodiment, H is less than or equal to 29 mm. In an additional embodiment, H is less than or equal to 28 mm.

In one embodiment, the golf club head 700 can have a CG height CGH of less than or equal to 25 mm. In an additional embodiment, the golf club head 700 can have a CG height CGH of less than or equal to 24 mm. In an additional embodiment, the golf club head 700 can have a CG height CGH of less than or equal to 23 mm. In an additional embodiment, the golf club head 700 can have a CG height CGH of less than or equal to 22 mm. In an additional embodiment, the golf club head 700 can have a CG height CGH of less than or equal to 21 mm. In an additional embodiment, the golf club head 700 can have a CG height CGH of less than or equal to 20 mm. In an additional embodiment, the golf club head 700 can have a CG height

CGH of less than or equal to 19 mm. In an additional embodiment, the golf club head **700** can have a CG height CGH of less than or equal to 18 mm.

Another advantage to the illustrated support arm **762** is it provides a high MOI-Y due to its orientation. By concentrating mass at the heel end and toe end of the golf club head **700** the MOI-Y can be increased. The support arm **762** is angled to concentrate much of its mass near the toe **706**, increasing MOI-Y compared with a back portion located more centrally on the golf club head **700**. In one embodiment, the MOI-Y of the golf club head **700** is greater than or equal to 200 kg-mm². In an additional embodiment, the MOI-Y of the golf club head **700** is greater than or equal to 210 kg-mm². In an additional embodiment, the MOI-Y of the golf club head **700** is greater than or equal to 220 kg-mm². In an additional embodiment, the MOI-Y of the golf club head **700** is greater than or equal to 230 kg-mm². In an additional embodiment, the MOI-Y of the golf club head **700** is greater than or equal to 240 kg-mm². In an additional embodiment, the MOI-Y of the golf club head **700** is greater than or equal to 250 kg-mm². In an additional embodiment, the MOI-Y of the golf club head **700** is greater than or equal to 260 kg-mm². In an additional embodiment, the MOI-Y of the golf club head **700** is greater than or equal to 270 kg-mm².

The support arm **762** can include an arm centerline CL, as illustrated in FIG. 8A, which is oriented parallel to the rear surface **719** of the striking face **718** and extends along the center of the support arm **762** from the periphery portion **701** towards the supported region **742**. The angle α is measured between the ground plane GP and the centerline CL. In one embodiment, the angle α is greater than or equal to 5 degrees and less than or equal to 45 degrees. In an additional embodiment, the angle α is greater than or equal to 10 degrees and less than or equal to 40 degrees. In an additional embodiment, the angle α is greater than or equal to 15 degrees and less than or equal to 35 degrees. In an additional embodiment, the angle α is greater than or equal to 20 degrees and less than or equal to 30 degrees. In an additional embodiment, the angle α is greater than or equal to 23 degrees and less than or equal to 28 degrees.

The support arm **762** can have an arm width AW measured perpendicularly to the arm centerline CL and parallel to the rear surface **719** of the striking face **718**. The arm width AW can vary along the length of the support arm **762**. In one embodiment the arm width of at least one portion of the support arm is greater than or equal to 6 mm. In an additional embodiment the arm width of at least one portion of the support arm is greater than or equal to 8 mm. In an additional embodiment the arm width of at least one portion of the support arm is greater than or equal to 10 mm.

The support arm **762** can have an arm thickness AT measured perpendicular to the rear surface **719** of the striking face **718**. The arm thickness AT can vary along the length of the support arm **762**. In one embodiment the arm thickness AT of at least one portion of the support arm is greater than or equal to 2 mm. In an additional embodiment the arm thickness AT of at least one portion of the support arm is greater than or equal to 3 mm. In an additional embodiment the arm thickness AT of at least one portion of the support arm is greater than or equal to 4 mm. In an additional embodiment the arm thickness AT of at least one portion of the support arm is greater than or equal to 5 mm. In an additional embodiment the arm thickness AT of at least one portion of the support arm is greater than or equal to 6 mm.

The rib **764** of the support arm **762** can have a rib width RW measured perpendicularly to the arm centerline CL and parallel to the rear surface **719** of the striking face **718**. The rib width RW can vary along the length of the rib. In one embodiment, the rib width RW of at least a portion of the rib is greater than or equal to 1 mm. In an additional embodiment, the rib width RW of at least a portion of the rib is greater than or equal to 2 mm. In an additional embodiment, the rib width RW of at least a portion of the rib is greater than or equal to 3 mm. In an additional embodiment, the rib width RW of at least a portion of the rib is greater than or equal to 4 mm.

The rib **764** of the support arm **762** can have a rib thickness RT measured perpendicular to the rear surface **719** of the striking face **718**. The rib thickness RT can vary along the length of the rib. In one embodiment, the rib thickness RT of at least a portion of the rib is greater than or equal to 2 mm. In an additional embodiment, the rib thickness RT of at least a portion of the rib is greater than or equal to 3 mm. In an additional embodiment, the rib thickness RT of at least a portion of the rib is greater than or equal to 4 mm. In an additional embodiment, the rib thickness RT of at least a portion of the rib is greater than or equal to 5 mm. In an additional embodiment, the rib thickness RT of at least a portion of the rib is greater than or equal to 6 mm.

The supported region **742**, as illustrated in FIG. 10, is specifically located on the rear surface **719** of the striking face **718**. The striking face heel reference plane **759** extends parallel to the y-axis and the x-axis and is offset 1 mm towards the heel from the heel-most extent of the scorelines **760** formed in the striking face **718**. The geometric center **743** of the supported region **742** is located a supported region offset length SROL toward from the striking face heel reference plane **759** measured parallel to the ground plane GP and parallel to the striking face **718** with the golf club head **700** in an address position. In one embodiment, the supported region offset length SROL is greater than or equal to 20 mm. In an additional embodiment, the supported region offset length SROL is greater than or equal to 22 mm. In an additional embodiment, the supported region offset length SROL is greater than or equal to 24 mm. In an additional embodiment, the supported region offset length SROL is greater than or equal to 26 mm. In an additional embodiment, the supported region offset length SROL is greater than or equal to 27 mm. In an additional embodiment, the supported region offset length SROL is greater than or equal to 28 mm.

The striking face length SFL is measured from the striking face heel reference plane **759** to the toe-most extent of the striking face **718**, measured parallel to the ground plane GP and parallel to the striking face **718** with the golf club head **700** in an address position. In one embodiment, the striking face length SFL is greater than or equal to 60 mm. In an additional embodiment, the striking face length SFL is greater than or equal to 65 mm. In an additional embodiment, the striking face length SFL is greater than or equal to 70 mm. In an additional embodiment, the striking face length SFL is greater than or equal to 71 mm. In an additional embodiment, the striking face length SFL is greater than or equal to 72 mm. In an additional embodiment, the striking face length SFL is greater than or equal to 73 mm. In an additional embodiment, the striking face length SFL is greater than or equal to 74 mm.

In one embodiment, the supported region offset ratio, defined as the supported region offset length SROL divided by the striking face length SFL multiplied by 100%, is greater than or equal to 40%. In an additional embodiment,

rear supported region 747 is greater than 1.6. In an additional embodiment, the ratio of the supported region 742 divided by the area of the rear supported region 747 is greater than 1.8. In an additional embodiment, the ratio of the supported region 742 divided by the area of the rear supported region 747 is greater than 2.0. In an additional embodiment, the ratio of the supported region 742 divided by the area of the rear supported region 747 is greater than 2.5. In an additional embodiment, the ratio of the supported region 742 divided by the area of the rear supported region 747 is greater than 3.0. In an additional embodiment, the ratio of the supported region 742 divided by the area of the rear supported region 747 is greater than 3.5. In an additional embodiment, the ratio of the supported region 742 divided by the area of the rear supported region 747 is greater than 4.0. In an additional embodiment, the ratio of the supported region 742 divided by the area of the rear supported region 747 is greater than 5.0. In an additional embodiment, the ratio of the supported region 742 divided by the area of the rear supported region 747 is greater than 6.0. In an additional embodiment, the ratio of the supported region 742 divided by the area of the rear supported region 747 is greater than 7.0. In an additional embodiment, the ratio of the supported region 742 divided by the area of the rear supported region 747 is greater than 8.0. In an additional embodiment, the ratio of the supported region 742 divided by the area of the rear supported region 747 is greater than 9.0. In an additional embodiment, the ratio of the supported region 742 divided by the area of the rear supported region 747 is greater than 10.0.

The contact energy absorption factor is defined as the ratio of the front diameter FD divided by the diameter of a golf ball, which is approximately 42.75 mm. In one embodiment, the contact energy absorption factor is greater than 0.1. In an additional embodiment, the contact energy absorption factor is greater than 0.2. In an additional embodiment, the contact energy absorption factor is greater than 0.3. In an additional embodiment, the contact energy absorption factor is greater than 0.4. In an additional embodiment, the contact energy absorption factor is greater than 0.5. In an additional embodiment, the contact energy absorption factor is greater than 0.6. In an additional embodiment, the contact energy absorption factor is greater than 0.7. In an additional embodiment, the contact energy absorption factor is greater than 0.8. In an additional embodiment, the contact energy absorption factor is greater than 0.9. In an additional embodiment, the contact energy absorption factor is greater than 1.0. In an additional embodiment, the contact energy absorption factor is less than 0.2. In an additional embodiment, the contact energy absorption factor is less than 0.3. In an additional embodiment, the contact energy absorption factor is less than 0.4. In an additional embodiment, the contact energy absorption factor is less than 0.5. In an additional embodiment, the contact energy absorption factor is less than 0.6. In an additional embodiment, the contact energy absorption factor is less than 0.7. In an additional embodiment, the contact energy absorption factor is less than 0.8. In an additional embodiment, the contact energy absorption factor is less than 0.9. In an additional embodiment, the contact energy absorption factor is less than 1.0.

In additional embodiments, the elastomer elements 702 may not be circular. They may have additional shapes which may include square, rectangular, octagonal, etc.

Identical golf club heads with different elastomer elements were subjected to acoustic testing to determine the effectiveness of different embodiments of elastomer elements. The testing was performed with each club head striking a Titleist ProV1 golf ball with a club head speed at

impact of approximately 95 miles per hour. The acoustic qualities of the embodiments illustrated in FIGS. 11A and 11D were recorded when each golf club head struck a golf ball. FIGS. 12A and 12B reflect the recording of the golf club head utilizing the cylindrical elastomer element embodiment illustrated in FIG. 11A striking a golf ball and FIGS. 13A and 13B reflect the recording of the golf club head utilizing the tapered elastomer element embodiment illustrated in FIG. 11D striking a golf ball. FIG. 12A illustrates the periodogram power spectral density estimate of the FIG. 11A cylindrical embodiment. FIG. 12B illustrates the sound power estimate of the FIG. 11A cylindrical embodiment. FIG. 13A illustrates the periodogram power spectral density estimate of the FIG. 11D tapered embodiment. FIG. 13B illustrates the sound power estimate of the FIG. 11D tapered embodiment.

As illustrated in FIGS. 12A and 12B, the dominant frequency for the cylindrical elastomer element 702 of FIG. 11A is 4,279.7 HZ. As illustrated in FIGS. 13A and 13B, the dominant frequency for the tapered elastomer element 702 of FIG. 11D is 4317.4 Hz. Generally, when an iron type golf club head strikes a golf ball, sound frequencies produced between approximately 1,000 Hz and 3,800 Hz are produced by golf club and golf ball interaction and golf ball resonances while sound frequencies above approximately 3,800 Hz are produced solely by the golf club head. Thus, the first sound power peak in the sound power estimate graphs of FIGS. 12B and 13B correlates primarily to the golf ball and the subsequent sound power peak correlates to the vibration of the striking face of the golf club head. As illustrated in FIGS. 12B and 13B the peak sound power estimate below 3,800 Hz, corresponding to the golf ball, is approximately 1.00×10^{-3} watts. As illustrated in FIG. 12B, the sound power generated by the golf club head utilizing the cylindrical elastomer element embodiment illustrated in FIG. 11A peaks at approximately 1.40×10^{-3} watts. As illustrated in FIG. 13B, the sound power generated by the golf club head utilizing the tapered elastomer element embodiment illustrated in FIG. 11D peaks at approximately 1.04×10^{-3} watts. Sound power levels correlate directly with the loudness of the sound produced by the golf club striking a golf ball. Therefore, it is evident that the sound produced by the golf club head utilizing the cylindrical elastomer element embodiment illustrated in FIG. 11A is significantly less loud than the golf club head utilizing the tapered elastomer element embodiment illustrated in FIG. 11D.

Additionally, the sound power generated by the golf club head utilizing the cylindrical elastomer element embodiment illustrated in FIG. 11A divided by the sound power generated by the golf ball is approximately 1.40. The sound power generated by the golf club head utilizing the cylindrical elastomer element embodiment illustrated in FIG. 11D divided by the sound power generated by the golf ball is approximately 1.04. In some embodiments, it is preferable to have the sound power generated by the golf club head divided by the sound power generated by the golf ball to be less than 1.50. In some embodiments, it is preferable to have the sound power generated by the golf club head divided by the sound power generated by the golf ball to be less than 1.30. In some embodiments, it is preferable to have the sound power generated by the golf club head divided by the sound power generated by the golf ball to be less than 1.20. In some embodiments, it is preferable to have the sound power generated by the golf club head divided by the sound power generated by the golf ball to be less than 1.10.

generated by the golf ball to be less than 1.10. In some embodiments, it is preferable to have the sound power generated by the golf club head divided by the sound power generated by the golf ball to be less than 1.00.

FIGS. 14A-L depict additional embodiments of an elastomer element 702, which can also be referred to as a deformable member. These embodiments are designed with variable compressive stiffness, spring rate, or flexural modulus. This can be achieved through various geometries as well as combinations of various co-molded materials of different durometers.

FIG. 14A illustrates a cross sectional view of an elastomer element 702 having a larger rear portion 744 than front portion 702. The front portion 702 and rear portion 744 are substantially planar. FIG. 14B illustrates a cross sectional view of an elastomer element 702 having a larger rear portion 744 than front portion 702. The rear portion 744 is substantially planar and the front portion 702 is hemispherical. FIG. 14C illustrates a cross sectional view of an elastomer element 702 having a larger rear portion 744 than front portion 702. The elastomer element 702 includes a front constant diameter region 746 and a rear constant diameter region 745, where the rear constant diameter region 746 has a larger diameter than the front constant diameter region 745. FIG. 14D illustrates a cross sectional view of an elastomer element 702 similar to that of FIG. 14A but includes a first material 770 and a second material 780. In one embodiment, the first material 770 can be stiffer than the second material 780. In an additional embodiment, the second material 780 can be stiffer than the first material 770. FIG. 14E illustrates a cross sectional view of an elastomer element 702 similar to that of FIG. 14B but includes a first material 770 and a second material 780. FIG. 14F illustrates a cross sectional view of an elastomer element 702 similar to that of FIG. 14C but includes a first material 770 and a second material 780.

FIG. 14G illustrates a cross sectional view of an elastomer element 702 similar to that of FIG. 14A but the center of the front portion 703 is offset from a center of the rear portion 744. The offset can be towards the topline, towards the sole, towards the toe, towards the heel, or any combination thereof. FIG. 14H illustrates a cross sectional view of an elastomer element 702 similar to that of FIG. 14B but the center of the front portion 703 is offset from a center of the rear portion 744. FIG. 14I illustrates a cross sectional view of an elastomer element 702 similar to that of FIG. 14C but the center of the front portion 703 is offset from a center of the rear portion 744. FIG. 14J illustrates a cross sectional view of an elastomer element 702 which necks down in diameter between the front portion 703 and the rear portion 744. FIG. 14K illustrates a cross sectional view of an elastomer element 702 which necks down in diameter between the front portion 703 and the rear portion 744. FIG. 14L illustrates a cross sectional view of an elastomer element 702 similar to that of FIG. 14J but includes a first material 770 and a second material 780.

Any of these embodiments of elastomer element 702 described herein can be flipped, such that the rear portion 744 abuts the rear surface of the striking face rather than the front portion 704. Additionally, the embodiments illustrated in FIGS. 14A-14L are circular when viewed from a front view in a preferred embodiment. In other embodiments, the elastomer elements may comprise different shapes. In some embodiments, the flexural modulus of the first material can be greater than the flexural modulus of the second material.

FIGS. 15A-15D depict a golf club head 800 having an elastomer element 702. FIG. 15A depicts a rear view of the

golf club head 800. FIG. 15B depicts a perspective view of the golf club head 800 of FIG. 15A. FIG. 15C depicts an additional perspective view of the golf club head 800 of FIG. 15A. FIG. 15D depicts a section view E-E of the golf club head 800 of FIG. 15A. FIG. 16 depicts the section view E-E of the golf club head 800 of FIG. 15D without the adjustment driver 830 and elastomer element 702 installed. FIG. 17A depicts a perspective view of the adjustment driver 830 and elastomer element 702 of the golf club head 800 of FIG. 15A. FIG. 17B depicts an additional perspective view of the adjustment driver 830 and elastomer element 702 of the golf club head 800 of FIG. 15A. FIG. 17C depicts a side view of the adjustment driver 830 and elastomer element 702 of the golf club head 800 of FIG. 15A. FIG. 17D depicts a section view of the adjustment driver 830 and elastomer element 702 of FIG. 17A. FIG. 17E depicts an additional perspective of the section view of the adjustment driver 830 and elastomer element 702 of FIG. 17A.

As illustrated in FIGS. 15D and 16, the golf club head 800 includes a striking face 818 having a rear surface 819. The golf club head 800 also includes a back portion 812 configured to support the elastomer element 702. The golf club head 800 is made with a hollow body construction and the back portion 812 covers a substantial portion of the back of the golf club head 800. The back portion 812 is located behind the striking face 818 and extends between the topline 807 and the sole 805 and from the heel 804 to the toe 806 forming a cavity 820. The elastomer element 702 is disposed within the cavity 820. As illustrated in FIG. 15D, the striking face 818 can be formed separately and welded to the rest of the golf club head 800. More specifically, the separately formed striking face portion can include a portion of the sole, forming an L-shaped striking face portion. In other embodiments, the striking face 818 may be formed integrally with the rest of the golf club.

The golf club head 800 includes an adjustment driver 830 much like the adjustment driver 330 described earlier and illustrated in FIGS. 3A and 3B. The golf club head 800 also includes a deformable member 702 disposed between the striking face 818 and the adjustment driver 830. The deformable member 702 can take the form of any of the elastomer elements described herein. The adjustment driver 830 is configured to retain the elastomer element 702 between the adjustment driver 830 and the striking face 818, with the front portion 703 of the elastomer element 702 contacting the rear surface 819 of the striking face 818 and the rear portion 744 of the elastomer element 702 contacting the adjustment driver 830. The adjustment driver can include an interface 834 configured to retain the elastomer element 702. The interface 834 can include a recess with a lip 809 surrounding at least a portion of the elastomer element 702 as illustrated in FIGS. 15D and 17A-17E.

The golf club head 800 can include an adjustment receiver 890, much like the adjustment receiver 306 illustrated in FIGS. 3A and 3B. As illustrated in FIG. 16, the adjustment receiver 890 can include an aperture formed in the back portion 812 of the golf club head 800. The aperture can include a threaded portion 893. Additionally, the adjustment receiver 890 can include a receiver shelf 895 for the adjustment driver 830 to engage when it is installed in the adjustment receiver 890 as illustrated in FIG. 15D. The adjustment driver 830, as illustrated in FIGS. 15D and 17A-17E, can include a threaded portion 833 configured to engage the threaded portion 893 of the adjustment receiver 890. Additionally, the adjustment driver 830 can include a flange 835 configured to engage the receiver shelf 895 of the adjustment receiver 890 when the adjustment driver 830 is

installed in the adjustment receiver **890**. The receiver shelf **895** and flange **835** help to ensure the elastomer element properly and consistently engages the rear surface **819** of the striking face **818** and provides the support necessary for optimal performance. While the adjustment driver **330** discussed earlier is configured such that it may be adjusted after assembly, the preferred embodiment of the adjustment driver **830** illustrated in FIGS. **15A-15D** and **17A-17E** is configured to be installed to a set position during assembly and remain in that position. The receiver shelf **895** and flange **835** help to ensure the adjustment driver **830** is installed consistently and that the elastomer element properly and consistently engages the rear surface **819** of the striking face **818** and provides the support necessary for optimal performance. The adjustment driver **830** can also include a screw drive **832** configured to receive a tool and allow the adjustment driver **830** to be rotated relative to the golf club head **800**. Finally, the adjustment driver **830** can have a mass. In some embodiments, the mass of the golf club head can be adjusted by swapping out the adjustment driver **830** for another adjustment driver **830** having a different mass. The difference in mass can be achieved through the use of different materials for different adjustment drivers such as aluminum, brass, polymers, steel, titanium, tungsten, etc. In another embodiment, not illustrated, mass elements could be added to the adjustment driver to change the mass. In one embodiment, mass elements could be added to the recess of the adjustment driver. Additionally, the mass element added to the recess could also be used to change the distance between the rear portion of the elastomer element and the rear surface of the striking face, altering the compression of the elastomer element.

FIGS. **18-22** depict a golf club head **900** similar to the golf club head **800** depicted in FIGS. **15A-15D**. Golf club head **900** however includes a second deformable member **702B** in addition to a first deformable member **702A**. FIG. **18** depicts a rear view of the golf club head **900**. FIG. **19** depicts an exploded view of the golf club head **900** of FIG. **18**. FIG. **20** depicts a section view F-F of the golf club head **900**. FIG. **21** depicts a section view G-G of the golf club head **900**. FIG. **22** depicts a frontal view of the golf club head **900** of FIG. **18**, including the supported regions.

As illustrated in FIGS. **18-22**, the golf club head **900** includes a striking face **918** having a rear surface **919**. The golf club head **900** also includes a back portion **912** configured to support the first deformable member **702A** and the second deformable member **702B**. The first deformable member **702A** can be the same as the deformable member **700** described earlier. The first deformable member **702A** and a second deformable member **702B** can each take the form of any of the elastomer elements described herein. They may take the same form, or they may take different forms. The golf club head **900** is made with a hollow body construction and the back portion **912** covers a substantial portion of the back of the golf club head **900**. The back portion **912** is located behind the striking face **918** and extends between the topline **917** and the sole **905** from the heel **904** to the toe **906** forming a cavity **920**. In the preferred illustrated embodiments the first deformable member **702A** is spaced from and does not contact the second deformable member **702B**. In an alternative embodiment, the first deformable member **702A** may be spaced closely to and contact the second deformable member **702B**.

Much like golf club head **800**, the golf club head **900** includes an adjustment driver **830** configured to retain the first deformable member **702A**. The front portion **703A** of the first deformable member **702A** contacts the rear surface

919 of the striking face **918**. The back portion **912** of the golf club head **900** includes a back cover **913**. In the illustrated embodiment, the back cover **913** includes a recess **915** configured to retain the second deformable member **702B** such that the front portion **703B** of the second deformable member **702B** contacts the rear surface **919** of the striking face **918**. The back cover **913** also includes an aperture **914** for the adjustment driver **830**. In one embodiment, the second deformable member is attached to the back cover **913** with an adhesive. Additionally, the back cover **913** can be attached to the rest of the golf club head **900** with an adhesive, which may include, for example, double sided tape. In one embodiment, the striking face **918** of the golf club head **900** is made from a high density material such as steel, whereas the back cover **913** is made from a low density material, such as plastic, which may include for example, acrylonitrile butadiene styrene. In an alternative embodiment, the back cover may also be made of a high density material.

As illustrated in FIG. **22**, the striking face includes a plurality of supported regions. The first supported region **742A** is defined by the portion of the rear surface **919** of the striking face **918** supported by the first deformable member **702A**, which is defined by the area inside the first supported region perimeter **740A** defined by the outer extent of the front portion **703A** of the first deformable member **702A** in contact with the rear surface **919** of the striking face **918**. The second supported region **742B** is defined by the portion of the rear surface **919** of the striking face **918** supported by the second deformable member **702B**, which is defined by the area inside the second supported region perimeter **740B** defined by the outer extent of the front portion **703B** of the second deformable member **702B** in contact with the rear surface **919** of the striking face **918**. The first supported region **742A** and second supported region **742B** wouldn't normally be visible from the front of the golf club head **900** but was added in FIG. **22** for illustrative purposes.

The first geometric center **743A** of the first supported region **742A** is located a first supported region offset length **SROL 1** toward from the striking face heel reference plane **959**, measured parallel to the ground plane and parallel to the striking face **918** with the golf club head **900** in an address position. The second geometric center **743B** of the second supported region **742B** is located a second supported region offset length **SROL 2** toward from the striking face heel reference plane **959**, measured parallel to the ground plane and parallel to the striking face **918** with the golf club head **900** in an address position.

In a preferred embodiment, **SROL 1** is approximately 36.0 mm and **SROL 2** is approximately 17.6 mm. In a preferred embodiment **SROL 1** is greater than **SROL 2**. In a preferred embodiment, **SROL 1** divided by **SROL 2** is greater than 1.0. In a preferred embodiment, **SROL 1** divided by **SROL 2** is greater than 1.25. In a preferred embodiment, **SROL 1** divided by **SROL 2** is greater than 1.50. In a preferred embodiment, **SROL 1** divided by **SROL 2** is greater than 1.75. In a preferred embodiment, **SROL 1** divided by **SROL 2** is greater than 2.0. In an alternative embodiment, not illustrated, **SROL 2** is greater than **SROL 1**.

In one embodiment, the first deformable member **702A** is made of the same material as the second deformable member **702B** and thus has the same hardness. In an additional embodiment, the first deformable member **702A** is made of a material which has a greater hardness than the material of the second deformable member **702B**. In an alternative embodiment, the material of the first deformable member **702A** has a lower modulus than the material of the second

deformable member 702B. In one embodiment, the first deformable member 702A has a Shore A 50 durometer and the second deformable member has a Shore A 10 durometer. In one embodiment, the first deformable member 702A has a Shore A durometer greater than 25 and the second deformable member has a Shore A durometer less than 25.

It should be noted that the first deformable member could be housed, structured, or supported similarly to the second deformable member and also the second deformable member could be housed, structured, or supported similarly to the first deformable member. Additionally, the first deformable member and second deformable member could be housed, structured, or supported in any fashion described throughout this disclosure.

FIG. 23 depicts a perspective view of golf club head 900 and an additional embodiment of the second deformable member 702C. The second deformable member 702C is illustrated in an exploded fashion behind the golf club head 900. FIG. 24 depicts the second deformable member 702C illustrated in FIG. 23. FIG. 25 depicts a section view F-F of the golf club head 900 including the second deformable member 702C illustrated in FIGS. 23 and 24. The back portion 912 of the golf club head 900 includes an aperture 930 configured to receive the second deformable member 702C, or alternatively the second deformable member 702B. The second deformable member 702C, as illustrated in FIGS. 23-25, includes an annular groove 940 formed therein configured to engage the perimeter of the aperture 930 of the back portion 912 of the golf club head 900 and secure the second deformable member 702C to the golf club head 900. Portions of the second deformable member 702C can be configured to deform as the second deformable member 702C is installed in the aperture 930 of the golf club head 900 until the groove 940 engages the aperture 930.

Although specific embodiments and aspects were described herein and specific examples were provided, the scope of the invention is not limited to those specific embodiments and examples. One skilled in the art will recognize other embodiments or improvements that are within the scope and spirit of the present invention. Therefore, the specific structure, acts, or media are disclosed only as illustrative embodiments. The scope of the invention is defined by the following claims and any equivalents therein.

The invention claimed is:

1. A golf club head comprising:
 a club head body comprising a back portion and a striking face;
 wherein said striking face comprises a front surface configured to strike a golf ball and a rear surface opposite said front surface;
 wherein said back portion is spaced from said rear surface;
 a first deformable member residing between said back portion and said rear surface of said striking face;
 wherein said first deformable member comprises a front surface in contact with said rear surface of said striking face and a rear surface in contact with said back portion; and
 a second deformable member residing between said back portion and said rear surface of said striking face;
 wherein said second deformable member comprises a front surface in contact with said rear surface of said striking face and a rear surface in contact with said back portion; and
 a coordinate system centered at a center of gravity of said golf club head, said coordinate system comprising a y-axis extending vertically, perpendicular to a ground plane when

said golf club head is in an address position at prescribed loft and lie, an x-axis perpendicular to said y-axis and parallel to the striking face, extending towards a heel of said golf club head, and a z-axis, perpendicular to said y-axis and said x-axis and extending through said striking face, wherein said striking face comprises a plurality of scorelines, wherein said striking face comprises a heel reference plane extending parallel to said y-axis and said-x-axis, wherein said heel reference plane is offset 1 millimeter towards said heel from a heel-most extent of said scorelines, wherein said striking face comprises a striking face length measured from said heel reference plane to a toe-most extent of said front surface of said striking face parallel to said x-axis;

wherein said rear surface of said striking face comprises a first supported region, wherein a perimeter of said front surface of said first deformable member defines said first supported region, wherein said first supported region comprises a first geometric center, wherein said first geometric center of said first supported region is located a first supported region offset length toward from said heel reference plane measured parallel to said x-axis;

wherein said rear surface of said striking face comprises a second supported region, wherein a perimeter of said front surface of said second deformable member defines said second supported region, wherein said second supported region comprises a second geometric center, wherein said second geometric center of said second supported region is located a second supported region offset length toward from said heel reference plane measured parallel to said x-axis;

wherein said first supported region offset length divided by said second supported region offset length is greater than 1.0.

2. The golf club head of claim 1, wherein said first supported region offset length divided by said second supported region offset length is greater than 1.5.

3. The golf club head of claim 1, wherein said first supported region offset length divided by said second supported region offset length is greater than 2.0.

4. The golf club head of claim 1, wherein at least a portion of said striking face comprises a thickness of less than or equal to 2.2 mm.

5. The golf club head of claim 1, wherein said front surface of said first deformable member is circular having a front diameter, wherein said rear surface of said first deformable member is circular having a rear diameter, wherein said front diameter is less than said rear diameter and wherein said front surface of said second deformable member is circular having a front diameter, wherein said rear surface of said second deformable member is circular having a rear diameter, wherein said front diameter is less than said rear diameter.

6. The golf club head of claim 1, wherein said first deformable member has a greater Shore A durometer than said second deformable member.

7. The golf club head of claim 1, wherein said striking face comprises a first density, wherein said back portion comprises a back cover, wherein said back cover comprises a recess, wherein said second deformable member is at least partially retained within said recess, wherein said back cover comprises a second density, wherein said first density is greater than said second density.

8. The golf club head of claim 1, wherein said center of gravity of said golf club head is located less than or equal to 20 millimeters above said ground plane, measured parallel

31

to said y-axis, and wherein said golf club head comprises an MOI-Y greater than or equal to 250 kg-mm².

9. A golf club head comprising:

a club head body comprising a back portion and a striking face;

wherein said striking face comprises a front surface configured to strike a golf ball and a rear surface opposite said front surface;

wherein said back portion is spaced from said rear surface;

a first deformable member residing between said back portion and said rear surface of said striking face;

wherein said first deformable member comprises a front surface in contact with said rear surface of said striking face; and

a second deformable member residing between said back portion and said rear surface of said striking face;

wherein said second deformable member comprises a front surface in contact with said rear surface of said striking face;

wherein said first deformable member has a greater Shore A durometer than said second deformable member;

wherein said golf club head comprises an interior cavity formed between said back portion and said striking face, wherein an aperture is formed through said back portion, an adjustment driver residing within said aperture, said adjustment driver comprising a recess adjacent said interior cavity, wherein at least a portion of said first deformable member resides within said recess, wherein said back portion comprises a shelf surrounding said aperture and wherein said adjustment driver comprises a flange, said flange in contact with said shelf.

10. The golf club head of claim 9, wherein said striking face comprises a first density, wherein said back portion comprises a back cover, wherein said back cover comprises a recess, wherein said second deformable member is at least partially retained within said recess, wherein said back cover comprises a second density, wherein said first density is greater than said second density.

11. The golf club head of claim 9, wherein at least a portion of said striking face comprises a thickness of less than or equal to 2.2 mm.

12. The golf club head of claim 9, further comprising a coordinate system centered at a center of gravity of said golf club head, said coordinate system comprising a y-axis extending vertically, perpendicular to a ground plane when said golf club head is in an address position at prescribed loft and lie, an x-axis perpendicular to said y-axis and parallel to the striking face, extending towards a heel of said golf club head, and a z-axis, perpendicular to said y-axis and said x-axis and extending through said striking face, wherein said striking face comprises a plurality of scorelines, wherein said striking face comprises a heel reference plane extending parallel to said y-axis and said-x-axis, wherein said heel reference plane is offset 1 millimeter towards said heel from a heel-most extent of said scorelines, wherein said striking face comprises a striking face length measured from said heel reference plane to a toe-most extent of said front surface of said striking face parallel to said x-axis, wherein said rear surface of said striking face comprises a first supported region, wherein a perimeter of said front surface of said first deformable member defines said first supported region, wherein said first supported region comprises a first geometric center, wherein said first geometric center of said first supported region is located a first supported region offset length toward from said heel reference plane measured

32

parallel to said x-axis, wherein said rear surface of said striking face comprises a second supported region, wherein a perimeter of said front surface of said second deformable member defines said second supported region, wherein said second supported region comprises a second geometric center, wherein said second geometric center of said second supported region is located a second supported region offset length toward from said heel reference plane measured parallel to said x-axis, wherein said first supported region offset length divided by said second supported region offset length is greater than 1.5.

13. A golf club head comprising:

a club head body comprising a back portion and a striking face;

wherein said striking face comprises a front surface configured to strike a golf ball and a rear surface opposite said front surface;

wherein said back portion is spaced from said rear surface;

a first deformable member residing between said back portion and said rear surface of said striking face;

wherein said first deformable member comprises a front surface in contact with said rear surface of said striking face; and

a second deformable member residing between said back portion and said rear surface of said striking face;

wherein said second deformable member comprises a front surface in contact with said rear surface of said striking face;

wherein said first deformable member has a greater Shore A durometer than said second deformable member;

wherein said front surface of said first deformable member is circular having a front diameter, wherein said rear surface of said first deformable member is circular having a rear diameter, wherein said front diameter is less than said rear diameter, wherein said front surface of said second deformable member is circular having a front diameter, wherein said rear surface of said second deformable member is circular having a rear diameter, wherein said front diameter is less than said rear diameter.

14. A golf club head comprising:

a club head body comprising a back portion and a striking face;

wherein said striking face comprises a front surface configured to strike a golf ball and a rear surface opposite said front surface;

wherein said back portion is spaced from said rear surface;

a first deformable member residing between said back portion and said rear surface of said striking face;

wherein said first deformable member comprises a front surface in contact with said rear surface of said striking face; and

a second deformable member residing between said back portion and said rear surface of said striking face;

wherein said second deformable member comprises a front surface in contact with said rear surface of said striking face;

wherein said back portion comprises a back cover;

wherein said back cover comprises a recess; and

wherein said second deformable member is at least partially retained within said recess.

15. The golf club head of claim 14, wherein said striking face comprises a first density, wherein said back cover comprises a second density, wherein said first density is greater than said second density.

16. The golf club head of claim 14, wherein said first deformable member has a greater Shore A durometer than said second deformable member.

17. The golf club head of claim 14, wherein at least a portion of said striking face comprises a thickness of less than or equal to 2.2 mm. 5

18. The golf club head of claim 14, wherein said front surface of said first deformable member is circular having a front diameter, wherein said rear surface of said first deformable member is circular having a rear diameter, wherein said front diameter is less than said rear diameter, wherein said front surface of said second deformable member is circular having a front diameter, wherein said rear surface of said second deformable member is circular having a rear diameter, wherein said front diameter is less than said rear diameter. 10 15

19. The golf club head of claim 14, wherein said golf club head comprises an interior cavity formed between said back portion and said striking face, wherein an aperture is formed through said back portion, an adjustment driver residing within said aperture, said adjustment driver comprising a recess adjacent said interior cavity, wherein at least a portion of said first deformable member resides within said recess, wherein said back portion comprises a shelf surrounding said aperture and wherein said adjustment driver comprises a flange, said flange in contact with said shelf. 20 25

* * * * *