



(19) **United States**

(12) **Patent Application Publication**
Weaver et al.

(10) **Pub. No.: US 2017/0061816 A1**
(43) **Pub. Date: Mar. 2, 2017**

(54) **SYSTEMS, METHODS AND APPARATUS FOR ENCOURAGING ENERGY CONSCIOUS BEHAVIOR BASED ON AGGREGATED THIRD PARTY ENERGY CONSUMPTION**

G05D 23/19 (2006.01)
G06Q 50/06 (2006.01)
F24F 11/00 (2006.01)
H02J 3/14 (2006.01)
G05B 15/02 (2006.01)

(71) Applicant: **Google Inc.**, Mountain View, CA (US)

(52) **U.S. Cl.**

(72) Inventors: **Jason C. Weaver**, Austin, TX (US);
Bradley A. Kayton, Hollis, NH (US)

CPC *G09B 19/00* (2013.01); *H02J 3/14* (2013.01); *G05F 1/66* (2013.01); *G05B 15/02* (2013.01); *G06Q 50/06* (2013.01); *F24F 11/006* (2013.01); *F24F 11/0015* (2013.01); *F24F 11/0012* (2013.01); *G05D 23/1917* (2013.01); *H02J 2003/143* (2013.01); *F24F 2011/0075* (2013.01); *F24F 2011/0091* (2013.01); *F24F 2011/0047* (2013.01); *F24F 2011/0058* (2013.01); *F24F 2011/0049* (2013.01); *H04L 67/12* (2013.01)

(73) Assignee: **Google Inc.**, Mountain View, CA (US)

(21) Appl. No.: **15/351,202**

(22) Filed: **Nov. 14, 2016**

Related U.S. Application Data


(63) Continuation of application No. 14/789,716, filed on Jul. 1, 2015, now Pat. No. 9,507,363, which is a continuation of application No. 14/473,893, filed on Aug. 29, 2014, now Pat. No. 9,081,405, which is a continuation of application No. 13/327,459, filed on Dec. 15, 2011, now Pat. No. 9,500,385, which is a continuation of application No. 12/241,588, filed on Sep. 30, 2008, now Pat. No. 8,160,752.

(57) **ABSTRACT**

Accessing an energy management policy for a plurality of devices is described, wherein the devices are coupled with a first structure. The energy usage of the devices is monitored. An energy usage rule and energy usage is then compared. The energy management policy and energy usage is also compared. Based on the comparing, an instruction is generated to modify an energy usage profile of said device to correlate with the energy usage rule associated with the devices and the energy management policy, thereby enabling efficient energy management.

Publication Classification

(51) **Int. Cl.**
G09B 19/00 (2006.01)
G05F 1/66 (2006.01)






FIG. 1




FIG. 2

300




FIG. 3




FIG. 4

500




FIG. 5

600




FIG. 6

**SYSTEMS, METHODS AND APPARATUS
FOR ENCOURAGING ENERGY CONSCIOUS
BEHAVIOR BASED ON AGGREGATED
THIRD PARTY ENERGY CONSUMPTION**

CROSS REFERENCES

[0001] This application is a continuation of U.S. patent application Ser. No. 14/789,716 filed on Jul. 1, 2015, which is incorporated herein by reference. U.S. patent application Ser. No. 14/789,716 is a continuation of U.S. patent application Ser. No. 14/473,893 filed on Aug. 29, 2014, which is incorporated herein by reference. U.S. patent application Ser. No. 14/473,893 is a continuation of U.S. patent application Ser. No. 13/327,459 filed on Dec. 15, 2011, which is incorporated herein by reference. U.S. patent application Ser. No. 13/327,459 is a continuation of U.S. patent application Ser. No. 12/241,588 filed on Sep. 30, 2008, which is incorporated herein by reference.

FIELD

[0002] The field of the present invention relates to computer systems. More particularly, embodiments of the present invention relate to energy management systems.

BACKGROUND

[0003] Consumers experiment with different ways of reducing household energy usage. For example, consumers may turn off air conditioning during certain parts of the day, run certain appliances only during the early morning hours, and replace large inefficient appliances with smaller energy efficient ones. Additionally, consumers may use measuring devices to calculate the energy usage rate of a particular device. Then, depending upon the measured energy usage, a consumer may decide to turn the device on and off to adjust the home's overall energy usage.

[0004] However, there exist limitations as to the current system for measuring the energy usage of a particular device. While a device's energy usage may be determined for a given point in time, it is unclear what this determination means. For example, an energy usage measurement might specify that a device is using 2 kilowatts per hour. While this information may be useful to a scientist, the average consumer is not well acquainted with the kilowatt. Furthermore, it is not clear to the consumer what the 2 kilowatts per hour static measurement means in context with the energy usage of a possible new device, other devices, and/or the entire household of devices. Thus, current energy usage measurements are cryptic and not very useful to the average consumer.

BRIEF SUMMARY

[0005] Accessing an energy management policy for a plurality of devices is described, wherein the devices are coupled with a first structure. The energy usage of the devices is monitored. An energy usage rule and energy usage is then compared. The energy management policy and energy usage is also compared. Based on the comparing, an instruction is generated to modify an energy usage profile of said device to correlate with the energy usage rule associated with the devices and the energy management policy, thereby enabling efficient energy management.

BRIEF DESCRIPTION OF THE DRAWINGS

[0006] The accompanying drawings, which are incorporated in and form a part of this specification, illustrate embodiments of the present invention for managing energy usage and, together with the description, serve to explain principles discussed below:

[0007] FIG. 1 is a block diagram of an example system for managing energy usage in accordance with embodiments of the present invention.

[0008] FIG. 2 is a block diagram of an example system for managing energy usage in accordance with embodiments of the present invention.

[0009] FIG. 3 is a flowchart of an example method of managing energy usage in accordance with embodiments of the present invention.

[0010] FIG. 4 is a diagram of an example computer system used for managing energy usage in accordance with embodiments of the present invention.

[0011] FIG. 5 is a flowchart of an example method of managing energy usage in accordance with embodiments of the present invention.

[0012] FIG. 6 is a flowchart of an example method of managing energy usage in accordance with embodiments of the present invention.

[0013] The drawings referred to in this description should not be understood as being drawn to scale unless specifically noted.

DESCRIPTION OF EMBODIMENTS

[0014] Reference will now be made in detail to embodiments of the present invention, examples of which are illustrated in the accompanying drawings. While the invention will be described in conjunction with various embodiment(s), it will be understood that they are not intended to limit the present invention to these embodiments. On the contrary, the present invention is intended to cover alternatives, modifications and equivalents, which may be included within the spirit and scope of the various embodiments as defined by the appended claims.

[0015] Furthermore, in the following detailed description, numerous specific details are set forth in order to provide a thorough understanding of the present invention. However, the present invention may be practiced without these specific details. In other instances, well known methods, procedures, components, and circuits have not been described in detail as not to unnecessarily obscure aspects of the present embodiments.

[0016] Unless specifically stated otherwise as apparent from the following discussions, it is appreciated that throughout the present detailed description, discussions utilizing terms such as "accessing", "monitoring", "comparing", "modifying", "enabling", "tracking", "generating", "estimating", "alerting", or the like, refer to the actions and processes of a computer system, or similar electronic computing device. The computer system or similar electronic computing device manipulates and transforms data represented as physical (electronic) quantities within the computer system's registers and memories into other data similarly represented as physical quantities within the computer system memories or registers or other such information storage, transmission, or display devices. The present invention is also well suited to the use of other computer systems such as, for example, optical and mechanical computers.

Overview of Discussion

[0017] Embodiments in accordance with the present invention pertain to a system for managing energy usage. In one embodiment, the system described herein enables conservation of household energy by advising a user to modify the household's energy usage to correlate to a desired energy usage for that household.

[0018] More particularly, one embodiment of the present invention functions as a household energy manager. For example, the energy manager attaches to a household wall and replaces the typical heating-cooling thermostat controller. The energy manager then utilizes an energy-measuring module coupled with a household device to monitor the energy usage of the household device. For example, an energy-measuring module coupled with a dishwasher may measure a dishwasher utilizing 1.20 kilowatts per hour of electricity.

[0019] In addition to monitoring individual appliances, the energy manager may utilize an energy-measuring module, such as a smart meter, coupled with the house to monitor the total household's energy usage. For example, a smart meter may measure the overall energy usage of all appliances within a household, including the dishwasher, to be 21 kilowatts per hour of electricity.

[0020] The energy manager then may access an energy usage rule describing a desired energy usage for a device and/or the household. This energy usage rule may be pre-programmed and internal to the energy manager or may be accessed at a server positioned external to the energy manager. This server in turn may receive a demand-response call from an energy utility company. For example, a demand-response call may indicate that it is desirable that the aforementioned dishwasher is to use up to a maximum of 1.00 kilowatt per hour of electricity at any given time. Furthermore, an overall energy management policy may specify that the household may use up to a maximum of 20 kilowatts per hour of energy at any point in time.

[0021] Based on the comparison between the measured energy usage of a household device and that device's desired energy usage, the energy manager may modify the device's energy usage to conform with the overall desired energy usage. For example, based on the comparison between the dishwasher's measured 1.20 kilowatts per hour of energy usage, and the household's use of 21 kilowatts per hour of electricity, the energy manager may modify the dishwasher's energy usage by turning it off and on at time periods separate from other high energy usage appliances, to keep the overall household energy use below 20 kilowatts per hour at any given point in time.

[0022] Thus, an energy manager may utilize an internally preprogrammed energy usage rule and/or a demand-response call received via a server from an energy utility company to advise a user to modify a device's energy usage.

[0023] The following discussion will begin with a detailed description of the structure of components herein in accordance with the present invention. This discussion will then be followed by a detailed description of the operation and function of the components herein.

Energy Manager

[0024] FIG. 1 is a block diagram of an example energy manager 100 in accordance with embodiments of the present invention. Energy manager 100, coupled with first structure

140, comprises energy usage rule accessor 105, energy usage rule comparator 125, and energy usage profile generator 135

[0025] Continuing with FIG. 2, a block diagram is shown of an example energy manager 100 in which energy usage rule accessor 105 comprises server accessor 220 and user instruction accessor 230. In another embodiment, energy usage rule comparator 125 comprises passive power consumption tracker 235. In one embodiment, energy manager 100 further comprising interface compatibility module 205 and graphical display module 215.

[0026] Energy manager 100 is shown coupled wirelessly with device 204 via energy-measuring module 250a and compatible communication module 210. Of note, energy-measuring module 250a may be coupled with energy manager 100 in such a way as to be part of energy manager 100. Energy-measuring module 250a operates as an inductive donut surrounding the electrical cord that couples device 204 with an electrical outlet of first structure 140. As will be described herein, energy-measuring module 250a listens for information such as energy usage signatures specific to device 204. This information is communicated wirelessly to energy manager 100 via a wireless transmitter and receiver coupled with energy measuring module 250a and compatible communication module 210, such as but not limited to the wireless Ethernet, ZigBee, X10, or some other suitable wireless protocol.

[0027] In another embodiment, energy manager 100 is shown coupled wirelessly with energy-measuring module 250b. Energy-measuring module 250b may be a digital meter coupled with the outside of the home. Energy utility 240 has access to this digital meter. The digital meter provides information regarding the total energy usage of the household. This information is communicated wirelessly to energy manager 100 via a wireless transmitter and receiver coupled with energy-measuring module 250b and energy manager 100, such as such as but not limited to the wireless Ethernet, ZigBee, X10, or some other suitable wireless protocol.

[0028] In one embodiment, energy manager 100 is shown coupled wirelessly with energy-measuring modules 250c1 and 250c2 of a group of energy-measuring modules denoted as 250c, that are themselves coupled with subpanels positioned on the side wall and ceiling of first structure 140. Of note, in another embodiment, energy manager 100 may also be coupled with energy-measuring modules 250c1 and 250c2 via a wire. Additionally, energy manager 100 is well suited to being coupled with a plurality of more than two energy-measuring modules of energy-measuring module group 250c at any number of locations within first structure 140.

[0029] Energy-measuring modules 250c1 and 250c2 that are coupled with the subpanels and positioned in the proximity of device 204 listen for information such as energy usage signatures specific to device 204. For example, a certain amount of signal noise flows between and through energy-measuring modules 250c1 and 250c2. By identifying and comparing said signal noise received at energy-measuring modules 250c1 and 250c2, better granularity in reading the energy signature of device 204 can be obtained. The more 250c energy-measuring modules that are positioned at first structure 140, the more data that can be collected. The more data that can be collected, the more accurate is the determination of energy usage per device 204.

[0030] Of note, energy usage rule 202 may be any recommendation or instruction for energy usage as it relates to device 204, either alone, or as part of an energy management policy for one or more devices. In one embodiment, an energy management policy may designate the overall desired household energy usage as well as the desired energy usage for individual devices therein.

[0031] In one embodiment, energy usage rule 202 is preprogrammed within energy manager 100. In another embodiment, energy usage rule 202 is external to energy manager 100, located at server 225, and provided to server 225 via energy utility 240 or other Internet hosted servers. In one embodiment, server 225 acts as a central management server. Energy utility 240 is coupled with energy manager 100 via Internet 245 and server 225, and is coupled with first structure 140 via energy-measuring module 250b.

[0032] In another embodiment, unit 260 is coupled with device 204 and electrical outlet 265 with which device 204 is also coupled. Additionally, the present invention is well suited to having any number of units 260 coupled with any number of devices and any number of electrical outlets. Unit 260 is configured to receive an instruction to modify an energy usage profile of device 204 to correlate with device 204's energy usage rule. In essence, unit 260 may control the power to device 204. Of note, unit 260 may receive instructions to modify the energy usage profile of device 204 from any device capable of sending receivable instructions.

[0033] In one embodiment, an energy manager 100 coupled with a subpanel within first structure 140 wirelessly transmits an instruction to unit 260 to modify the energy usage profile of device 204. In another embodiment, user 255 may email an instruction to unit 260 to modify device 204 coupled therewith. More particularly, in one example, unit 260 is coupled with a lamp. Energy manager 100 sends a message to unit 260 that the lamp is utilizing too many kilowatts per hour of energy and needs to be turned down. Unit 260 then dims the lamp's lighting, thus decreasing the lamp's energy usage according to the instructions.

[0034] Continuing with FIG. 2, device 204 may be any device that may be coupled with first structure 140. Of note, device 204 may be any device capable of utilizing energy within first structure 140. However, for purposes of brevity and clarity, device 204 is sometimes referred to herein as "household device". For example, device 204 may be a washer, a dryer, a refrigerator, a dishwasher, a toaster, etc. Furthermore, first structure 140 may be any structure with which one or more devices may be coupled and within which one or more devices may use electricity. However, for purposes of brevity and clarity, first structure 140 is sometimes referred to herein as "household".

Operation

[0035] More generally, in embodiments in accordance with the present invention, energy manager 100 is used to monitor and instruct a user to modify the energy usage profile of one or more devices within a household to correlate to a desired energy usage for that device and/or household. In another embodiment, energy manager 100 is used to monitor and automatically modify the energy usage profile of one or more devices within a household to correlate to a desired energy usage for that device and/or household. Desired energy usage may be based on energy usage rules internal to energy manager 100 and/or energy usage rules ultimately received from an energy utility. Such

an instruction and/or modification are particularly useful to conserve household energy usage.

[0036] More particularly, and referring to FIG. 2, in one embodiment, energy usage rule accessor 105 accesses an energy usage rule 202 of device 204, wherein device 204 is coupled with first structure 140. Then, energy usage rule comparator 125 receives an energy usage measurement of device 204 and compares energy usage rule 202 with the energy usage measurement. Next, energy usage profile generator 135 generates an instruction to modify an energy usage profile of device 204 to correlate with the energy usage, thereby enabling efficient energy management.

[0037] An energy usage measurement of one or more devices refers to the total amount of energy measured for each device and/or for cumulative devices within first structure 140. For example, energy-measuring module 250a measures energy through a study of a device's energy usage signature that vacillates with its energy usage. For example, every device that plugs into an electrical system has a unique energy usage signature. In other words, every device exhibits its unique signal patterns during its electrical usage. These signals are used to calculate a total amount of energy being used at any given time by device 204.

[0038] An energy usage profile of device 204 refers to the overall energy usage of device 204 and device's 204 interaction with other devices within first structure 140, taking into account all available input, such as user 255 input, energy utility 240 input, and/or other input received via Internet 245 and server 225. Additionally, an energy usage profile of device 204 may be integrated with an energy usage profile of a device located within one or more structures other than first structure 140.

[0039] In one embodiment, energy usage rule accessor 105 comprises server accessor 220, configured for accessing an energy management instruction at server 225, wherein server 225 is positioned apart from first structure 140. Server 225 holds instructions received from energy utility 240. These instructions, for example, may command energy manager 100 to conserve energy relating to one or more structures that are subscribed to a demand response program. This command to conserve energy may take the form of an instruction to turn down a thermostat's set-point in the summer and to turn up the thermostat's set-point in the winter during critical peak energy draw situations. In essence, the instructions provide that the AC is to be turned down in the summer and that the heater is to be turned down in the winter at certain critical points in time.

[0040] However, "cheaters" could put a local heat source such as a match (in the summer) or a local cold source such as an ice-cube (in the winter) to attempt to trick the thermostat that the adjustment being made will have a positive effect on the energy load. Energy manager 100 may then profile the actual energy load reduction vs. the projected energy load reduction. If it is determined that the difference between the actual energy load reduction vs. the projected energy load reduction is too great, then a demand response situation may be triggered.

[0041] In a demand response situation, energy manager 100 may ignore the actual temperature reading and may alert authorities of the cheating. For example, when the demand response situation has been triggered and using sophisticated algorithms, energy manager 100 may determine the appropriate actions in proceeding with an energy load reduction, regardless of the energy manager 100's local temperature

reading. Energy manager **100** may also flag a server **225** as to suspicious behavior for later follow-up by authorities.

[0042] In another embodiment, user instruction accessor **230** is configured for accessing an instruction from user **255**, wherein the instruction provides guidance as to user's **255** desired energy usage for device **204**. For example, in one embodiment, user **255** may input information into energy manager **100** such as to what temperature user **255** would like a room to remain for the next five hours.

[0043] In one embodiment, the user instruction is a result of a dialogue generated by energy manager **100** with user **255**. For example, energy manager **100** may create a dialogue with user **255** via text and/or sound to learn how and when to automatically modify the in-home environment taking into account the comfort of user **255**. Energy manager **100**, for example, may interview user **255** to improve user's personal satisfaction with the HVAC and energy automation effectiveness. One or all of the available energy manager **100**'s available user interfaces may query, "Are you cold, hot, or just right now?" or "We made the assumption due to the time of day and day-in-the-month not to turn the heat on at this time to save you money . . . did you like the decision?" The answers to these queries may be used to create an energy usage profile of user **255** and the household.

[0044] After establishing a home owner's preference in temperature and pattern of usage, energy manager **100** may also factor in local weather conditions into pro-active plans for heating and cooling. For example, an Internet hosted server (coupled with server **225** via Internet **245**) may provide forecasted weather data for the home in neighborhood, identifiable by zip code. Energy manager **100** may use the anticipation of a coming weather pattern, user preference knowledge, and scheduled or critical peak energy rates (actual or expected) to take pro-active steps. For example, these pro-active steps may include gradually cooling down the house to 65 degrees throughout the morning until 11 am, while taking into account that user's **255** disregard for the cold in the morning as well as taking advantage of cheaper energy rates.

[0045] In another embodiment, an instruction is generated to modify an energy usage profile of first device **204** coupled with first structure **140** according to an energy usage profile of a second device coupled with a second structure, such that the energy usage associated with first structure **140** and the energy usage associated with the second structure does not occur at the same time. For example, two different homes both have an energy manager **100**, are coupled with server **225**, and enter into a local grid "balancing algorithm". Home #1 wants to use its compressor. Home #2 wants to heat its swimming pool. If both homes use this type of energy at the same time, the power grid will be taxed with a cumulative amount of power usage. However, if the two homes stagger its energy usage, then the power grid's average usage will remain the same. In other words, when home #1 is done with using its compressor, the pool heater of home #2 will be recommended to be powered on.

[0046] For example, energy manager **100** of home #1 generates an instruction to the effect that home #1 should power on its compressor between the hours of 2 p.m. and 4 p.m. Energy manager **100** of home #2 generates an instruction to the effect that home #2 should power on its pool heater between the hours of 4 p.m. and 6 p.m. The residents of home #1 may then follow its energy manager **100**'s

instructions. The residents of home #2 may also then follow its energy manager **100**'s instructions.

[0047] In another embodiment of the present invention, when home #1 is done with using its compressor, the pool heater of home #2 will automatically power on.

[0048] In other words, energy manager **100** causes "peak load management" to occur, in which some or all devices within a home may be turned off in critical peak power situations. This peak load management can be performed based on geography, such as but not limited to peak load management per house and peak load management per neighborhood.

[0049] In one embodiment of the present invention, energy manager **100** comprises interface compatibility module **205**, configured for enabling coupling of energy manager **100** with compatible communication module **210**, wherein energy manager **100** utilizes compatible communication module **210** to access an energy usage measurement. For example, interface compatibility module **205** provides a means of choosing the best method of Internet connectivity for user **255**. It comprises a compatible communication module **210** that allows user **255** to buy a compatible wireless networking module, a household-wiring module, or other appropriate module that allows for further customization by user **255** to match user's **255** existing home network. For example, compatible communication module **210** enables the coupling of wireless connector 802.11 with energy manager **100**. Wireless connector 802.11 then enables communication with energy measuring module **250a**.

[0050] In another embodiment of the present invention, energy manager **100** comprises graphical display module **215**, configured for enabling communication with user **255**. For example, graphical display module **215** may include various aesthetic properties relating to color, texture, shape, and lighting. In one embodiment, graphical display module **215** may be a glass touch screen panel. The panel may be color and incorporate graphics. The panel may enable communication via icons, graphs, pie charts, etc.

[0051] In one embodiment, energy manager **100** generates an instruction that is receivable by a human user **255** of device **204**. This instruction may be receivable through any number of mediums, including graphical display module **215** positioned as shown in FIG. 2 or positioned anywhere that enables coupling wired or wireless coupling with first structure **140**. Additionally, human user **255** of device **204** may access the generated instruction at any device within first structure **140** that is configured to transmit the instruction, such as but not limited to a desktop computer and/or portable electronic device. Further, human user **255** of device **204** may access the generated instruction as an email message, SMS message, or other electronic message via a device capable of supporting the transmission and display of the message. In another embodiment, energy manager **100** generates an instruction that is receivable by device **204**. The instruction enables device **204** to alter its energy usage profile based on the comparing of the energy usage rule for device **204** and device **204**'s energy usage.

[0052] In one embodiment, energy manager **100** comprises passive power consumption tracker **235**, configured for tracking a difference between the sum of energy usage of all devices, wherein all these devices are in an active state and coupled with first structure **140**, and a total energy used within first structure **140** to generate a passive power con-

sumption analysis. For example, energy manager **100** may provide calculated estimates of passive power consumption. The difference between the sum of each appliance's energy usage and the total energy usage is per household is passive power consumption and untracked power usage. This untracked power usage is un-optimizable usage. Passive power consumption is considered to be the most significant drain of power on a power grid. Wall nuts and other passive power drains are undocumented and yet pull more current than any other sink. Even though an appliance is "off" doesn't mean that the appliance isn't consuming power. Tracking this passive power usage increases the user's **255** awareness of energy usage and creates opportunities to conserve overall energy.

[**0053**] In one embodiment of the present invention, an upgrade to energy manager **100** is accessed. For example, energy manager **100** may access, via server **225**, upgrades to its functionalities and interoperability capacity with devices. In one embodiment, device **204** is upgraded within the home. Energy manager **100** may then access, via server **225**, device **204**'s manufacturer to receive upgraded energy standards for device **204**.

[**0054**] It is important to note that energy manager **100** may be a direct replacement for the heating-cooling thermostat controller that connects to the home air conditioner/heater. For example, a consumer may purchase energy manager **100**, pull their current thermostat off their household wall, and mount energy manager **100** in its place. Energy manager **100** then performs all of the air conditioner/heater operations that would be expected from the displaced heating-cooling thermostat as well as the operations attributable to energy manager **100** described herein. Furthermore, a new face plate may include, but is not limited to, an increased display size, a faster processor within, added features to make energy manager **100** more user friendly.

[**0055**] FIG. 3 is a flowchart **300** of an example method of managing energy usage. With reference now to **305** of FIG. 3, an energy usage rule **202** for device **204** is accessed, wherein device **204** is coupled with first structure **140**.

[**0056**] With reference to **310** of FIG. 3, in another embodiment energy usage of device **204** is monitored. This monitoring may be automatically performed or upon command by user **255**, energy utility **240**, or some other authorized monitor. For example, a device's **204** energy usage may be monitored by energy utility **240** via energy measuring module **250b** for inconsistencies in thermostat readings.

[**0057**] With reference to **315** of FIG. 3, in one embodiment, energy usage rule **202** is compared with the energy usage of device **202**. Finally, with reference to **320** of FIG. 3, in one embodiment, based on **315** comparing of energy usage rule **202** and the energy usage of device **204**, an instruction is generated to modify an energy usage profile of device **204** to correlate with energy usage rule **202**, thereby enabling efficient energy management.

[**0058**] Thus, embodiments of the present invention enable the generation of an instruction for a user to modify an energy usage profile of one or more devices within a household to correlate to a desired energy usage for that device and/or household. Additionally, embodiments of the present invention enable the generation of an instruction to automatically modify an energy usage profile of one or more devices within a household to correlate to a desired energy usage for that device and/or household. Furthermore, an instruction to modify an energy usage profile for a device

and/or household may be based on instructions from a user and instructions from a utility company via a server.

Example Computer System Environment

[**0059**] With reference now to FIG. 4, portions of the invention for generating a pre-recorded quick response are composed of computer-readable and computer-executable instructions that reside, for example, in computer-usable media of a computer system. That is, FIG. 4 illustrates one example of a type of computer that can be used to implement embodiments, which are discussed below, of the present invention.

[**0060**] FIG. 4 illustrates an example computer system **400** used in accordance with embodiments of the present invention. It is appreciated that system **400** of FIG. 4 is an example only and that the present invention can operate on or within a number of different computer systems including general purpose networked computer systems, embedded computer systems, routers, switches, server devices, user devices, various intermediate devices/artifacts, stand alone computer systems, and the like. As shown in FIG. 4, computer system **400** of FIG. 4 is well adapted to having peripheral computer readable media **402** such as, for example, a floppy disk, a compact disc, and the like coupled thereto.

[**0061**] System **400** of FIG. 4 includes an address/data bus **404** for communicating information, and a processor **406A** coupled to bus **404** for processing information and instructions. As depicted in FIG. 4, system **400** is also well suited to a multi-processor environment in which a plurality of processors **406A**, **406B**, and **406C** are present. Conversely, system **400** is also well suited to having a single processor such as, for example, processor **406A**. Processors **406A**, **406B**, and **406C** may be any of various types of microprocessors. System **400** also includes data storage features such as a computer usable volatile memory **408**, e.g. random access memory (RAM), coupled to bus **404** for storing information and instructions for processors **406A**, **406B**, and **406C**.

[**0062**] System **400** also includes computer usable non-volatile memory **410**, e.g. read only memory (ROM), coupled to bus **404** for storing static information and instructions for processors **406A**, **406B**, and **406C**. Also present in system **400** is a data storage unit **412** (e.g., a magnetic or optical disk and disk drive) coupled to bus **404** for storing information and instructions. System **400** also includes an optional alpha-numeric input device **414** including alpha-numeric and function keys coupled to bus **404** for communicating information and command selections to processor **406A** or processors **406A**, **406B**, and **406C**. System **400** also includes an optional cursor control device **416** coupled to bus **404** for communicating user input information and command selections to processor **406A** or processors **406A**, **406B**, and **406C**. System **400** of the present embodiment also includes an optional display device **418** coupled to bus **404** for displaying information.

[**0063**] Referring still to FIG. 4, optional display device **418** of FIG. 4 may be a liquid crystal device, cathode ray tube, plasma display device or other display device suitable for creating graphic images and alpha-numeric characters recognizable to a user. Optional cursor control device **416** allows the computer user to dynamically signal the movement of a visible symbol (cursor) on a display screen of display device **418**. Many implementations of cursor control

device 416 are known in the art including a trackball, mouse, touch pad, joystick or special keys on alpha-numeric input device 414 capable of signaling movement of a given direction or manner of displacement. Alternatively, it will be appreciated that a cursor can be directed and/or activated via input from alpha-numeric input device 414 using special keys and key sequence commands.

[0064] System 400 is also well suited to having a cursor directed by other means such as, for example, voice commands. System 400 also includes an I/O device 420 for coupling system 400 with external entities.

[0065] Referring still to FIG. 4, various other components are depicted for system 400. Specifically, when present, an operating system 422, applications 424, modules 426, and data 428 are shown as typically residing in one or some combination of computer usable volatile memory 408, e.g. random access memory (RAM), and data storage unit 412. However, it is appreciated that in some embodiments, operating system 422 may be stored in other locations such as on a network or on a flash drive; and that further, operating system 422 may be accessed from a remote location via, for example, a coupling to the Internet. In one embodiment, the present invention, for example, is stored as an application 424 or module 426 in memory locations within RAM 408 and memory areas within data storage unit 412. System 400 is also well suited to having a temperature sensor 430, an ambient light sensor 432, and a relative humidity sensor 434.

[0066] Computing system 400 is only one example of a suitable computing environment and is not intended to suggest any limitation as to the scope of use or functionality of the present invention. Neither should the computing environment 400 be interpreted as having any dependency or requirement relating to any one or combination of components illustrated in the example computing system 400.

[0067] The present invention may be described in the general context of computer-executable instructions, such as program modules, being executed by a computer. Generally, program modules include routines, programs, objects, components, data structures, etc., that perform particular tasks or implement particular abstract data types. The present invention may also be practiced in distributed computing environments where tasks are performed by remote processing devices that are linked through a communications network. In a distributed computing environment, program modules may be located in both local and remote computer-storage media including memory-storage devices.

[0068] FIG. 5 is a flowchart illustrating a process 500 for managing energy usage, in accordance with one embodiment of the present invention. In one embodiment, process 500 is carried out by processors and electrical components under the control of computer readable and computer executable instructions. The computer readable and computer executable instructions reside, for example, in data storage features such as computer usable volatile and non-volatile memory. However, the computer readable and computer executable instructions may reside in any type of computer readable medium. In one embodiment, process 500 is performed by energy manager 100 of FIG. 1.

[0069] With reference to 505 of FIG. 5, a signal of device 204 is monitored, wherein the signal is an energy usage signature specific to device 204 and device 204 is coupled with first structure 140. With reference to 510 of FIG. 5, an analysis of energy usage of device 204 is generated based on

the monitoring of a signal of device 204. The analysis describes an energy usage profile of device 204.

[0070] In one embodiment, method 500 further comprises estimating savings with regards to replacing device 204 with a new device, wherein the estimating is based on the analysis described herein of method 500. For example, by installing energy manager 100, user 255 can get contextual advice on how to efficiently and affordably upgrade user's 255 current HVAC unit. Energy manager 100 estimates how much money would be saved by installing a new HVAC unit based on algorithms that do the following: measure, store, and analyze energy usage history; utilize a Seasonal Energy Efficiency Rating (SEER) of a new HVAC unit and how it would profile in the current household; and measure current HVAC unit run time and the temperature drop rate over various time intervals.

[0071] Energy manager 100 may, through its back-end server 225 connection in Internet 245, enable partnerships with local (or national) HVAC companies. Energy manager 100 may change its line-up of eligible replacement HVAC units based on factors such as pricing and availability in real-time. Energy manager 100 may provide contextual advertisement for HVAC unit vendors, or for any other product or service. The messaging from energy manager's 100 face-plate, connected PC interface, or connected mobile interface provides such useful information as, "You would save \$130 per month if you upgraded to a Y SEER AC."

[0072] In yet another embodiment of the present invention, method 500 further comprises generating an analysis that informs user 255 of the costs associated with changing the settings of device 204. For example, energy manager 100 may generate an analysis that informs user 255 that changing the dishwasher to run at half power instead of at full power may save user 255 \$20 per month.

[0073] In another embodiment, method 500 further comprises comparing the energy usage of first structure 140 with an energy usage of a second structure based on the analysis described herein of method 500. For example, with energy managers 100 in different homes, comparisons may be made between and among homes. A home in neighborhood N1 can compare its energy usage to a friend's home in neighborhood N2. Energy manager 100 may then relay to user 255 the following, "Your friend, Jim Smith, is spending \$500 per month to heat/cool their house." Or, energy manager 100 may relay to user 255, "Your sister's fridge is costing \$50 per month to keep the food cold, which is in the top 10% of homes in the nation in terms of effectiveness and efficiency." This neighbor comparison functionality works on competitive psychology. This functionality enables more sales of new and energy efficient units and overall electricity conservation for the power energy grid.

[0074] In another embodiment, method 500 further comprises alerting user 255 to specific maintenance tasks for device 204 that are recommended based on an analysis of energy usage of device 204 described herein. For example, method 500 comprises alerting user 255 that a new filter for device 204 is needed based on the analysis described herein of method 500. For example, energy manager 100 may estimate when enough time has passed based on overall usage to determine that a new filter for the HVAC unit is needed. Energy manager 100 may show reminders for replacing these HVAC filters. Energy manager 100 may show statistics on how much money is saved or lost by replacing or waiting to replace HVAC filters.

[0075] In another embodiment, method 500 further comprises calculating the efficiency of the HVAC correlated to the energy efficiency of the home (including insulation and air leakage through ducts, under doors, and around windows). For example, based on the duration that it takes to drop the temperature of the home to the desired temperature while taking into consideration the cost of electricity, energy manager 100 calculates the efficiency of the HVAC correlated to the energy efficiency of the home.

[0076] Similarly, energy manager 100 may calculate the current efficiency of an appliance such as a refrigerator. Utilizing an energy-measuring module 250a between the refrigerator and the electrical outlet, energy manager 100 can make algorithmic conclusions based on the setting and the history of the refrigerator. Thus, energy manager 100 may generate an analysis on the estimated energy efficiency of the refrigerator.

[0077] In another embodiment, method 500 further comprises alerting user 255 of a possible failure of device 204 based on an analysis of historical data or data on a remote server. This historical data includes the monitored energy usage data for device 204 described herein. Method 500 further comprises alerting user 255 of possible device 204 failure based on device's 204 history. For example, circuits sometimes begin to eat up larger and larger amounts of current or show erratic current draw before they fail. A "healthy history" of current usage per device 204 may be compared to current spikes or other erratic current draw to predict the failure of device 204.

[0078] In another embodiment, method 500 further comprises calculating the break even date of a replacement product. For example, energy manager 100 monitors the energy usage history for device 204. Then, after device 204 is replaced, energy manager 100 marks the replacement date. Energy manager 100 may then calculate the break even date and any realized savings based off of electric rate data. Energy manager 100 may then communicate these calculations to user 255 via graphical display module 215. Energy manager 100 may also communicate a victory notification to user 255.

[0079] In another embodiment, method 500 further comprises assisting user 255 with achieving a money savings goal by managing user's 255 energy usage. For example, a user's 255 financial savings goal and an interaction between user 255 and user's 255 device(s) 204 may result in a dialogue with device(s) 204 or even with the whole house. Energy manager 100 may also keep user 255 current on user's 255 financial savings. Energy manager 100 may tie its energy usage management of device(s) 204 with an incentive, such as, "By turning the AC up to 89 degrees, we are saving for our Fiji vacation."

[0080] In another embodiment, method 500 further comprises querying and negotiating with user 255 to assist user 255 in meeting an energy budget target. For example, energy manager 100 may both interview and negotiate with user 255. The interviews may be periodic questions, posed through user-interfaces. These question posed may relate to personal comfort, and preferences on HVAC and energy automation effectiveness. For example, one question might be, "Are you cold, hot, or just right at this time?" The answer to this question will inform energy manager 100 of the threshold of environmental comfort for user 255 based on a registered temperature reading. Energy manager 100 may

also poll user 255 if user 255 is the only one home or if other friends or relatives are at home to determine what actions should be taken.

[0081] Another possible question may be, "We made the assumption due to the time of day and the day in the month not to turn the heat on at this time in order to save you money . . . did you like this decision?" A positive response from user 255 will reinforce the algorithmic decision made. Whereas a negative response will provide the initiative to make a change.

[0082] The negotiation (via email, SMS, Instant Messaging, or directly accessing the interface of energy manager 100) of user 255 with energy manager 100 relates to trying to help user 255 hit a pre-set energy budget target. For example, if after 20 days into the month the user's 255 trend line is above the forecasted month end bill and/or energy usage, energy manager 100 may send user 255 an SMS messaging requesting permission to turn the heat down three degrees.

[0083] In another embodiment, method 500 further comprises profiling a device 204 based on the history of device 204 and environmental factors. For example, energy manager 100 may support the use of one energy-measuring module 250a used to connect device 204 to energy manager 100. Based on the energy consumption over time and against assorted environmental factors energy manager 100 will profile device 100 as to its energy consumption, energy costs, and as a percentage of room device class, and whole-home totals. This one energy-measuring module 250a may be rotated around the home to eventually construct a whole home energy profile, with or without the presence of energy-measuring module 250b.

[0084] Furthermore, this device-level energy audit can be conducted over varying levels of time and report to user 255 its higher level of confidence on its estimates based on the variable of time allowed to measure a particular device 204. Energy manager 100 may compare similar devices of its class via information on Internet hosted servers. Moreover, energy manager 100 may compare similar devices for the home via historical information from one or more energy utility 240. Energy manager may also make a forecast regarding device 204 based on company trends and forecasts.

[0085] In another embodiment, method 500 further comprises managing an energy co-op of a pool of energy manager 100 user(s) 255. For example, energy manager(s) 100 is able to aggregate homes within and across neighborhoods, grouping them into a logical large single pool. A logical large single pool of houses might be homes located geographically near each other. Energy manager 100 thus provides a distributed "buying block" of energy user's 255. This "buying block", having purchased from energy wholesalers, is able to act in a cooperative capacity as energy manager 100 user(s) 255. Beneficially, user(s) 255 would experience reduced energy costs. Server 225 may manage this co-op.

[0086] In yet another embodiment of the present technology, a plurality of energy usage signatures is aggregated by remote server 225. This plurality of energy usage signatures is compiled for comparison with subsequently received energy usage signatures. One or more of the energy usage signatures may be identified by user 255 of the device(s). In one embodiment, remote server 225 receives from user 255 of device 204 the identification information, including but

not limited to device type, manufacturer, and model information to be associated with its energy usage signature. The server then aggregates this identification of device 204 in a database at server 225.

[0087] More particularly, energy manager 100 may detect a new energy usage signature within first structure 140. Energy manager 100 may notify user 255 that a new energy usage signature (device 204) exists and prompt user 255 for the device's identification. User 255 then may identify device 204 as washer model #4305. Energy manager 100 then sends this energy usage signature along with its identification to server 225. Remote server 255 stores this identification in a database that is accessible to users of device 204 and devices other than device 204. In this way, a database of energy usage signatures and related identifications is built and accessible by, but not limited to, users of various devices, manufacturers, and energy utility companies.

[0088] In another embodiment, the plurality of energy usage signatures of first structure 140 received by server 225 are provided for use and comparison of one or more energy usage signatures by an energy manager 100 in a second structure. For example, the energy usage signatures detected in structure 140 and their identification that is stored in a database at server 225 are provided to an energy manager 100 of a second structure for use and comparison with one or more energy usage signatures therein.

[0089] For example, energy manager 100 of a second structure uses the identified energy usage signatures associated with the devices in first structure 140 to identify the energy usage signatures detected in the second structure. In this manner, energy manager 100 takes advantage of a database of identifications of energy usage signatures located at a remote server in order to more quickly identify the devices within a household with which it is coupled. Of note, users of devices coupled with different structures provide assistance in the collection and identification of energy usage signatures for any number of devices.

[0090] FIG. 6 is a flowchart illustrating a process for managing energy usage in accordance with embodiments of the present invention is shown. With reference now to 605 of FIG. 6, an energy usage rule 202 for device 204 is accessed, wherein device 204 is coupled with first structure 140.

[0091] With reference to 610 of FIG. 6, in another embodiment energy usage of device 204 is monitored. This monitoring may be automatically performed or upon command by user 255, energy utility 240, or some other authorized monitor. For example, a device's 204 energy usage may be monitored by energy utility 240 via energy measuring module 250b for inconsistencies in thermostat readings.

[0092] User 255 may access these instructions at, but not limited to, energy manager 100, at a device coupled with first structure 140, at a server 255 coupled with energy manager 100 and/or first structure 140, and/or at a device at a second structure coupled wired or wirelessly with first structure 140.

[0093] With reference to 615 of FIG. 6, in one embodiment, energy usage rule 202 is compared with the energy usage of device 202. Finally, with reference to 620 of FIG. 6, in one embodiment, based on 615 comparing of energy usage rule 202 and the energy usage of device 204, an instruction is generated to modify an energy usage profile of device 204 to correlate with energy usage rule 202, wherein

the instruction is formatted for interpretation by a human user, thereby enabling efficient energy management. An instruction is formatted for interpretation by a human user if the instruction is transmitted in such a way that it could be understood by a human user.

[0094] Thus, embodiments of the present invention enable the generation of an instruction for a human user to modify an energy usage profile of one or more devices within a household to correlate to a desired energy usage for that device and/or household. Additionally, embodiments of the present invention enable the generation of an instruction to automatically modify an energy usage profile of one or more devices within a household to correlate to a desired energy usage for that device and/or household.

[0095] Thus, embodiments of the present invention increase consumer awareness as to conservation of energy by enabling the generation of an analysis of a device's energy usage. In one embodiment, the analysis informs a consumer of estimated savings with regards to replacing a device with a new device. In another embodiment, the analysis provides a comparison of the energy usage and energy costs of two different households. Furthermore, embodiments of the present invention inform a consumer when a new filter for a device is needed based on a generated analysis. Thus, embodiments of the present invention are beneficial by increasing a consumer's awareness of energy conservation opportunities.

[0096] Although the subject matter has been described in a language specific to structural features and/or methodological acts, it is to be understood that the subject matter defined in the appended claims is not necessarily limited to the specific features or acts described above. Rather, the specific features and acts described above are disclosed as example forms of implementing the claims.

What is claimed is:

1. An energy management system for encouraging energy-conscious behavior, the system comprising:
 - one or more processors; and
 - a memory communicatively coupled with and readable by the one or more processors and having stored therein processor-readable instructions which, when executed by the one or more processors, cause the one or more processors to:
 - determine energy usage information for a plurality of structures, the energy usage information indicating an energy usage information associated with the plurality of structures;
 - compare energy usage information of a first structure to the energy usage information associated with the plurality of structures;
 - determine one or more differences between the energy usage information of the first structure and the energy usage information associated with the plurality of structures based on the comparing; and
 - communicate to a user linked with the first structure, the energy usage information of the first structure, the energy usage information associated with the plurality of structures, and/or an indication of the one or more differences.
2. The energy management system for encouraging energy-conscious behavior of claim 1, wherein the processor-readable instructions that, when executed, cause the one or more processors to communicate to the first associated

with the first structure comprise processor-readable instructions which, when executed, cause the one or more processors to:

provide a graphical display to the user that graphically indicates the energy usage information of the first structure, the energy usage information associated with the plurality of structures, and the indication of the one or more differences.

3. The energy management system for encouraging energy-conscious behavior of claim 1, wherein the plurality of structures are in a neighborhood of the first structure.

4. The energy management system for encouraging energy-conscious behavior of claim 3, wherein a zip code of the user is used to identify the plurality of structures determined to be in the neighborhood of the first structure.

5. The energy management system for encouraging energy-conscious behavior of claim 1, wherein the energy usage information associated with the plurality of structures comprises a cost.

6. The energy management system for encouraging energy-conscious behavior of claim 1, wherein the processor-readable instructions that, when executed, cause the one or more processors to communicate to the first associated with the first structure comprise processor-readable instructions which, when executed, cause the one or more processors to communicate an efficiency measurement for a subset of the plurality of structures in comparison to the plurality of structures, the first structure, or both.

7. The energy management system for encouraging energy-conscious behavior of claim 1, wherein the energy usage information for each structure of the plurality of structures represents total energy consumption of all electrical items within the corresponding structure.

8. The energy management system for encouraging energy-conscious behavior of claim 1, wherein the energy usage information for each structure of the plurality of structures represents energy consumption of a subset of electrical devices operating in the corresponding structure.

9. A method of encouraging energy-conscious behavior, comprising:

determining energy usage information for a plurality of structures, the energy usage information indicating an energy usage information associated with the plurality of structures;

comparing energy usage information of a first structure to the energy usage information associated with the plurality of structures;

determining one or more differences between the energy usage information of the first structure and the energy usage information associated with the plurality of structures based on the comparing; and

communicating to a first user associated with the first structure, the energy usage information of the first structure, the energy usage information associated with the plurality of structures, and/or an indication of the one or more differences.

10. The method of encouraging energy-conscious behavior of claim 9, wherein communicating to the first associated with the first structure comprises:

providing a graphical display that graphically indicates the energy usage information of the first structure, the energy usage information associated with the plurality of structures, and the indication of the one or more differences.

11. The method of encouraging energy-conscious behavior of claim 9, wherein the plurality of structures are in a neighborhood of the first structure.

12. The method of encouraging energy-conscious behavior of claim 11, wherein a zip code of the user is used to identify the plurality of structures determined to be in the neighborhood of the first structure.

13. The method of encouraging energy-conscious behavior of claim 9, wherein the energy usage information associated with the plurality of structures indicates a total cost.

14. The method of encouraging energy-conscious behavior of claim 9, wherein communicating to the first user associated with the first structure comprises communicating an efficiency indication for a subset of the plurality of structures in comparison to at least the plurality of structures.

15. The method of encouraging energy-conscious behavior of claim 9, wherein the energy usage information for the first structure represents total energy consumption of electrical devices within the structure.

16. The method of encouraging energy-conscious behavior of claim 9, wherein the energy usage information for the first structure represents energy consumption of a subset of devices operating in the first structure.

17. A non-transitory processor-readable medium for encouraging energy-conscious behavior comprising processor-readable instructions configured to cause one or more processors to:

determine energy usage information for a plurality of structures, the energy usage information indicating an energy usage information associated with the plurality of structures;

compare the energy usage information of a first structure to the energy usage information associated with the plurality of structures;

determine one or more differences between the energy usage information of the first structure and the energy usage information associated with the plurality of structures based on the comparing; and

communicate to a first user linked with the first structure, the energy usage information of the first structure, the energy usage information associated with the plurality of structures, and/or an indication of the one or more differences.

18. The non-transitory processor-readable medium for encouraging energy-conscious behavior of claim 17, wherein the processor-readable instructions configured to cause the one or more processors to communicate to the first associated with the first structure comprise processor-readable instructions configured to cause the one or more processors to:

provide a graphical display that graphically indicates the energy usage information of the first structure, the energy usage information associated with the plurality of structures, and the indication of the one or more differences.

19. The non-transitory processor-readable medium for encouraging energy-conscious behavior of claim 17, wherein the plurality of structures are in a neighborhood of the first structure.

20. The non-transitory processor-readable medium for encouraging energy-conscious behavior of claim 19,

wherein a zip code of the user is used to identify the plurality of structures determined to be in the neighborhood of the first structure.

* * * * *