



- (51) International Patent Classification:
A61M 16/08 (2006.01)
- (21) International Application Number:
PCT/NZ2013/000222
- (22) International Filing Date:
4 December 2013 (04.12.2013)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
- | | | |
|------------|--------------------------------|----|
| 61/733,360 | 4 December 2012 (04.12.2012) | US |
| 61/733,359 | 4 December 2012 (04.12.2012) | US |
| 61/877,622 | 13 September 2013 (13.09.2013) | US |
| 61/877,566 | 13 September 2013 (13.09.2013) | US |
| 61/877,784 | 13 September 2013 (13.09.2013) | US |
| 61/877,736 | 13 September 2013 (13.09.2013) | US |
- (71) Applicants: FISHER & PAYKEL HEALTHCARE LIMITED [NZ/NZ]; 15 Maurice Paykel Place, East Tamaki, Auckland, 2013 (NZ). AMADIO, Christopher Jaye Norman [NZ/NZ]; 15 Maurice Paykel Place, East Tamaki, Auckland, 2013 (NZ).
- (72) Inventors; and
- (71) Applicants : STOKS, Elmo Benson [NZ/NZ]; 15 Maurice Paykel Place, East Tamaki, Auckland, 2013 (NZ). NORTH, Charles Christopher [NZ/NZ]; 15 Maurice

Paykel Place, East Tamaki, Auckland, 2013 (NZ). SUJAU, Mahran Maumoon [NZ/NZ]; 15 Maurice Paykel Place, East Tamaki, Auckland, 2013 (NZ). STROOBANT, Josh [NZ/NZ]; 15 Maurice Paykel Place, East Tamaki, Auckland, 2013 (NZ). MILLAR, Gavin Walsh [NZ/NZ]; 15 Maurice Paykel Place, East Tamaki, Auckland, 2013 (NZ). BUSWELL, Matthew Liam [NZ/NZ]; 15 Maurice Paykel Place, East Tamaki, Auckland, 2013 (NZ). AL-TIAY, Ibrahim [NZ/NZ]; 15 Maurice Paykel Place, East Tamaki, Auckland, 2013 (NZ). McCAULEY, David Leon [NZ/NZ]; 15 Maurice Paykel Place, East Tamaki, Auckland, 2013 (NZ). VAN SCHALKWYK, Andre [ZA/NZ]; 15 Maurice Paykel Place, East Tamaki, Auckland, 2013 (NZ). MUNKELT, Katja [DE/NZ]; 15 Maurice Paykel Place, East Tamaki, Auckland, 2013 (NZ). WILSON, Matthew Robert [NZ/NZ]; 15 Maurice Paykel Place, East Tamaki, Auckland, 2013 (NZ). OOSTHUYSEN, Helgard [ZA/NZ]; 15 Maurice Paykel Place, East Tamaki, Auckland, 2013 (NZ). PATEL, Sanjay [NZ/NZ]; 15 Maurice Paykel Place, East Tamaki, Auckland, 2013 (NZ). d'ANDREA, Dominique Richard [FR/NZ]; 15 Maurice Paykel Place, East Tamaki, Auckland, 2013 (NZ). DOVER, Grant Martin [NZ/NZ]; 15 Maurice Paykel Place, East Tamaki, Auckland, 2013 (NZ). BARKER, Dean Antony [GB/NZ]; 15 Maurice Paykel Place, East Tamaki, Auckland, 2013 (NZ). HARWOOD, Jonathan Dav-

[Continued on next page]

(54) Title: MEDICAL TUBES AND METHODS OF MANUFACTURE



FIG. 5A

(57) Abstract: The disclosure relates to medical tubes and methods of manufacturing medical tubes. The tube may be a composite structure made of two or more distinct components that are spirally wound to form an elongate tube. For example, one of the components may be a spirally wound elongate hollow body, and the other component may be an elongate structural component also spirally wound between turns of the spirally wound hollow body. The tube need not be made from distinct components, however. For instance, an elongate hollow body formed (e.g., extruded) from a single material may be spirally wound to form an elongate tube. The elongate hollow body itself may in transverse cross-section have a thin wall portion and a relatively thicker or more rigid reinforcement portion. The tubes can be incorporated into a variety of medical circuits or may be employed for other medical uses.





id [NZ/NZ]; 15 Maurice Paykel Place, East Tamaki, Auckland, 2013 (NZ).

(74) **Agent:** BALDWINS INTELLECTUAL PROPERTY; PO Box 852, Wellington, 6011 (NZ).

(81) **Designated States** (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IR, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

Published:

- with international search report (*Art. 21(3)*)
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (*Rule 48.2(h)*)

MEDICAL TUBES AND METHODS OF MANUFACTURE

INCORPORATION BY REFERENCE

[0001] This application claims the benefit of priority under 35 U.S.C. § 119(e) to U.S. Provisional Application No. 61/733,359, entitled MEDICAL TUBES AND METHODS OF MANUFACTURE, filed on December 4, 2012; U.S. Provisional Application No. 61/733,360, entitled MEDICAL TUBES AND METHODS OF MANUFACTURE, filed on December 4, 2012; U.S. Provisional Application No. 61/877,622, entitled MEDICAL TUBES AND METHODS OF MANUFACTURE, filed on September 13, 2013; U.S. Provisional Application No. 61/877,566, entitled HUMIDIFICATION SYSTEM, filed on September 13, 2013; U.S. Provisional Application No. 61/877,784, entitled CONNECTIONS FOR HUMIDIFICATION SYSTEM, filed on September 13, 2013; and U.S. Provisional Application No. 61/877,736, entitled ZONE HEATING FOR RESPIRATORY CIRCUITS, filed on September 13, 2013, each of which is incorporated herein by reference in its entirety.

[0002] In addition, PCT Application No. PCT/IB2012/001786, entitled MEDICAL TUBES AND METHODS OF MANUFACTURE, filed May 30, 2012, is also incorporated herein by reference in its entirety.

BACKGROUND

Field

[0003] This disclosure relates generally to tubes suitable for medical use, and in particular to tubes for use in medical circuits suitable for providing gases to and/or removing gases from a patient, such as in positive airway pressure (PAP), respirator, anaesthesia, ventilator, and insufflation systems.

Description of the Related Art

[0004] In medical circuits, various components transport warm and/or humidified gases to and from patients. For example, in some breathing circuits such as PAP or assisted breathing circuits, gases inhaled by a patient are delivered from a heater-humidifier through an inspiratory tube. As another example, tubes can deliver humidified gas (commonly CO₂)

into the abdominal cavity in insufflation circuits. This can help prevent “drying out” of the patient’s internal organs, and can decrease the amount of time needed for recovery from surgery. Unheated tubing allows significant heat loss to ambient cooling. This cooling may result in unwanted condensation or “rainout” along the length of the tubing transporting warm, humidified air. A need remains for tubing that insulates against heat loss and, for example, allows for improved temperature and/or humidity control in medical circuits. Accordingly, it is an object of the invention to overcome or ameliorate one or more of the disadvantages of the prior art or to at least provide the public with a useful choice.

SUMMARY

[0005] Medical tubes and methods of manufacturing medical tubes are disclosed herein in various embodiments. In some embodiments, the tube may be a composite structure made of two or more distinct components that are spirally wound to form an elongate tube. For example, one of the components may be a spirally wound elongate hollow body, and the other component may be an elongate structural component also spirally wound between turns of the spirally wound hollow body. In other embodiments, the tube need not be made from distinct components. For instance, an elongate hollow body formed (e.g., extruded) from a single material may be spirally wound to form an elongate tube. The elongate hollow body itself may in transverse cross-section have a thin wall portion and a relatively thicker or more rigid reinforcement portion. The tubes can be incorporated into a variety of medical circuits or may be employed for other medical uses.

[0006] In at least one embodiment, a composite tube can comprise a first elongate member comprising a hollow body spirally wound to form at least in part an elongate tube having a longitudinal axis, a lumen extending along the longitudinal axis, and a hollow wall surrounding the lumen. A second elongate member may be spirally wound and joined between adjacent turns of the first elongate member, the second elongate member forming at least a portion of the lumen of the elongate tube. The name “first elongate member” and “second elongate member” do not necessarily connote an order, such as the order in which the components are assembled. As described herein, the first elongate

member and the second elongate member can also be portions of a single tube-shaped element.

[0007] In various embodiments, the foregoing component has one, some, or all of the following properties, as well as properties described elsewhere in this disclosure.

[0008] The first elongate member can be a tube. The first elongate member can form in longitudinal cross-section a plurality of bubbles with a flattened surface at the lumen. Adjacent bubbles can be separated by a gap above the second elongate member, or may not be directly connected to each other. The bubbles can have perforations. The second elongate member can have a longitudinal cross-section that is wider proximal the lumen and narrower at a radial distance from the lumen. Specifically, the second elongate member can have a longitudinal cross-section that is generally triangular, generally T-shaped, or generally Y-shaped. One or more conductive filaments can be embedded or encapsulated in the second elongate member. The one or more conductive filaments can be heating filaments (or more specifically, resistance heating filaments) and/or sensing filaments. The tube can comprise pairs of conductive filaments, such as two or four conductive filaments. Pairs of conductive filaments can be formed into a connecting loop at one end of the composite tube. The one or more conductive filaments can be spaced from the lumen wall. In at least one embodiment, the second elongate member can have a longitudinal cross-section that is generally triangular, generally T-shaped, or generally Y-shaped, and one or more conductive filaments can be embedded or encapsulated in the second elongate member on opposite sides of the triangle, T-shape, or Y-shape.

[0009] The foregoing component according to any or all of the preceding embodiments can be incorporated into a medical circuit component, an inspiratory tube, an expiratory tube, a PAP component, an insufflation circuit, an exploratory component, or a surgical component, among other applications.

[0010] A method of manufacturing a composite tube is also disclosed. The resulting tube can have one, some, or all of the properties described above or anywhere in this disclosure. In at least one embodiment, the method comprises providing a first elongate member comprising a hollow body and a second elongate member configured to provide structural support for the first elongate member. The second elongate member is spirally

wrapped around a mandrel with opposite side edge portions of the second elongate member being spaced apart on adjacent wraps, thereby forming a second-elongate-member spiral. The first elongate member is spirally wrapped around the second-elongate-member spiral, such that portions of the first elongate member overlap adjacent wraps of the second-elongate-member spiral and a portion of the first elongate member is disposed adjacent the mandrel in the space between the wraps of the second-elongate-member spiral, thereby forming a first-elongate-member spiral.

[0011] In various embodiments, the foregoing method can comprise one, some, or all of the following. The method can comprise supplying air at a pressure greater than atmospheric pressure to an end of the first elongate member. The method can comprise cooling the second-elongate-member spiral and the first-elongate-member spiral, thereby forming a composite tube having a lumen extending along a longitudinal axis and a hollow space surrounding the lumen. The method can comprise forming the first elongate member. The method can comprise extruding the first elongate member with a first extruder. The method can comprise forming the second elongate member. The method can comprise extruding the second elongate member with a second extruder. The second extruder can be configured to encapsulate one or more conductive filaments in the second elongate member. Forming the second elongate member can comprise embedding conductive filaments in the second elongate member. The conductive filaments can be non-reactive with the second elongate member. The conductive filaments can comprise alloys of aluminum or copper or other conductive materials. The method can comprise forming pairs of conductive filaments into a connecting loop at one end of the composite tube. The first extruder can be distinct from the second extruder.

[0012] A medical tube is also disclosed. In at least one embodiment, the tube comprises an elongate hollow body spirally wound to form an elongate tube having a longitudinal axis, a lumen extending along the longitudinal axis, and a hollow wall surrounding the lumen, wherein the elongate hollow body has in transverse cross-section a wall defining at least a portion of the hollow body. The tube can further comprise a reinforcement portion extending along a length of the elongate hollow body being spirally positioned between adjacent turns of the elongate hollow body, wherein the reinforcement

portion forms a portion of the lumen of the elongate tube. The reinforcement portion can be relatively thicker or more rigid than the wall of the elongate hollow body.

[0013] In various embodiments, the foregoing tube has one, some, or all of the following properties, as well as properties described elsewhere in this disclosure. The reinforcement portion can be formed from the same piece of material as the elongate hollow body. The elongate hollow body in transverse cross-section can comprise two reinforcement portions on opposite sides of the elongate hollow body, wherein spiral winding of the elongate hollow body joins adjacent reinforcement portions to each other such that opposite edges of the reinforcement portions touch on adjacent turns of the elongate hollow body. Opposite side edges of the reinforcement portions can overlap on adjacent turns of the elongate hollow body. The reinforcement portion can be made of a separate piece of material than the elongate hollow body. The hollow body can form in longitudinal cross-section a plurality of bubbles with a flattened surface at the lumen. The bubbles can have perforations. The medical tube can also comprise one or more conductive filaments embedded or encapsulated within the reinforcement portion. The conductive filament can be a heating filament and/or or sensing filament. The medical tube can comprise two conductive filaments, wherein one conductive filament is embedded or encapsulated in each of the reinforcement portions. The medical tube can comprise two conductive filaments positioned on only one side of the elongate hollow body. Pairs of conductive filaments can be formed into a connecting loop at one end of the elongate tube. The one or more filaments can be spaced from the lumen wall.

[0014] The foregoing tube according to any or all of the preceding embodiments can be incorporated into a medical circuit component, an inspiratory tube, an expiratory tube, a PAP component, an insufflation circuit, an exploratory component, or a surgical component, among other applications.

[0015] A method of manufacturing a medical tube is also disclosed. In at least one embodiment, the method comprises spirally winding an elongate hollow body around a mandrel to form an elongate tube having a longitudinal axis, a lumen extending along the longitudinal axis, and a hollow wall surrounding the lumen, wherein the elongate hollow body has in transverse cross-section a wall defining at least a portion of the hollow body and

two reinforcement portions on opposite sides of the elongate body forming a portion of the wall of the lumen, the two reinforcement portions being relatively thicker or more rigid than the wall defining at least a portion of the hollow body. The method can further comprise joining adjacent reinforcement portions to each other such that opposite edges of the reinforcement portions touch on adjacent turns of the elongate hollow body.

[0016] In various embodiments, the foregoing method can comprise one, some, or all of the following or any other properties described elsewhere in this disclosure. Joining adjacent reinforcement portions to each other can cause edges of the reinforcement portions to overlap. The method can further comprise supplying air at a pressure greater than atmospheric pressure to an end of the elongate hollow body. The method can further comprise cooling the elongate hollow body to join the adjacent reinforcement portions to each other. The method can further comprise extruding the elongate hollow body. The method can further comprise embedding conductive filaments in the reinforcement portions. The method can further comprise forming pairs of conductive filaments into a connecting loop at one end of the elongate tube.

[0017] A breathing tube is also disclosed. In at least one embodiment, the tube comprises a first elongate member comprising a hollow body spirally wound to form at least in part an elongate tube having a longitudinal axis, a lumen extending along the longitudinal axis, and a hollow wall surrounding the lumen, the wall having an inner portion proximal the lumen and an outer portion facing away from the lumen, wherein the inner portion of the wall has a smaller thickness than the outer portion of the wall.

[0018] In various embodiments, the foregoing breathing tube can comprise one, some, or all of the following properties or any other properties described elsewhere in this disclosure. The breathing tube can further comprising a second elongate member spirally wound and joined between adjacent turns of the first elongate member, the second elongate member forming at least a portion of the lumen of the elongate tube. The thickness of the outer portion of the wall can be in the range of about 0.14 mm and about 0.44 mm. The thickness of the outer portion of the wall can be about 0.24 mm. The thickness of the inner portion of the wall can be in the range of about 0.05 mm and about 0.30 mm. The thickness of the inner portion of the wall can be about 0.10 mm.

[0019] A breathing tube is also disclosed. In at least one embodiment, the tube comprises a first elongate member comprising a hollow body spirally wound to form at least in part an elongate tube having a longitudinal axis, a lumen extending along the longitudinal axis, and a hollow wall surrounding the lumen, the hollow body forming in longitudinal cross section a plurality of bubbles, a bubble having a maximum width along the longitudinal axis and a maximum height perpendicular to the longitudinal axis between the outward-facing apex of the wall and the lumen, wherein the ratio of the maximum height to the maximum width is at least about 0.16.

[0020] In various embodiments, the foregoing breathing tube can comprise one, some, or all of the following properties or any other properties described elsewhere in this disclosure. The breathing tube can further comprise a second elongate member spirally wound and joined between adjacent turns of the first elongate member, the second elongate member forming at least a portion of the lumen of the elongate tube. The maximum height can be in the range of about 1.2 mm and about 8.2 mm. The maximum height can be about 3.2 mm. The maximum width can be in the range of about 3.5 mm and about 7.5 mm. The maximum width can be about 5.5 mm. The ratio of the maximum height to the maximum width can be greater than 1.0.

[0021] A breathing tube is also disclosed. In at least one embodiment, the tube comprises a first elongate member comprising a hollow body spirally wound to form at least in part an elongate tube having a longitudinal axis, a lumen extending along the longitudinal axis, and a hollow wall surrounding the lumen, the hollow body forming in longitudinal cross section a plurality of bubbles, wherein a vertical distance between corresponding points on adjacent bubbles defines a pitch, wherein the ratio of pitch to the maximum outer diameter of the composite tube is less than about 0.35.

[0022] In various embodiments, the foregoing breathing tube can comprise one, some, or all of the following properties or any other properties described elsewhere in this disclosure. The breathing tube can further comprising a second elongate member spirally wound and joined between adjacent turns of the first elongate member, the second elongate member forming at least a portion of the lumen of the elongate tube. The pitch can be in the range of about 1.2 mm and about 8.1 mm. The pitch can be about 5.1 mm. The maximum

outer diameter can be in the range of about 19.5 mm and 25.5 mm. The maximum outer diameter can be about 22.5 mm.

[0023] A composite tube is also disclosed. In at least one embodiment, the tube comprises a first elongate member comprising a hollow body spirally wound to form at least in part an elongate tube having a longitudinal axis, a lumen extending along the longitudinal axis, and a hollow wall surrounding the lumen, the hollow body forming in longitudinal cross section a plurality of bubbles, a bubble having a maximum height, perpendicular to the longitudinal axis, between the outward-facing apex of the wall and the lumen that defines the maximum height of the first elongate member; and a second elongate member spirally wound and joined between adjacent turns of the first elongate member, the second elongate member forming at least a portion of the lumen of the elongate tube, the second elongate member having a maximum height, perpendicular to the longitudinal axis, between the outward-facing apex of the second elongate member and the lumen, wherein the ratio of the difference between the maximum height of the first elongate member and the maximum height of the second elongate member to the maximum outer diameter of the composite tube is less than about 0.049:1.

[0024] In various embodiments, the foregoing composite tube can comprise one, some, or all of the following properties or any other properties described elsewhere in this disclosure. The wall can have an inner portion proximal the lumen and an outer portion facing away from the lumen and the inner portion of the wall has a smaller thickness than the outer portion of the wall.

[0025] A composite tube is also disclosed. In at least one embodiment, the tube comprises a first elongate member comprising a hollow body spirally wound to form at least in part an elongate tube having a longitudinal axis, a lumen extending along the longitudinal axis, and a hollow wall surrounding the lumen, the wall having an inner portion proximal the lumen and an outer portion facing away from the lumen; and a second elongate member spirally wound between adjacent turns of the first elongate member, the second elongate member forming at least a portion of the lumen of the elongate tube and the first elongate member being joined at connection points on adjacent turns of the second elongate

member; wherein the composite tube's bend radius is limited by the length of the outer portion between the connection points.

[0026] In various embodiments, the foregoing composite tube can comprise one, some, or all of the following properties or any other properties described elsewhere in this disclosure. The wall has an inner portion proximal the lumen and an outer portion facing away from the lumen and the inner portion of the wall has a smaller thickness than the outer portion of the wall.

[0027] A breathing tube is also disclosed. In at least one embodiment, the tube comprises a first elongate member comprising a hollow body component, wherein the weight per length of the tube within at least a portion of the 300 mm nearest an end of the tube is less than about 0.08 g/mm.

[0028] In various embodiments, the foregoing breathing tube can comprise one, some, or all of the following properties or any other properties described elsewhere in this disclosure. The first elongate member can comprise a hollow body spirally wound to form at least in part an elongate tube having a longitudinal axis, a lumen extending along the longitudinal axis, and a hollow wall surrounding the lumen. The breathing tube can further comprise a second elongate member spirally wound and joined between adjacent turns of the first elongate member, the second elongate member forming at least a portion of the lumen of the elongate tube. The breathing tube can comprise one or more conductive filaments embedded or encapsulated within the second elongate member. At least one of the one or more conductive filaments can be a heating filament. At least one of the one or more conductive filaments can be a sensing filament. The tube mass in the 300 mm nearest an end of the tube can be less than about 24 g. The weight per length of the tube within at least a portion of the 300 mm nearest an end of the tube can be less than about 0.06 g/mm. The tube mass in the 300 mm nearest an end of the tube can be less than about 16 g. The thickness of the wall can be at most about 0.50 mm.

[0029] A breathing tube is also disclosed. In at least one embodiment, the tube comprises a first elongate member comprising a hollow body spirally wound to form at least in part an elongate tube having a longitudinal axis, a lumen extending along the longitudinal axis, and a hollow wall surrounding the lumen, the wall having an inner portion proximal the

lumen and an outer portion facing away from the lumen, wherein, in at least a portion of the composite tube, when force is applied to the outer portion of the wall with a 2.5-mm probe until the outer portion of the wall contacts the inner portion, the outer portion deflects by a vertical distance that satisfies the equation: $D > 0.5 \times F_{2.5}$, where D represents the vertical distance in millimeters, and $F_{2.5}$ represents the force in Newtons applied by the 2.5-mm probe.

[0030] In various embodiments, the foregoing breathing tube can comprise one, some, or all of the following properties or any other properties described elsewhere in this disclosure. The breathing tube can further comprise a second elongate member spirally wound and joined between adjacent turns of the first elongate member, the second elongate member forming at least a portion of the lumen of the elongate tube. The outer portion can deflect more than about 1 mm when a force of about 1 N is applied with the 2.5-mm probe.

[0031] A conduit suitable for use with a tube for delivering humidified gases to a patient is also disclosed. In at least one embodiment, the conduit comprises a connector configured to connect to the tube, the connector comprising a lumen extending along a longitudinal axis and walls surrounding the lumen, the lumen defining a flow path for the humidified gases when in use; and a printed circuit board assembly comprising a printed circuit board and further comprising a dividing portion embedded in the walls of the connector and extending across the lumen of the connector along a diameter or chord line, such that the dividing portion generally bisects at least part of the flow path, at least part of the dividing portion being overmolded by an overmolding composition, a wiring portion adjacent the dividing portion and projecting outward from the wall of the connector in a direction away from the lumen of the connector, and a sensor portion disposed in the lumen of the connector and projecting from the dividing portion along the longitudinal axis, the sensor portion comprising at least one sensor, and the sensor portion being overmolded by the overmolding composition.

[0032] In various embodiments, the foregoing conduit can comprise one, some, or all of the following properties or any other properties described elsewhere in this disclosure. The printed circuit board assembly can further comprise a support portion adjacent the dividing portion and projecting outward from the connector in a direction away from the

lumen and in a direction opposite the wiring portion. The wiring portion can be configured to electrically connect to one or more heater wires from the conduit. The at least one sensor can comprise a thermistor. The sensor portion can project upstream of the flow path. The at least one sensor can comprise a sensor adjacent an upstream leading edge of the sensor portion. The sensor portion can project downstream of the flow path. The at least one sensor can comprise a sensor adjacent a downstream leading edge of the sensor portion. The overmolding composition proximal the sensor portion can have a tapered shape extending along the longitudinal axis. The overmolding can be thinnest proximal a leading edge of the sensor portion. The sensor portion can have an airfoil shape extending along the longitudinal axis. The sensor portion can have a bullet or torpedo shape.

[0033] A respiratory conduit is also disclosed. In at least one embodiment, the conduit comprises a lumen extending along a longitudinal axis and a wall surrounding the lumen, the lumen defining a gas-flow path when in use; and an overmolded printed circuit board assembly secured to the wall, the printed circuit board assembly comprising a printed circuit board and further comprising a mount portion disposed in the lumen of the connector and projecting along the longitudinal axis, and a temperature sensor on a surface of the mount portion.

[0034] In various embodiments, the foregoing conduit can comprise one, some, or all of the following properties or any other properties described elsewhere in this disclosure. The temperature sensor can be a thermistor.

[0035] A respiratory conduit is also disclosed. In at least one embodiment, the conduit comprises a lumen extending along a longitudinal axis and walls surrounding the lumen, the lumen defining a gas-flow path when in use; and a component secured to the walls and extending across the lumen along a diameter or chord line, such that the component generally bisects at least part of the flow path, the component comprising a mount portion disposed in the lumen and projecting along the longitudinal axis, a temperature sensor on a surface of the mount portion, and electrical connection to the sensor.

[0036] In various embodiments, the foregoing conduit can comprise one, some, or all of the following properties or any other properties described elsewhere in this disclosure.

The temperature sensor can be a thermistor. The component can be a printed circuit board. The electrical connection can span the component's length along the diameter or chord line.

[0037] A respiratory conduit is also disclosed. In at least one embodiment, the conduit comprises a lumen extending along a longitudinal axis and a wall surrounding the lumen, the lumen defining a gas-flow path when in use; and an overmolded printed circuit board assembly secured to the wall, the printed circuit board assembly comprising a printed circuit board and further comprising a mount portion disposed in the lumen and projecting along the longitudinal axis, and a temperature sensor on a surface of the mount portion, wherein the overmolding proximal the mount portion has a tapered shape.

[0038] In various embodiments, the foregoing conduit can comprise one, some, or all of the following properties or any other properties described elsewhere in this disclosure. The temperature sensor can be a thermistor.

[0039] A respiratory conduit is also disclosed. In at least one embodiment, the conduit comprises a lumen extending along a longitudinal axis and a wall surrounding the lumen, the lumen defining a gas-flow path when in use; and a component connected to the wall and comprising a mount portion disposed in the lumen and projecting along the longitudinal axis, the mount portion comprising a temperature sensor positioned longitudinally upstream from the connection to the wall.

[0040] In various embodiments, the foregoing breathing tube can comprise one, some, or all of the following properties or any other properties described elsewhere in this disclosure. The temperature sensor can be a thermistor. The temperature sensor can be proximal an upstream extreme of the mount portion. The mount portion can be overmolded. The overmolding can be thinnest proximal the temperature sensor. The mount can project longitudinally downstream. The mount can have an airfoil shape extending along the longitudinal axis. The mount can have a bullet or torpedo shape. A vertical distance between the mount and the wall can be at least 30% of the lumen's diameter.

[0041] A respiratory conduit segment is also disclosed. In at least one embodiment, the segment comprises a lumen extending along a longitudinal axis and a wall surrounding the lumen, the lumen defining a gas-flow path when in use; and a printed circuit board assembly comprising a printed circuit board and comprising a first portion extending

across the lumen along a diameter or chord line, such that a portion of the printed circuit board assembly generally bisects at least part of the flow path, the first portion being overmolded by an overmolding composition, a second portion adjacent the first portion projecting outward from the wall in a direction away from the lumen, the second portion comprising one or more connection pads on the printed circuit board configured to receive one or more wires from a first assembly, a third portion adjacent the first portion projecting outward from the wall in a direction away from the lumen and in a direction opposite the second portion, the third portion comprising one or more connection pads on the printed circuit board configured to receive one or more wires from a second assembly that is distinct from the first assembly, and one or more conductive tracks on the printed circuit board electrically coupled to the one or more connection pads of the second portion and to the one or more connection pads of the third portion and configured to provide electrical connectivity between the first assembly and the second assembly.

[0042] In various embodiments, the foregoing segment can comprise one, some, or all of the following properties or any other properties described elsewhere in this disclosure. The first assembly can be a breathing tube. The second assembly can be a breathing tube. The printed circuit board assembly can further comprise a mount portion disposed in the lumen of the connector and projecting along the longitudinal axis, and a temperature sensor on a surface of the mount portion.

[0043] In various embodiments, a breathing tube comprises a first elongate member comprising a hollow body spirally wound to form at least in part an elongate tube having a longitudinal axis, a lumen extending along the longitudinal axis, and a hollow wall surrounding the lumen, the hollow body forming in longitudinal cross section a plurality of bubbles, a bubble having a maximum width along the longitudinal axis and a maximum height perpendicular to the longitudinal axis between the outward-facing apex of the wall and the lumen, wherein the ratio of the maximum height to the maximum width is at least about 0.16. A second elongate member may be spirally wound and joined between adjacent turns of the first elongate member, the second elongate member forming at least a portion of the lumen of the elongate tube. The maximum height may be in the range of about 0.7 mm and about 7.7 mm. The maximum height may be about 2.7 mm. The maximum width may be in

the range of about 2.0 mm and about 6.0 mm. The maximum width may be about 4.0 mm. The maximum height to the maximum width may be greater than 1.0.

[0044] In various embodiments, a breathing tube comprises a first elongate member comprising a hollow body spirally wound to form at least in part an elongate tube having a longitudinal axis, a lumen extending along the longitudinal axis, and a hollow wall surrounding the lumen, the hollow body forming in longitudinal cross section a plurality of bubbles, wherein a vertical distance between corresponding points on adjacent bubbles defines a pitch, wherein the ratio of pitch to the maximum outer diameter of the composite tube is less than about 0.35. A second elongate member may be spirally wound and joined between adjacent turns of the first elongate member, the second elongate member forming at least a portion of the lumen of the elongate tube. The pitch may be in the range of about 1.2 mm and about 8.1 mm. The pitch may be about 5.1 mm. The maximum outer diameter may be in the range of about 19.5 mm and 25.5 mm. The maximum outer diameter may be about 22.5 mm.

[0045] In various embodiments, a composite tube comprises a first elongate member comprising a hollow body spirally wound to form at least in part an elongate tube having a longitudinal axis, a lumen extending along the longitudinal axis, and a hollow wall surrounding the lumen, the hollow body forming in longitudinal cross section a plurality of bubbles, a bubble having a maximum height, perpendicular to the longitudinal axis, between the outward-facing apex of the wall and the lumen that defines the maximum height of the first elongate member; and a second elongate member spirally wound and joined between adjacent turns of the first elongate member, the second elongate member forming at least a portion of the lumen of the elongate tube, the second elongate member having a maximum height, perpendicular to the longitudinal axis, between the outward-facing apex of the second elongate member and the lumen, wherein the ratio of the difference between the maximum height of the first elongate member and the maximum height of the second elongate member to the maximum outer diameter of the composite tube is less than about 0.049:1. The wall may have an inner portion proximal the lumen and an outer portion facing away from the lumen and the inner portion of the wall may have a smaller thickness than the outer portion of the wall.

[0046] In various embodiments, a composite tube comprises a first elongate member comprising a hollow body spirally wound to form at least in part an elongate tube having a longitudinal axis, a lumen extending along the longitudinal axis, and a hollow wall surrounding the lumen, the wall having an inner portion proximal the lumen and an outer portion facing away from the lumen; and a second elongate member spirally wound between adjacent turns of the first elongate member, the second elongate member forming at least a portion of the lumen of the elongate tube and the first elongate member being joined at connection points on adjacent turns of the second elongate member; wherein the composite tube's bend radius is limited by the length of the outer portion between the connection points. The wall may have an inner portion proximal the lumen and an outer portion facing away from the lumen and the inner portion of the wall may have a smaller thickness than the outer portion of the wall.

[0047] In various embodiments, a conduit suitable for use with a tube for delivering humidified gases to a patient is provided, the conduit comprising a connector configured to connect to the tube, the connector comprising a lumen extending along a longitudinal axis and walls surrounding the lumen, the lumen defining a flow path for the humidified gases when in use; and a printed circuit board assembly comprising a printed circuit board and further comprising a dividing portion embedded in the walls of the connector and extending across the lumen of the connector along a diameter or chord line, such that the dividing portion generally bisects at least part of the flow path, at least part of the dividing portion being overmolded by an overmolding composition, a wiring portion adjacent the dividing portion and projecting outward from the wall of the connector in a direction away from the lumen of the connector, and a sensor portion disposed in the lumen of the connector and projecting from the dividing portion along the longitudinal axis, the sensor portion comprising at least one sensor, and the sensor portion being overmolded by the overmolding composition. The printed circuit board assembly may further comprise a support portion adjacent the dividing portion and projecting outward from the connector in a direction away from the lumen and in a direction opposite the wiring portion. The wiring portion may be configured to electrically connect to one or more heater wires from the conduit. The at least one sensor may comprise a thermistor. The sensor portion may project

upstream of the flow path. The at least one sensor may comprise a sensor adjacent an upstream leading edge of the sensor portion. The sensor portion may project downstream of the flow path. The at least one sensor may comprise a sensor adjacent a downstream leading edge of the sensor portion. The overmolding proximal the sensor portion may have a tapered shape extending along the longitudinal axis. The overmolding may be thinnest proximal a leading edge of the sensor portion. The sensor portion may have an airfoil shape extending along the longitudinal axis. The sensor portion may have a bullet or torpedo shape.

[0048] In various embodiments, a respiratory conduit comprises a lumen extending along a longitudinal axis and a wall surrounding the lumen, the lumen defining a gas-flow path when in use; and an overmolded printed circuit board assembly secured to the wall, the printed circuit board assembly comprising a printed circuit board and further comprising a mount portion disposed in the lumen and projecting along the longitudinal axis, and a temperature sensor on a surface of the mount portion, wherein the overmolding proximal the mount portion has a tapered shape. The temperature sensor may be a thermistor.

[0049] In various embodiments, a respiratory conduit comprises a lumen extending along a longitudinal axis and a wall surrounding the lumen, the lumen defining a gas-flow path when in use; and a component connected to the wall and comprising a mount portion disposed in the lumen and projecting along the longitudinal axis, the mount portion comprising a temperature sensor positioned longitudinally upstream from the connection to the wall. The temperature sensor may be a thermistor. The temperature sensor may be proximal an upstream extreme of the mount portion. The mount portion may be overmolded. The overmolding may be thinnest proximal the temperature sensor. The mount may project longitudinally downstream. The mount may have an airfoil shape extending along the longitudinal axis. The mount may have a bullet or torpedo shape. A vertical distance between the mount and the wall may be at least 30% of the lumen's diameter.

[0050] In various embodiments, a respiratory conduit segment comprises a lumen extending along a longitudinal axis and a wall surrounding the lumen, the lumen defining a gas-flow path when in use; and a printed circuit board assembly comprising a printed circuit board and comprising a first portion extending across the lumen along a diameter or chord

line, such that a portion of the printed circuit board assembly generally bisects at least part of the flow path, the first portion being overmolded by an overmolding composition, a second portion adjacent the first portion projecting outward from the wall in a direction away from the lumen, the second portion comprising one or more connection pads on the printed circuit board configured to receive one or more wires from a first assembly, a third portion adjacent the first portion projecting outward from the wall in a direction away from the lumen and in a direction opposite the second portion, the third portion comprising one or more connection pads on the printed circuit board configured to receive one or more wires from a second assembly that is distinct from the first assembly, and one or more conductive tracks on the printed circuit board electrically coupled to the one or more connection pads of the second portion and to the one or more connection pads of the third portion and configured to provide electrical connectivity between the first assembly and the second assembly. The first assembly may be a breathing tube. The second assembly may be a breathing tube. The printed circuit board assembly may further comprise a mount portion disposed in the lumen of the connector and projecting along the longitudinal axis, and a temperature sensor on a surface of the mount portion.

[0051] In various embodiments, a composite tube comprises a first elongate member comprising a hollow body spirally wound to form at least in part an elongate tube having a longitudinal axis, a lumen extending along the longitudinal axis, and a hollow wall surrounding the lumen; a second elongate member spirally wound and joined between adjacent turns of the first elongate member, the second elongate member forming at least a portion of the lumen of the elongate tube; wherein at least a portion of the first elongate member is formed of a breathable material. In one example, the composite tube may be provided with a source of humidification fluid and/or be pre-charged with a volume of humidification fluid, and a heater provided to heat the fluid such that fluid vapour passes through the breathable material into or from the lumen. The heater may comprise one or more heating filaments disposed in the second elongate member.

[0052] For purposes of summarizing the invention, certain aspects, advantages and novel features of the invention have been described herein. It is to be understood that not

necessarily all such advantages may be achieved in accordance with any particular embodiment of the invention. Thus, the invention may be embodied or carried out in a manner that achieves or optimizes one advantage or group of advantages as taught herein without necessarily achieving other advantages as may be taught or suggested herein.

BRIEF DESCRIPTION OF THE DRAWINGS

[0053] Example embodiments that implement the various features of the disclosed systems and methods will now be described with reference to the drawings. The drawings and the associated descriptions are provided to illustrate embodiments and not to limit the scope of the disclosure.

[0054] FIG. 1 shows a schematic illustration of a medical circuit incorporating one or more medical tubes.

[0055] FIG. 2A shows a side-plan view of a section of an example composite tube.

[0056] FIG. 2B shows a longitudinal cross-section of a top portion a tube similar to the example composite tube of FIG. 2A.

[0057] FIG. 2C shows another longitudinal cross-section illustrating a first elongate member in the composite tube.

[0058] FIG. 2D shows another longitudinal cross-section of a top portion of a tube.

[0059] FIG. 2E shows another longitudinal cross-section of a top portion of a tube.

[0060] FIG. 2F shows a tube with a portion exposed in longitudinal cross-section.

[0061] FIG. 2G shows a longitudinal cross-section of a portion of a tube similar to the example tube of FIG. 2F.

[0062] FIG. 2H shows a longitudinal cross-section of a top portion of a tube.

[0063] FIG. 3 shows a jig suitable for determining bubble deflection.

[0064] FIG. 4 shows a curve of force vs. bubble deflection.

[0065] FIGS. 5A–5C show examples of first elongate member shapes configured to improve thermal efficiency.

[0066] FIGS. 5D–5F show examples of filament arrangements configured to improve thermal efficiency.

[0067] FIG. 6A shows a longitudinal cross section of a portion of a composite tube in a neutral position.

[0068] FIG. 6B shows the portion of the composite tube of FIG. 6A in a bent position, in which the composite tube has been bent to a \cap -shape.

[0069] FIG. 6C shows a composite tube that has been bent to a \cap -shape.

[0070] FIG. 6D shows a composite tube that has been bent beyond the minimum radius of curvature.

[0071] FIG. 7A shows a transverse cross-section of a second elongate member in the composite tube.

[0072] FIG. 7B shows another transverse cross-section of a second elongate member.

[0073] FIG. 7C shows another example second elongate member.

[0074] FIG. 7D shows another example second elongate member.

[0075] FIG. 7E shows another example second elongate member.

[0076] FIG. 7F shows another example second elongate member.

[0077] FIG. 7G shows another example second elongate member.

[0078] FIG. 8A shows a schematic of a composite tube with a variable pitch.

[0079] FIG. 8B is a graph depicting an example temperature profile in a variable-pitch composite tube.

[0080] FIG. 9A shows a front-plan cross-sectional schematic of a flexibility jig.

[0081] FIG. 9B shows a detailed front-plan cross-sectional schematic of rollers on the flexibility jig of FIG. 9A.

[0082] FIGS. 9C–9F show a flexibility jig in use. FIGS. 9C and 9E show a front-perspective view of samples under testing in the jig. FIGS. 9D and 9F show a rear-perspective view of samples under testing in the jig.

[0083] FIG. 10A shows a crush resistance testing jig.

[0084] FIG. 10B shows a plot of load vs. extension, used for determining crush stiffness.

- [0085] FIGS. 11A–11D demonstrate radius of curvature properties of tubes.
- [0086] FIGS. 12A–12C show examples of first elongate member stacking.
- [0087] FIG. 13 shows an alternative embodiment of the second elongate member.
- [0088] FIGS. 14A–14E show variations of a tube, adapted to provide increased lateral stretch in the tube.
- [0089] FIGS. 15A–15E show a stretched state of the tubes shown in FIGS. 13A–E, respectively.
- [0090] FIG. 16 shows an example medical circuit according to at least one embodiment.
- [0091] FIG. 17 shows an insufflation system according to at least one embodiment.
- [0092] FIG. 18 is a schematic illustration of a coaxial tube, according to at least one embodiment.
- [0093] FIGS. 19A–19B show a composite tube in use with a patient interface.
- [0094] FIG. 20A shows a composite tube in use with a full face mask.
- [0095] FIG. 20B shows a composite tube in use with a nasal mask.
- [0096] FIG. 20C shows a composite tube in use with a nasal/pillow mask.
- [0097] FIG. 21A shows an aspect in a method for forming the composite tube.
- [0098] FIG. 21B shows a spiral-wound second elongate member.
- [0099] FIG. 21C shows another aspect in a method for forming the composite tube.
- [0100] FIG. 21D shows another aspect in a method for forming the composite tube.
- [0101] FIG. 21E shows another aspect in a method for forming the composite tube.
- [0102] FIG. 21F shows another aspect in a method for forming the composite tube.
- [0103] FIGS. 22A–22C show example configurations of longitudinal cross sections of tubes.
- [0104] FIGS. 23A–23H show an alternative method of forming a tube.

[0105] FIGS. 24A–24B show another example illustrating a single elongate hollow body being spirally wound to form a medical tube.

[0106] FIGS. 24C–24F show examples of other single elongate hollow bodies being spirally wound to form a medical tube.

[0107] FIGS. 25A–25L show a general flow chart and more detailed schematics and photographs relating to a method for attaching a connector to the end of the tube that is configured in use to connect to a humidifier.

[0108] FIGS. 26A–26E show a connector for attaching filaments to an electrical connector.

[0109] FIGS. 27A–27E show a clamshell suitable for use with the connector of FIGS. 25A–25L.

[0110] FIGS. 28A–28F and 29A–29L show connectors that can be used for medical circuits having electrical wires running therethrough and associated methods of assembly.

[0111] FIGS. 30A–30O show schematics relating to a connector suitable for attaching a tube to a patient interface.

[0112] FIGS. 31A–31B show a stop portion suitable for use with the connector of FIGS. 30A–30O.

[0113] FIGS. 32A–32D show an anti-rotation feature suitable for use with the connector of FIGS. 30A–30O.

[0114] FIGS. 33A–33D illustrate an example PCB assembly.

[0115] FIG. 34 illustrates a segmented inspiratory limb for use with a humidification system, the segmented inspiratory limb having an intermediate connector configured to couple heating filaments and/or temperature sensors in the two segments.

[0116] FIGS. 35A–35E show schematics relating to a connector suitable for attaching a tube to a humidifier port, patient interface, or any other suitable component.

[0117] FIGS. 36A–36K show schematics relating to another connector suitable for attaching a tube to a humidifier port, patient interface, or any other suitable component.

[0118] FIG. 37A shows a longitudinal cross-section of a top portion of a tube comprising two first elongate members.

[0119] FIG. 37B shows another longitudinal cross-section of a top portion of a tube comprising two first elongate members.

[0120] Generally throughout the drawings, reference numbers are reused to indicate correspondence between referenced (or similar) elements. Nevertheless, corresponding referenced (or similar) elements may have different reference numbers in some circumstances. In addition, the first digit(s) of each reference number generally indicate the figure in which the element first appears.

DETAILED DESCRIPTION

[0121] Details regarding several illustrative embodiments for implementing the apparatuses and methods described herein are described below with reference to the figures. The invention is not limited to these described embodiments.

Breathing Circuit Comprising One Or More Medical Tubes

[0122] For a more detailed understanding of the disclosure, reference is first made to FIG. 1, which shows a breathing circuit according to at least one embodiment, which includes one or more medical tubes. Tube is a broad term and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (that is, it is not to be limited to a special or customized meaning) and includes, without limitation, cylindrical and non-cylindrical passageways. Certain embodiments may incorporate a composite tube, which may generally be defined as a tube comprising two or more portions, or, specifically, in some embodiments, two or more components, as described in greater detail below. Such a breathing circuit can be a continuous, variable, or bi-level positive airway pressure (PAP) system or other form of respiratory therapy.

[0123] Gases can be transported in the circuit of FIG. 1 as follows. Dry gases pass from a ventilator/blower 105 to a humidifier 107, which humidifies the dry gases. The humidifier 107 connects to the inlet 109 (the end for receiving humidified gases) of the inspiratory tube 103 via a port 111, thereby supplying humidified gases to the inspiratory tube 103. An inspiratory tube is a tube that is configured to deliver breathing gases to a patient, and may be made from a composite tube as described in further detail below. The gases flow

through the inspiratory tube **103** to the outlet **113** (the end for expelling humidified gases), and then to the patient **101** through a patient interface **115** connected to the outlet **113**.

[0124] An expiratory tube **117** optionally connects to the patient interface **115**. An expiratory tube is a tube that is configured to move exhaled humidified gases away from a patient. Here, the expiratory tube **117** returns exhaled humidified gases from the patient interface **115** to the ventilator/blower **105**.

[0125] In this example, dry gases enter the ventilator/blower **105** through a vent **119**. A fan **121** can improve gas flow into the ventilator/blower by drawing air or other gases through vent **119**. The fan **121** can be, for instance, a variable speed fan, where an electronic controller **123** controls the fan speed. In particular, the function of the electronic controller **123** can be controlled by an electronic master controller **125** in response to inputs from the master controller **125** and a user-set predetermined required value (preset value) of pressure or fan speed or gases flow rate via a dial **127**.

[0126] The humidifier **107** comprises a humidification chamber **129** containing a volume of water **130** or other suitable humidifying liquid. Preferably, the humidification chamber **129** is removable from the humidifier **107** after use. Removability allows the humidification chamber **129** to be more readily sterilized or disposed. However, the humidification chamber **129** portion of the humidifier **107** can be a unitary construction. The body of the humidification chamber **129** can be formed from a non-conductive glass or plastics material. But the humidification chamber **129** can also include conductive components. For instance, the humidification chamber **129** can include a highly heat-conductive base (for example, an aluminum base) contacting or associated with a heater plate **131** on the humidifier **107**.

[0127] The humidifier **107** can also include electronic controls. In this example, the humidifier **107** includes an electronic, analog or digital master controller **125**. Preferably, the master controller **125** is a microprocessor-based controller executing computer software commands stored in associated memory. In response to the user-set humidity or temperature value input via a user interface **133**, for example, and other inputs, the master controller **125** determines when (or to what level) to energize heater plate **131** to heat the water **130** within humidification chamber **129**.

[0128] Any suitable patient interface 115 can be incorporated. Patient interface is a broad term and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (that is, it is not to be limited to a special or customized meaning) and includes, without limitation, masks (such as tracheal mask, face masks and nasal masks), cannulas, and nasal pillows. A temperature probe 135 can connect to the inspiratory tube 103 near the patient interface 115, or to the patient interface 115. The temperature probe 135 monitors the temperature near or at the patient interface 115. A heating filament (not shown) associated with the temperature probe can be used to adjust the temperature of the patient interface 115 and/or inspiratory tube 103 to raise the temperature of the inspiratory tube 103 and/or patient interface 115 above the saturation temperature, thereby reducing the opportunity for unwanted condensation.

[0129] In FIG. 1, exhaled humidified gases are returned from the patient interface 115 to the ventilator/blower 105 via the expiratory tube 117. The expiratory tube 117 can also be a composite tube, as described in greater detail below. However, the expiratory tube 117 can also be a medical tube as previously known in the art. In either case, the expiratory tube 117 can have a temperature probe and/or heating filament, as described above with respect to the inspiratory tube 103, integrated with it to reduce the opportunity for condensation. Furthermore, the expiratory tube 117 need not return exhaled gases to the ventilator/blower 105. Alternatively, exhaled humidified gases can be passed directly to ambient surroundings or to other ancillary equipment, such as an air scrubber/filter (not shown). In certain embodiments, the expiratory tube is omitted altogether.

Composite Tubes

[0130] FIG. 2A shows a side-plan view of a section of example composite tube 201. In general, the composite tube 201 comprises a first elongate member 203 and a second elongate member 205. Member is a broad term and is to be given its ordinary and customary meaning to a person of ordinary skill in the art (i.e., it is not to be limited to a special or customized meaning) and includes, without limitation, integral portions, integral components, and distinct components. Thus, although FIG. 2A illustrates an embodiment made of two distinct components, it will be appreciated that in other embodiments (such as described in

below), the first elongate member **203** and second elongate member **205** can also represent regions in a tube formed from a single material. Thus, the first elongate member **203** can represent a hollow portion of a tube, while the second elongate member **205** represents a structural supporting or reinforcement portion of the tube which adds structural support to the hollow portion. The hollow portion and the structural supporting portion can have a spiral configuration, as described herein.

[0131] The composite tube **201** may be used to form the inspiratory tube **103** and/or the expiratory tube **117** in a breathing circuit, as described above, a coaxial tube as described below, or any other tubes as described elsewhere in this disclosure. In certain embodiments, the composite tube **201** is at least an inspiratory tube **103**.

[0132] The following describes components and properties of example composite tubes **201** in greater detail. Sub-headings are used, such as “first elongate member” and “second elongate member.” These sub-headings are not, and should not be construed as, limiting. For example, aspects of one or more embodiments described under the first-elongate-member subheading can also apply to one or more embodiments described under the second-elongate-member subheading, and the reverse is also true.

First Elongate Member

[0133] In FIG. 2A, the first elongate member **203** comprises a hollow body spirally wound to form, at least in part, an elongate tube having a longitudinal axis **LA—LA** and a lumen **207** (tube bore) extending along the longitudinal axis **LA—LA**. The first elongate member **203** has an inner portion **211** near the lumen **207**. In certain embodiments, a surface of the inner portion **211** forms the lumen **207**. The first elongate member **203** also has an outer portion **219** opposite the inner portion and facing away from the lumen **207** in the radial direction. As discussed in greater detail below, the first elongate member **203** can form in longitudinal cross-section a plurality of bubbles. In certain embodiments, the bubbles have a cross-sectional profile resembling the letter “D.” The bubbles can be arced at the outward-facing surface. The bubbles can be flatter at the surface at the lumen **207**. In at least one embodiment, the first elongate member **203** is a tube.

[0134] Preferably, the first elongate member **203** is flexible. Flexible refers to the ability to bend. Furthermore, the first elongate member **203** is preferably transparent or, at least, semi-transparent or semi-opaque. A degree of optical transparency allows a caregiver or user to inspect the lumen **207** for blockage or contaminants or to confirm the presence of moisture.

[0135] A variety of plastics, including medical grade plastics, are suitable for the body of the first elongate member **203**. Examples of suitable materials include Polyolefin elastomers, Polyether block amides, Thermoplastic co-polyester elastomers, EPDM-Polypropylene mixtures, and Thermoplastic polyurethanes. In certain embodiments, the material is selected such that the material density of the resulting first elongate member **203** is less than or equal to 1 g/cm^3 (or about 1 g/cm^3).

[0136] The first elongate member **203** material is preferably soft. Softness reflects the amount the material “gives” or compresses upon application of a force. A soft material gives or compresses more than a firm material. Bubble deflection can be used to quantify the softness of the first elongate member **203** material. Bubble deflection is distance that the outer portion **219** of the first elongate member **203** vertically deflects (that is, displaces radially inward in the direction of the lumen **207**) upon application of a force. Bubble deflection can be tested, for example, using a bubble deflection jig, such as the jig **301** shown in the photograph of FIG. 3.

[0137] In one softness test, four samples of composite tubes having the properties shown in TABLE 1 (hereinafter “Type 1”) and four samples of composite tubes having the properties shown in TABLE 2 (hereinafter “Type 2”) were each tested on the jig **301** of FIG. 3.

Table 1

Feature	Dimension (mm)	Range (\pm)
Lumen diameter	17.2	5.0
Pitch	5.1	3.0
Bubble width	4.0	2.0
Bead width	2.3	+3.0/-2.0
Bubble height	2.7	+5.0/-2.0
Bead height	1.6	1.5
Bubble thickness on top, farthest from lumen (outer wall thickness)	0.24	+0.20/-0.10
Bubble thickness adjacent lumen (inner wall thickness)	0.10	+0.20/-0.05
Outer diameter of tube	22.5	3.0

Table 2

Feature	Dimension (mm)	Range(\pm)
Lumen diameter	18.25	0.25
Pitch	8.2	0.15
Bubble width	7.0	1
Bead width	2.30	0.15
Bubble height	4.0	0.05
Bead height	1.95	0.15
Bubble thickness on top, farthest from lumen (outer wall thickness)	0.42	0.04
Bubble thickness adjacent lumen (inner wall thickness)	0.22	0.04
Outer diameter of tube	26	0.5

[0138] A probe 303 with a 2.5-mm diameter applied a force to each sample 305 and bubble deflection was measured. The resulting curves are plotted in FIG. 4. Until their respective outer portion 219 contacted the inner portion 211, Type 1 samples generally required less force to achieve a similar bubble deflection as Type 2 samples. In certain embodiments, until the outer portion 219 contacts the inner wall 211, the bubble deflection can satisfy the equation: $D > 0.5 \times F_{2.5}$, where D represents the bubble deflection in millimeters and $F_{2.5}$ represents the force in Newtons applied by a 2.5-mm probe. For

example, the first elongate member **203** can deflect more than 1 mm when a force of 1 N is applied with a 2.5-mm probe **303**, until the outer portion **219** contacts the inner portion **211**.

[0139] It should be appreciated that, although the configuration in TABLE 1 may be preferred in certain embodiments, other configurations and variations, may be used in other embodiments as may be desired.

[0140] FIG. 2B shows a longitudinal cross-section of a top portion of the example composite tube **201** of FIG. 2A. FIG. 2B has the same orientation as FIG. 2A. This example further illustrates the hollow-body shape of the first elongate member **203**. As seen in this example, the first elongate member **203** forms in longitudinal cross-section a plurality of hollow bubbles. Thus, in this description, the term “bubble” refers to cross-sectional shape of a wind or turn of the first elongate member **203**. Portions **209** of the first elongate member **203** overlap adjacent wraps of the second elongate member **205**. An inner portion **211** of the first elongate member **203** forms the wall of the lumen **207**.

[0141] The hollow body structure of the first elongate member **203** contributes to the sound damping properties to the composite tube **201**. In at least one embodiment, the outer diameter of the first elongate member **203** is larger than the outer diameter of the second elongate member **205**. The bubble-shaped structure forms a cushion. Thus, the fluid (gas or liquid) filled bubble-shaped first elongate member **203** can muffle the noise made when the composite tube **201** is dragged over an object, such as the edge of a desk or bedside table. In this way, the composite tube **201** can be quieter compared with one-piece solid-body corrugated tubes,

[0142] The hollow body structure of the first elongate member **203** also contributes to the insulating properties to the composite tube **201**. An insulating composite tube **201** is desirable because, as explained above, it prevents heat loss. This can allow the composite tube **201** to deliver gas from a heater-humidifier to a patient while maintaining the gas's conditioned state with minimal energy consumption.

[0143] It was discovered that having a gap **213** between adjacent turns of the first elongate member **203**, that is, between adjacent bubbles, unexpectedly improved the overall insulating properties of the composite tube **201**. Thus, in certain embodiments, adjacent bubbles are separated by a gap **213**. Furthermore, certain embodiments include the

realization that providing a gap **213** between adjacent bubbles increases the heat transfer resistivity (the R value) and, accordingly, decreases the heat transfer conductivity of the composite tube **201**. This gap configuration was also found to improve the flexibility of the composite tube **201** by permitting shorter-radius bends. A triangular second elongate member **205** or a T-shaped second elongate member **205**, as shown in FIG. **2B**, can help maintain a gap **213** between adjacent bubbles. Nevertheless, in certain embodiments, adjacent bubbles are touching. For example, adjacent bubbles can be bonded together.

[0144] FIG. **2C** shows a longitudinal cross-section of the bubbles in FIG. **2B**. As shown, the portions **209** of the first elongate member **203** overlapping adjacent wraps of the second elongate member **205** are characterized by a degree of bond region **217**. A larger bond region improves the tube's resistance to delamination at the interface of the first and second elongate members. Additionally or alternatively, the shape of the bead and/or the bubble can be adapted to increase the bond region **217**. For example, FIG. **2D** shows a relatively small bonding area on the left-hand side. FIG. **5B** also demonstrates a smaller bonding region. In contrast, FIG. **2E** has a much larger bonding region than that shown in FIG. **2D**, because of the size and shape of the bead. FIGS. **5A** and **5C** also illustrate a larger bonding region. Each of these figures is discussed in more detail below. It should be appreciated that, although the configurations in FIGS. **2E**, **3A**, and **5C** may be preferred in certain embodiments, other configurations, including those of FIGS. **2D**, **5B**, and other variations, may be used in other embodiments as may be desired.

[0145] FIG. **2D** shows a longitudinal cross-section of a top portion of another composite tube. FIG. **2D** has the same orientation as FIG. **2B**. This example further illustrates the hollow-body shape of the first elongate member **203** and demonstrates how the first elongate member **203** forms in longitudinal cross-section a plurality of hollow bubbles. In this example, the bubbles are completely separated from each other by a gap **213**. A generally triangular second elongate member **205** supports the first elongate member **203**.

[0146] FIG. **2H** shows a longitudinal cross-section of a top portion of another composite tube. FIG. **2H** has the same orientation as FIG. **2B**.

[0147] In the example of FIG. **2H**, the cross-sectional thickness of the inner portion **211** of the first elongate member **203** forming the wall of the lumen is less than the

thickness of the outer portion **219**. Because the first elongate member **203** has a D-shaped bubble profile, the outer-facing portion of the first elongate member **203** has material slack between adjacent winds of the second elongate member, which facilitates movement and stretching as the composite tube **201** is bent into a \cap -shape. Because the configuration of FIG. **2H** results in a thinner bubble near the lumen **207**, such a configuration allows the inner portion **211** to compress or “bunch” more readily when the composite tube **201** is bent into a \cap -shape. Thus, certain embodiments include the realization that a configuration in which the cross-sectional thickness of the inner portion **211** is less than the cross-sectional thickness of the outer portion **219** can improve the flexibility of the composite tube **201** by permitting shorter radius bends. In addition, certain embodiments include the realization that overall tube flexibility can be improved by providing a first elongate member **203** with a variable cross-sectional wall thickness. Desirably, the thickness of the inner portion **211** is less than the thickness of the outer portion **219**.

[0148] In at least one embodiment, the thickness of the inner portion **211** is at least 20% (or about 20%) less than the thickness of the outer portion **219**. For example, in certain embodiments, the thickness of the inner portion **211** is at least 30% (or about 30%), at least 40% (or about 40%), at least 50% (or about 50%), or at least 60% (or about 60%) less than the thickness of the outer portion **219**. In certain embodiments, the thickness of the inner portion **211** is 27% (or about 27%) less than the thickness of the outer portion **219**. In certain embodiments, the thickness of the inner portion **211** is 32% (or about 32%) less than the thickness of the outer portion **219**. In certain embodiments, the thickness of the inner portion **211** is 58% (or about 58%) less than the thickness of the outer portion **219**. In certain embodiments, the thickness of the inner portion **211** is 64% (or about 64%) less than the thickness of the outer portion **219**.

[0149] The thickness of the outer portion **219** can be in the range of 0.14 mm (or about 0.14 mm) and 0.44 mm (or about 0.44 mm), such as 0.22 mm (or about 0.22 mm) or 0.24 mm (or about 0.24 mm). The thickness of the inner portion **211** can be in the range of 0.05 mm (or about 0.05 mm) and 0.30 mm (or about 0.30 mm), and preferably 0.10 mm (or about 0.10 mm) or 0.16 mm (or about 0.16 mm).

[0150] Referring again to FIG. 2H, the height (designated as **H—H**) of a single longitudinal cross-sectional bubble of the first elongate member **203** can be greater than the width (designated as **W—W**) of a single longitudinal cross-sectional bubble of the first elongate member **203**. Because a greater height increases the amount of material slack in the outer wall of the bubble of the first elongate member **203**, such configuration can improve the flexibility of the composite tube **201** by permitting shorter radius bends. Accordingly, certain embodiments include the realization that overall tube flexibility can be improved by providing a first elongate member **203** with a longitudinal cross-sectional height that is greater than the longitudinal cross-sectional width. It should be appreciated that, although this example configuration may be preferred in certain embodiments, other configurations and variations, may be used in other embodiments as may be desired. For example, the height of a longitudinal cross-sectional bubble of the first elongate member **203** can be less than its width.

[0151] In at least one embodiment, the bubble height (**H—H**) can be in the range of 1.2 mm (or about 1.2 mm) and 8.2 mm (or about 8.2 mm), such as 1.2 mm (or about 1.2 mm), 1.7 mm (or about 1.7 mm), 1.8 mm (or about 1.8 mm), 2.7 mm (or about 2.7 mm), 2.8 mm (or about 2.8 mm), 3 mm (or about 3 mm), 3.2 mm (or about 3.2 mm), 3.5 mm (or about 3.5 mm), 3.8 mm (or about 3.8 mm), 4 mm (or about 4 mm), 4.5 mm (or about 4.5 mm), 7.7 mm (or about 7.7 mm), or 8.2 mm (or about 8.2 mm). In at least one embodiment, the bubble width (**W—W**) can be in the range of 1.7 mm (or about 1.7 mm) and 8 mm (or about 8 mm), such as 1.7 mm (or about 1.7 mm), 3.2 mm (or about 3.2 mm), 3.5 mm (or about 3.5 mm), 4.0 mm (or about 4.0 mm), 4.2 mm (or about 4.2 mm), 5.2 mm (or about 5.2 mm), 5.5 mm (or about 5.5 mm), 6 mm (or about 6 mm), 7 mm (or about 7 mm), 7.5 mm (or about 7.5 mm), or 8 mm (or about 8 mm).

[0152] The relationship between bubble height (**H—H**) and bubble width (**W—W**) can be expressed as a ratio. A ratio of bubble height (**H—H**) to bubble width (**W—W**) equal to 0 is least flexible. Flexibility increases as the ratio increases. In at least one embodiment, the ratio of bubble height (**H—H**) to bubble width (**W—W**) can be in the range of 0.15 (or about 0.15) and 1.5 mm (or about 1.5), such as 0.16 (or about 0.16), 0.34 (or about 0.34), 0.50 (or about 0.50), 0.56 (or about 0.56), 0.57 (or about 0.57), 0.58 (or about 0.58),

0.67 (or about 0.67), 0.68 (or about 0.68), 0.73 (or about 0.73), 0.85 (or about 0.85), 1.1 (or about 1.1). and 1.3 (or about 1.3).

[0153] It can be desirable for the outer profile of the corrugated tube to be relatively smooth. Relative smoothness, as used in this description, relates to the ridges between the first elongate member **203** and second elongate member **205** along the length of the composite tube **201**. A relatively smoother corrugated tube has flatter, more closely spaced, or otherwise less pronounced ridges. A relatively smoother profile can advantageously reduce noise when the corrugated tube is dragged across an object, such as a desk or table edge.

[0154] An example parameter for quantifying relative smoothness is the vertical difference between an outer radial apex **221** of first elongate member **203** and an outer radial apex **223** of the second elongate member **205** of a composite tube **201** (as shown, for example, in FIG. **2H**). As the distance between the outer radial apex **221** and the outer radial apex **223** decreases, the composite tube **201** feels relatively smoother. In at least one embodiment, the vertical distance is in the range of 1 mm (or about 1 mm) and 4.6 mm (or about 4.6 mm), such as 1.0 mm (or about 1.0 mm), 1.1 mm (or about 1.1 mm), 1.3 mm (or about 1.3 mm), 1.4 mm (or about 1.4 mm), 1.6 mm (or about 1.6 mm), 1.9 mm (or about 1.9 mm), 2.0 mm (or about 2.0 mm), 2.3 mm (or about 2.3 mm), 2.4 mm (or about 2.4 mm), 3.0 mm (or about 3.0 mm), 3.3 mm (or about 3.3 mm), or 4.6 mm (or about 4.6 mm). It is also possible to quantify relative smoothness as the vertical distance between an outer radial apex **221** of the first elongate member **203** and an outer radial nadir **225** of the second elongate member **205** of the composite tube **201**. For example, the vertical distance can be 1.5 mm (or about 1.5 mm).

[0155] Another example parameter for quantifying relative smoothness is the ratio of the vertical difference between a radial apex **221** of first elongate member **203** and a radial apex **223** (or a radial nadir **225**) of the second elongate member **205** of a composite tube **201** to the maximum outer diameter of the composite tube **201** (that is, from outer radial apex **221** to outer radial apex **221** on the opposite side of the tube **201**). As the maximum outer diameter increases, the vertical difference between the outer radial apex **221** and the outer radial apex **223** or nadir **225** has less effect on relative smoothness. In at least one

embodiment, the ratio is in the range of 0.04 to 0.18, such as 0.04, 0.05, 0.07, 0.08, 0.09, 0.10, 0.11, 0.12, 0.16, 0.17, or 0.18 or thereabout.

[0156] As another example, the distance between corresponding points from one turn to the next (that is, the pitch) can be selected to quantify relative smoothness. In certain embodiments, the pitch can be in the range of 2.1 mm (or about 2.1 mm) and 9.5 mm (or about 9.5 mm), such as 2.1 mm (or about 2.1 mm), 3.8 mm (or about 3.8 mm), 4.8 mm (or about 4.8 mm), 5.1 mm (or about 5.1 mm), 5.5 mm (or about 5.5 mm), 5.8 mm (or about 5.8 mm), 6.4 mm (or about 6.4 mm), 7.5 mm (or about 7.5 mm), 8.1 mm (or about 8.1 mm), or 9.5 mm (or about 9.5 mm).

[0157] The ratio of the pitch of the composite tube **201** to the vertical difference between a radial apex **221** of the first elongate member **203** and a radial apex **223** of the second elongate member **205** of the composite tube **201** can be selected to quantify relative smoothness. In certain embodiments, the ratio is in the range of 1.3 (or about 1.3) and 4.8 (or about 4.8), such as 1.31 (or about 1.31), 1.76 (or about 1.76), 2.39 (or about 2.39), 2.42 (or about 2.42), 2.53 (or about 2.53), 2.71 (or about 2.71), 2.75 (or about 2.75), 3.26 (or about 3.26), 3.75 (or about 3.75), 4.13 (or about 4.13), 4.64 (or about 4.64), or 4.75 (or about 4.75).

[0158] The ratio of pitch to maximum outer diameter can also be selected to improve relative smoothness. In certain embodiments, the ratio of pitch to the outer diameter of the tube can be in the range of 0.10 (or about 0.10) and 0.35 (or about 0.32), such as 0.11 (or about 0.11), 0.23 (or about 0.23), 0.28 (or about 0.28), 0.29 (or about 0.29), 0.30 (or about 0.30), 0.31 (or about 0.31), or 0.32 (or about 0.32).

[0159] As discussed above, the hollow portion of the first elongate member **203** can be filled with a fluid, that is, a liquid or gas. The first elongate member **203** can be substantially sealed so as to prevent the quantity of fluid escaping. The first elongate member **203** can also be open at one or both ends to allow a continuous flow of liquid or gas.

[0160] The gas can be air, which is desirable because of its low thermal conductivity (2.62×10^{-2} W/m·K at 300K). A gas that is more viscous than air may also be used advantageously, as a higher viscosity reduces heat transfer under conditions of natural convection. Thus, gases such as argon (17.72×10^{-3} W/m·K at 300K), krypton (9.43×10^{-3} W/m·K at 300K), and xenon (5.65×10^{-3} W/m·K at 300K) can increase insulating

performance. Each of these gases is non-toxic, chemically inert, fire-inhibiting, and commercially available. The hollow portion of the first elongated member **203** can be sealed at both ends of the tube, causing the gas within to be substantially stagnant. Alternatively, the hollow portion can be a secondary pneumatic connection, such as a pressure sample line for conveying pressure feedback from the patient-end of the tube to a controller.

[0161] Examples of liquids can include water or other biocompatible liquids with a high thermal capacity. For instance, nanofluids can be used. An example nanofluid with suitable thermal capacity comprises water and nanoparticles of substances such as aluminum.

[0162] In use, the fluid in the hollow portion of the first elongate member **203** can be configured to be used to measure one or more properties of the tube **201**, the first elongate member **203**, the second elongate member **205**, and/or the gas in the tube **201** lumen **207**. In at least one embodiment, the pressure of gas passing along the tube lumen (“lumen gas”) can be measured. A reference measurement of the pressure of the fluid in the hollow portion of the first elongate member **203** (“hollow fluid”) is made before the lumen gas begins to circulate. As the lumen gas begins to pass through the tube **201**, the pressure of the lumen gas will tend to cause a proportional rise in the pressure of the hollow fluid within the first elongate member **203**. By comparing a measurement taken in use with the reference measurement, the pressure of the lumen gas within the tube **201** can be determined. In another embodiment, a hollow fluid is chosen that changes one or more properties based on the operational heat range of the lumen gas within the tube **201**. In this manner, by measuring the property of the hollow fluid, the temperature of the lumen gas can be determined. For example, a hollow fluid which expands with temperature can be used. In use, the temperature of the hollow fluid will tend towards the temperature of the lumen gas flow. By then measuring the pressure of the hollow fluid, the temperature of the lumen gas can be determined. This may have particular benefit when the temperature of the lumen gas flow is difficult or undesirable to measure directly.

[0163] In at least one embodiment, the extrudate used to form the first elongate member **203** further comprises a mineral filler. The extrusion process is described in greater detail below. Talc or hydrous magnesium silicate is suitable mineral filler. In addition to talc, other suitable mineral fillers include calcium carbonate, calcium magnesium carbonate

such as dolomite, barium sulfate, wollastonite, kaolin, and mica, each of which can be added alone or in combination. Suitable mineral fillers can also have particle sizes less than 10 μm (or about 10 μm), or less than 2.5 μm (or about 2.5 μm).

[0164] It was discovered that the addition of mineral filler to the plastic extrudate reduces the stickiness of the resultant first elongate member 203. Stickiness refers to the tactile gumminess or clinginess of the first elongate member 203 material. A stickier material feels gummier than a less sticky material. A stickier material can also tend to cling to more unwanted matter, such as dirt or hair, than a less sticky material. The addition of mineral filler was discovered to reduce the noise the tube makes when it is moved, flexed, and so forth by reducing the extent to which adjacent bubbles stick (and unstick) to each other when bunched (and unbunched) around the vicinity of a bend.

[0165] It was also discovered that the addition of mineral filler to the extrudate can further reduce the noise made when the first elongate member 203 is dragged over an object, such as the edge of a desk or bedside table. The mineral filler may help reflect sound within the surrounding polymer so that the sound does not pass straight through. The improved sound reflection also may give the polymer phase more opportunity to absorb the sound energy, the mineral filler thereby providing intrinsic sound damping. The mineral filler may also reduce the hardness of the plastic extrudate and thereby improve sound damping properties.

[0166] In certain embodiments, the mineral filler is in the range of 1.5 to 10 (or about 1.5 to about 10) weight percent of the total extrudate. In certain embodiments, the mineral filler is in the range of 1.5 to 5 (or about 1.5 to about 5) weight percent of the total extrudate. In certain embodiments, the mineral filler is in the range of 10 (or about 10) weight percent or less of the total extrudate. In certain embodiments, the mineral filler is in the range of 5 (or about 5) weight percent or less of the total extrudate. In certain embodiments, the mineral filler is in the range of 1.5 (or about 1.5) weight percent or more of the total extrudate.

[0167] In FIG. 2F, the first elongate member 203 forms in longitudinal cross-section a plurality of hollow bubbles. In this example, there are a plurality of bubbles, and more specifically, two adjacent wraps of the first elongate member 203, between wraps of the

second elongate member **205**. This configuration is shown in greater detail in FIG. **2G**. As described and shown elsewhere in this disclosure, certain configurations can implement greater than two, for example, three, wraps of the first elongate member **203** between wraps of the second elongate member **205**.

[0168] Embodiments comprising a plurality of adjacent wraps of the first elongate member **203** between wraps of the second elongate member **205** can be advantageous because of improvements in overall tube flexibility. As described below, the substantially solid second elongate member **205** is generally less flexible than the hollow first elongate member **203**. Accordingly, certain embodiments include the realization that overall tube flexibility can be improved by increasing the number of bubbles of first elongate member **203** between wraps of the second elongate member **205**.

[0169] Another advantage of embodiments comprising a plurality of adjacent wraps of the first elongate member **203** between wraps of the second elongate member **205** is improved recovery from crushing. It was observed that, after crushing, samples having multiple bubbles between wraps of the first elongate member **203** recovered their shape more quickly than samples having a single bubble between wraps of the first elongate member **203**.

[0170] Yet another advantage of embodiments comprising a plurality of adjacent wraps of the first elongate member **203** between wraps of the second elongate member **205** is improved resistance to crushing. Crush resistance is a mechanical property that plays an important role in the resilience of the tube while in service. The hospital environment can be harsh, as the tube can be subjected to crushing by a patient's arm or leg, bed frames, and other equipment. Example crush resistance properties are discussed in greater detail below.

[0171] Yet another advantage to the multiple-bubble configuration is that the configuration imparts the ability to hold or transport additional fluids. As explained above, the hollow portion of the first elongate member **203** can be filled with a gas. The multiple discrete bubbles or hollow portions can be filled with multiple discrete gases. For example, one hollow portion can hold or transport a first gas and a second hollow portion can be used as a secondary pneumatic connection, such as a pressure sample line for conveying pressure feedback from the patient-end of the tube to a controller. As another example, multiple discrete bubbles or hollow portions can be filled with a combination of liquids, or a

combination of liquids and gases. A first bubble can hold or transport a gas, and a second bubble can hold or transport a liquid, for instance. Suitable liquids and gases are described above.

[0172] It should be appreciated that, although the configurations in FIGS. 2F and 2G may be preferred in certain embodiments, other configurations, may be utilized in other embodiments as may be desired.

Second Elongate Member

[0173] Referring again to FIGS. 2A and 2B, the second elongate member 205 is also spirally wound and joined to the first elongate member 203 between turns of the first elongate member 203. The second elongate member 205 can form at least a portion of the lumen 207 of the elongate tube. The second elongate member 205 acts as structural support for the first elongate member 203.

[0174] CPAP machines ordinarily weigh in the range of 2 and 4 kg (or about 2 and 4 kg). Thus, the break strength of the composite tube 201 (the horizontal tensile load or force required to cause separation of the first elongate member 203 and the second elongate member 205) desirably is high enough to prevent separation if a user attempts to use the composite tube 201 to lift a CPAP machine connected to the composite tube 201. Thus, the break strength is preferably greater than 20 N (or about 20 N) and, more preferably, greater than 30 N (or about 30 N). In certain embodiments, the break strength is in the range of 75 and 80 N (or about 75 and 80 N). The yield strength (the maximum stress that can be developed without causing plastic deformation) can be in the range of 55 and 65 N (or about 55 and 65 N). In certain embodiments, the composite tube 201 will not stretch (horizontally deflect) more than 0.5 mm (or about 0.5 mm) when a lateral force of 2 N is applied.

[0175] In at least one embodiment, the second elongate member 205 is wider at the base (proximal the lumen 207) and narrower at the top. For example, the second elongate member can be generally triangular in shape, generally T-shaped, or generally Y-shaped. However, any shape that meets the contours of the corresponding first elongate member 203 is suitable.

[0176] Preferably, the second elongate member **205** is flexible, to facilitate bending of the tube. Desirably, the second elongate member **205** is less flexible than the first elongate member **203**. This improves the ability of the second elongate member **205** to structurally support the first elongate member **203**. For example, the modulus of the second elongate member **205** is preferably 30 – 50MPa (or about 30 – 50 MPa). The modulus of the first elongate member **203** is less than the modulus of the second elongate member **205**. The second elongate member **205** can be solid or mostly solid.

[0177] FIG. **6A** shows a longitudinal cross section of a composite tube **201** in a neutral position. FIG. **6A** focuses on one wind or bubble of the first elongate member **203** and two winds of the second elongate member **205**. The first elongate member **203** and second elongate member **205** have a radially-outermost connection point **601**. In this example, the inner portion **211** of the first elongate member **203** is thinner than the outer portion **219** of the first elongate member **203**. Also in this example, the second elongate member **205** has a triangular cross section. The lumen **207** is situated under the base of the first elongate member **203** and second elongate member **205**. FIG. **6B** shows the composite tube **201** of FIG. **6A** in a bent position, in which the composite tube **201** has been bent to a \cap shape (as shown in FIG. **6C**). FIG. **6B** again focuses on one wind or bubble of the first elongate member **203** and two winds of the second elongate member **205**. More specifically, FIG. **6B** focuses on the wind or bubble of the first elongate member **203** at the top of the \cap shape, that is, at the location of maximum bend. The radius of curvature of the composite tube **201** is constrained by the length of the section of the outer portion **219** between adjacent outermost connection points **601**. If the composite tube **201** is bent beyond the minimum radius of curvature, the outer wall forms dimples **605**, as shown in FIG. **6D**.

[0178] A variety of polymers and plastics, including medical grade plastics, are suitable for the body of the second elongate member **205**. Examples of suitable materials include Polyolefin elastomers, Polyether block amides, Thermoplastic co-polyester elastomers, EPDM-Polypropylene mixtures and Thermoplastic polyurethanes. In certain embodiments, the first elongate member **203** and the second elongate member **205** may be made from the same material. The second elongate member **205** may also be made of a different color material from the first elongate member **203**, and may be transparent,

translucent or opaque. For example, in one embodiment the first elongate member **203** may be made from a clear plastic, and the second elongate member **205** may be made from an opaque blue, black, or other color plastic.

[0179] This spirally-wound structure comprising a flexible, hollow body and an integral support can provide crush resistance, while leaving the tube wall flexible enough to permit short-radius bends without kinking, occluding or collapsing. Preferably, the tube can be bent around a 25 mm diameter metal cylinder without kinking, occluding, or collapsing, as defined in the test for increase in flow resistance with bending according to ISO 5367:2000(E).

[0180] This structure also can provide a smooth lumen **207** surface, which helps keep the tube free from deposits and improves gas flow. The hollow body has been found to improve the insulating properties of a tube, while allowing the tube to remain light weight.

[0181] In some embodiments, the second elongate member **205** can be made of a material that wicks water. For example, an absorbent sponge-like material can be used. In such embodiments, the second elongate member **205** can be connected to a water source, such as a water bag. In use, water would be conveyed along at least a portion of the length of the second elongate member **205** (preferably, substantially the whole length). As gas passes along the second elongate member **205**, water vapor will tend to be picked up by the gases in the lumen **207**, thereby humidifying the gas flow.

[0182] In some embodiments, the one or more heating filaments **215** embedded in the second elongate member **205**, as shown in FIG. **2B**, can be controlled to alter the rate of evaporation and thereby alter the level of humidification provided to the gas flow. Although FIG. **2B** specifically shows heating filaments **215**, it should be understood that the second elongate member **205** can encapsulate or house other conductive material(s), such as one or more filaments, and specifically sensors (not shown). Such conductive materials can be disposed in the second elongate member **205** for heating or sensing the gas flow. Heating filaments **215** can minimize the cold surfaces onto which condensate from moisture-laden air can form. Heating filaments **215** can also be used to alter the temperature profile of gases in the lumen **207** of composite tube **201**.

[0183] In the example of FIG. 2B, two heating filaments 215 are encapsulated in the second elongate member 205, one on either side of the vertical portion of the “T.” The heating filaments 215 comprise conductive material, such as alloys of Aluminum (Al) and/or Copper (Cu), or conductive polymer. Preferably, the material forming the second elongate member 205 is selected to be non-reactive with the metal in the heating filaments 215 when the heating filaments 215 reach their operating temperature. The filaments 215 may be spaced away from lumen 207 so that the filaments are not exposed to the lumen 207. At one end of the composite tube, pairs of filaments can be formed into a connecting loop.

[0184] In at least one embodiment, a plurality of filaments are disposed in the second elongate member 205. The filaments can be electrically connected together to share a common rail. For example, a first filament, such as a heating filament, can be disposed on a first side of the second elongate member 205. A second filament, such as a sensing filament, can be disposed on a second side of the second elongate member 205. A third filament, such as a ground filament, can be disposed between the first and second filaments. The first, second, and/or third filaments can be connected together at one end of the second elongate member 205.

[0185] FIG. 2E shows a longitudinal cross-section of a top portion of another composite tube. FIG. 2E has the same orientation as FIG. 2B. In the example of FIG. 2E, the heating filaments 215 are spaced farther apart from each other than the filaments 215 in FIG. 2B. It was discovered that increasing the space between heating filaments can improve heating efficiency, and certain embodiments include this realization. Heating efficiency refers to the ratio of the amount of heat input to the tube to the amount of energy output or recoverable from the tube. Generally speaking, the greater the energy (or heat) that is dissipated to ambient atmosphere from the tube, the lower the heating efficiency. For improved heating performance, the heating filaments 215 can be equally (or about equally) spaced along the bore of the tube. Alternatively, the filaments 215 can be positioned at extremities of the second elongate member 205, which may provide simpler manufacturing.

[0186] Reference is next made to FIGS. 7A through 7G which demonstrate example configurations for the second elongate member 205. FIG. 7A shows a cross-section of a second elongate member 205 having a shape similar to the T-shape shown in FIG. 2B.

In this example embodiment, the second elongate member **205** does not have heating filaments. Other shapes for the second elongate member **205** may also be utilized, including variations of the T-shape as described below and triangular shapes.

[0187] FIG. **7B** shows another example second elongate member **205** having a T-shape cross-section. In this example, heating filaments **215** are embedded in cuts **701** in the second elongate member **205** on either side of the vertical portion of the “T.” In some embodiments, the cuts **701** can be formed in the second elongate member **205** during extrusion. The cuts **701** can alternatively be formed in the second elongate member **205** after extrusion. For example, a cutting tool can form the cuts in the second elongate member **205**. Preferably, the cuts are formed by the heating filaments **215** as they are pressed or pulled (mechanically fixed) into the second elongate member **205** shortly after extrusion, while the second elongate member **205** is relatively soft. Alternatively, one or more heating filaments can be mounted (e.g., adhered, bonded, or partially embedded) on the base of the elongate member, such that the filament(s) are exposed to the tube lumen. In such embodiments, it can be desirable to contain the filament(s) in insulation to reduce the risk of fire when a flammable gas such as oxygen is passed through the tube lumen.

[0188] FIG. **7C** shows yet another example second elongate member **205** in cross-section. The second elongate member **205** has a generally triangular shape. In this example, heating filaments **215** are embedded on opposite sides of the triangle.

[0189] FIG. **7D** shows yet another example second elongate member **205** in cross-section. The second elongate member **205** comprises four grooves **703**. The grooves **703** are indentations or furrows in the cross-sectional profile. In some embodiments, the grooves **703** can facilitate the formation of cuts (not shown) for embedding filaments (not shown). In some embodiments, the grooves **703** facilitate the positioning of filaments (not shown), which are pressed or pulled into, and thereby embedded in, the second elongate member **205**. In this example, the four initiation grooves **703** facilitate placement of up to four filaments, for example, four heating filaments, four sensing filaments, two heating filaments and two sensing filaments, three heating filaments and one sensing filament, or one heating filament and three sensing filaments. In some embodiments, heating filaments can be located on the outside of the second elongate member **205**. Sensing filaments can be located on the inside.

[0190] FIG. 7E shows still another example second elongate member 205 in cross-section. The second elongate member 205 has a T-shape profile and a plurality of grooves 303 for placing heating filaments.

[0191] FIG. 7F shows yet another example second elongate member 205 in cross-section. Four filaments 215 are encapsulated in the second elongate member 205, two on either side of the vertical portion of the "T." As explained in more detail below, the filaments are encapsulated in the second elongate member 205 because the second elongate member 205 was extruded around the filaments. No cuts were formed to embed the heating filaments 215. In this example, the second elongate member 205 also comprises a plurality of grooves 703. Because the heating filaments 215 are encapsulated in the second elongate member 205, the grooves 703 are not used to facilitate formation of cuts for embedding heating filaments. In this example, the grooves 703 can facilitate separation of the embedded heating filaments, which makes stripping of individual cores easier when, for example, terminating the heating filaments.

[0192] FIG. 7G shows yet another example second elongate member 205 in cross-section. The second elongate member 205 has a generally triangular shape. In this example, the shape of the second elongate member 205 is similar to that of FIG. 7C, but four filaments 215 are encapsulated in the second elongate member 205, all of which are central in the bottom third of the second elongate member 205 and disposed along a generally horizontal axis.

[0193] As explained above, it can be desirable to increase the distance between filaments to improve heating efficiency. In some embodiments, however, when heating filaments 215 are incorporated into the composite tube 201, the filaments 215 can be positioned relatively central in the second elongate member 205. A centralized position promotes robustness of the composite tubing for reuse, due in part to the position reducing the likelihood of the filament breaking upon repeating flexing of the composite tube 201. Centralizing the filaments 215 can also reduce the risk of an ignition hazard because the filaments 215 are coated in layers of insulation and removed from the gas path.

[0194] As explained above, some of the examples illustrate suitable placements of filaments 215 in the second elongate member 205. In the foregoing examples comprising

more than one filament **215**, the filaments **215** are generally aligned along a horizontal axis. Alternative configurations are also suitable. For example, two filaments can be aligned along a vertical axis or along a diagonal axis. Four filaments can be aligned along a vertical axis or a diagonal axis. Four filaments can be aligned in a cross-shaped configuration, with one filament disposed at the top of the second elongate member, one filament disposed at the bottom of the second elongate member (near the tube lumen), and two filaments disposed on opposite arms of a “T,” “Y,” or triangle base.

Dimensions

[0195] TABLES 3 and 4 show some example dimensions of medical tubes described herein, as well as some ranges for these dimensions. The dimensions refer to a transverse cross-section of a tube. In these tables, lumen diameter represents the inner diameter of a tube. Pitch represents the distance between two repeating points measured axially along the tube, namely, the distance between the tip of the vertical portions of adjacent “T”s of the second elongate member. Bubble width represents the width (maximum outer diameter) of a bubble. Bubble height represents the height of a bubble from the tube lumen. Bead height represents the maximum height of the second elongate member from the tube lumen (e.g., the height of the vertical portion of the “T”). Bead width represents the maximum width of the second elongate member (e.g., the width of the horizontal portion of the “T”). Bubble thickness represents the thickness of the bubble wall.

Table 3

Feature	Infant		Adult	
	Dimension (mm)	Range (\pm)	Dimension (mm)	Range (\pm)
Lumen diameter	11	1	18	5
Pitch	4.8	1	7.5	2
Bubble width	4.2	1	7	1
Bead width	2.15	1	2.4	1
Bubble height	2.8	1	3.5	0.5
Bead height	0.9	0.5	1.5	0.5
Bubble thickness	0.4	0.35	0.2	0.15

Table 4

Feature	Infant		Adult	
	Dimension (mm)	Range (\pm)	Dimension (mm)	Range (\pm)
Lumen diameter	11	1	18	5
Pitch	4.8	1	7.5	2
Bubble width	4.2	1	7	1
Bead width	2.15	1	3.4	1
Bubble height	2.8	1	4.0	0.5
Bead height	0.9	0.5	1.7	0.5
Bubble thickness	0.4	0.35	0.2	0.15

[0196] In another example embodiment, a medical tube has the approximate dimensions shown in TABLE 5.

Table 5

Feature	Dimension (mm)
Pitch	6.4
Bubble width	5.5
Bubble height	3.2
Bubble thickness on top, farthest from lumen (outer wall thickness)	0.22
Bubble thickness adjacent lumen (inner wall thickness)	0.16

[0197] In another example embodiment, a medical tube has the approximate dimensions shown in TABLE 6.

Table 6

Feature	Dimension (mm)	Range (±)
Lumen diameter	17.2	5.0
Pitch	5.1	3.0
Bubble width	4.0	2.0
Bead width	2.3	+3.0/-2.0
Bubble height	2.7	+5.0/-2.0
Bead height	1.6	1.5
Bubble thickness on top, farthest from lumen (outer wall thickness)	0.24	+0.20/-0.10
Bubble thickness adjacent lumen (inner wall thickness)	0.10	+0.20/-0.05
Outer diameter of tube	22.5	3.0

[0198] Preferably, the low ends of the ranges of TABLE 6 correspond to each other, and the high ends of the ranges of Table 6 correspond to each other.

[0199] The embodiments of TABLES 5 and 6 can be particularly advantageous for obstructive sleep apnea applications.

[0200] TABLES 7, 8, and 9 provide example ratios between the dimensions of tube features for the tubes described in TABLES 3, 4, and 6 respectively.

Table 7

Ratios	Infant	Adult
Lumen diameter : Pitch	2.3 : 1	2.4 : 1
Pitch : Bubble width	1.1 : 1	1.1 : 1
Pitch : Bead width	2.2 : 1	3.1 : 1
Bubble width : Bead width	2.0 : 1	2.9 : 1
Lumen diameter : Bubble height	3.9 : 1	5.1 : 1
Lumen diameter : Bead height	12.2 : 1	12.0 : 1
Bubble height : Bead height	3.1 : 1	2.3 : 1
Lumen diameter : Bubble thickness	27.5 : 1	90.0 : 1

Table 8

Ratios	Infant	Adult
Lumen diameter : Pitch	2.3 : 1	2.4 : 1
Pitch : Bubble width	1.1 : 1	1.1 : 1
Pitch : Bead width	2.2 : 1	2.2 : 1
Bubble width : Bead width	2.0 : 1	2.1 : 1
Lumen diameter : Bubble height	3.9 : 1	4.5 : 1
Lumen diameter : Bead height	12.2 : 1	10.6 : 1
Bubble height : Bead height	3.1 : 1	2.4 : 1
Lumen diameter : Bubble thickness	27.5 : 1	90.0 : 1

Table 9

Ratios	Value
Lumen diameter : Pitch	3.4 : 1
Pitch : Bubble width	0.93 : 1
Pitch : Bead width	2.2 : 1
Bubble width : Bead width	1.7 : 1
Lumen diameter : Bubble height	5.4 : 1
Lumen diameter : Bead height	10.8 : 1
Bubble height : Bead height	1.7 : 1
Lumen diameter : Bubble thickness on top, farthest from lumen	71.7 : 1
Lumen diameter : Bubble thickness adjacent lumen	172 : 1

Variable Pitch and/or Variable Diameter

[0201] The foregoing description discloses various constant pitch and constant diameter configurations. Certain embodiments can incorporate variable pitch and/or variable diameter, however.

[0202] A variable pitch can be desirable because it can better allow heat delivered to the gas flow to be varied along the length of the tube. The ability to control where the heat is delivered in a tube can be used to control or reduce rainout within the tube. For example, an end-of-tube temperature set point may be achieved for a given condition, yet be insufficient to prevent rainout within the tube, particularly at or near to the inlet of the tube where the gas temperature may be close to the dew point temperature (high relative

humidity). Certain embodiments include the realization that redistributing the heat source to concentrate it near the entrance of the tube can help to ensure a greater axial concentration of heat in this region, $Q(z)$ [W/m], where z is the axial displacement of the tube, beginning at the unit end.

[0203] FIG. 8A shows an example composite tube 201 with variable pitch. In this example, the tube 201 has a smaller pitch proximal the unit end 801. Thus, the heating filaments 215 in this region will be more densely spaced, enabling greater heating at that part of the tube 201 as well as greater and more accurate temperature control. The tube 201 has a larger pitch at the patient end 803. The greater spacing between heating filaments 215 can allow the gases to decrease in temperature as they approach the patient. This can prevent the patient from receiving gases that are too hot and can reduce rainout formation. FIG. 8B shows the temperature profile of the composite tube of FIG. 8A. Other temperature profiles are also possible and can be customized to achieve specific desired effects.

[0204] The geometry of the tube 201 also affects the mechanical properties of the tube. By increasing the size of the bubble of the first elongate member, the flexibility of the tube 201 will be increase. Conversely, a smaller bubble size will produce a more rigid region of the tube 201. By altering flexibility and rigidity, the mechanical properties of the tube 201 can be customized. By varying the diameter of the tube 201, it is possible to have a smaller diameter near a patient interface which will increase patient comfort, improve the aesthetics, and reduce the invasiveness of the interface.

Additional Properties

[0205] TABLES 10–13 show some example properties of a composite tube (labeled “A”), described herein, having a heating filament integrated inside the second elongate member. For comparison, properties of a Fisher & Paykel model RT100 disposable corrugated tube (labeled “B”) having a heating filament helically wound inside the bore of the tube are also presented.

[0206] Measurement of resistance to flow (RTF) was carried out according to Annex A of ISO 5367:2000(E). The results are summarized in TABLE 10. As seen below, the RTF for the composite tube is lower than the RTF for the model RT100 tube.

Table 10

Flow rate (L/min)	RTF (cm H ₂ O)			
	3	20	40	60
A	0	0.05	0.18	0.38
B	0	0.28	0.93	1.99

[0207] Condensate or “rainout” within the tube refers to the weight of condensate collected per day at 20 L/min gas flow rate and room temperature of 18°C. Humidified air is flowed through the tube continuously from a chamber. The tube weights are recorded before and after each day of testing. Three consecutive tests are carried out with the tube being dried in between each test. The results are shown below in TABLE 11. The results showed that rainout is significantly lower in the composite tube than in the model RT100 tube.

Table 11

Tube	A (Day 1)	A (Day 2)	A (Day 3)	B (Day 1)	B (Day 2)	B (day 3)
Weight before (g)	136.20	136.70	136.70	111.00	111.10	111.10
Weight after (g)	139.90	140.00	139.20	190.20	178.80	167.10
Condensate weight (g)	3.7	3.3	2.5	79.20	67.70	56.00

[0208] The power requirement refers to the power consumed during the condensate test. In this test, the ambient air was held at 18°C. Humidification chambers (*see, e.g.*, the humidification chamber 129 in FIG. 1) were powered by MR850 heater bases. The heating filaments in the tubes were powered independently from a DC power supply. Different flow rates were set and the chamber was left to settle to 37°C at the chamber output. Then, the DC voltage to the circuits was altered to produce a temperature of 40°C at the circuit output. The voltage required to maintain the output temperature was recorded and the resulting power calculated. The results are shown in TABLE 12. The results show that composite Tube A uses significantly more power than Tube B. This is because Tube B uses a

helical heating filament in the tube bore to heat the gas from 37°C to 40°C. The composite tube does not tend to heat gas as quickly because the heating filament is in the wall of the tube (embedded in the second elongate member). Instead, the composite tube is designed to maintain the gas temperature and prevent rainout by maintaining the tube bore at a temperature above the dew point of the humidified gas.

Table 12

Flow rate (L/min)	40	30	20
Tube A, power required (W)	46.8	38.5	37.8
Tube B, power required (W)	28.0	27.5	26.8

[0209] Vertical deflection can be used to quantify flexibility of a composite tube. Vertical deflection can be tested, for example, using a three-point bend test. A first 300 mm-length sample of Tube A and a second 300 mm-length sample of Tube B were each tested on a flexibility jig. A front-plan cross-sectional schematic of the flexibility jig is shown in FIG. 9A. The jig 901 used a 25-mm rod 903 with a fixed mass of 120 g to apply a force to each tube 201, which was positioned between two rollers 905 and 907. The rollers were spaced 150 mm apart. The force exerted by the rod 903 was about 1.2 N ($0.12 \text{ kg} \times 9.81 \text{ m/s}^2$). A detailed front-plan cross-sectional schematic of rollers 905 and 907 is shown in FIG. 9B. Both rollers 905 and 907 had the same dimensions, which are shown in FIG. 9B. An Instron 5560 Test System instrument was used to measure load and extension. Each tube sample was tested three times; measuring the extension of the tube against the applied load, to obtain average respective stiffness constants. The average stiffness constants for Tube A and Tube B are reproduced in TABLE 13.

Table 13

Tube	Stiffness (N/mm)
A	0.028
B	0.088

[0210] Tube weight can be very important, particularly for CPAP applications. If a patient experiences less weight near the patient's face, the patient will be more comfortable during sleep. A lighter composite tube 201 will not pull the patient's head in a particular direction as much as a heavier tube. To ensure patient comfort, it is possible to specify that the total mass or weight in a region near the patient end of the composite tube 201 must be less than a specified value. In certain embodiments, the tube mass in the 300 mm nearest the patient end is less than 24 g (or about 24 g). Desirably, the tube mass in the 300 mm nearest the patient end is less than 16 g (or about 16 g). In certain embodiments, the tube mass in the 300 mm nearest the patient end is less than 15 g (or about 15 g). It is also possible to specify that the total mass of the composite tube be less than a specified value. In certain embodiments, the tube mass is less than 130 g (or about 130 g). Desirably, the tube mass is less than 120 g (or about 120 g). In certain embodiments, the tube mass is less than 100 g (or about 100 g).

[0211] The following discussion now describes additional properties relating to a composite tube 201 with two bubbles between wraps of the second elongate member 205, as discussed above.

[0212] A first 300 mm-length sample of tube comprising two bubbles between wraps of the second elongate member 205 and a second 300 mm-length sample of tube comprising one bubble between wraps of the second elongate member 205 were each tested on the flexibility jig 901 discussed above. The vertical deflection was measured using the position of the fixed weight with respect to a vertical support 909 of the flexibility jig, shown in the photographs of FIGS. 9C through 9F.

[0213] FIG. 9C shows a front-perspective view of the second sample under testing in the jig 901. FIG. 9D shows a rear-perspective view of the second sample under testing in the jig 901. FIG. 9E shows a front-perspective view of the first sample under testing in the jig 901. FIG. 9F shows a rear-perspective view of the first sample under testing in the jig 901. As shown in FIGS. 9C through 9F, the second sample shown in FIGS. 9E and 9F had substantially greater vertical deflection than the first sample shown in FIGS. 9C and 9D. Specifically, the second sample had a vertical deflection of 3 mm, while the first sample was much more flexible, having a vertical deflection of 42 mm.

[0214] Crush resistance testing was performed on four tube samples using an Instron machine set up as shown in the photograph in FIG. 10A. The cylinder 1001 was plunged downwards 16 mm from the top of the tube at a rate of 60 mm/min. The Instron machine has a load cell to accurately measure force exerted on a component versus extension. The load vs. extension was plotted, as shown in FIG. 10B.

[0215] The crush stiffness for each sample was found by fitting a line of best fit to the data of FIG. 10B and calculating its gradient. The calculated crush stiffness for each sample is shown in TABLE 14A. In TABLE 14A (and elsewhere in this disclosure), the designation “double bubble” refers to a sample of tube comprising two bubbles between wraps of the second elongate member 205, when the sample is viewed in longitudinal cross section. The designation “single bubble” refers to a sample of tube comprising a single bubble between wraps of the second elongate member 205, when the sample is viewed in longitudinal cross section. The average crush stiffness (measured in N/mm) represents the average maximum force per unit width which produces no crush.

Table 14A

Sample	Crush Stiffness (N/mm)	Average
Double Bubble, Sample 1	3.26	3.21
Double Bubble, Sample 2	3.15	
Single Bubble, Sample 1	3.98	3.86
Single Bubble, Sample 2	3.74	

[0216] As shown in the foregoing table, single bubble tubes had an average crush stiffness of 3.86 N/mm, while double bubble tubes had an average crush stiffness of 3.21 N/mm. In other words, the double bubble tubes had an approximately 16.8% lower resistance to crush than the single bubble tubes. Nevertheless, crush stiffness per unit thickness for the double bubble tubes was observed to be approximately 165% of the value for the single bubble tubes, as shown below in TABLE 14B.

Table 14B

	Bubble Thickness (mm)	Crush Stiffness (N/mm)	Stiffness/Bubble Thickness (N/mm ²)
Double Bubble	0.22	3.21	14.32
Single Bubble	0.43	3.86	8.70

[0217] Stated another way, when outer bubble thickness is taken into account, the double bubble tube is around 65% more resistant to crush than the single bubble tube variant. Similar to the bubbles shown in FIGS. 2F and 2G, the tested bubbles in the double bubble configuration are taller than they are wide, which results in more material in the vertical plane. Thus, it is believed that the unexpected improvement in crush resistance per unit thickness of the bubble may be attributed to the additional vertical web between beads working in the direction of crush.

[0218] Tensile testing was also performed on the single and double bubble tube samples. Both samples were 230 mm in length and were elongated by 15 mm at a rate of 10 mm/min. The force required to elongate the samples was measured. The results are shown in TABLE 14C.

Table 14C

Sample	Peak Force at 15mm extension (N)
Double Bubble	17.60
Single Bubble	54.65

[0219] As shown in TABLE 14C, the double bubble tube was significantly more extensible in the axial (longitudinal) plane. This increase in longitudinal extensibility is believed to be due to the single bubble tube having more material between the beads working in the axial plane.

Thermal Properties

[0220] In embodiments of a composite tube **201** incorporating a heating filament **215**, heat can be lost through the walls of the first elongate member **203**, resulting in uneven heating. As explained above, one way to compensate for these heat losses is to apply an external heating source at the first elongate member **203** walls, which helps to regulate the temperature and counter the heat loss. Other methods for optimizing thermal properties can also be used, however.

[0221] Reference is again made to FIGS. **5A** through **5C**, which demonstrate example configurations for bubble height (that is, the cross-sectional height of the first elongate member **203** measured from the surface facing the inner lumen to the surface forming the maximum outer diameter) to improve thermal properties.

[0222] The dimensions of the bubble can be selected to reduce heat loss from the composite tube **201**. Generally, increasing the height of the bubble increases the effective thermal resistance of the tube **201**, because a larger bubble height permits the first elongate member **203** to hold more insulating air. However, it was discovered that, at a certain bubble height, changes in air density cause convection inside the tube **201**, thereby increasing heat loss. Also, at a certain bubble height the surface area becomes so large that the heat lost through surface outweighs the benefits of the increased height of the bubble. Certain embodiments include these realizations.

[0223] The radius of curvature and the curvature of the bubble can be useful for determining a desirable bubble height. The curvature of an object is defined as the inverse of the radius of curvature of that object. Therefore, the larger a radius of curvature an object has, the less curved the object is. For example, a flat surface would have a radius of curvature of ∞ and therefore a curvature of 0.

[0224] FIG. **5A** shows a longitudinal cross-section of a top portion of a composite tube. FIG. **5A** shows an embodiment of a composite tube **201** where the bubble has a large height. In this example, the bubble has a relatively small radius of curvature and therefore a large curvature. Also, the bubble is approximately three to four times greater in height than the height of the second elongate member **205**.

[0225] FIG. 5B shows a longitudinal cross-section of a top portion of another composite tube. FIG. 5B shows an embodiment of a composite tube 201 where the bubble is flattened on top. In this example, the bubble has a very large radius of curvature but a small curvature. Also, the bubble is approximately the same height as the second elongate member 205.

[0226] FIG. 5C shows a longitudinal cross-section of a top portion of another composite tube. FIG. 5C shows an embodiment of a composite tube 201 where the width of the bubble is greater than the height of the bubble. In this example, the bubble has radius of curvature and the curvature between that of FIG. 5A and FIG. 5B, and the center of the radius for the upper portion of the bubble is outside of the bubble (as compared to FIG. 5A). The inflection points on the left and right sides of the bubble are about at the middle (heightwise) of the bubble (as opposed to in the lower portion of the bubble, as in FIG. 5A). Also, the height of the bubble is approximately double that of the second elongate member 205, resulting in a bubble height between that of FIG. 5A and FIG. 5B.

[0227] The configuration of FIG. 5A resulted in the lowest heat loss from the tube. The configuration of FIG. 5B resulted in the highest heat loss from the tube. The configuration of FIG. 5C had intermediate heat loss between the configurations of FIG. 5A and 5B. However, the large external surface area and convective heat transfer in the configuration of FIG. 5A led to inefficient heating. Thus, of the three bubble arrangements of FIGS. 5A–5C, FIG. 5C was determined to have the best overall thermal properties. The practical implication of this thermal efficiency is that, when the same thermal energy was input to the three tubes, the configuration of FIG. 5C allowed for the largest temperature rise along the length of the tube. The bubble of FIG. 5C is sufficiently large to increase the insulating air volume, but not large enough to cause a significant convective heat loss. The configuration of FIG. 5B was determined to have the poorest thermal properties, namely that the configuration of FIG. 5B allowed for the smallest temperature rise along the length of the tube. The configuration of FIG. 5A had intermediate thermal properties and allowed for a lower temperature rise than the configuration of FIG. 5C.

[0228] It should be appreciated that although the FIG. 5C configuration may be preferred in certain embodiments, other configurations, including those of FIGS. 5A, 5B and other variations, may be utilized in other embodiments as may be desired.

[0229] TABLE 15 shows the height of the bubble, the outer diameter of the tube, and the radius of curvature of the configurations shown in each of FIGS. 5A, 5B, and 5C.

Table 15

Tube (Fig.)	5A	5B	5C
Bubble height (mm)	3.5	5.25	1.75
Outer diameter (mm)	21.5	23.25	19.75
Radius of curvature (mm)	5.4	3.3	24.3

[0230] TABLE 16A shows the height of the bubble, the outer diameter, and the radius of curvature of further configurations as shown in FIGS. 11A, 11B, and 11C.

Table 8A

Tube (Fig.)	10A	10B	10C
Bubble height (mm)	6.6	8.4	9.3
Outer diameter (mm)	24.6	26.4	27.3
Radius of curvature (mm)	10	8.7	5.7

[0231] It should be noted that, in general, the smaller the radius of curvature, the tighter the tube can be bent around itself without the bubble collapsing or “kinking.” For example, FIG. 11D shows a tube that has been bent beyond its radius of curvature (specifically, it shows the tube of FIG 11A bent around a radius of curvature of 5.7 mm), thereby causing kinking in the walls of the bubble. Kinking is generally undesirable, as it can detract from the appearance of the tube, and can impair the thermal properties of the tube.

[0232] Accordingly, in some applications, the configurations with increased bending properties (such as those shown in FIGS. 5A or 5B) can be desirable despite having less efficient thermal properties. In some applications, it has been found that a tube with an outer diameter of 25 mm to 26 mm (or about 25 mm to about 25 mm) provides satisfactory performance. It should be appreciated that although the configurations of FIGS. 5A and 5B

may be preferred in certain embodiments, other configurations, including those of FIGS. 11A–11D and other variations, may be utilized in other embodiments as may be desired.

[0233] Reference is again made to FIGS. 5C through 5F which demonstrate example positioning of heating element 215 with similar bubble shapes to improve thermal properties. The location of the heating element 215 can change the thermal properties within the composite tube 201.

[0234] FIG. 5C shows a longitudinal cross-section of a top portion of another composite tube. FIG. 5C shows an embodiment of a composite tube 201 where the heating elements 215 are centrally located in the second elongate member 205. This example shows the heating elements 215 close to one another and not close to the bubble wall.

[0235] FIG. 5D shows a longitudinal cross-section of a top portion of another composite tube. FIG. 5D shows an embodiment of a composite tube 201 in which the heating elements 215 are spaced farther apart, as compared to FIG. 5C, in the second elongate member 205. These heating elements are closer to the bubble wall and provide for better regulation of heat within the composite tube 201.

[0236] FIG. 5E shows a longitudinal cross-section of a top portion of another composite tube. FIG. 5E shows an embodiment of a composite tube 201 wherein the heating elements 215 are spaced on top of each other in the vertical axis of the second elongate member 205. In this example, the heating elements 215 are equally close to each bubble wall.

[0237] FIG. 5F shows a longitudinal cross-section of a top portion of another composite tube. FIG. 5F shows an embodiment of a composite tube 201 where the heating elements 215 are spaced at opposite ends of the second elongate member 205. The heating elements 215 are close to the bubble wall, especially as compared to FIGS. 5C–5E.

[0238] Of the four filament arrangements of FIGS. 5C–5F, FIG. 5F was determined to have the best thermal properties. Because of their similar bubble shapes, all of the configurations experienced similar heat loss from the tube. However, when the same thermal energy was input to the tubes, the filament configuration of FIG. 5F allowed for the largest temperature rise along the length of the tube, for the bulk gas temperature within the tube. The configuration of FIG. 5D was determined to have the next best thermal properties

and allowed for the next largest temperature rise along the length of tube. The configuration of FIG. 5C performed next best. The configuration of FIG. 5E had the poorest performance and allowed for the smallest temperature rise along the length of the tube, when the same amount of heat was input.

[0239] It should be appreciated that although the FIG. 5F configuration may be preferred in certain embodiments, other configurations, including those of FIGS. 5C, 5D, 5E, and other variations, may be utilized in other embodiments as may be desired.

[0240] Reference is next made to FIGS. 12A through 12C, which demonstrate example configurations for stacking of the first elongate member 203. It was discovered that heat distribution can be improved in certain embodiments by stacking multiple bubbles. These embodiments can be more beneficial when using an internal heating filament 215. FIG. 12A shows a longitudinal cross-section of a top portion of another composite tube. FIG. 12A shows a cross section of a composite tube 201 without any stacking.

[0241] FIG. 12B shows a longitudinal cross-section of a top portion of another composite tube. FIG. 12B shows another example composite tube 201 with stacked bubbles. In this example, two bubbles are stacked on top of each other to form the first elongate member 203. As compared to FIG. 12A, the total bubble height is maintained, but the bubble pitch is half of FIG. 12A. Also, the embodiment in FIG. 12B has only a slight reduction in air volume. The stacking of the bubbles reduces natural convection and heat transfer in the gap between bubbles 213 and lowers the overall thermal resistance. The heat flow path increases in the stacked bubbles allowing heat to more easily distribute through the composite tube 201.

[0242] FIG. 12C shows a longitudinal cross-section of a top portion of another composite tube. FIG. 12C shows another example of a composite tube 201 with stacked bubbles. In this example, three bubbles are stacked on top of each other to form the first elongate member 203. As compared to FIG. 12A, the total bubble height is maintained, but the bubble pitch is a third of FIG. 12A. Also, the embodiment in FIG. 12B has only a slight reduction in air volume. The stacking of the bubbles reduces natural convection and heat transfer in the gap between bubbles 213.

[0243] Referring now to FIG. 13, additional possible properties of the second elongate member 205 are shown. The second elongate member 205 comprises one or more coaxial cables 1301 having a conductor 1303 surrounded by an insulation layer 1305, a shield layer 1307, and a sheath layer 1309. In certain embodiments, one or more of cables 1301 can be a multi-axial cable, that is, have multiple conductors 1303 arranged within the insulation layer 1305. In this manner, a single assembly containing multiple wires (including heater wires and/or sensor wires) can be used in the second elongate member 205, thereby simplifying assembly and providing some shielding (via the shield layer 1307) from RF interference and the like.

[0244] In some embodiments, one or more data transmission cables can be included in the second elongate member 205. The data transmission cables can comprise fiber optic cables. In at least one embodiment, a single fiber optic cable is included in the second elongate member 205 and used in a passive mode. In a passive mode, at a first end of the cable, a light source and a light sensor are provided. At a second end, a reflector is provided. In use, the light source provides a quantity of light having certain properties towards the reflector. The reflector then reflects the light towards the light sensor, which can analyze the reflected light to determine the properties of the light. The reflector can be adapted to change the property of the reflected light depending on a property of the system. For example, the reflector can be used to monitor condensation within the interface. The reflector can comprise a material which, for example, changes color depending on the presence of condensation at the second end. The reflector can alternatively or additionally include a material which changes color or the like depending on the level of humidity (either relative humidity or absolute humidity), and/or the temperature of gas at the second end, and/or gas composition such as inhaled O₂ or exhaled CO₂.

[0245] Referring again to FIG. 2B, in some embodiments, a fluid (gas or liquid) flow can be passed along the space inside the first elongate member 203. In such embodiments, it is desirable that at least a portion of the first elongate member 203 is formed of a breathable material. Breathable is used herein to mean appreciably permeable to water vapor and substantially impermeable to liquid water and the bulk flow of gases. Suitable breathable materials include an activated perfluorinated polymer material with extreme

hydrophilic properties, such as NAFION®, or a hydrophilic polyester block copolymer, such as SYMPATEX®. Other suitable materials include polymers commercially embodied in EVAQUA™ and EVAQUA 2™ conduits (Fisher & Paykel Healthcare Ltd., Auckland, New Zealand). Suitable materials are further described in PCT Publication WO 2011/077250, filed Dec. 22, 2010 and published June 30, 2011, and U.S. Patent No. 6,769,431, filed May 8, 2001 and issued Aug. 3, 2003.

[0246] The flow through the first elongate member 203 can be useful for drying or humidifying the gas flow through the tube 201 lumen 207, as desired. Conversely, the flow through the tube 201 lumen 207 can be useful for drying or humidifying the gas flow through the first elongate member 203, as desired. Exhaled respiratory gases can be carried through the first elongate member 203. As another example, a liquid such as liquid water can be carried. As yet another example, a humidified or saturated gas stream can be carried. As yet another example, a dry gas stream or a stream of compressed ambient air can be carried. In the foregoing embodiments, the first elongate member 203 can be open on both ends, to facilitate the flow of fluid through the first elongate member 203. One end of the first elongate member 203 can be connected to a suitable source, such as a source of exhaled respiratory gas, liquid water, humidified gas, dry gas, or compressed air, as desired. The other end can be connected to a suitable outlet or allowed to vent to the atmosphere.

[0247] For example, with reference to FIG. 2B, the portion 211 of the first elongate member 203 that forms the lumen 207 of the tube 201 can be formed of the breathable material, as described above. The outward-facing portion 219 (facing the ambient atmosphere and facing away from the lumen) of the first elongate member 203 can be formed of an impermeable material, that is, a material that is not appreciably permeable to water vapor, liquid water, or the bulk flow of gases, as described elsewhere in this disclosure. In use, a quantity of humidification fluid (such as water) can be passed through the space formed by the first elongate member 203. As the humidification fluid is heated (for example, by the heating filaments 215 disposed in the second elongate member 205), a portion of the humidification fluid will tend to evaporate. The water vapor can then pass through the breathable portion 211 into the bulk gas flow through the lumen 207, thereby humidifying the bulk gas flow. In such an embodiment, the combination of the humidification fluid, first

elongate member **203**, and heating filaments **215** can provide a means for humidifying the gas flow within the lumen **207** such that a standalone humidifier can be omitted from the system.

[0248] As another example, a gas flow can be passed along the space inside the first elongate member **203**. For example, exhaled respiratory gases can be carried. Referring again to FIG. **2B**, the first elongate member **203** or at least the outward-facing portion **219** of the first elongate member **203** is made of a breathable material, as described above. In this manner, as the exhaled gas travels along the length of the first elongate member **203**, it will tend to dry from about 100% relative humidity at the patient-end to reduced humidity level at the opposite end.

[0249] Co-extrusion is a suitable method for forming a first elongate member **203** comprising a portion (**211** or **219**, depending on the desired application) formed of a breathable material and a portion (**219** or **211**, depending on the desired application) formed of an impermeable material.

[0250] In addition, although certain foregoing embodiments have been described with reference to a single first elongate member **203** comprising breathable and impermeable portions, it should be appreciated that desired results (such as humidification of the gas flow within the lumen **207**) also can be achieved using a plurality of first elongate members **203**. Suitable embodiments are shown in FIGS. **12B**, **12C**, **37A** and **37B**.

[0251] FIG. **37A** shows a cross section of tube comprising two first elongate members. A first first-elongate-member **203a** is disposed proximal the tube lumen **207**. A second first-elongate-member **203b** faces the ambient atmosphere and faces away from the lumen **207**. The inner portion of the first first-elongate-member **203a** forms the lumen **207** wall. The first first-elongate-member **203a** can define a conduit for a humidification fluid, such as liquid water. The first first-elongate-member **203a** can be formed from a breathable material. As the humidification fluid is heated (for example, by the heating filaments **215** disposed in the second elongate member **205**), a portion of the humidification fluid will tend to evaporate. The vapor can then pass through the walls of the first first-elongate-member **203a** into the bulk gas flow through the lumen **207**, thereby humidifying the bulk gas flow. In such an embodiment, the combination of the humidification fluid, first first-elongate-member

203a, and heating filaments **215** can provide a means for humidifying the gas flow within the lumen **207** such that a standalone humidifier can be omitted from the system. It should be appreciated that the dimensions shown in FIG. **37A** are not necessarily to scale. For example, the first first-elongate-member **203a** can be relatively larger, and the second first-elongate-member **203b** can be relatively smaller as shown in FIG. **12B**. It should also be appreciated that the heating filaments **215** need not necessarily be housed in the second elongate member **205**. For example, as shown in FIG. **12B**, the second elongate member can be omitted. The heating filaments **215** can be housed, for instance, in a portion of the second first-elongate-member **203b** proximal the first first-elongate-member **203a**.

[0252] FIG. **37B** also shows a cross section of tube comprising two first elongate members. A first first-elongate-member **203a** is disposed proximal the tube lumen **207**. A second first-elongate-member **203b** faces the ambient atmosphere and faces away from the lumen **207**. The inner portion of the first first-elongate-member **203a** forms part of the lumen **207** wall. An inner portion of the second first-elongate-member **203b** also forms part of the lumen **207** wall. As discussed above with reference to FIG. **37A**, the first first-elongate-member **203a** can define a conduit for a humidification fluid, such as liquid water, and the combination of the humidification fluid, first first-elongate-member **203**, and heating filaments **215** can provide a means for humidifying the gas flow within the lumen **207** such that a standalone humidifier can be omitted from the system. Again, it should be appreciated that the dimensions shown in FIG. **37B** are not necessarily to scale. For example, the first first-elongate-member **203a** can be relatively larger, and the second first-elongate-member **203b** can be relatively smaller as shown in FIG. **12B**. It should also be appreciated that the heating filament need not necessarily be housed in the second elongate member. For example, as shown in FIG. **12B**, the second elongate member can be omitted. The heating filament can be housed, for instance, in a portion of the second first-elongate-member **203b** proximal the first first-elongate-member **203a**. [0235] Referring now to FIGS. **14A–14E** and **15A–15E**, some variations of the composite tube **201** configuration are shown which are adapted to provide increased lateral stretch in the composite tube **201**. FIGS. **15A–15E** show a stretched state of the composite tubes shown in FIGS. **14A–14E**, respectively.

[0253] Certain embodiments include the realization that the tubes shown in FIGS. 14A, 14B, and 14E comprise a second elongate member 205 having a shape that increases stretch capability. For example, in FIG. 14A, the second elongate member 205 is substantially oblate having a profile substantially the same height as the first elongate member 203. As shown in FIG. 15A, this allows the second elongate member 205 to deform outwards to at least twice the width compared to the second elongate member 205 at rest. In FIG. 14B and 14E, the second elongate member 205 is shaped so as to have an accordion-like shape. On stretching, the second elongate member 205 can therefore accommodate an increase amount of stretching by flattening (as shown in FIGS. 15B and 15E, respectively).

[0254] In FIGS. 14C and 14D, the first elongate member 203 is given a shape that allows it to deform outward, thereby allowing an increased lateral stretch (as shown in FIGS. 15C and 15D, respectively).

Medical Circuits

[0255] Reference is next made to FIG. 16, which shows an example medical circuit according to at least one embodiment. The circuit comprises one or more composite tubes as described above, namely for the inspiratory tube 103 and/or the expiratory tube 117. The properties of the inspiratory tube 103 and the expiratory tube 117 are similar to the tubes described above with respect to FIG. 1. The inspiratory tube 103 has an inlet 109, communicating with a humidifier 107, and an outlet 113, through which humidified gases are provided to the patient 101. The expiratory tube 117 also has an inlet 109, which receives exhaled humidified gases from the patient, and an outlet 113. As described above with respect to FIG. 1, the outlet 113 of the expiratory tube 117 can vent exhaled gases to the atmosphere, to the ventilator/blower unit 105, to an air scrubber/filter (not shown), or to any other suitable location.

[0256] As described above, heating filaments 215 can be placed within the inspiratory tube 103 and/or the expiratory tube 117 to reduce the risk of rain out in the tubes by maintaining the tube wall temperature above the dew point temperature.

Component of an Insufflation System

[0257] Laparoscopic surgery, also called minimally invasive surgery (MIS), or keyhole surgery, is a modern surgical technique in which operations in the abdomen are performed through small incisions (usually 0.5 to 1.5 cm) as compared to larger incisions needed in traditional surgical procedures. Laparoscopic surgery includes operations within the abdominal or pelvic cavities. During laparoscopic surgery with insufflation, it may be desirable for the insufflation gas (commonly CO₂) to be humidified before being passed into the abdominal cavity. This can help prevent “drying out” of the patient’s internal organs, and can decrease the amount of time needed for recovery from surgery. Insufflation systems generally comprise humidifier chambers that hold a quantity of water within them. The humidifier generally includes a heater plate that heats the water to create a water vapour that is transmitted into the incoming gases to humidify the gases. The gases are transported out of the humidifier with the water vapor.

[0258] Reference is next made to FIG. 17, which shows an insufflation system 1701, according to at least one embodiment. The insufflation system 1701 includes an insufflator 1703 that produces a stream of insufflation gases at a pressure above atmospheric for delivery into the patient 1705 abdominal or peritoneal cavity. The gases pass into a humidifier 1707, including a heater base 1709 and humidifier chamber 1711, with the chamber 1711 in use in contact with the heater base 1709 so that the heater base 1709 provides heat to the chamber 1711. In the humidifier 1707, the insufflation gases are passed through the chamber 1711 so that they become humidified to an appropriate level of moisture.

[0259] The system 1701 includes a delivery conduit 1713 that connects between the humidifier chamber 1711 and the patient 1705 peritoneal cavity or surgical site. The conduit 1713 has a first end and second end, the first end being connected to the outlet of the humidifier chamber 1711 and receiving humidified gases from the chamber 1711. The second end of the conduit 1713 is placed in the patient 1705 surgical site or peritoneal cavity and humidified insufflation gases travel from the chamber 1711, through the conduit 1713 and into the surgical site to insufflate and expand the surgical site or peritoneal cavity. The system also includes a controller (not shown) that regulates the amount of humidity supplied

to the gases by controlling the power supplied to the heater base 1709. The controller can also be used to monitor water in the humidifier chamber 1711. A smoke evacuation system 1715 is shown leading out of the body cavity of the patient 1705.

[0260] The smoke evacuation system 1715 can be used in conjunction with the insufflation system 1701 described above or may be used with other suitable insufflation systems. The smoke evacuation system 1715 comprises a discharge or exhaust limb 1717, a discharge assembly 1719, and a filter 1721. The discharge limb 1717 connects between the filter 1721 and the discharge assembly 1719, which in use is located in or adjacent to the patient 1705 surgical site or peritoneal cavity. The discharge limb 1717 is a self-supporting tube (that is, the tube is capable of supporting its own weight without collapsing) with two open ends: an operative site end and an outlet end.

[0261] At least one embodiment includes the realization that the use of a composite tube as the conduit 1713 can deliver humidified gases to the patient 1705 surgical site with minimized heat loss from the humidified gases.

Coaxial Tube

[0262] A coaxial breathing tube can also comprise a composite tube as described above. In a coaxial breathing tube, a first gas space is an inspiratory limb or an expiratory limb, and the second gas space is the other of the inspiratory limb or expiratory limb. One gas passageway is provided between the inlet of said inspiratory limb and the outlet of said inspiratory limb, and one gas passageway is provided between the inlet of said expiratory limb and the outlet of said expiratory limb. In one embodiment, the first gas space is said inspiratory limb, and the second gas space is said expiratory limb. Alternatively, the first gas space can be the expiratory limb, and the second gas space can be the inspiratory limb.

[0263] Reference is next made to FIG. 18, which shows a coaxial tube 1801 according to at least one embodiment. In this example, the coaxial tube 1801 is provided between a patient 1801 and a ventilator 1805. Expiratory gases and inspiratory gases each flow in one of the inner tube 1807 or the space 1809 between the inner tube 1807 and the outer tube 1811. It will be appreciated that the outer tube 1811 may not be exactly aligned with the inner tube 1807. Rather, “coaxial” refers to a tube situated inside another tube.

[0264] For heat transfer reasons, the inner tube 1807 can carry the inspiratory gases in the space 1813 therewithin, while the expiratory gases are carried in the space 1809 between the inner tube 1807 and the outer tube 1811. This airflow configuration is indicated by arrows. However, a reverse configuration is also possible, in which the outer tube 1811 carries inspiratory gases and the inner tube 1807 carries expiratory gases.

[0265] In at least one embodiment, the inner tube 1807 is formed from a corrugated tube, such as a Fisher & Paykel model RT100 disposable tube. The outer tube 1811 can be formed from a composite tube, as described above.

[0266] With a coaxial tube 1801, the ventilator 1805 may not become aware of a leak in the inner tube 1807. Such a leak may short circuit the patient 1801, meaning that the patient 1801 will not be supplied with sufficient oxygen. Such a short circuit may be detected by placement of a sensor at the patient end of the coaxial tube 1801. This sensor may be located in the patient end connector 1815. A short circuit closer to the ventilator 1805 will lead to continued patient 1801 re-breathing of the air volume close to the patient 1801. This will lead to a rise in the concentration of carbon dioxide in the inspiratory flow space 1813 close to the patient 1801, which can be detected directly by a CO₂ sensor. Such a sensor may comprise any one of a number of such sensors as is currently commercially available. Alternatively, this re-breathing may be detected by monitoring the temperature of the gases at the patient end connector 1815, wherein a rise in temperature above a predetermined level indicates that re-breathing is occurring.

[0267] In addition to the above to reduce or eliminate the formation of condensation within either the inner tube 1807 or outer tube 1811, and to maintain a substantially uniform temperature in the gases flow through the coaxial tube 1801, a heater, such as a resistance heater filament, may be provided within either the inner tube 1807 or outer tube 1811, disposed within the gases spaces 1809 or 1813, or within the inner tube 1807 or outer tube 1811 walls themselves.

Nasal Cannulas and Other Patient Interfaces

[0268] Reference is next made to FIG. 19A, which shows composite tube 201 in use with a nasal cannula patient interface 1901. In this example, the patient interface 1901 is

positioned on the face of the patient **1903** with headgear **1905** secured around the back of the head of the patient **1901**. The patient interface includes a cannula body **1907** and a delivery tube **1909**. A composite tube **201**, as described, communicates with the delivery tube **1909** to supply inspiratory gases to the patient interface **1901**.

[0269] In the past, the delivery tube **1909** has been used to decouple the weight of heated respiratory tubing from the patient interface **1901**. Previously-used delivery tubes **1909** consisted of a length of flexible tubing. It was important that the delivery tube **1909** be lightweight so that the mass of the delivery tube **1909** did not drag the patient interface **1901** off a patient's face. Heated tubes were substantially bulkier and heavier than unheated tubes. Thus, previously-used delivery tubes **1909** were unheated. In order to achieve satisfactory flexibility, previously-used delivery tubes **1909** also had poor insulation properties. Without good insulating and heating, rainout in the delivery tubes **1909** was a problem. Thus, delivery tubes **1909** were kept as short as possible to minimize rainout. The short length did not consistently prevent the weight of heated respiratory tubing from dragging the patient interface **1901**, however. Thus, previously-used delivery tubes have a number of drawbacks.

[0270] The composite tubes **201** described herein provide good insulation while maintaining good flexibility and light weight. Thus, in some embodiments, the delivery tube **1909** can be a composite tube **201**. Composite tubes **201** can provide improved insulation properties over delivery tubes previously known in the art. In addition, the length of the delivery tube can be longer and provide better decoupling of tube drag. The composite-tube **201** delivery tube **201** can optionally have heating filaments (not shown) in the second elongate member (not shown). The heating filaments, if present, can provide heat input. Alternatively, the heating filaments can provide structural support for the second elongate member without being energized.

[0271] The length of the unheated composite-tube **201** delivery tube **1909** can be greater than the length of a normal unheated extension while still maintaining the same or less amount of heat loss because of the better insulation properties of the composite tube **201**. An increased length of delivery tube **1909** is beneficial to keep the patient's movement from dragging on the tube connections. An increased extension length will also allow for better head movement without compromising patient comfort.

[0272] In addition, certain embodiments include the realization that eliminating a separate delivery tube **1909** can have a number of benefits, discussed below. Thus, as shown in FIG. **19B**, the delivery tube **1909** and composite tube **201** can desirably be a unitary component, which extends to the cannula body **1907**.

[0273] In a typical patient interface **1901**, a heated tube (in place of composite tube **201** of FIG. **19A**) supplies inspiratory gases to an unheated delivery tube **1909**. The temperature of the inspiratory gases can experience significant thermal losses (for example, 20°C or more or thereabout) along the length of the unheated delivery tube **1909**. To compensate, the temperature at the patient end of the heated tube is held higher than the required temperature actually delivered to the patient **1901**. In addition, condensation can rain out as the temperature drops in the delivery tube **1909**. It was realized that extending a heated composite tube **201** to the cannula body **1907** in place of the delivery tube **1909**, as shown in FIG. **19B**, can reduce input energy requirements, as the patient end of the composite tube **201** can be held at a lower temperature. This configuration can also reduce rainout by eliminating the unheated delivery tube **1909** from the patient interface.

[0274] Desirably, the composite tube **201** can be tapered. In at least one embodiment, the patient-end portion of the composite tube **201** is tapered to fit the inlet of the cannula body **1907**. In at least one embodiment, the diameter of a length of the composite tube **201** near the patient end is smaller than the diameter of the remainder of the composite tube **201**. For example, the length of the composite tube **201** near the patient end can be in the range of 50 to 300 mm (or about 50 to 300 mm). A smaller diameter tube near the patient end can advantageously reduce tube weight near the cannula body.

[0275] The composite tube **201** can comprise a temperature sensor (not shown) near at least the patient end of the composite tube **201**. In addition to, or instead of, a temperature sensor, the composite tube **201** can comprise another kind of sensor (not shown) near at least the patient end of the composite tube **201**. For example, the composite tube **201** can comprise a pressure sensor (not shown) near at least the patient end of the composite tube **201**. Pressure sensors can be particularly advantageous for CPAP control and nasal high-flow therapy. When the composite tube **201** and delivery tube **1909** are a unitary component, the sensor(s) are close to the patient's **1903** nostrils, which can provide more accurate

information relating to the delivered gas. Example patient-end sensor configurations are described in greater detail below.

[0276] A unitary configuration is also desirable because it can reduce wiring on a patient **1901**. If the cannula body **1907** is equipped with one or more sensors or other electrical components, it is necessary to provide an electrical connection to the cannula body **1907**. If the composite tube **201** and the delivery tube are a unitary component, electrical lines can run along the composite tube **201**, as described above, to the patient end of the composite tube **201** at the cannula body **1907**. No separate electrical connection to the cannula body **1907** is required.

[0277] The unitary configuration can incorporate a variable-pitch composite tube **201**, as described above. In a tube that has no or little unheated extension, the heating would continue to the cannula body **1907** where the sensing element would be located. These tubes require reduced end-of-tube temperatures to ensure the delivery of saturated gases at 37 C. This is because, ordinarily, the end of tube temperature is set to much higher than 37°C to account for heat loss in the unheated extension. However, a configuration without an unheated extension is more likely to suffer condensation near the unit end. Redistributing the heating to a region proximal to the unit end of the tube will help to boost $T_{\text{gas}} > T_{\text{dew}}$, and hence reduce the occurrence of condensation, without delivering excessively high end of tube temperature.

[0278] It should be appreciated that, although the configurations in FIG. **19B** may be preferred in certain embodiments, other configurations, including the configuration of FIG. **19A**, may be utilized in other embodiments as may be desired.

[0279] The composite tubes **201** of this disclosure can also be incorporated in and/or used with other patient interfaces, such as a full face mask **2001** (FIG. **20A**), a nasal mask **2003** (FIG. **20B**), and a nasal/pillow mask **2005** (FIG. **20C**). As discussed above, the composite tube **201** can serve as a delivery tube **1909** or eliminate the need for a delivery tube entirely.

Cleaning

[0280] Returning again to FIG. 2A, in at least one embodiment, materials for a composite tube can be selected to handle various methods of cleaning. In some embodiments, high level disinfection (around 20 cleaning cycles) can be used to clean the composite tube 201. During high level disinfection, the composite tube 201 is subject to pasteurization at about 75°C for about 30 minutes. Next, the composite tube 201 is bathed in 2% glutaraldehyde for about 20 minutes. The composite tube 201 is removed from the glutaraldehyde and submerged in 6% hydrogen peroxide for about 30 minutes. Finally, the composite tube 201 is removed from the hydrogen peroxide and bathed in 0.55% orthophthalaldehyde (OPA) for about 10 minutes.

[0281] In other embodiments, sterilization (around 20 cycles) can be used to clean the composite tube 201. First, the composite tube 201 is placed within autoclave steam at about 121 °C for about 30 minutes. Next, the temperature of the autoclave steam is increased to about 134 °C for about 3 minutes. After autoclaving, the composite tube 201 is surrounded by 100% ethylene oxide (ETO) gas. Finally, the composite tube 201 is removed from the ETO gas and submerged in about 2.5% glutaraldehyde for about 10 hours.

[0282] The composite tube 201 may be made of materials to withstand the repeated cleaning process. In some embodiments, part or all of the composite tube 201 can be made of, but is not limited to, styrene-ethylene-butene-styrene block thermo plastic elastomers, for example Kraiburg TF6STE. In other embodiments, the composite tube 201 can be made of, but is not limited to, hytrel, urethanes, or silicones.

Methods Of Manufacture

[0283] Reference is next made to FIGS. 21A through 21F which demonstrate example methods for manufacturing composite tubes.

[0284] Turning first to FIG. 21A, in at least one embodiment, a method of manufacturing a composite tube comprises providing the second elongate member 205 and spirally wrapping the second elongate member 205 around a mandrel 2101 with opposite side edge portions 2103 of the second elongate member 205 being spaced apart on adjacent wraps, thereby forming a second-elongate-member spiral 2105. The second elongate member 205

may be directly wrapped around the mandrel in certain embodiments. In other embodiments, a sacrificial layer may be provided over the mandrel.

[0285] In at least one embodiment, the method further comprises forming the second elongate member **205**. Extrusion is a suitable method for forming the second elongate member **205**. The second extruder can be configured to extrude the second elongate member **205** with a specified bead height. Thus, in at least one embodiment, the method comprises extruding the second elongate member **205**.

[0286] As shown in FIG. **21B**, extrusion can be advantageous because it can allow heating filaments **215** to be encapsulated in the second elongate member **205** as the second elongate member is formed **205**, for example, using an extruder having a cross-head extrusion die. Thus, in certain embodiments, the method comprises providing one or more heating filaments **215** and encapsulating the heating filaments **215** to form the second elongate member **205**. The method can also comprise providing a second elongate member **205** having one or more heating filaments **215** embedded or encapsulated in the second elongate member **205**.

[0287] In at least one embodiment, the method comprises embedding one or more filaments **215** in the second elongate member **205**. For example, as shown in FIG. **21C**, filaments **215** can be pressed (pulled or mechanically positioned) into the second elongate member **205** to a specified depth. Alternatively, cuts can be made in the second elongate member **205** to a specified depth, and the filaments **215** can be placed into the cuts. Preferably, pressing or cutting is done shortly after the second elongate member **205** is extruded and the second elongate member **205** is soft.

[0288] As shown in FIGS. **21D** and **21E**, in at least one embodiment, the method comprises providing the first elongate member **203** and spirally wrapping the first elongate member **203** around the second-elongate-member spiral **2105**, such that portions of the first elongate member **203** overlap adjacent wraps of the second-elongate-member spiral **205** and a portion of the first elongate member **203** is disposed adjacent the mandrel **2101** in the space between the wraps of the second-elongate-member spiral **2105**, thereby forming a first-elongate-member spiral **2107**. FIG. **21D** shows such an example method, in which heating filaments **215** are encapsulated in the second elongate member **205**, prior to forming the

second-elongate-member spiral. FIG. 21E shows such an example method, in which heating filaments 215 are embedded in the second elongate member 205, as the second-elongate-member spiral 2105 is formed. An alternative method of incorporating filaments 215 into the composite tube comprises encapsulating one or more filaments 215 between the first elongate member 203 and the second elongate member 205 at a region where the first elongate member 203 overlaps the second elongate member 205.

[0289] As discussed above, at least one embodiment comprises a tube having multiple wraps of the first elongate member 203 between wraps of the second elongate member 205. Accordingly, in certain embodiments, the method comprises providing the first elongate member 203 and spirally wrapping the first elongate member 203 around the second-elongate-member spiral 2105, such that a first side portion of the first elongate member 203 overlaps a wrap of the second-elongate-member spiral 2105 and a second side portion of the first elongate member 203 contacts an adjacent side portion of the first elongate member 203. A portion of the first elongate member 203 is disposed adjacent the mandrel 2101 in the space between the wraps of the second-elongate-member spiral 2105, thereby forming a first-elongate-member spiral 2107 comprising multiple wraps of the first elongate member 203 between wraps of the second elongate member 205.

[0290] In at least one embodiment, the first elongate member 203 is wrapped multiple times between winds of the second elongate member 205. An example schematic of the resulting longitudinal cross-section is shown in FIG. 22A. Adjacent wraps of the first elongate member 203 can be fused using any suitable technique, such as heat fusing, adhesive, or other attachment mechanism. In at least one embodiment, adjacent molten or softened bubbles can be touched together and thereby bonded while hot and subsequently cooled with an air jet. Adjacent wraps of the first elongate member 203 can also be joined by winding them on the mandrel in a softened state and allowing them to cool.

[0291] In at least one embodiment, the first elongate member 203 is wrapped a single time or multiple times between winds of the second elongate member 205, and the bubble or bubbles between winds of the second elongate member 205 are further collapsed into additional discrete bubbles using an appropriate technique such as a heat treatment. An example schematic of the resulting longitudinal cross-section is shown in FIG. 22B. As

shown in FIG. 22B, one bubble of the first elongate member 203 can be collapsed into two or three or more discrete bubbles using any suitable technique, such as application of a mechanical force with an object or application of a force with a directed air jet. Another example schematic of a resulting longitudinal cross-section is shown in FIG. 22C. In this example, a center portion of a bubble is collapsed such that the top of the bubble is bonded to the bottom of the bubble to form two discrete bubbles separated by a flat bottom portion. Then, adjacent side portions of the two discrete bubbles are bonded to form a structure comprising three discrete bubbles.

[0292] The above-described alternatives for incorporating one or more heating filaments 215 into a composite tube have advantages over the alternative of having heating filaments in the gas path. Having the heating filament(s) 215 out of the gas path improves performance because the filaments heat the tube wall where the condensation is most likely to form. This configuration reduces fire risk in high oxygen environments by moving the heating filament out of the gas path. This feature also reduces performance as it reduces the heating wires effectiveness at heating the gases that are passing through the tube. Nevertheless, in certain embodiments, a composite tube 201 comprises one or more heating filaments 215 placed within the gas path. For example, heating filaments can be emplaced on the lumen wall (tube bore), for example, in a spiral configuration. An example method for disposing one or more heating filaments 215 on the lumen wall comprises bonding, embedding, or otherwise forming a heating filament on a surface of the second elongate member 205 that, when assembled, forms the lumen wall. Thus, in certain embodiments, the method comprises disposing one or more heating filaments 215 on the lumen wall.

[0293] Regardless of whether the heating filaments 215 are embedded or encapsulated on the second elongate member 205 or disposed on the second elongate member 205, or otherwise placed in or on the tube, in at least one embodiment, pairs of filaments can be formed into a connecting loop at one end of the composite tube to form a circuit.

[0294] FIG. 21F shows a longitudinal cross-section of the assembly shown in FIG. 21E, focusing on a top portion of the mandrel 2101 and a top portion of the first-elongate-member spiral 2107 and second-elongate-member spiral 2105. This example shows the second-elongate-member spiral 2105 having a T-shaped second elongate member 205.

As the second-elongate member is formed, heating filaments **215** are embedded in the second elongate member **205**. The right side of FIG. **21F** shows the bubble-shaped profile of the first-elongate-member spiral, as described above.

[0295] The method can also comprise forming the first elongate member **203**. Extrusion is a suitable method for forming the first elongate member **203**. Thus, in at least one embodiment, the method comprises extruding the first elongate member **203**. The first elongate member **203** can also be manufactured by extruding two or more portions and joining them to form a single piece. As another alternative, the first elongate member **203** can also be manufactured by extruding sections that produce a hollow shape when formed or bonded adjacently on a spiral-tube forming process.

[0296] The method can also comprise supplying a gas at a pressure greater than atmospheric pressure to an end of the first elongate member **203**. The gas can be air, for example. Other gases can also be used, as explained above. Supplying a gas to an end of the first elongate member **203** can help maintain an open, hollow body shape as the first elongate member **203** is wrapped around the mandrel **2101**. The gas can be supplied before the first elongate member **203** is wrapped around the mandrel **2101**, while the first elongate member **203** is wrapped around the mandrel **2101**, or after the first elongate member **203** is wrapped around the mandrel **2101**. For instance, an extruder with an extrusion die head/tip combination can supply or feed air into the hollow cavity of the first elongate member **203** as the first elongate member **203** is extruded. Thus, in at least one embodiment, the method comprises extruding the first elongate member **203** and supplying a gas at a pressure greater than atmospheric pressure to an end of the first elongate member **203** after extrusion. A pressure of 15 to 30 cm H₂O (or about 15 to 30 cm H₂O) has been found to be suitable.

[0297] In at least one embodiment, the first elongate member **203** and the second elongate member **205** are spirally wound about the mandrel **2101**. For example, the first elongate member **203** and second elongate member **205** may come out of an extrusion die at an elevated temperature of 200°C (or about 200°C) or more and then be applied to the mandrel after a short distance. Preferably, the mandrel is cooled using a water jacket, chiller, and/or other suitable cooling method to a temperature of 20 °C (or about 20 °C) or less, e.g., approaching 0 °C (or about 0 °C). After 5 (or about 5) spiral wraps, the first elongate member

203 and second elongate member **205** are further cooled by a cooling fluid (liquid or gas). In one embodiment, the cooling fluid is air emitted from a ring with jets encircling the mandrel. After cooling and removing the components from the mandrel, a composite tube is formed having a lumen extending along a longitudinal axis and a hollow space surrounding the lumen. In such an embodiment, no adhesive or other attachment mechanism is needed to connect the first and second elongate members. Other embodiments may utilize an adhesive or other attachment mechanism to bond or otherwise connect the two members. In another embodiment, the second elongate member **205** after extrusion and placement of the heating filaments may be cooled to freeze the location of the heating filaments. The second elongate member **205** may then be re-heated when applied to the mandrel to improve bonding. Example methods for re-heating include using spot-heating devices, heated rollers, etc.

[0298] The method can also comprise formed pairs of heating or sensing filaments into a connecting loop at one end of the composite tube. For example, end sections of two heating or sensing filaments can be extricated from the second elongate member **205** and then formed into a connecting loop e.g., by tying, bonding, soldering, adhering, fusing, etc. the two filaments together. As another example, end sections of the heating filaments can be left free from the second elongate member **205** during the manufacturing process and then formed into a connecting loop when the composite tube is assembled.

[0299] With reference now to FIGS. **23A–23H**, an alternative method of forming a tube **201** involves an extrusion tool **2301** having a series of flow paths running therealong. The extrusion tool **2301** can be used to form tubes such as the example tubes shown in FIGS. **23G** and **23H**. As shown, tubes produced using the extrusion tool **2301** can include a plurality of first elongate members **203** extending generally along the longitudinal axis of the tube. In some embodiments, the extrusion tool **2301** includes a body **2310** and a central extension **2320**. In some embodiments, the body **2310** and extension **2320** are generally cylindrical. The body **2310** can include one or more flow paths **2312** that allow for the passage of a molten plastic or another material through the body **2310** from an input end **2314** to an output or extrusion end **2316**. In some embodiments, the flow paths have a substantially conical longitudinal cross-section (that is, are wider where the molten plastic first enters at the input **2314** and narrower near the extrusion end **2316**). The flow paths can

have various configurations to produce tubes **201** having various profiles. For example, the flow path configuration shown at the output or extrusion end **2316** in FIGS. **23C** and **23D** can produce a tube **201** having an end view profile as shown in FIG. **23A**. FIG. **21B** shows an end view of the tube of FIG. **23A** including second elongate members **205**, which may include heating filaments **215**, disposed between adjacent bubbles or first elongate members **203**. In use, the tool **2301** is adapted to rotate so as to induce the tube **201** to be helically formed. As shown in FIG. **23F**, the central extension **2320** can couple the extrusion tool **2301** to an extruder **2330**. Bearings **2322** disposed between the central extension **2320** and the extruder **2330** can allow the central extension **2320** and body **2310** to rotate relative to the extruder **2330**. The rate of rotation of the tool **2301** can be adjusted to change the pitch or helix angle of the first elongate members **203**. For example, a faster rate of rotation can produce a smaller helix angle, as shown in FIG. **23G**. A slower rate of rotation can produce a larger helix angle, as shown in FIG. **23H**.

[0300] As discussed above with reference to FIG. **8A** and **8B**, certain embodiments can comprise a composite tube with a variable pitch. When manufacturing such embodiments, a mandrel **2101** and control system is preferably provided that can alter the effective pitch of the first elongate member **203** and second elongate member **205** (that is, the “ropes”). This can be achieved, for example, by controlling the ratio of rope speed to mandrel **2101** precession rate while maintaining a constant tangential speed at the critical dimension, that is, the pitch center diameter of the ropes. Pitch center diameter determines the pitch center going through the middle of the ropes. This value depends on speed. It is also predictable, so if the pitch center diameter is different from expected, speed can be adjusted to bring the pitch center diameter to the expected value. Altering the effective pitch can also be achieved, for example, by controlling the ratio of rope speed to mandrel **2101** precession while maintaining a constant rotational rate for the spiral composite tube **201** so formed. By controlling the rope speed, any changes in extrudate output are compensated for.

[0301] Yet another approach for manufacturing a variable-pitch composite tube **201** uses an integrated system in which extrusion rate and mandrel **2101** precession rate are altered in unison. For example, in this mode, the rope speed may stay the same, but the

precession of the mandrel **2101** when enabled will require a slowdown in extrusion rate to match the extrudate output with the tangential speed of the spiral tube **201** so formed.

[0302] Still another approach for manufacturing a variable-pitch composite tube **201** moves the incident angle of the second elongate member **205** and first elongate member **203** to alter the pitch of the tube **201**. In these embodiments, the extruders can be on a slide way, which will allow a change in angle, such as a rotary table where the center of rotation is where the second elongate member **205** and first elongate member **203** meet the mandrel **2101**. This method can allow up to 3–5 mm (or about 3–5 mm) of variation in pitch.

[0303] Reference is next made to FIG. **24A** through **24F** which show transverse cross-sections of tubes comprising a single tube-shaped element having a first elongate member or portion **203** and a second elongate member or portion **205**. As illustrated, the second elongate portions **205** are integral with the first elongate portions **203**, and extend along the entire length of the single tube-shaped element. In the embodiments illustrated, the single tube-shaped element is an elongate hollow body having in transverse cross-section a relatively thin wall defining in part the hollow portion **2201**, with two reinforcement portions **205** with a relatively greater thickness or relatively greater rigidity on opposite sides of the elongate hollow body adjacent the relatively thin wall. These reinforcement portions form a portion of the inner wall of the lumen **207** after the elongate hollow body is spirally wound, such that these reinforcement portions are also spirally positioned between adjacent turns of the elongate hollow body.

[0304] In at least one embodiment, the method comprises forming an elongate hollow body comprising the first elongate portion **203** and the reinforcement portion **205**. Extrusion is a suitable method for forming the elongate hollow body. Suitable cross-sectional shapes for the tube-shaped element are shown in FIG. **24A** through **24F**.

[0305] The elongate hollow body can be formed into a medical tube, as explained above, and the foregoing discussion is incorporated by this reference. For example, in at least one embodiment, a method of manufacturing a medical tube comprises spirally wrapping or winding the elongate hollow body around a mandrel. This may be done at an elevated temperature, such that the elongate hollow body is cooled after being spirally wound to join adjacent turns together. As shown in FIG. **24B**, opposite side edge portions of the

reinforcement portions **205** can touch on adjacent turns. In other embodiments, opposite side edge portions of the second elongate member **205** can overlap on adjacent turns, as shown in FIGS. **24D** and **24E**. Heating filaments **215** can be incorporated into the second elongate member as explained above and as shown in FIG. **24A** through **24F**. For example, heating filaments may be provided on opposite sides of the elongate hollow body such as shown in FIGS. **24A–24D**. Alternatively, heating filaments may be provided on only one side of the elongate hollow body, such as shown in FIGS. **24E–24F**. Any of these embodiments could also incorporate the presence of sensing filaments.

Placement of Chamber-End Connector with Electrical Connectivity

[0306] Reference is next made to FIG. **25A**, which shows an example flow chart for attaching a connector to the end of the tube that is configured in use to connect to a humidifier. For example, as described above with reference to FIG. **1**, inlet **109** of the inspiratory tube **103** connects to humidifier **107** via port **111**. The example flow chart of FIG. **25A** can make an inlet **109** capable of physically and electrically connecting to the humidifier **107**.

[0307] In this example, a seal **2503** is inserted into a seal housing **2501**. The act of seal insertion is also shown in greater detail in FIG. **25B**. The seal housing **2501** is made of a molded plastic. One open end is sized and configured for connecting to a humidifier. The seal **2503** can be an o-ring, as shown in FIG. **25B**. A suitable configuration for the o-ring can be a double-toric configuration comprising thicker concentric toruses connected by a thinner web. In this example, the o-ring is molded from a single elastomeric material, such as rubber or silicone. The seal **2503** is seated in a compliant ridge in the seal housing **2501**. The seal **2503** is designed to seal against an outer surface of the port of the humidifier chamber. The seal **2503** can deflect to extend along the outer surface of the port. In other words, the double o-ring configuration includes an inner O-ring and an outer O-ring connected by a flange. The outer O-ring will be sealed within the connector while the inner O-ring can deflect along the flange portion and squeeze against the outer surface of the port. In such a position, a horizontal plane extending through a center axis of the inner O-ring may

be in a different plane than a horizontal plane extending through a center axis of the outer O-ring.

[0308] Turning again to the example of FIG. 25A, a printed circuit board (PCB) is inserted into a compliant dock on the seal housing 2501. The act of PCB insertion is shown in greater detail in FIG. 25C. In FIG. 25C, an assembly 2505 comprising a PCB and a PCB electrical connector is inserted into a compliant dock on the seal housing 2501. A variety of PCBs of suitable size and configuration can be used. A variety of PCB electrical connectors can also be used. For example, the PCB electrical connector can be a straight-through connector or a bi-directional connector. The PCB comprises four connection pads suitable for receiving four conductive filaments encased in the second elongate member of the tube. However, the PCB can be configured to receive a suitable number of conductive filaments, if the second elongate member contains more or fewer than four conductive filaments.

[0309] Turning again to the example of FIG. 25A, and as shown in greater detail in FIG. 25D, a seal retainer 2507 is clipped onto one open end of the seal housing 2501 with the seal 2503 seated on the compliant ridge. Clipping the seal retainer 2507 in place compresses the seal 2503 and thereby forms a liquid- and gas-resistant connection between the seal housing 2501 and the seal retainer 2507. In this example, the seal retainer 2507 is made from a molded plastic. In this example, the seal retainer 2507 also comprises a protruding portion sized and shaped to fit around the PCB. The protruding portion serves to support and protect the more flexible and fragile PCB. The protruding portion can be omitted in certain embodiments, however. The resulting assembly comprising the seal housing 2501, seal 2503, PCB and PCB connector assembly 2505, and the seal retainer 2507 is referred to herein as a connector tube assembly 2515.

[0310] Turning again to the example of FIG. 25A, the tube is prepared for connection to the connector tube assembly 2515. As shown FIG. 25A and in greater detail in FIG. 25E, in step 2511, a portion of the second elongate member at one end of the tube is separated from the first elongate member. Then, in step 2513, a length of the separated second elongate member is stripped away to reveal four conductive filaments (or the number of conductive filaments contained in the second elongate member). Step 2513 is shown in greater detail in FIG. 35F.

[0311] As explained in FIG. 25A and as shown in greater detail in FIG. 25G, the portion of the tube with the stripped length of the second elongate member is inserted in the connector tube assembly 2515. In FIG. 25G, the second elongate member 205 has a bent shape to accommodate the position of the PCB connector assembly 2505. The PCB connector assembly 2505 can also be sized and positioned to reduce or eliminate the bent shape, for example, by shifting the PCB connector assembly further toward the connector end. As shown in step 2517 of FIG. 25A and FIG. 25H, the four conductive filaments are inserted in the four connection pads of the PCB. Then, as shown in FIGS. 25A and 25I, a bead of solder 2519 is placed over each filament-connection pad connection to secure the filament to the connection pad and ensure a good electrical connection between each filament and its corresponding connection pad.

[0312] The foregoing step of placing the bead of solder 2519 can be omitted in certain embodiments. FIGS. 26A–26E show an example connector assembly configuration that does not require soldering to connect the filaments to the connector assembly.

[0313] FIG. 26A shows a connector assembly 2601 comprising a clip housing 2603 and a circuit connector 2605. A stripped length 2607 of the second elongate member 205 exposes the heating filaments 215 that can be inserted in the clips 2609 in the clip housing 2403. Each clip 2609 is electrically conductive. Suitable materials for a clip 2609 include, for example, aluminum, copper, and gold. A clip 2609 retains a heating filament 215 without the need for solder. An electrical lead 2611 can run between each clip 2609 and the circuit connector 2605.

[0314] FIG. 26B shows a top-down view of the connector assembly 2601 showing the clips 2609 positioned in the clip housing 2603.

[0315] FIG. 26C shows a clip 2609 in greater detail. The clip 2609 comprises a folded portion 2613, a retention tab portion 2615, a flanged portion 2617, and elongated portion 2619. A heating filament (not shown) is inserted into the flanged portion 2617 so that the folded portion 2613 accepts and retains the heating filament. The shape of the flanged portion 2617 facilitates insertion of the heating filament and guides the heating filament into place. Nevertheless, the flanged portion 2617 can have a straight shape, if desired. The flanged portion 2617 can also have another suitable shape, such as a partial

flange. The folded portion has a catch portion **2621** that is compliant with the retention tab portion **2615**. The retention tab portion **2615** is angled so that a heating filament is able to slide past the retention tab portion **2615** in one direction into the folded portion **2613**. The retention tab portion **2615** also catches the heating filament to prevent it from inadvertently falling out of the folded portion **2613**. The elongated portion **2619** is electrically conductive and transmits the electrical current from the heating filament into and/or across the clip housing **2603**.

[0316] FIG. **26D** is a cross section of the view of FIG. **26C** and demonstrates the position of the tab portion **2615** and the catch portion **2621** in greater detail. FIG. **26E** shows how the clips **2609** are positioned in the clip housing **2603**. The clip housing **2603** is shown transparent to demonstrate the position of the elongated portion **2619**.

[0317] Referring again to FIG. **25A**, to ensure that all pieces of the connector tube assembly **2515** are securely fixed to each other, a layer of glue **2521** is then applied. Glue is a broad term and refers to a material for joining, fixing, or attaching other materials. A glue can be adhesive or sticky to the touch when it is in a liquid or semi-solid state. When the glue has dried or otherwise cured into a solid state, the glue can be adhesive or non-adhesive or non-sticky to the touch. The glue can be a resin, such as an epoxy resin, or an elastomer (thermoset or thermoplastic). Use of TPE materials can be advantageous because they are generally flexible and can accommodate twisting, bending, or pressure without shattering.

[0318] An example method for applying the glue **2521** is shown in FIG. **25J**. In this method, a two-block mold is provided. In this example, the mold is made of a metal, such as aluminum or stainless steel, however any suitable material can be used. For instance, the mold can be made from Teflon® PTFE blocks. One block is configured to accommodate the protruding PCB and PCB connector assembly **2505** of the connector tube assembly **2515** and the adjacent tube, and the other block is configured to accommodate the opposite portion of the tube and connector tube assembly **2515**. The tube is placed in the compliant mold portions such that the blocks stack one on top of the other. A liquid glue is introduced into an inlet hole in the mold, and the glue is allowed to harden. Then, the mold is removed to expose the glued tube-and-connector assembly **2523**, which includes a layer of hardened glue **2521** covering the PCB and the joint between the tube and the connector tube assembly **2515**.

The glue layer can cover the PCB and all of the soldered connections on the PCB. In this manner, the layer of glue can protect the PCB and the connections from corrosion. In other words, the glue serves at least three functions: sealing the connector and the conduit, holding the PCB in place and potting the PCB; the glue layer forms a pneumatic seal, a mechanical bond and a PCB pot. In addition, the glue layer can act as an electrically insulating barrier, for example, by keeping out moisture and liquids from reaching the electrical components and creating a conductive path to a user of the device.

[0319] Returning again to FIG. 25A, the tube-and-connector assembly 2523 is then in condition for final assembly. As shown in greater detail in FIG. 25K, a first clamshell 2525 and a second clamshell 2527 are snapped together around the tube-and-connector assembly 2523 such that a portion of the PCB connector is left exposed. The first clamshell 2523 and second clamshell 2527 shown in FIG. 25K are top and bottom clamshells, respectively.

[0320] An alternative clamshell design is shown in FIGS. 27A–27E, in which the first 2525 and second 2527 clamshells are left and right clamshells, respectively. The clamshell 2525, 2527 portions (FIG. 25K or FIGS. 27A–27E) can be made of molded plastic or any other suitable material. The clamshell 2525, 2527 portions (FIG. 25K or FIGS. 27A–27E) serve to further protect the tube-and-connector assembly 2523 (FIGS. 25A and 25J) and to maintain the tube-and-connector assembly in a bent position that promotes the return of condensate to the humidifier unit when in use. As shown in FIG. 25L, the final assembly can readily snap into a humidifier with a compliant electrical connector near the connection port.

[0321] Although the foregoing manufacturing method has been described with reference to a flow chart, the flow chart merely provides an example method for attaching a connector to the end of the tube that is configured in use to connect to a humidifier. The method described herein does not imply a fixed order to the steps. Nor does it imply that any one step is required to practice the method. Embodiments may be practiced in any order and combination that is practicable.

Placement of Alternative Device-End Connectors

[0322] Reference is next made to FIGS. 28A–28F which show a connector which can be used for medical circuits having electrical wires running therethrough. The connector 2801 comprises a cut-out 2802, which in certain embodiments is 30 mm (or about 30 mm) across. In certain embodiments, on one end of the cut-out 2802 is a L-shaped arm 2803 which extends in part outward from the connector 2801 and in part parallel to the longitudinal axis of the connector 2801.

[0323] The arm 2803 can have one or more electrical conductors 2804 embedded therein. The conductors 2804 can be made of copper or brass or another suitably conductive material and can be formed as flat L-shaped pieces running substantially along the length of the arm 2803.

[0324] The connector 2801 can further comprise an inner portion 2805 adapted to sit substantially inside a portion of the tube 201 and an outer portion 2806 adapted to substantially surround a portion of the tube 201.

[0325] A portion of the second elongate member 205 is stripped away to reveal the one or more filaments 215 embedded therein. Preferably about 5 mm of the filaments 215 are revealed. The connector 2801 is then attached to the tube 215 such that the inner portion 2805 sits within tube 201 and the outer portion 2806 sits around the tube 201. Preferably the connector 2801 is oriented such that the revealed ends of the filaments 215 are located at or near the cut-out 2802.

[0326] The revealed ends of the filaments 215 are then electrically and/or physically connected to the conductors 2804. This can be done by soldering the ends to the conductors 2804, or any other method known in the art.

[0327] A member 2807 can be inserted or molded on top of at least a portion of connector 2801 and, optionally, tube 201 to promote the attachment between the connector 2801 and the tube 201. The member 2807 can be a hard material or a soft material, such as a soft rubber or elastomer.

[0328] In some embodiments, a substantially L-shaped elbow 2808 can be placed over the assembly. The elbow 2808 can provide some additional strength to the connection

and can provide a predetermined bend in the tube **201** (such that the connector **2801** can tend to sit at an angle of about 90° from the body of the tube **201**).

[0329] Reference is next made to FIGS. **29A–29L** which shows another connector **2901** which can be used for medical circuits having electrical wires running therethrough. Referring first to FIG. **29A**, the connector **2901** permits a composite tube to be connected to a device, such as a CPAP device (not shown). The connector **2901** carries an electrical terminal on an L-shaped arm **2903**, which engages a complementary electrical terminal of the device to permit electrical signals or electrical energy to be transmitted between the device and a composite tube. In the illustrated arrangement, the electrical terminal of the connector **2901** is a plug **2905** that complies with a receptacle or port of the device. This arrangement could also be reversed, however, if desired. In this example, the plug electrically communicates with electrical contacts **2906** for establishing an electrical connection with a composite tube. Here, the electrical contacts **2906** are molded into the connector **2901**. The connector **2901** further comprises filament holders **2907** that are also molded into the connector **2901**. The connector **2901** also comprises a cut-out **2902**, which in certain embodiments is 30 mm (or about 30 mm) across.

[0330] As shown in FIGS. **29B** and **29C**, a portion (e.g., a 10-mm portion) of the second elongate member **205** is stripped away to reveal a small length of the one or more filaments **215** embedded therein. Preferably, about 5 mm or 10 mm of the filaments **215** are revealed.

[0331] As shown in FIG. **29E**, the connector **2901** is then attached to the tube **215** such that an inner portion **2909** of the connector **2901** sits within tube **201** and an outer portion **2911** of the connector **2901** sits around the tube **201**. Preferably the connector **2901** and composite tube **201** are oriented such that the revealed ends of the filaments **215** are located at or near the cut-out **2902** and the filaments **215** are aligned to meet near the contacts **2906**.

[0332] As shown in FIG. **29F**, the heating filaments **215** are positioned under the wire holders **2907** so that each heating filament **215** is positioned over a contact **2906**.

[0333] As shown in FIG. **29G**, a bead of solder **2913** is placed over each heating filament **215** at the respective contact **2906**. The combination of connector **2901** and

composite tube **201** is designated here as a connector-tube assembly **2917**. As shown in FIG. **29H**, a mold tool core **2915** is inserted into the connector **2901**. As shown in FIG. **29I**, the connector-tube assembly **2917** and core **2915** are placed in an injection mold tool **2919**. In FIG. **29J**, a molded material **2921** is molded over the cut-out (not shown), thereby bonding the connector **2901** and composite tube **201**. Suitable molded materials **2921** include plastic and rubber. The connector-tube assembly **2917** and core **2915** are removed from the injection mold tool (not shown), as in FIG. **29K**.

[0334] As shown in FIG. **29L**, the core **2915** is removed, thereby providing a composite tube **201** with a device-end connector **2901**. The method of FIGS. **29A–29J** allows the plug **2903** to be electrically connected to the heating filament and/or other electrical element(s) (not shown) of the composite tube **201**. Preferably, the heating circuit of the device provides electrical energy to the heating filament of the composite tube **201** so that the heating filament can provide heat energy to the flow of humidified air passing through the composite tube **201**. As discussed herein, such an arrangement can prevent or limit condensation within the composite tube **201**. In addition, or in the alternative, the plug **2903** and device port could provide for other electrical signals, such as data signals, to be communicated between the device and the composite tube **201**. For example, a sensor at the patient interface-end of the composite tube **201** could provide data regarding one or more parameters of the flow of air (e.g., temperature, humidity level) for use by the control system of the device. Any other desirable electrical signals could also be transmitted.

[0335] The foregoing methods of attaching connectors to composite tubes are provided by way of example. The methods described do not imply a fixed order to the steps. Nor do they imply that any one step is required to practice the methods. Embodiments may be practiced in any order and combination that is practicable.

Placement of Patient-End Connector with Electrical Connectivity

[0336] Reference is next made to FIGS. **30A–30O**, which show an example connector **3000** for connecting one end of the tube **201** to a patient interface (not shown). The end of the connector **3000** that connects to the patient interface is indicated by reference **3001**.

[0337] FIG. 30A shows a side perspective view of the connector 3000.

[0338] As shown in FIG. 30B–30F, the connector 3000 comprises a PCB assembly 3003 and an insert 3005, designated together as an insert assembly 3007 when assembled together, and a cover 3009. Each of FIGS. 30B–30D and 30F shows a side-perspective view that generally corresponds with the view of FIG. 30A. FIG. 30E shows a side-plan view.

[0339] The insert 3005 and cover 3009 are preferably molded plastic components. The insert 3005 can serve one or more purposes, including providing a receptor for the tube 201, providing a suitable conduit for the gas flow path, providing a housing for the PCB assembly 3003, and providing a housing for a sensor (not shown), such as a thermistor. The cover 3009 protects and covers the relatively fragile PCB assembly 3003 and protects the connection between the tube 201 and the insert 3005. As shown in FIGS. 30D and 30E, the end of the insert 3005 that is inserted in the tube 201 (that is, the end that is opposite end 3001) can be angled, which can aid insertion into the tube 201. In some embodiments, however, the end that is opposite end 3001 can be blunt or tapered.

[0340] As shown in FIG. 30D, the insert desirably includes a stop portion 3006a. The stop portion 3006a can promote correct placement of the tube 201 with respect to the insert 3005. The stop portion 3006a can also serve to protect the PCB assembly 3003 from directly contacting the tube 201. An alternative configuration is shown in FIG. 30E. In FIG. 30E, stop portion 3006b is formed as a spiral or helical component, such as a spiral or helical rib. This configuration is advantageous because the shape complements the spirally wound tube 201, thereby providing a secure connection between insert 3005 and tube 201.

[0341] Yet another alternative configuration is shown in FIGS. 31A and 31B. In these figures, stop portion 3006c is formed as a spiral or helical component, such as a spiral or helical rib. Again, this configuration is advantageous because the shape complements the spirally wound tube 201 (FIG. 31B), thereby providing a secure connection between insert 3005 and tube 201. In this configuration, the stop portion 3006c comprises an orientational stopping feature 3101. As shown in FIG. 31B, a surface of the orientation stopping feature 3101 is tapered such that the orientational stopping feature 3101 resembles a fin. The shape of the orientational stopping feature 3101 can pinch, grasp, or otherwise retain the second

elongate member **205** of the tube **201**. The orientational stopping feature **3101** thus can serve to better hold the tube **201** in the correct position by preventing the tube **201** from shifting and/or turning.

[0342] Returning to FIG. **30E**, the patient end **3001** of the insert **3005** is larger than it is in FIG. **30D** and illustrates how the size can be modified for different applications (for example, connecting to infant or adult patient interfaces).

[0343] FIG. **30G** shows a cross section of the connector **3000** and generally corresponds with the same side perspective view as FIG **30A**. In certain embodiments, there is an insulating gap, such as an air gap, between the tube **201** and the insert **3005** to protect the sensor (discussed below) from heat radiating from the heating filament(s) in the tube **201**, which can induce sensor error at low flows. In FIG. **30G**, such a gap would appear above and below sensor portion **3017**. Alternative, in certain embodiments, the insert **3005** is formed such that air bubbles are encapsulated in the insert **3005**. For example, the insert **3005** can comprise a foamed plastic.

[0344] FIG. **30H** shows a cross section of the insert assembly **3007** and generally corresponds with the side perspective view of FIG. **30D**. FIG. **30I** shows an alternative cross section of the insert assembly **3007** and generally corresponds with the side plan view of FIG. **30E**. These figures show greater details regarding the relative placement of the tube **201**, insert assembly **3007**, and/or cover **3009**.

[0345] As shown in FIGS. **30G–30I**, a generally annular catch structure **3013**, which comprises two molded rings extending radially outward from the body of the insert **3005**. The molded rings comply with a notch **3011**, which comprises a molded ring extending radially inward from the cover **3009**. The notch **3011** and catch structure **3013** hold the cover **3009** on the insert **3005**.

[0346] An alternative configuration for the catch structure **3013** is shown in FIGS. **32A** and **32B**. Again, the catch structure **3013** is generally annular and comprises two molded rings extending radially outward from the body of the insert **3005**. A plurality of anti-rotation projections **3201** extends perpendicularly between the rings. In this example, there are four projections **3201** evenly spaced around the circumference of the catch structure **3013** (e.g., at 90° intervals). The projections **3201** engage compliant notches in the cover

(not shown) and prevent the cover from rotating on the insert assembly. Yet another alternative configuration for the catch structure **3013** is shown in FIGS. **32C–32D**. Again, the catch structure **3013** is generally annular and comprises two molded rings extending radially outward from the body of the insert **3005**. Anti-rotation notches **3203** are disposed between the rings. In this example, there are four notches **3203** evenly spaced around the circumference of the catch structure **3013** (e.g., at 90° intervals). These notches **3203** engage compliant projections in the cover (not shown) and prevent the cover from rotating on the insert assembly.

[0347] FIGS. **30G–30I** further illustrate that PCB assembly **3003** comprises a PCB **3015**, a sensor portion **3017**, and a locating portion **3019**. The PCB assembly **3003** is located such that, in use, the sensor portion **3017** is within the fluid flow path through the insert **3005**.

[0348] The sensor portion **3017** includes one or more sensors, such as a temperature sensor. The sensor is preferably located on the projecting portion of the sensor portion **3017**. A suitable temperature sensor includes a thermistor, thermocouple, resistance temperature detector, or bi-metallic thermometer.

[0349] The PCB **3015** completes the heating and/or sensing circuit of the composite tube **201**.

[0350] The locating portion **3019** improves stability and facilitates locating the PCB assembly **3003** during manufacturing. Nevertheless, the locating portion **3019** can be omitted in certain embodiments.

[0351] FIG. **30I** also illustrates that the PCB assembly **3003** can be further stabilized in the insert **3005** by recessing at least part of the PCB **3015** and/or the locating portion **3019** in the outer surface of the insert **3005**. The recessed configuration is also shown in FIG. **30N**.

[0352] The configurations of FIGS. **30G–30I** have a number of advantages. For example, certain embodiments include the realization that placing the sensor portion **3017** within the fluid flow path promotes accurate measurements, regardless of flow rate, ambient temperatures, and so forth. In addition, certain embodiments include the realization that there

is less potential for fluid leak than a configuration having a separate sensor attached to a connector, due to poor user setup of the circuit.

[0353] Further, certain embodiments include the realization that, because the PCB assembly 3003 passes across the full width of the insert 3005, the PCB assembly 3003 can be used to pass connection leads across a tube 201. As discussed below, FIGS. 33A–33D illustrate a PCB assembly 3301 design capable of passing connection leads across a tube, the respective figures illustrating two sides of the PCB assembly 3301. The concept of passing connection leads across a tube 201 is further discussed below with reference to FIG. 34, in the context of an intermediate connector between two tube 201 segments.

[0354] Turning first to FIGS. 33A and 33B, the PCB assembly 3301 includes connection pads 3303, 3305 for the heating filament and/or sensor connections. The connection pads 3303, 3305 are configured to be on opposite sides of the PCB assembly 3303 to facilitate connections with spirally-wound heating filaments.

[0355] The PCB assembly 3301 includes sensor connection pads 3307 for the sensor. The sensor can be coupled to a diode through signal connection pads 3309 on the PCB assembly 3301. As illustrated, the PCB assembly 3301 includes a gap 3311 configured to thermally insulate the sensor from the other electrical components and tracks. In some embodiments, the gap 3311 can be filled with an insulating material to further thermally isolate the sensor connected to sensor connection pads 3307. In addition, the PCB assembly 3301 can be configured to position the sensor apart from the other active and/or passive electrical components, such as with the protruding feature 3313.

[0356] The PCB assembly 3301 includes power connection pad 3315 for a diode electrically coupled to the heating filaments through conductive tracks on the PCB assembly 3301. The power connection pad 3315 can be electrically and thermally coupled to heat sink 3317 to aid in dissipating heat, to reduce or minimize effects on the accuracy of the temperature reading of the thermistor coupled to the sensor connection pads 3307.

[0357] FIGS. 33C and 33D show the PCB assembly 2901 of FIGS. 33A and 33B in place across insert 2605, discussed above with respect to FIGS. 30A–30O, or an intermediate connector 3403, discussed below with respect to FIG. 34.

[0358] Thus, in at least one embodiment, a respiratory conduit segment, such as the insert **2605** or intermediate connector **3403**, comprises a lumen extending along a longitudinal axis and a wall surrounding the lumen, the lumen defining a gas-flow path when in use; and a PCB assembly **3301** comprising a printed circuit board and further comprising a first portion extending across the lumen along a diameter or chord line, such that a portion of the printed circuit board assembly generally bisects at least part of the flow path, the first portion being overmolded by an overmolding composition, a second portion adjacent the first portion projecting outward from the wall in a direction away from the lumen, the second portion comprising one or more connection pads **3303** on the printed circuit board configured to receive one or more wires from a first assembly, a third portion adjacent the first portion projecting outward from the wall in a direction away from the lumen and in a direction opposite the second portion, the third portion comprising one or more connection pads **3305** on the printed circuit board configured to receive one or more wires from a second assembly that is distinct from the first assembly, and one or more conductive tracks on the printed circuit board electrically coupled to the one or more connection pads of the second portion and to the one or more connection pads of the third portion and configured to provide electrical connectivity between the first assembly and the second assembly.

[0359] The first assembly and second assembly can each be a breathing tube. Or the first assembly can be a breathing tube and the second assembly can be a patient interface, for example.

[0360] Returning again to the examples of FIGS. **30G–30I**, the sensor portion **3017** is mounted or formed such that the sensor portion **3017**, PCB **3015**, and locating portion **3019** form a unit. For example, sensor portion **3017**, PCB **3015**, and locating portion **3019** can be mounted to each other using a suitable process such as soldering. Sensor portion **3017**, PCB **3015**, and locating portion **3019** can be unitarily formed from a suitable material, such as a circuit board substrate.

[0361] The sensor portion **3017** can be electrically connected to the PCB **3015** using a suitable technique, such as circuit printing. For example, the electrical connection can comprise conductive tracks, such as copper tracks. To electrically connect the conductive filaments in the second elongate member of the tube **201** to the connection pads

of the PCB assembly **3003**, a procedure similar to that shown and described above with respect to FIGS. **25E–25I** can be used. Additional electrical components, such as diodes (not shown), can be located at either side of the PCB **3015** inside and/or outside of the gas path. Locating a diode outside the gas path is discussed above with reference to sensor connection pads **3307** and signal connection pads **3309** and as shown in FIGS. **33A–33B**.

[0362] Returning again to the examples of FIGS. **30G–30I**, the PCB assembly **3003** can be mounted within the insert **3005** using, for example, an overmolding process, as known in the art. A material having a thermal conductivity in the range of 0.03–0.6 W/m·K or thereabout, such as polypropylene (thermal conductivity 0.1–0.22 W/m·K), can be used for at least a portion of the overmolding. Use of a material with low thermal conductivity can advantageously reduce interference from the ambient environment during sensor measurements, as it poorly conducts heat from the sensor portion **3017** to the insert **3005** walls. Certain embodiments include the realization that overmolding of a unitary PCB assembly **3003** allows more consistent placement of a sensor than overmolding a sensor alone. Furthermore, certain embodiments include the realization that overmolding a sensor placed inside center of the tube may make the sensor less sensitive to radiant effects.

[0363] As shown in FIGS. **30G–30I**, the PCB assembly **3003** passes through the width of the insert **3005** and is supported by opposite walls of the insert **3005**. Because the PCB assembly **3003** is supported on opposite sides of the insert **3005**, the PCB assembly **3003** can be relatively thin (that is, having less thickness and less width than a PCB with one support on the tube). The thin profile can promote fluid flow by providing less resistance to flow than a thicker profile.

[0364] The overmolding around the sensor portion **3017** is preferably configured to reduce the drag on fluids flowing around the sensor portion **3017**. The overmolding can have an aerodynamically efficient tapered shape, such as an airfoil shape, for example, a wing shape, a fully tapered torpedo shape (as shown in FIGS. **30F** and **30G**), or bullet shape that is partially tapered with one blunt edge (as shown in FIG. **30H**). These tapered shapes promote fluid flow. In addition, when placed within the fluid flow, these tapered shapes reduce turbulence and vortices at the trailing edge of the tapered shape, which can cause unwanted cooling of humidified gas and forming of condensation. Condensation formation can lead to

inaccurate measurement, as well as unwanted temperature drop in the gas delivered to a patient. Thus, the tapered shape can promote more accurate readings. In addition, the tapered shape can reduce collection of condensate that does form and also reduce buildup of patient secretions, by promoting runoff.

[0365] The tapered shape can also be selected to reduce turbulent flow by reducing the formation of vortices in the flow and increase the likelihood that the flow remains laminar.

[0366] The distance between the tapered shape and the inner wall of the insert **3005** is preferably selected to allow for more space. In at least one embodiment, the distance between tapered shape and the inner wall of the insert **3005** is at least 10% (or about 10%) or at least 30% (or about 30%), such as 33% (or about 33%) or 40% (or about 40%) of the inner diameter. In at least one embodiment, the distance between the tapered shape and the inner wall of the insert **3005** is greater than 2 mm (or about 2 mm). Allowing for more space decreases the likelihood that condensate becomes trapped in the space.

[0367] The overmolding promotes reading a more averaged temperature. There is some temperature variation across the insert **3005**, with higher temperatures toward the center of the insert **3005** and lower temperatures along the insert **3005** walls. An asymmetric temperature profile, in which the highest temperature is offset from the center line of the insert **3005**, is especially prevalent with bent tubes **203**. The overmolding has a larger surface area than the sensor portion **3017** of the PCB assembly **3003** and the overmolding material distributes the heat so that that the sensor of the sensor portion **3017** measures a more averaged temperature across the fluid path.

[0368] FIG. **30J** shows an end view of the connector **3000** taken along the width of the connector, as seen from the patient end portion **3001** of the connector **3000**, and looking toward the tube (not shown). In this view, the overmolded tapered shape housing the PCB assembly **3003**(not shown) is generally centered. FIG. **30K** shows an alternative configuration. In this view, the tapered shape is offset from the center line. As shown in FIGS. **30J** and **30K**, the junctions **3018** between the inner wall of the insert **3005** and the overmolded tapered shape housing the PCB assembly optionally can have fillets to reduce

flow disturbance and reduce areas for fluid build-up. The fillets of the junctions **3018** can be 1 mm (or about 1 mm) in radius, for example.

[0369] FIG. **30L** shows the offset positioning of the tapered shape of FIG. **30K** in greater detail. Because the sensor **3020** projects outward from the PCB assembly **3003**, the offset configuration can improve accuracy by placing the sensor **3020** closer to the center line. In addition, the offset configuration can also be desirable because the PCB assembly **3003** can be housed in one side of the mold tool during manufacturing, thereby simplifying the manufacturing process.

[0370] FIG. **30M** shows a longitudinal cross section of the insert assembly **3007** showing additional details of the PCB assembly **3003**. A sensor **3020** is placed into the flow path. The sensor **3020** can provide temperature and/or gas flow information to allow assessment of conditions near the patient interface. The sensor **3020** is preferably located close to the edge of the projecting part of the sensor portion **3017**. The thickness of the overmolding proximal the sensor **3020** is preferably thinner than the thickness of the overmolding around the other portions of the PCB assembly **3003**, as shown in FIG. **30O**. Reducing the overmolding thickness increases heat transfer to promote more accurate temperature measurements.

[0371] With reference again to FIG. **30M**, conductive tracks **3021** electrically connect the sensor **3020** to the PCB **3015**. (Note that sensor **3020** is not specifically shown in FIG. **30M**; rather the structure designated **3020** represents the general position of the sensor. The structure designated **3020** shows two conductive pads that the sensor would bridge across. The structure is designated as a sensor for sake of illustration.) Through holes **3023** allow components to make contact with the required conductive layers. FIG. **30N** shows an alternative configuration of the PCB assembly **3003**. In FIG. **30N**, the conductive tracks **3021** have a tortuous path. It was realized that increasing the length of the conductive tracks **3021** within the fluid path allows the temperature of the conductive tracks **3021** to more closely reflect the temperature within the fluid path, thereby reducing ambient effects on the sensor **3020** through the conductive tracks **3021**. Preferably, there is increased surface area of copper near the sensor **3020**. The increased copper promotes accurate detection of temperature around the sensor **3020** area.

[0372] In certain embodiments, the tapered shape can extend upstream along the gas path towards the source of the gas flow. This configuration promotes more accurate measurement by ensuring the sensor 3020 projects into the fluid flow, before the fluid is cooled as it passes the overmolding. This configuration can also promote more accurate measurements by reducing the “stem effect.” All contact-type temperature sensors are subject to stem effect. When a probe is immersed in a fluid flow, a thermally conductive path is created by the probe’s stem. In a case where the ambient temperature is cooler than the temperature of the measured fluid stream, heat is conducted away from the probe tip via the probe’s stem to the outer atmosphere. This results in the sensing tip reading a temperature that is lower than the actual surrounding fluid. And in a case where the ambient temperature is hotter than the temperature of the measured fluid stream, heat is conducted toward the probe tip via the probe’s stem from the outer atmosphere. This results in the sensing tip reading a temperature that is higher than the actual surrounding fluid. The tapered shape configuration reduces the stem effect by projecting the sensor 3020 away from the part of the sensor portion 3017 connecting the PCB 3015 and locating portion 3019 (that is, away from the “stem”). In certain embodiments, the tapered shape extends upstream by at least 6 mm (or about 6 mm) from the part of the sensor portion 3017 connecting the PCB 3015 and locating portion 3019.

[0373] In certain embodiments, the tapered shape can extend downstream away from the source of the gas flow. This configuration can be advantageous, for example, when the design of the overmolded PCB assembly 3003 significantly alters the average downstream fluid properties such that it is desirable to accurately measure the fluid properties leaving the tube.

[0374] Heating filaments (not shown here but described above) in the second elongate member can be connected to the PCB 3015, which can provide termination points to complete the heating filament circuit. The PCB 3015 can also be used to provide additional termination points to provide power to additional heating filaments in a secondary tube, such as in a segmented inspiratory limb configuration for use with a humidification system, the segmented inspiratory limb having a connector configured to couple heating filaments and

sensors in two segments. A suitable PCB assembly configuration is discussed above with reference to FIGS. 33A–33D.

[0375] Returning again to FIG. 30M, this configuration eliminates the need to have a separate power line running to the heating filaments. This configuration further ensures that the heating filaments run along the tube 203 and terminate at approximately the same position on the tube 203 as the sensor 3020. Thus, the configuration minimizes temperature drop from the end of the heating filaments to the sensor 3020. This configuration can also reduce temperature drop from the end of the heating filaments and a second heating filament in an additional section of tube. The configuration can also be used to heat the covering connector of the sensor 3020, thereby reducing heat losses to a cold ambient, and further improving accuracy in temperature measurement.

[0376] Although the foregoing describes placing one or more sensors at the patient end of a tube 201, it should be appreciated that this sensor configuration can be applied along any part of the fluid pathway of a tube 201.

[0377] For example, FIG. 34 illustrates a portion of a segmented inspiratory limb 3401 for use with a respiratory humidification system, the segmented inspiratory limb 3401 comprising a first segment 3401a and a second segment 3401b and having an intermediate connector 3403 configured to couple first heater wires 3405a to second heater wires 3405b and a first temperature sensor 3407a to a second temperature sensor 3407b in the respective segments 3401a and 3401b. Coupling the two segments 3401a and 3401b can comprise mechanically coupling the segments to form a single can be conduit through which humidified gases can be delivered to a user wherein mechanically coupling the segments 3401a and 3401b can result in electrically coupling the respective heater wires 3405a, 3405b and the respective temperature sensors 3407a, 3407b through the intermediate connector 3403. The PCB assembly 3301 shown in FIGS. 33A and 33B is suitable for use with the intermediate connector 3403 of FIG. 34.

[0378] Returning again to FIG. 34, the segmented inspiratory limb 3401 can comprise a structure 3409 forming a lumen through which humidified gases can pass. The structure 3409 can include paths formed within walls of the structure 3409 configured to house heater wires 3405a or 3405b such that the heater wires 3405a or 3405b are shielded

from the humidified gases travelling through the lumen and/or are covered by an external surface of the structure **3409** so that they are not exposed. For example, the structure **3409** can be a composite tube wherein the heater wire paths are coils molded into the tube, as discussed above. The structure **3409** can comprise any type of suitable material and can include insulating material and/or flexible material. In some embodiments, the structure **3409** and the intermediate connector **3403** can be configured such that, when the first and second segments **3401a** and **3401b** are mechanically coupled, the heater wires **3405a** and **3405b** wrap over the intermediate connector **3403** in such a way as to be electrically coupled to the intermediate connector **3403**. In some embodiments, the first segment **3401a** and/or the intermediate connector **3403** can exclude any flying leads for connecting to the second segment **3401b**, thereby facilitating connection of the second segment **3401b** to the first segment **3401a**.

[0379] The structure **3409** at complementary ends of the first and second segments **3401a** and **3401b** can be configured to house the intermediate connector **3403**. Thus, the intermediate connector **3403** can be internal to the inspiratory limb **3401**. In some embodiments, the complementary ends of the first and second segments **3401a** and **3401b** can be configured to shield the intermediate connector **3403** from humidified gases travelling through the inspiratory limb **3401**. In some embodiments, the intermediate connector **3403** is both internal to the inspiratory limb **3401** and shielded from humidified gases in the conduit, thereby reducing or eliminating exposure of electrical connections on the intermediate connector **3403**.

[0380] In some embodiments, the first heater wires **3405a** can comprise two wires **3411** and **3413** and the second heater wires **3405b** can comprise two wires **3415** and **3417**. The two wires **3411** and **3413** in the first segment **3401a** can be electrically coupled to one another through electrical components **3419** wherein the electrical coupling creates an electrical path through the wire **3411**, at least a portion of the electrical components **3419**, and the wire **3413**. Similarly, the two wires **3415** and **3417** in the second segment **3401b** can be electrically coupled to one another through electrical components **3419** and/or electrically shorted together at an end of the segment **3401b** opposite the intermediate connector **3403**, such as through a patient-end connector (not shown). By coupling the wires **3415** and **3417**

of the second segment **3401b** at the intermediate connector **3403**, electrical connections at the patient-end of the inspiratory limb **3401** are reduced or eliminated which can reduce cost, system complexity, and/or risk to the patient.

[0381] The intermediate connector **3403** can be configured to allow a single controller to control power to the heater wires **3405a**, **3405b**, such as a humidifier controller. In some embodiments, the humidifier controller controls the heater wires **3405a**, **3405b** without any additional control functionality located on the intermediate connector **3403**. For example, the intermediate connector **3403** can include passive components without any logic circuitry wherein the passive components direct power to heater wires **3405a** and/or **3405b** as selected by the controller. This can allow the intermediate connector **3403** to be designed using relatively inexpensive components and can reduce the complexity of the design.

[0382] In some embodiments, heating of the two segments **3401a** and **3401b** can be accomplished using a maximum of four wires in each segment **3401a**, **3401b**. For example, in the first segment **3401a** the four wires can include a first heater wire **3411**, a second heater wire **3413**, a signal temperature sensor wire **3419**, and a return temperature sensor wire **3421**. In the second segment **3401b** the four wires can include a first heater wire **3415**, a second heater wire **3417**, a signal temperature sensor wire **3423**, and a return temperature sensor wire **3425**. By coupling the second heater wires **3415**, **3417** to the first heater wires **3411**, **3413** at connection points **3427**, and by coupling the second temperature sensor wires **3423**, **3425** to the first temperature sensor wires **3419**, **3421** at connection points **3427**, a controller can be configured to provide power independently to the first heater wires **3405a** and the second heater wires **3405b** and to read temperature sensor data independently from the temperature sensors **204a** and **204b** without including more than four wires in either segment **3401a** or **3401b**. In some embodiments, control of the heater wires **3405a** and **3405b** and reading of the temperature sensors **3407a** and **3407b** can be accomplished using less than four wires in each segment (*e.g.*, using three wires or using two wires) or more than four wires in each segment (*e.g.*, using five wires, using six wires, using seven wires, using eight wires, or using more than eight wires).

[0383] The intermediate connector **3403** can include electrical components **3419** configured to allow a controller to selectively control heater wires **3405a**, **3405b**. The

controller can be configured to control heating of the inspiratory limb **3401** using two modes wherein a first control mode comprises providing power to the heater wires **3405a** in the first segment, and a second control mode comprises providing power to the heater wires **3405a** and **3405b** in the first and second segments **3401a** and **3401b**. Thus, the controller can be configured to independently control heater wire sections. This ability allows for the controller to control heating of the inspiratory limb **3401** when the second segment **3401b** is not present by solely controlling the heating of the inspiratory limb according to the first control mode, thereby allowing for the respiratory humidification system to be used in a variety of circumstances without modifying the controller or humidification unit. In some embodiments, the control modes can include a mode where power is delivered only to the heater wires **3405b** in the second segment **3401b**. In some embodiments, the controller includes an electrical power source that provides electrical current. The first and second control modes can be based at least in part on the voltage supplied by the power source wherein a positive voltage or positive current can trigger the first control mode and a negative voltage or a negative current can trigger the second control mode. In some embodiments, the power source provides rectified AC or DC power to the heater wires **3405a**, **3405b** and a change in the rectification or polarity triggers a change in the control mode. By switching control modes, control of heating in the breathing circuit can be accomplished with any power supply that can switch the polarity of the output signal. In some embodiments, the amount of power provided to the heater wires **3405a**, **3405b** can be adjusted by adjusting a duty cycle of power applied to the heater wires **3405a**, **3405b**. For example, pulse-width modulation (PWM) can be used to power the heater wires **3405a**, **3405b** and the duty cycle of the PWM signal can be adjusted to control the power delivered. In another example, the amount of power provided to the heater wires **3405a**, **3405b** can be adjusted by controlling the amplitude of the power signal.

[0384] The intermediate connector **3403** can include electrical components **3421** configured to allow a controller to selectively read temperature sensors **3407a**, **3407b**. Selective reading can be accomplished through the use of a source of electrical current wherein applying a positive current across the wires **3419** to **3421** can result in the controller measuring a temperature-related signal from the first temperature sensor **3407a** and applying

a negative current across the wires **3419** and **3421** can result in the controller measuring a temperature-related signal from the second temperature sensor **3407b** or from both the first and second temperature sensors **3407a**, **3407b**. The controller can use the readings from the temperature sensors **3407a**, **3407b** to adjust power to the heater wires **3405a**, **3405b**, using, for example pulse-width modulation. The first temperature sensor **3407a** can be positioned near the connection or intersection of the first and second segments **3401a** and **3401b** to provide to the controller a temperature of gases entering the second segment **3401b**, which can correspond to entering an incubator or other such region having a different ambient temperature. The second temperature sensor **3407b** can be positioned at a patient-end of the second segment **3401b** to provide to the controller a temperature of gases delivered to the patient or the temperature prior to the final piece before the patient, such as a wye-piece. The controller can use these temperature readings to adjust power to the heater wires **3405a**, **3405b** to maintain the temperature of the gas at the patient-end of the inspiratory limb **3401** at a targeted or suitable temperature. The targeted or suitable temperature can vary depending at least in part on the application and environment it is being used in, and can be about 37°C, about 40 °C, at least about 37°C and/or less than or equal to about 38°C, at least about 36.5°C and/or less than or equal to about 38.5°C, at least about 36°C and/or less than or equal to about 39°C, at least about 35°C and/or less than or equal to about 40°C, at least about 37°C and/or less than or equal to about 41°C, or at least about 39.5°C and/or less than or equal to about 40.5°C. In some embodiments, the second temperature sensor **3407b** can be positioned inside the incubator but not attached to the breathing circuit. By measuring the temperature inside the incubator, the temperature of the second segment **3401b** can be calculated.

[0385] The controller can independently control the amount of power delivered in the first and second control modes, as described herein. Based at least in part on feedback from the temperature sensors **3407a** and/or **3407b**, the controller can independently adjust power delivered in the first and second control modes, thereby resulting in varying heater power ratios between the first and second segments **3401a** and **3401b**.

[0386] In some embodiments, the first temperature sensor **3407a** is positioned within the flow of gas within the inspiratory limb **3401**. In some embodiments, the

intermediate connector **3403** or the first segment **3401a** can include a mechanical component that decreases turbulence in the flow of the gas across the first temperature sensor **3407a** which can increase accuracy in the temperature sensor's **3407a** readings. In some embodiments, the mechanical component (e.g., a cross-member feature within the inspiratory conduit) that decreases turbulence also secures the temperature sensor **3407a** within the flow of the gases. In some embodiments, the intermediate connector **3403** and the mechanical component are configured to thermally isolate the temperature sensor **3407a** from the electrical components on the intermediate connector **3403**.

[0387] In some embodiments, the intermediate connector **3403** includes additional connection points in addition to the connection points **3427** illustrated in FIG. **34**. The additional connection points can be used to incorporate further functionality into the breathing circuit such as, for example, incorporating a memory device (PROM), a micro-controller, additional circuits, and the like.

[0388] Moreover, the composite tube **201** can be an inspiratory tube or an expiratory tube.

Placement of Spiral-Style Connector

[0389] Reference is next made to FIGS. **35A–35F** which show a connector without electrical connectivity to a PCB. However, as will be appreciated by those skilled in the art, that the connector could be equally adapted to have electrical connectivity to a PCB. The connector is suitable for connecting to, for example, a patient interface or a humidifier. It is particularly suited for use as a patient-end connector and/or device-end connector in an obstructive-sleep apnea environment.

[0390] A spiral-ended molded insert **3501** is provided. The end of the insert **3501** opposite the spiral end is molded for insertion on or attachment to a humidifier port, and/or a patient interface port, and/or any other desired component. The insert **3501** can be a hard material, such as a hard plastic, for example, polypropylene.

[0391] As shown in FIG. **35C**, the spiral end of the insert **3501** is screwed into the compliant turns of the tube **201**. In this example, the spiral turns of the insert **3501** are sized and configured to fit into the turns of the first elongate member **203** of the tube **201**.

[0392] It should be noted that, in the case of a tube having one or more electrically powered wires therein, an electrical connection can be provided on at least a portion of the insert **3501**. When the insert **3501** is installed, the electrical connector will preferably align with the wires, thereby facilitating electrical connection. Solder or the like can then be used to secure the connection.

[0393] A member **3503** can be inserted or molded on top of at least a portion of insert **3501** and, optionally, tube **201** to promote the attachment between the insert **3501** and the tube **201**. The member **3503** can be a hard material or a soft material, such as a soft plastic, rubber, or PTFE, for example polypropylene. In some cases, the insert **3501** (or at least the spiral end of the insert **3501**) provides sufficient lateral crush resistance to enable high-pressure molding techniques to be used, where the pressure can exceed the lateral crush resistance of the tube **201** without the insert **3501**. Member **3503** can also advantageously provide a soft surface to grip on when inserting and removing tube from a component.

[0394] The foregoing method of attaching a connector to a spiral-wound tube is provided by way of example. The method described herein does not imply a fixed order to the steps. Nor does it imply that any one step is required to practice the method. Embodiments may be practiced in any order and combination that is practicable.

Placement of Alternative Patient-End Connector

[0395] Reference is next made to FIGS. **36A–36K**. FIGS. **36A** and **36B** show a patient-end connector **3601** without electrical connectivity. The connector **3601** has a patient end **3603** with a standard-size medical taper suitable for use with a patient interface. The tube end **3605** of the connector **3601** is suitable for connection to a composite tube **201**, as described below. The connector **3601** is preferably a pre-molded component formed from a suitable material such as plastic, rubber, or PTFE.

[0396] As shown in FIGS. **36C** and **36D**, a portion (e.g., a 10-mm portion) of the second elongate member **205** is stripped away to reveal a small length of the one or more filaments **215** embedded therein. Preferably, about 5 mm or 10 mm of the filaments **215** are revealed. As shown in FIG. **36D**, the filaments **215** are twisted together and optionally secured, for example, by soldering, thereby creating a closed loop circuit.

[0397] Turning next to FIG. 36G, the tube end 3605 of the connector 3601 is inserted into the tube 201 and the twisted filaments 215 are placed under a retaining loop 3607. The retaining loop 3607 diminishes movement of the filaments 215 during molding. The retaining loop 3607 also advantageously aligns the rotational pitch of the composite tube 201 to the connector 3601, which in turn promotes proper alignment of the tube 201 in the mold. The combination of connector 3601 and composite tube 201 is designated here as a connector-tube assembly 3609.

[0398] As shown in FIG. 36H, a mold tool core 3611 is inserted into the connector 3601. As shown in FIG. 36I, the connector-tube assembly 3609 and core 3611 are placed in an injection mold tool 3613. In FIG. 36J, a molded material 3615 is molded over junction region between the composite tube 201 and the connector 3601, thereby bonding composite tube 201 and the connector 3601. Suitable molded materials 3615 include plastic and rubber. The connector-tube assembly 3609 and core 3611 are removed from the injection mold tool (not shown), as in FIG. 36K. The core 3611 is removed, thereby providing a composite tube 201 with a patient-end connector 3601.

[0399] The foregoing method of attaching a connector to a composite tube is provided by way of example. The method described does not imply a fixed order to the steps. Nor does it imply that any one step is required to practice the methods. Embodiments may be practiced in any order and combination that is practicable.

[0400] The foregoing description of the invention includes preferred forms thereof. Modifications may be made thereto without departing from the scope of the invention. To those skilled in the art to which the invention relates, many changes in construction and widely differing embodiments and applications of the invention will suggest themselves without departing from the scope of the invention as defined in the appended claims. The disclosures and the descriptions herein are purely illustrative and are not intended to be in any sense limiting.

[0401] Through the description and the claims, the terms “comprises,” “comprising,” and the like are to be construed in an inclusive sense, that is, in the sense of “including but not limited to,” unless the context clearly requires otherwise.

[0402] Although the invention has been described by way of example and with reference to possible embodiments thereof, it is to be understood that modifications or improvements may be made thereto without departing from the spirit and scope of the invention and without diminishing its attendant advantages. Furthermore, where reference has been made to specific components or integers of the invention having known equivalents, such equivalents are herein incorporated as if individually set forth.

[0403] Any discussion of the prior art throughout the specification should in no way be considered as an admission that such prior art is widely known or forms part of the common general knowledge in the field anywhere in the world.

WHAT IS CLAIMED IS:

1. A breathing tube comprising:
a first elongate member comprising a hollow body spirally wound to form at least in part an elongate tube having a longitudinal axis, a lumen extending along the longitudinal axis, and a hollow wall surrounding the lumen, the wall having an inner portion proximal the lumen and an outer portion facing away from the lumen,
wherein the inner portion of the wall has a smaller thickness than the outer portion of the wall.
2. The breathing tube of Claim 1, further comprising a second elongate member spirally wound and joined between adjacent turns of the first elongate member, the second elongate member forming at least a portion of the lumen of the elongate tube.
3. The breathing tube of Claim 1 or 2, wherein the thickness of the outer portion of the wall is in the range of about 0.14 mm and about 0.44 mm.
4. The breathing tube of any of Claims 1–3, wherein the thickness of the outer portion of the wall is about 0.24 mm.
5. The breathing tube of any of Claims 1–4, wherein the thickness of the inner portion of the wall is in the range of about 0.05 mm and about 0.30 mm.
6. The breathing tube of any of Claims 1–5, wherein the thickness of the inner portion of the wall is about 0.10 mm.
7. A breathing tube comprising:
a first elongate member comprising a hollow body component,
wherein the weight per length of the tube within at least a portion of the 300 mm nearest an end of the tube is less than about 0.08 g/mm.
8. The breathing tube of Claim 7, wherein the first elongate member comprises a hollow body spirally wound to form at least in part an elongate tube having a longitudinal axis, a lumen extending along the longitudinal axis, and a hollow wall surrounding the lumen.
9. The breathing tube of Claim 8, further comprising a second elongate member spirally wound and joined between adjacent turns of the first elongate member, the second elongate member forming at least a portion of the lumen of the elongate tube.

10. The breathing tube of Claim 9, comprising one or more conductive filaments embedded or encapsulated within the second elongate member.

11. The breathing tube of Claim 10, wherein at least one of the one or more conductive filaments is a heating filament.

12. The breathing tube of Claim 10 or 11, wherein at least one of the one or more conductive filaments is a sensing filament.

13. The breathing tube of any of Claims 7–12, wherein the tube mass in the 300 mm nearest an end of the tube is less than about 24 g.

14. The breathing tube of any of Claims 7–13, wherein the weight per length of the tube within at least a portion of the 300 mm nearest an end of the tube is less than about 0.06 g/mm.

15. The breathing tube of any of Claims 7–14, wherein the tube mass in the 300 mm nearest an end of the tube is less than about 16 g.

16. The breathing tube of any of Claims 7–15, wherein the thickness of the wall is at most about 0.50 mm.

17. A breathing tube comprising:

a first elongate member comprising a hollow body spirally wound to form at least in part an elongate tube having a longitudinal axis, a lumen extending along the longitudinal axis, and a hollow wall surrounding the lumen, the wall having an inner portion proximal the lumen and an outer portion facing away from the lumen,

wherein, in at least a portion of the composite tube, when force is applied to the outer portion of the wall with a 2.5-mm probe and until the outer portion of the wall contacts the inner portion., the outer portion deflects by a vertical distance that satisfies the equation:

$$D > 0.5 \times F_{2.5},$$

where D represents the vertical distance in millimeters, and F_{2.5} represents the force in Newtons applied by the 2.5-mm probe.

18. The breathing tube of Claim 17, further comprising a second elongate member spirally wound and joined between adjacent turns of the first elongate member, the second elongate member forming at least a portion of the lumen of the elongate tube.

19. The breathing tube of Claim 17 or 18, wherein the outer portion deflects more than about 1 mm when a force of about 1 N is applied with the 2.5-mm probe.

20. A respiratory conduit comprising:

a lumen extending along a longitudinal axis and a wall surrounding the lumen, the lumen defining a gas-flow path when in use; and

an overmolded printed circuit board assembly secured to the wall, the printed circuit board assembly comprising a printed circuit board with a sensor portion disposed in the lumen of the conduit and projecting along the longitudinal axis, and a temperature sensor on a surface of the sensor portion.

21. The conduit of Claim 20, wherein the temperature sensor is a thermistor.

22. A respiratory conduit comprising:

a lumen extending along a longitudinal axis and walls surrounding the lumen, the lumen defining a gas-flow path when in use; and

a component secured to the walls and extending across the lumen along a diameter or chord line, such that the component generally bisects at least part of the flow path, the component comprising a sensor portion disposed in the lumen and projecting along the longitudinal axis, and a temperature sensor on a surface of the sensor portion.

23. The conduit of Claim 22, wherein the temperature sensor is a thermistor.

24. The conduit of Claim 22 or 23, wherein the component is a printed circuit board.

25. The conduit of any of Claims 22–24, wherein the electrical connection spans the component's length along the diameter or chord line.




FIG. 1




FIG. 2A




FIG. 2B




FIG. 2C



FIG. 2D



FIG. 2E




FIG. 2F




FIG. 2G




FIG. 2H




FIG. 3




FIG. 4




FIG. 5A

205



FIG. 5B

205



FIG. 5C




FIG. 5D



FIG. 5E



FIG. 5F




FIG. 6A




FIG. 6B




FIG. 6C



FIG. 6D




FIG. 7A




FIG. 7B




FIG. 7C




FIG. 7D

20/84




FIG. 7E




FIG. 7F




FIG. 7G




FIG. 8A




FIG. 8B




FIG. 9A



FIG. 9B




FIG. 9C



FIG. 9D




FIG. 9E




FIG. 9F




FIG. 10A




FIG. 10B




FIG. 11A




FIG. 11B




FIG. 11C




FIG. 11D




FIG. 12A




FIG. 12B




FIG. 12C




FIG. 13

RELAXED STATE

STRETCHED STATE.




FIG. 14A




FIG. 15A




FIG. 14B



FIG. 15B




FIG. 14C




FIG. 15C



FIG. 14D




FIG. 15D



FIG. 14E




FIG. 15E




FIG. 16




FIG. 17




FIG. 18





FIG. 19A






FIG. 20A




FIG. 20B




FIG. 20C





FIG. 21B




FIG. 21C




FIG. 21D




FIG. 21E




FIG. 21F




FIG. 22A




FIG. 22B




FIG. 22C




FIG. 23A




FIG. 23B




FIG. 23C




FIG. 23D




FIG. 23E




FIG. 23F

203




FIG. 23G

203




FIG. 23H




FIG. 24A




FIG. 24B



FIG. 24C



FIG. 24D




FIG. 24E




FIG. 24F







FIG. 25A






FIG. 25E




FIG. 25F




FIG. 25G




FIG. 25H




FIG. 25I



FIG. 25J




FIG. 25K



FIG. 25L




FIG. 26A

FIG. 26B




FIG. 26C

FIG. 26D




FIG. 26E




FIG. 27A




FIG. 27B




FIG. 27C




FIG. 27D




FIG. 27E




FIG. 28A




FIG. 28B




FIG. 28C




FIG. 28D




FIG. 28E




FIG. 28F




FIG. 29A




FIG. 29B




FIG. 29C




FIG. 29D




FIG. 29E



FIG. 29F




FIG. 29G




FIG. 29H



FIG. 29I




FIG. 29J




FIG. 29K




FIG. 29L




FIG. 30A




FIG. 30B




FIG. 30C

FIG. 30D




FIG. 30E



FIG. 30F




FIG. 30G




FIG. 30H




FIG. 30I




FIG. 30J

FIG. 30K

70/84




FIG. 30L




FIG. 30M




FIG. 30N




FIG. 300




FIG. 31A





FIG. 31B



75/84




FIG. 32D




FIG. 32C




FIG. 33B






FIG. 33A






FIG. 34




FIG. 35A




FIG. 35B




FIG. 35C




FIG. 35D

80/84




FIG. 35E



FIG. 36A




FIG. 36B




FIG. 36C




FIG. 36D




FIG. 36E



FIG. 36F




FIG. 36G




FIG. 36H



FIG. 36I




FIG. 36J




FIG. 36K

84/84




FIG. 37A




FIG. 37B



INTERNATIONAL SEARCH REPORT

International application No.

PCT/NZ2013/000222

A. CLASSIFICATION OF SUBJECT MATTER

A61M 16/08 (2006.01)

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPODOC, WPI and A61M 16/08, 39/08, 2016/08, 2039/08, F16L 11/20, 11/24, B29D 24/00, B29L 2023/007 and keywords: spiral and double and wall and weight and length and deflect and temperature and sensor and similar terms.

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
	Documents are listed in the continuation of Box C	

 Further documents are listed in the continuation of Box C
 See patent family annex

* Special categories of cited documents:		
"A" document defining the general state of the art which is not considered to be of particular relevance	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention	
"E" earlier application or patent but published on or after the international filing date	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone	
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art	
"O" document referring to an oral disclosure, use, exhibition or other means	"&" document member of the same patent family	
"P" document published prior to the international filing date but later than the priority date claimed		

Date of the actual completion of the international search
28 March 2014Date of mailing of the international search report
28 March 2014

Name and mailing address of the ISA/AU

 AUSTRALIAN PATENT OFFICE
 PO BOX 200, WODEN ACT 2606, AUSTRALIA
 Email address: pct@jpaustralia.gov.au
 Facsimile No.: +61 2 6283 7999

Authorised officer

 David Melhuish
 AUSTRALIAN PATENT OFFICE
 (ISO 9001 Quality Certified Service)
 Telephone No. 0262832426

INTERNATIONAL SEARCH REPORT		International application No.
C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT		PCT/NZ2013/000222
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P,A	WO 2012/164407 A1 (FISHER & PAYKEL HEALTHCARE CORPORATION LIMITED) 06 December 2012 whole document	1 - 6
A	US 2004/0244858 A1 (JEONG) 09 December 2004 whole document	1 - 6
X A	US 5640951 A (HUDDART et al.) 24 June 1997 column 5 lines 30 to 48 whole document	7, 8, 13 - 16 1 - 6
A	EP 2133611 B1 (COVIDIEN AG) 28 September 2011 whole document	1 - 6
A	US 4531551 A (EICHELBERGER et al.) 30 July 1985 whole document	1 - 6
A	US 2073335 A (CONNELL) 09 March 1937 whole document	1 - 6
X	US 2009/0078259 A1 (KOOIJ et al.) 26 March 2009 paragraphs 51 to 61 and 71	7, 13 - 16
X	WO 2012/053910 A1 (FISHER & PAYKEL HEALTHCARE LIMITED) 26 April 2012 page 17 line 30, figure 3B	7, 13 - 16
A	US 5600752 A (LOPATINSKY) 04 February 1997 whole document	7
X	US 2004/0079371 A1 (GRAY) 29 April 2004 paragraphs 7, 49 and 50	7, 8, 13 - 17, 19
A	WO 1996/020748 A1 (MALLINCKRODT MEDICAL, INC.) 11 July 1996 whole document	17
A	WO 2003/026721 A2 (FUKUNAGA et al.) 03 April 2003 whole document	17
A	US 2003/0183294 A1 (CARLSON) 02 October 2003 whole document	17
A	US 2004/0099268 A1 (SMITH et al.) 27 May 2004 whole document	17
X	US 2004/0182392 A1 (GERDER et al.) 23 September 2004 paragraphs 22 to 24, figure 1	20, 21
X	US 7814907 B2 (BREMNER et al.) 19 October 2010 column 6 lines 44 to 56, figure 3	22 - 25
	JP 11-033119 A (FRONTIER KK) 09 February 1999	

INTERNATIONAL SEARCH REPORT		International application No.
C (Continuation).		PCT/NZ2013/000222
DOCUMENTS CONSIDERED TO BE RELEVANT		
Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	figures 1 and 3, paragraphs 9 and 10	22 - 25
Y	US 6138674 A (GULL et al.) 31 October 2000 column 4 lines 39 to 48, figure 2	20, 21
Y	WO 2007/051230 A1 (RESMED LTD) 10 May 2007 paragraphs 29 to 33, figures 2 and 3	20, 21
Y	US 2004/0101026 A1 (NITTA et al.) 27 May 2004 figure 2	20, 21

Box No. II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
the subject matter listed in Rule 39 on which, under Article 17(2)(a)(i), an international search is not required to be carried out, including
2. Claims Nos.:
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
3. Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a)

Box No. III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

See Supplemental Box for Details

1. As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. As all searchable claims could be searched without effort justifying additional fees, this Authority did not invite payment of additional fees.
3. As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- The additional search fees were accompanied by the applicant's protest and, where applicable, the payment of a protest fee.
- The additional search fees were accompanied by the applicant's protest but the applicable protest fee was not paid within the time limit specified in the invitation.
- No protest accompanied the payment of additional search fees.

Supplemental Box**Continuation of: Box III**

This International Application does not comply with the requirements of unity of invention because it does not relate to one invention or to a group of inventions so linked as to form a single general inventive concept.

This Authority has found that there are different inventions based on the following features that separate the claims into distinct groups:

- Claims 1 to 6 directed to a breathing tube having a spirally wound hollow body forming a lumen, wherein the inner portion of the wall of the lumen is thinner than the outer portion of the wall. The feature of the inner wall being thinner is specific to this group of claims.
- Claims 7 to 16 directed to a breathing tube wherein the weight per length of a portion of the tube is less than 0.08 g/mm. The feature of this particular weight per length is specific to this group of claims.
- Claims 17 to 19 directed to a breathing tube having a spirally wound hollow body forming a lumen, wherein when force is applied to the outer portion of the wall with a 2.5 mm probe and the outer portion of the wall contacts the inner portion, the outer portion deflects by a vertical distance in millimetres that is greater than half the applied force in Newtons. The feature of this particular amount of deflection is specific to this group of claims.
- Claims 20 to 25 directed to a respiratory conduit with a temperature sensor. The feature of the temperature sensor is specific to this group of claims.

PCT Rule 13.2, first sentence, states that unity of invention is only fulfilled when there is a technical relationship among the claimed inventions involving one or more of the same or corresponding special technical features. PCT Rule 13.2, second sentence, defines a special technical feature as a feature which makes a contribution over the prior art.

When there is no special technical feature common to all the claimed inventions there is no unity of invention.

In the above groups of claims, the identified features may have the potential to make a contribution over the prior art but are not common to all the claimed inventions and therefore cannot provide the required technical relationship. Therefore there is no special technical feature common to all the claimed inventions and the requirements for unity of invention are consequently not satisfied *a priori*.

INTERNATIONAL SEARCH REPORT Information on patent family members		International application No. PCT/NZ2013/000222	
This Annex lists known patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.			
Patent Document/s Cited in Search Report		Patent Family Member/s	
Publication Number	Publication Date	Publication Number	Publication Date
WO 2012/164407 A1	06 Dec 2012	CA 2838011 A1	06 Dec 2012
		FR 2975916 A1	07 Dec 2012
		GB 2505622 A	05 Mar 2014
		IT TO20120486 A1	04 Dec 2012
		TW 201315494 A	16 Apr 2013
		WO 2012164407 A1	06 Dec 2012
US 2004/0244858 A1	09 Dec 2004	JP 2004537012 A	09 Dec 2004
		KR 20030062002 A	23 Jul 2003
		KR 100486150 B1	29 Apr 2005
		KR 20030062003 A	23 Jul 2003
		KR 100486151 B1	29 Apr 2005
		KR 20030062004 A	23 Jul 2003
		KR 20030067239 A	14 Aug 2003
		KR 20030073825 A	19 Sep 2003
		US 2004244858 A1	09 Dec 2004
		WO 03010459 A1	06 Feb 2003
US 5640951 A	24 Jun 1997	EP 0672430 A2	20 Sep 1995
		JP H08109984 A	30 Apr 1996
		US 5640951 A	24 Jun 1997
EP 2133611 B1	28 Sep 2011	EP 2133611 B1	28 Sep 2011
		JP 2009297514 A	24 Dec 2009
		US 2009301593 A1	10 Dec 2009
		US 8312899 B2	20 Nov 2012
US 4531551 A	30 Jul 1985	EP 0111248 A2	20 Jun 1984
		EP 0111248 B1	27 Aug 1986
		JP S59113392 A	30 Jun 1984
		JP H022031 B2	16 Jan 1990
		US 4531551 A	30 Jul 1985
US 2073335 A	09 Mar 1937	US 2099843 A	23 Nov 1937
US 2009/0078259 A1	26 Mar 2009	AU 2008221506 B2	20 Jan 2011
		CN 101396576 A	01 Apr 2009
		EP 2039386 A1	25 Mar 2009
		EP 2039386 B1	20 Nov 2013

Due to data integration issues this family listing may not include 10 digit Australian applications filed since May 2001.
Form PCT/ISA/210 (Family Annex)(July 2009)

INTERNATIONAL SEARCH REPORT		International application No.	
Information on patent family members		PCT/NZ2013/000222	
This Annex lists known patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.			
Patent Document/s Cited in Search Report		Patent Family Member/s	
Publication Number	Publication Date	Publication Number	Publication Date
		EP 2438953 A1	11 Apr 2012
		JP 2009072596 A	09 Apr 2009
		NZ 571348 A	28 May 2010
		NZ 584073 A	26 Aug 2011
		NZ 594204 A	21 Dec 2012
		US 2009078259 A1	26 Mar 2009

Due to data integration issues this family listing may not include 10 digit Australian applications filed since May 2001.
Form PCT/ISA/210 (Family Annex)(July 2009)

INTERNATIONAL SEARCH REPORT Information on patent family members		International application No. PCT/NZ2013/000222	
This Annex lists known patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.			
Patent Document/s Cited in Search Report		Patent Family Member/s	
Publication Number	Publication Date	Publication Number	Publication Date
WO 2012/053910 A1	26 Apr 2012	CA 2814601 A1	26 Apr 2012
		CN 103249448 A	14 Aug 2013
		EP 2629821 A1	28 Aug 2013
		GB 2498144 A	03 Jul 2013
		JP 2013540037 A	31 Oct 2013
		TW 201247257 A	01 Dec 2012
		US 2014000626 A1	02 Jan 2014
		WO 2012053910 A1	26 Apr 2012
US 5600752 A	04 Feb 1997	None	
US 2004/0079371 A1	29 Apr 2004	AU 2003244171 B2	15 Nov 2007
		AU 2003244579 A1	25 Mar 2004
		AU 2003244579 B2	11 Oct 2007
		AU 2003267875 A1	30 Apr 2004
		AU 2003267875 B2	06 Nov 2008
		BR 0303478 A	08 Sep 2004
		BR 0303478 B1	18 Feb 2014
		BR 0303481 A	08 Sep 2004
		BR 0303481 B1	11 Feb 2014
		CA 2439762 A1	09 Mar 2004
		CA 2439765 A1	09 Mar 2004
		CA 2498201 A1	25 Mar 2004
		CA 2624182 A1	09 Mar 2004
		CA 2624190 A1	09 Mar 2004
		CA 2685020 A1	25 Mar 2004
		EP 1396276 A2	10 Mar 2004
		EP 1396276 B1	16 Nov 2005
		EP 1396277 A2	10 Mar 2004
		EP 1396277 B1	16 Nov 2005
		EP 1484161 A2	08 Dec 2004
		EP 1484161 B1	03 Jan 2007
		EP 1495855 A2	12 Jan 2005
		EP 1495855 B1	10 Jan 2007
		EP 1545863 A1	29 Jun 2005

Due to data integration issues this family listing may not include 10 digit Australian applications filed since May 2001.
Form PCT/ISA/210 (Family Annex)(July 2009)

INTERNATIONAL SEARCH REPORT Information on patent family members		International application No. PCT/NZ2013/000222	
This Annex lists known patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.			
Patent Document/s Cited in Search Report		Patent Family Member/s	
Publication Number	Publication Date	Publication Number	Publication Date
		EP 1545863 B1	19 Aug 2009
		EP 1884343 A2	06 Feb 2008
		EP 1884343 B1	24 Jun 2009
		HK 1059748 A1	03 Mar 2006
		HK 1059749 A1	03 Mar 2006
		HK 1068844 A1	30 Mar 2007
		HK 1068845 A1	30 Mar 2007
		HK 1074188 A1	30 Oct 2009
		HK 1109364 A1	28 Aug 2009
		JP 2004275728 A	07 Oct 2004
		JP 4317416 B2	19 Aug 2009
		JP 2004148817 A	27 May 2004
		JP 4357261 B2	04 Nov 2009
		JP 2005537959 A	15 Dec 2005
		JP 4398372 B2	13 Jan 2010
		JP 2008307899 A	25 Dec 2008
		JP 4896091 B2	14 Mar 2012
		JP 2012076463 A	19 Apr 2012
		SG 108937 A1	28 Feb 2005
		SG 111150 A1	30 May 2005
		SG 128522 A1	30 Jan 2007
		SG 128523 A1	30 Jan 2007
		TW I237574 B	11 Aug 2005
		TW I283186 B	01 Jul 2007
		US 2004081784 A1	29 Apr 2004
		US 7291240 B2	06 Nov 2007
		US 2006108066 A1	25 May 2006
		US 7468116 B2	23 Dec 2008
		US 2004079371 A1	29 Apr 2004
		US 7469719 B2	30 Dec 2008
		US 2006165829 A1	27 Jul 2006
		US 2008011413 A1	17 Jan 2008
		US 2009065119 A1	12 Mar 2009
		US 2009126817 A1	21 May 2009
		US 2009260737 A1	22 Oct 2009
		WO 2004024429 A1	25 Mar 2004

Due to data integration issues this family listing may not include 10 digit Australian applications filed since May 2001.
Form PCT/ISA/210 (Family Annex)(July 2009)

INTERNATIONAL SEARCH REPORT Information on patent family members		International application No. PCT/NZ2013/000222	
This Annex lists known patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.			
Patent Document/s Cited in Search Report		Patent Family Member/s	
Publication Number	Publication Date	Publication Number	Publication Date
WO 1996/020748 A1	11 Jul 1996	IT 1272859 B	01 Jul 1997
		WO 9620748 A1	11 Jul 1996
WO 2003/026721 A2	03 Apr 2003	AU 2003225850 A1	19 Apr 2004
		BR 0212774 A	14 Dec 2004
		BR 0212774 B1	29 Nov 2011
		CA 2460773 A1	03 Apr 2003
		CA 2500081 A1	08 Apr 2004
		CA 2767462 A1	03 Apr 2003
		CN 1589167 A	02 Mar 2005
		EP 1432475 A2	30 Jun 2004
		EP 1432475 B1	07 Jun 2006
		EP 1556111 A1	27 Jul 2005
		EP 1556111 B1	07 Dec 2011
		EP 1621224 A2	01 Feb 2006
		EP 1729839 A2	13 Dec 2006
		HK 1073807 A1	15 Jan 2010
		JP 2005503869 A	10 Feb 2005
		JP 4348182 B2	21 Oct 2009
		JP 2006500152 A	05 Jan 2006
		MX PA04002687 A	18 Jun 2004
		NZ 532166 A	26 Jan 2007
		TW 1281870 B	01 Jun 2007
		US 2003075176 A1	24 Apr 2003
		US 6874500 B2	05 Apr 2005
		US 2004194781 A1	07 Oct 2004
		US 7261105 B2	28 Aug 2007
		US 2005039747 A1	24 Feb 2005
		US 7275541 B2	02 Oct 2007
		US 2003183232 A1	02 Oct 2003
		US 7717109 B2	18 May 2010
		US 2005188990 A1	01 Sep 2005
		WO 03026721 A2	03 Apr 2003
		WO 2004028609 A1	08 Apr 2004
		WO 2005079377 A2	01 Sep 2005

Due to data integration issues this family listing may not include 10 digit Australian applications filed since May 2001.
Form PCT/ISA/210 (Family Annex)(July 2009)

INTERNATIONAL SEARCH REPORT		International application No.	
Information on patent family members		PCT/NZ2013/000222	
This Annex lists known patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.			
Patent Document/s Cited in Search Report		Patent Family Member/s	
Publication Number	Publication Date	Publication Number	Publication Date
US 2003/0183294 A1	02 Oct 2003	US 6932119 B2	23 Aug 2005
US 2004/0099268 A1	27 May 2004	AU 4382301 A	15 Nov 2001
		BR 0102116 A	26 Dec 2001
		BR 0102116 B1	21 Sep 2010
		CA 2346628 A1	10 Nov 2001
		CA 2697142 A1	10 Nov 2001
		CA 2833707 A1	10 Nov 2001
		EP 1153627 A2	14 Nov 2001
		EP 1153627 B1	14 Nov 2007
		EP 1477200 A2	17 Nov 2004
		EP 1477200 B1	04 Oct 2006
		EP 1681071 A2	19 Jul 2006
		EP 1681071 B1	18 Feb 2009
		EP 2025359 A1	18 Feb 2009
		EP 2025359 B1	18 Sep 2013
		EP 2305336 A1	06 Apr 2011
		HK 1037551 A1	16 May 2008
		HK 1090312 A1	26 Jun 2009
		JP 2006192310 A	27 Jul 2006
		JP 4699268 B2	08 Jun 2011
		JP 2002058741 A	26 Feb 2002
		JP 5100932 B2	19 Dec 2012
		JP 2010227657 A	14 Oct 2010
		JP 5411078 B2	12 Feb 2014
		JP 2013048935 A	14 Mar 2013
		SG 100691 A1	26 Dec 2003
		TW 513318 B	11 Dec 2002
		US 2001054422 A1	27 Dec 2001
US 6769431 B2	03 Aug 2004		
US 2004099268 A1	27 May 2004		
US 7140366 B2	28 Nov 2006		
US 2006162726 A1	27 Jul 2006		
US 2009078260 A1	26 Mar 2009		
US 2004/0182392 A1	23 Sep 2004	GB 2399760 B	08 Jun 2005
		US 2004182392 A1	23 Sep 2004

Due to data integration issues this family listing may not include 10 digit Australian applications filed since May 2001.
Form PCT/ISA/210 (Family Annex)(July 2009)

INTERNATIONAL SEARCH REPORT Information on patent family members		International application No. PCT/NZ2013/000222	
This Annex lists known patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.			
Patent Document/s Cited in Search Report		Patent Family Member/s	
Publication Number	Publication Date	Publication Number	Publication Date
		US 7647926 B2	19 Jan 2010
US 7814907 B2	19 Oct 2010	AU 2003278649 B2	11 Jun 2009
		CA 2504359 A1	13 May 2004
		EP 1558322 A1	03 Aug 2005
		EP 1558322 B1	08 Jul 2009
		JP 2006504469 A	09 Feb 2006
		US 2006118113 A1	08 Jun 2006
		US 7814907 B2	19 Oct 2010
		WO 2004039444 A1	13 May 2004
JP 11-033119 A	09 Feb 1999	None	
US 6138674 A	31 Oct 2000	None	
WO 2007/051230 A1	10 May 2007	None	
US 2004/0101026 A1	27 May 2004	WO 02094359 A1	28 Nov 2002
End of Annex			
Due to data integration issues this family listing may not include 10 digit Australian applications filed since May 2001. Form PCT/ISA/210 (Family Annex)(July 2009)			