

PROTECT AND RETAIN THE NATURAL LOOK OF STONE.

Natural Stone Treatment WB is a water-based water repellent for limestone, marble, travertine and most other traditional masonry surfaces that delivers the same performance as solvent-based products. Developed to provide long-lasting penetrating protection, Natural Stone Treatment WB is VOC-compliant, ready-to-use and low-odor.



BEAUTIFUL

Natural Stone Treatment WB won't form a surface film or gloss. Only the beautiful natural appearance of the stone comes through.



VERSATILE

This formulation is suitable for interior and exterior surfaces and is compliant in most districts with more restrictive AIM VOC regulations.



BREATHABLE

This product does not trap moisture, maintaining the substrate's natural ability to breathe while keeping bulk water out.



Naturally beautiful.

- Superior to more common silane, siloxane, acrylic or metallic stearate water repellents
- Reduces the severity of biological staining common in regions with high relative humidity
- Treated surfaces resist dark staining and degradation caused by fungal growth, mold and mildew

Recommended for these substrates. Always test. Coverage is in sq.ft./m. per gallon.			
Substrate	Type	Use?	Coverage
Architectural Concrete Block+	Burnished	yes	100 - 175 sq. ft. 9 - 16 sq.m.
	Smooth	yes	
	Split-faced	yes	
	Ribbed	yes	
Concrete	Brick	yes	125 - 175 sq. ft. 12 - 16 sq.m.
	Tile	yes	
	Precast Panels	yes	
	Pavers	yes	
Fired Clay	Cast-in-place	yes	100 - 175 sq. ft. / 9 - 16 sq.m. 200 - 250 sq. ft. / 18 - 23 sq.m. 100 - 175 sq. ft. / 9 - 16 sq.m.
	Brick	yes	
	Tile*	yes	
	Terra Cotta (unglazed)	yes	
Marble, Travertine, Limestone	Pavers*	yes	N/A
	Polished	no	
Granite	Unpolished	yes	100 - 175 sq. ft. 9 - 16 sq.m.
	Polished	no	N/A
Sandstone	Unpolished	no	N/A
	Polished	no	N/A
Slate	Unpolished	yes	125 - 175 sq. ft. 12 - 16 sq.m.
	Unpolished	no	N/A

+Not recommended for polished or glazed surfaces.
 *Siloxane WB Concentrate or other protective treatments may be more appropriate. Contact PROSOCO customer care for more specific recommendations.
 *See specific application instructions for dense surfaces.
Always test to ensure desired results.
 Coverage estimates depend on surface texture and porosity.



WE ARE WHERE YOU ARE.

PROSOCO's nationwide network of field reps and technical advisers from coast to coast are here to help solve your biggest problems, your smallest problems and everything in between.

