



## Sprinter Model Mix MY2007 Weights, Dimensions and Info

Model	Wheelbase [in]	Roof-version	GVWR [lbs]	Engine V6 3.5l Gas/ V6 3.0l CRD	GAWR.F (standard) [lbs]	GAWR.F (option) [lbs]	GAWR.R [lbs]	Base CWF [lbs]	Base CWR [lbs]	Base CW [lbs]	max Payload [lbs]	UVW [lbs]	max Towing [lbs]	max Tongue Weight [lbs]	GCWR [lbs]	avail. Rear Axle Ratios (i)	Vehicle Length [in]	Vehicle Height [in]	Vehicle Width [in]	Front Overhang BA [in]	Rear Overhang [in]	Cargo Bed Length [in]	Ground to Cargo Floor [in]	Cargo Width at Wheelhouse [in]	
2500	Passenger Van*)	144.3	Standard	8,550	Gasoline	3,970	-	5,360	2,864	2,467	5,331	3,219	7,400	5,000	500	13,550	4,727; 5,100	232.5	96.3	79.7	39.5	48.8	32.5	27.6	53.1
	Passenger Van*)	144.3	High	8,550	Gasoline	3,970	-	5,360	2,888	2,522	5,410	3,140	7,400	5,000	500	13,550	4,727; 5,100	232.5	107.5	79.7	39.5	48.8	32.5	27.6	53.1
	Passenger Van*)	170.3	High	8,550	Gasoline	3,970	-	5,360	3,036	2,767	5,803	2,747	7,400	5,000	500	13,550	4,727; 5,100	273.2	107.5	79.7	39.5	63.6	73.2	27.4	53.1
	Passenger Van*)	144.3	Standard	8,550	Diesel	3,970	-	5,360	3,018	2,458	5,476	3,074	7,400	5,000	500	13,550	3,923; 4,182	232.5	96.3	79.7	39.5	48.8	32.5	27.6	53.1
	Passenger Van*)	144.3	High	8,550	Diesel	3,970	-	5,360	3,042	2,513	5,555	2,995	7,400	5,000	500	13,550	3,923; 4,182	232.5	107.5	79.7	39.5	48.8	32.5	27.6	53.1
	Passenger Van*)	170.3	High	8,550	Diesel	3,970	-	5,360	3,188	2,760	5,948	2,602	7,400	5,000	500	13,550	3,923; 4,182	273.2	107.5	79.7	39.5	63.6	73.2	27.4	53.1
	Cargo Van	144.3	Standard	8,550	Gasoline	3,970	-	5,360	2,738	1,973	4,711	3,839	7,400	5,000	500	13,550	4,727; 5,100	232.5	96.3	79.7	39.5	48.8	128.5	27.6	53.1
	Cargo Van	144.3	High	8,550	Gasoline	3,970	-	5,360	2,762	2,028	4,790	3,760	7,400	5,000	500	13,550	4,727; 5,100	232.5	107.5	79.7	39.5	48.8	128.5	27.6	53.1
	Cargo Van	170.3	High	8,550	Gasoline	3,970	-	5,360	2,840	2,282	5,122	3,428	7,400	5,000	500	13,550	4,727; 5,100	273.2	107.5	79.7	39.5	63.6	169.3	27.4	53.1
	Cargo Van	170.3	Mega	8,550	Gasoline	3,970	-	5,360	2,857	2,324	5,181	3,369	7,400	5,000	500	13,550	4,727; 5,100	273.2	116.7	79.7	39.5	63.6	169.3	27.4	53.1
	Cargo Van	170.3 ext.	High	8,550	Gasoline	3,970	-	5,360	2,806	2,443	5,249	3,301	7,400	5,000	500	13,550	4,727; 5,100	289.2	107.5	79.7	39.5	79.3	185.0	27.2	53.1
	Cargo Van	144.3	Standard	8,550	Diesel	3,970	-	5,360	2,892	1,892	4,784	3,766	7,400	5,000	500	13,550	3,923; 4,182	232.5	96.3	79.7	39.5	48.8	128.5	27.6	53.1
	Cargo Van	144.3	High	8,550	Diesel	3,970	-	5,360	2,917	2,019	4,936	3,614	7,400	5,000	500	13,550	3,923; 4,182	232.5	107.5	79.7	39.5	48.8	128.5	27.6	53.1
	Cargo Van	170.3	High	8,550	Diesel	3,970	-	5,360	2,994	2,273	5,267	3,283	7,400	5,000	500	13,550	3,923; 4,182	273.2	107.5	79.7	39.5	63.6	169.3	27.4	53.1
Cargo Van	170.3	Mega	8,550	Diesel	3,970	-	5,360	3,011	2,315	5,326	3,224	7,400	5,000	500	13,550	3,923; 4,182	273.2	116.7	79.7	39.5	63.6	169.3	27.4	53.1	
Cargo Van	170.3 ext.	High	8,550	Diesel	3,970	-	5,360	2,961	2,434	5,395	3,155	7,400	5,000	500	13,550	3,923; 4,182	289.2	107.5	79.7	39.5	79.3	185.0	27.2	53.1	
3500	Cargo Van	144.3	High	9,990	Diesel	4,080	4,410	7,060	3,086	2,374	5,460	4,530	7,400	7,500	750	17,490	3,923; 4,182	232.5	107.5	79.7	39.5	48.8	128.5	31.1	38.5
	Cargo Van	170.3	High	9,990	Diesel	4,080	4,410	7,060	3,208	2,654	5,862	4,128	7,400	7,500	750	17,490	3,923; 4,182	273.2	107.5	79.7	39.5	63.6	169.3	30.9	38.5
	Cargo Van	170.3 ext.	High	9,990	Diesel	4,080	4,410	7,060	3,183	2,795	5,978	4,012	7,400	7,500	750	17,490	3,923; 4,182	289.2	107.5	79.7	39.5	79.3	185.0	30.9	38.5
	Cargo Van	144.3	Standard	11,030	Diesel	4,080	4,410	7,720	3,062	2,319	5,381	5,649	N / A	7,500	750	18,530	3,923; 4,182	232.5	96.3	79.7	39.5	48.8	128.5	31.1	38.5
	Cargo Van	144.3	High	11,030	Diesel	4,080	4,410	7,720	3,086	2,374	5,460	5,570	N / A	7,500	750	18,530	3,923; 4,182	232.5	107.5	79.7	39.5	48.8	128.5	31.1	38.5
	Cargo Van	170.3	High	11,030	Diesel	4,080	4,410	7,720	3,208	2,654	5,862	5,168	N / A	7,500	750	18,530	3,923; 4,182	273.2	107.5	79.7	39.5	63.6	169.3	30.9	38.5
	Cargo Van	170.3 ext.	High	11,030	Diesel	4,080	4,410	7,720	3,183	2,795	5,978	5,052	N / A	7,500	750	18,530	3,923; 4,182	289.2	107.5	79.7	39.5	79.3	185.0	30.9	38.5
	Cargo Van	170.3 ext.	Mega	11,030	Diesel	4,080	4,410	7,720	3,197	2,844	6,041	4,989	N / A	7,500	750	18,530	3,923; 4,182	289.2	120.1	79.7	39.5	79.3	185.0	30.9	38.5

Model	Wheelbase [in]	Roof-version	GVWR [lbs]	Engine V6 3.0l CRD	GAWR.F (standard) [lbs]	GAWR.F (option) [lbs]	GAWR.R [lbs]	Base CWF [lbs]	Base CWR [lbs]	Base CW [lbs]	max Payload & Body Allowance [lbs]	UVW [lbs]	max Towing [lbs]	max Tongue Weight [lbs]	GCWR [lbs]	avail. Rear Axle ratios (i)	Vehicle Length [in]	Vehicle Height [in]	Vehicle Width [in]	Front Overhang BA [in]	Rear Frame Overhang [in]	Cab to Body Clearance CB [in]	Frame Width out. to out. [in]	Frame Height laden/unladen [in]	
3500	Chassis Cab	144.3	Standard	11,030	Diesel	4,080	4,410	7,720	3,014	1,473	4,487	6,543	N / A	7,500	750	18,530	3,923; 4,182	239.6	95.5	79.3	39.5	49.2	2.0	39.188 / 30.250	26.8 / 33.6
	Chassis Cab	170.3	Standard	11,030	Diesel	4,080	4,410	7,720	3,137	1,433	4,570	6,460	N / A	7,500	750	18,530	3,923; 4,182	269.5	95.5	79.3	39.5	53.1	2.0	39.188 / 30.250	26.8 / 33.6

\*) Weight for 9 + 1 seating

Prior to making any modification to or installing any equipment in or on a Sprinter, please check with DaimlerChrysler Manufacturing Intl. LLC ("DCMI") for additional and updated information, read the Sprinter DaimlerChrysler Body Builder Information Book when available, and if necessary, consult with DCMI's Engineering and Compliance Department.



## Sprinter Model Mix

Model	Wheelbase [in]	Roof-version	GVWR [lbs]	Engine V6 3.0l CRD	max Floor Width [in]	Loading Area [sq ft]	Interior Height [in]	Cargo Volume [cu ft]	max height Center of Gravity in z CG [mm / in]	Ground to Sliding Door Step [in]	Side Door Opening (Height / Width) [in]	Rear Door Opening (Height / Width) [in]	Tire Track Front / Rear [in]	Turning Circle [ft]	Tires & Load Ratings	Rim	
2500	Passenger Van*)	144.3	Standard	8,550	Gasoline	70.1	23.7	65.0	141.3	1300 / 51.2	20.2	59.8 / 51.2	60.6 / 61.6	68.0 / 68.2	47.6	LT245/75R16 120/116	6.5J x 16
	Passenger Van*)	144.3	High	8,550	Gasoline	70.1	23.7	76.4	158.9	1300 / 51.2	20.2	71.7 / 51.2	72.4 / 61.6	68.0 / 68.2	47.6	LT245/75R16 120/116	6.5J x 16
	Passenger Van*)	170.3	High	8,550	Gasoline	70.1	31.2	76.4	187.2	1300 / 51.2	19.9	71.7 / 51.2	72.4 / 61.6	68.0 / 68.2	54.6	LT245/75R16 120/116	6.5J x 16
	Passenger Van*)	144.3	Standard	8,550	Diesel	70.1	23.7	65.0	141.3	1300 / 51.2	20.2	59.8 / 51.2	60.6 / 61.6	68.0 / 68.2	47.6	LT245/75R16 120/116	6.5J x 16
	Passenger Van*)	144.3	High	8,550	Diesel	70.1	23.7	76.4	158.9	1300 / 51.2	20.2	71.7 / 51.2	72.4 / 61.6	68.0 / 68.2	47.6	LT245/75R16 120/116	6.5J x 16
	Passenger Van*)	170.3	High	8,550	Diesel	70.1	31.2	76.4	187.2	1300 / 51.2	19.9	71.7 / 51.2	72.4 / 61.6	68.0 / 68.2	54.6	LT245/75R16 120/116	6.5J x 16
	Cargo Van	144.3	Standard	8,550	Gasoline	70.1	59.2	65.0	318	1300 / 51.2	20.2	59.8 / 51.2	60.6 / 61.6	68.0 / 68.2	47.6	LT245/75R16 120/116	6.5J x 16
	Cargo Van	144.3	High	8,550	Gasoline	70.1	59.2	76.4	371	1300 / 51.2	20.2	71.7 / 51.2	72.4 / 61.6	68.0 / 68.2	47.6	LT245/75R16 120/116	6.5J x 16
	Cargo Van	170.3	High	8,550	Gasoline	70.1	79.7	76.4	494	1300 / 51.2	19.9	71.7 / 51.2	72.4 / 61.6	68.0 / 68.2	54.6	LT245/75R16 120/116	6.5J x 16
	Cargo Van	170.3	Mega	8,550	Gasoline	70.1	79.7	84.3	530	1300 / 51.2	19.9	71.7 / 51.2	72.4 / 61.6	68.0 / 68.2	54.6	LT245/75R16 120/116	6.5J x 16
	Cargo Van	170.3 ext.	High	8,550	Gasoline	70.1	86.1	76.4	547	1300 / 51.2	19.9	71.7 / 51.2	72.4 / 61.6	68.0 / 68.2	54.6	LT245/75R16 120/116	6.5J x 16
	Cargo Van	144.3	Standard	8,550	Diesel	70.1	59.2	65.0	318	1300 / 51.2	20.2	59.8 / 51.2	60.6 / 61.6	68.0 / 68.2	47.6	LT245/75R16 120/116	6.5J x 16
	Cargo Van	144.3	High	8,550	Diesel	70.1	59.2	76.4	371	1300 / 51.2	20.2	71.7 / 51.2	72.4 / 61.6	68.0 / 68.2	47.6	LT245/75R16 120/116	6.5J x 16
	Cargo Van	170.3	High	8,550	Diesel	70.1	79.7	76.4	494	1300 / 51.2	19.9	71.7 / 51.2	72.4 / 61.6	68.0 / 68.2	54.6	LT245/75R16 120/116	6.5J x 16
Cargo Van	170.3	Mega	8,550	Diesel	70.1	79.7	84.3	530	1300 / 51.2	19.9	71.7 / 51.2	72.4 / 61.6	68.0 / 68.2	54.6	LT245/75R16 120/116	6.5J x 16	
Cargo Van	170.3 ext.	High	8,550	Diesel	70.1	86.1	76.4	547	1300 / 51.2	19.9	71.7 / 51.2	72.4 / 61.6	68.0 / 68.2	54.6	LT245/75R16 120/116	6.5J x 16	
3500	Cargo Van	144.3	High	9,990	Diesel	70.1	58.1	76.4	371	1300 / 51.2	22.0	71.7 / 51.2	72.4 / 61.6	67.2 / 60.9	47.6	LT215/85R16 115/112	5.5J x 16
	Cargo Van	170.3	High	9,990	Diesel	70.1	78.6	76.4	494	1300 / 51.2	21.2	71.7 / 51.2	72.4 / 61.6	67.2 / 60.9	54.6	LT215/85R16 115/112	5.5J x 16
	Cargo Van	170.3 ext.	High	9,990	Diesel	70.1	85.0	76.4	547	1300 / 51.2	21.2	71.7 / 51.2	72.4 / 61.6	67.2 / 60.9	54.6	LT215/85R16 115/112	5.5J x 16
	Cargo Van	144.3	Standard	11,030	Diesel	70.1	58.1	65.0	318	1300 / 51.2	22.0	59.8 / 51.2	60.6 / 61.6	67.2 / 60.9	47.6	LT215/85R16 115/112	5.5J x 16
	Cargo Van	144.3	High	11,030	Diesel	70.1	58.1	76.4	371	1300 / 51.2	22.0	71.7 / 51.2	72.4 / 61.6	67.2 / 60.9	47.6	LT215/85R16 115/112	5.5J x 16
	Cargo Van	170.3	High	11,030	Diesel	70.1	78.6	76.4	494	1300 / 51.2	21.2	71.7 / 51.2	72.4 / 61.6	67.2 / 60.9	54.6	LT215/85R16 115/112	5.5J x 16
	Cargo Van	170.3 ext.	High	11,030	Diesel	70.1	85.0	76.4	547	1300 / 51.2	21.2	71.7 / 51.2	72.4 / 61.6	67.2 / 60.9	54.6	LT215/85R16 115/112	5.5J x 16
	Cargo Van	170.3 ext.	Mega	11,030	Diesel	70.1	85.0	84.3	600	1300 / 51.2	21.2	71.7 / 51.2	72.4 / 61.6	67.2 / 60.9	54.6	LT215/85R16 115/112	5.5J x 16

Model	Wheelbase [in]	Roof-version	GVWR [lbs]	Engine V6 3.0l CRD	max. Body Length BL [in / ft]	Front Axle to Back of Cab AC [in]	Cab to Axle CA [in]	Tire Track Front / Rear [in]	Turning Circle [ft]	Tires & Load Ratings	Rim	
3500	Chassis Cab	144.3	Standard	11,030	Diesel	155.2 / 13.0	59.1	85.2	67.2 / 60.9	47.6	LT215/85R16 115/112	5.5J x 16
	Chassis Cab	170.3	Standard	11,030	Diesel	194.1 / 16.2	59.1	111.2	67.2 / 60.9	54.6	LT215/85R16 115/112	5.5J x 16

\*) Weight for 9 + 1 seating

Prior to making any modification to or installing any equipment in or on a Sprinter, please check with DaimlerChrysler Manufacturing Intl. LLC ("DCMI") for additional and updated information, read the Sprinter DaimlerChrysler Body Builder Information Book when available, and if necessary, consult with DCMI's Engineering and Compliance Department.