


Features

- Onboard Intel® Atom® x7-E3950/ x5-E3940/ x5-E3930 Processor [i-Temp support]
- 2x DDR3L-1866 SO-DIMM sockets, Max. 16GB
- 2x independent displays, DisplayPort/ DVI-D/ LVDS or eDP via carrier board (IP419)
- HD audio via carrier board (IP419)
- Wide-range operating temperature from -40°C to 85°C




Specifications

CPU	Intel Atom® x7-E3950 Processor (1.6GHz~2.0GHz) Intel Atom® x5-E3940 Processor (1.6 GHz~1.8GHz) Intel Atom® x5-E3930 Processor (1.3 GHz~1.8GHz)
PCH	Integrated in Intel® SoC
Memory	2x DDR3L-1866 SO-DIMM sockets, Max. 16GB
BIOS	AMI
Watchdog Timer	256 levels
H/W Monitor	Yes
Storage Device Interface	N/A
Expansion Slots	4x PCI-E(x1)
Graphics Controller	Intel® SoC integrated Gen9 18EUs graphics
Video Output	Supports 2x DDI (DisplayPort / DVI-D) 1x 24-bit dual-channel or eDP
Ethernet	Intel® I210IT Gigabit LAN
I/O Chipset	Fintek F81804U-I
Serial Port	2x COM ports (Tx/Rx only)
USB 2.0	4x USB 2.0 via carrier board
USB 3.X	3x USB 3.0 via carrier board
Serial ATA	2x SATA III via carrier board
Audio	Intel® Atom® SoC built-in HD Audio
TPM	TPM (2.0)
Others	Digital I/O (4-in / 4-out)
Dimensions (L X W)	95mm x 95mm
Power Consumption	Intel® Atom® E3950 1.6GHz w/ 2x 8GB DDR3L-1600 +12V: 2.18A
Operating Temperature	-40°C ~85°C (-40°F ~ 185°F)
Storage Temperature	-40°C ~ 90°C (-40°F ~ 194°F)
Relative Humidity	10~90% (non-condensing)

Ordering Information

ET870-I50	COM Express (Type-6) CPU Module with Intel® Atom® x7-E3950 (2.0GHz), DDR3L dual-channel memory, eDP support
ET870-I50LV	COM Express (Type-6) CPU Module with Intel® Atom® x7-E3950 (2.0GHz), DDR3L dual-channel memory, LVDS support
ET870-I40	COM Express (Type-6) CPU Module with Intel® Atom® x5-E3940 (1.8GHz), DDR3L dual-channel memory, eDP support
ET870-I40LV	COM Express (Type-6) CPU Module with Intel® Atom® x5-E3940 (1.8GHz), DDR3L dual-channel memory, LVDS support
ET870-I30	COM Express (Type-6) CPU Module with Intel® Atom® x5-E3930 (1.8GHz), DDR3L dual-channel memory, eDP support
ET870-I30LV	COM Express (Type-6) CPU Module with Intel® Atom® x5-E3930 (1.8GHz), DDR3L dual-channel memory, LVDS support
IP419	Mini-ITX COM Express Type-6 (R3.0) carrier board
HSET870-A	Heatsink for ET870
HSET870-1	Heat Spreader for ET870

Dimensions and Drawing



1 Single Board Computers

2 CPU Modules

3 Motherboards

4 CPU Cards