

# INA3604

## Rackmount Network Appliance

Enterprise 1U Network Appliance with Intel® Xeon® E-2300 Processors & up to 16 GbE Ports



### Features

- Intel® Xeon® E-2300 Processors with C252 PCH
- 2x DDR4 UDIMM, RDIMM , Max. 64GB ( ECC )
- 6x RJ45 GbE with 2 pairs bypass on board
- 2x Gbe SFP ports on board
- Optional NIC slot
- 1x PCI-E (x8) expansion slot
- 500W AC single power supply

### Specifications

CPU	LGA1200 Socket for Intel® Xeon® E-2300 Processors
Chipset	Intel® C252 PCH chipset
Memory	2x DDR4 UDIMMs Max. 64GB
Display	1x LCM
Ethernet	6x Gbe RJ45 Ports (Intel i226V) with 2 pairs bypass 2x Gbe SFP port (Intel i210S)
Bypass	2-Segments, LAN3/4 & 5/6
Expansion	1x PCI-E(x8) slot (8-lane) for INA3604
IPMI	N/A
Storage	1x SATA DOM 1x internal 2.5" SATA SSD/HDD
TPM	TPM 2.0
I/O	1x LCM 3x LED (Power/ HDD/ Status) 1x Reset button 1x RJ45 console 2x USB3.2
Power Supply	Full-range 500-watt single power supply
Dimensions	438 (W) x 384.2 (D) x 44 (H) mm 17.24" (W) x 15.13" (D) x 1.73" (H)
Weight	7.5 kg (16.53 lbs)
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)
Storage Temperature	-20° ~ 70°C (-4°F ~ 158°F)
Operating Humidity	10~ 95%
Certification	CE/FCC

### Ordering Information

INA3604	INA3604 1U Rackmount Appliance, MBN808 Intel® RKL-E, C252 PCH, 2x DDR4 DIMMs, Max. 16 LAN Ports, 500W PSU, CPU cooler, 1x PCI-E(x8) slot, 1x LCM, Barebone without CPU/RAM/HDD/IBN Card
---------	---

### Dimensions

